

3.5 SSHD DATA SHEET

**Ferocious Performance.  
Superior Storage. Tireless Durability.**



FireCuda® 3.5-inch solid state hard drives blend SSD technology with an HDD platform for the instant-on performance and capacity you need.



### Best-Fit Applications

- Desktop PCs
- PC gaming
- Workstations
- High-performance direct-attached storage (DAS) devices

## Key Advantages

**Smart 1TB and 2TB** capacities with onboard flash memory.

**Save time** with a drive that boots in seconds, not minutes.<sup>1</sup>

**A perfect upgrade** for gamers, creative professionals and PC enthusiasts who want it all, now!

**Game up to 5× faster** than with traditional 7200-RPM hard drives, and eliminate the need to uninstall games in order to make room for new ones. Store up to 40 games per TB (at ~25GB per game).<sup>1</sup>

**SATA 6Gb/s** interface speed.

**Installs and operates** like a standard hard drive. No additional drivers or software required.

**The cutting edge never felt so safe** —5-year limited warranty is best-in-class for hard drive warranties.

<sup>1</sup> Performance may vary depending on user's hardware configuration and operating system.



Specifications	2TB	1TB
Standard Model Numbers	ST2000DX002	ST1000DX002
Interface	SATA 6Gb/s NCQ	SATA 6Gb/s NCQ
Form Factor (in)	3.5	3.5
<b>Features and Performance</b>		
NAND Type/Size	MLC/8GB	MLC/8GB
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5
Seek Average, Read (ms)	<9.5	<8.5
Seek Average, Write (ms)	<9.5	<8.5
Average Data Rate, Read, Avg All Zones (MB/s)	156	156
Average Data Rate From NAND Media (MB/s)	190	190
Max Sustained Data Rate, OD Read (MB/s)	210Mb/s	210Mb/s
DRAM Cache (MB)	64	64
Recording Technology	CMR	CMR
<b>Configuration/Organization</b>		
Heads/Disks	4/2	2/1
Bytes per Sector	4096	4096
<b>Reliability/Data Integrity</b>		
Load/Unload Cycles	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E14	1 per 10E14
Predicted Annualized Failure Rate (AFR)	<1%	<1%
Warranty, Limited (years)	5	5
<b>Power Management</b>		
Operating Power, Typical (W)	6.7	5.9
Idle2 Power, Typical (W)	4.5	3.36
Standby Mode/Sleep Mode, Typical (W)	0.75/0.75	0.63/0.63
<b>Environmental</b>		
Temperature, Operating (°C)	0 to 60	0 to 60
Temperature, Nonoperating (°C)	-40 to 70	-40 to 70
<b>Physical</b>		
Height (mm/in, max)	26.11mm/1.028in	19.87mm/0.782in
Width (mm/in, max)	—	—
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb, typical)	535g/1.18lb	400g/0.88lb
Carton Unit Quantity	20	25
Cartons per Pallet/Cartons per Layer	40/8	40/8

seagate.com



© 2020 Seagate Technology LLC. All rights reserved. Printed in USA. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Quantitative usage examples for various applications are for illustrative purposes. Actual quantities will vary based on various factors, including file size, file format, features and application software. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1903.2-2006US June 2020