



SCSI Commands Reference Manual

Serial Attached SCSI (SAS)

100293068, Rev. M
June 2022

©2022 Seagate Technology LLC. All rights reserved.

Publication number: 100293068, Rev. M June 2022

Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. SeaTools is a trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners.

No part of this publication may be reproduced in any form without written permission of Seagate Technology LLC.

Call 877-PUB-TEK1 (877-782-8351) to request permission.

Contents

1. Definitions, Symbols, Abbreviations, Keywords, And Conventions.....	24
1.1 Definitions	25
1.2 Symbols and abbreviations	33
1.3 Keywords	35
1.4 Conventions.....	36
2. General Concepts	37
2.1 Command Descriptor Block (CDB).....	37
2.1.1 CDB usage and structure	37
2.1.2 The fixed length CDB formats.....	38
2.1.3 The variable length CDB formats.....	40
2.2 Common CDB fields	42
2.2.1 Operation Code.....	42
2.2.2 SERVICE ACTION	42
2.2.3 Logical block address	43
2.2.4 TRANSFER LENGTH.....	43
2.2.5 PARAMETER LIST LENGTH	43
2.2.6 ALLOCATION LENGTH.....	43
2.2.7 CONTROL.....	44
2.2.8 Grouping function	44
2.3 Parameter Rounding.....	45
2.4 Sense data	46
2.4.1 Sense data introduction.....	46
3. Direct Access Block commands (SPC-6 and SBC-5)	65
3.1 BACKGROUND CONTROL command.....	71
3.2 CHANGE DEFINITION command.....	72
3.3 FORMAT UNIT command	74
3.3.1 FORMAT UNIT command overview	74
3.3.2 FORMAT UNIT parameter list	78
3.3.3 Parameter list header	79
3.3.4 Initialization pattern descriptor.....	83
3.3.5 Address descriptor formats.....	84
3.4 GET LBA STATUS (16) command.....	89
3.4.1 GET LBA STATUS (16) command overview.....	89
3.4.2 GET LBA STATUS parameter data	90
3.5 GET LBA STATUS (32) command.....	94
3.6 GET PHYSICAL ELEMENT STATUS command	95
3.6.1 GET PHYSICAL ELEMENT STATUS parameter data.....	97
3.6.2 Physical element status descriptor.....	98
3.7 GET STREAM STATUS command.....	100
3.7.1 GET STREAM STATUS parameter data.....	101
3.8 INQUIRY command	103
3.8.1 INQUIRY command introduction.....	103
3.8.2 Standard INQUIRY data.....	104
3.8.3 Vital product data.....	110
3.9 LOG SELECT command	111
3.9.1 Processing LOG SELECT when the parameter list length is zero	113
3.10 LOG SENSE command	116
3.11 MODE SELECT(6) command.....	118
3.12 MODE SELECT (10) command	120
3.13 MODE SENSE(6) command.....	121
3.13.1 MODE SENSE(6) command introduction	121

Contents

3.14	MODE SENSE(10) command	124
3.15	PERSISTENT RESERVE IN command	125
3.15.1	PERSISTENT RESERVE IN command introduction	125
3.15.2	READ KEYS service action	126
3.15.3	READ RESERVATION service action	127
3.15.4	REPORT CAPABILITIES service action	130
3.15.5	READ FULL STATUS service action	133
3.16	PERSISTENT RESERVE OUT command	136
3.16.1	PERSISTENT RESERVE OUT command introduction	136
3.16.2	PERSISTENT RESERVE OUT service actions	137
3.16.3	Basic PERSISTENT RESERVE OUT parameter list	138
3.16.4	Parameter list for the PERSISTENT RESERVE OUT command with REGISTER AND MOVE service	142
3.17	READ (6) command	144
3.18	READ (10) command	146
3.19	READ (12) command	150
3.20	READ (16) command	151
3.21	READ (32) command	152
3.22	READ BUFFER (10) command	154
3.22.1	READ BUFFER (10) command introduction	154
3.22.2	Combined header and data mode (00h)	155
3.22.3	Vendor specific mode (01h)	155
3.22.4	Data mode (02h)	155
3.22.5	Descriptor mode (03h)	156
3.22.6	Echo buffer mode (0Ah)	157
3.22.7	Echo buffer descriptor mode (0Bh)	157
3.22.8	Error history mode (1Ch)	158
3.23	READ BUFFER (16) command	164
3.24	READ CAPACITY (10) command	165
3.24.1	READ CAPACITY (10) overview	165
3.24.2	READ CAPACITY (10) parameter data	166
3.25	READ CAPACITY (16) command	167
3.25.1	READ CAPACITY (16) command overview	167
3.25.2	READ CAPACITY (16) parameter data	168
3.26	READ DEFECT DATA (10) command	170
3.26.1	READ DEFECT DATA (10) command overview	170
3.26.2	READ DEFECT DATA (10) parameter data	171
3.27	READ DEFECT DATA (12) command	172
3.27.1	READ DEFECT DATA (12) command overview	172
3.27.2	READ DEFECT DATA (12) parameter data	173
3.28	READ LONG (10) command	174
3.29	READ LONG (16) command	176
3.30	REASSIGN BLOCKS command	177
3.30.1	REASSIGN BLOCKS command overview	177
3.30.2	REASSIGN BLOCKS parameter list	178
3.31	RECEIVE DIAGNOSTIC RESULTS command	180
3.32	RELEASE (6) command	183
3.33	RELEASE (10) command	184
3.33.1	RELEASE (10) command introduction	184
3.33.2	Logical unit release	185
3.33.3	Third-party release	185
3.34	REMOVE ELEMENT AND TRUNCATE command	186
3.35	REPORT IDENTIFYING INFORMATION	187
3.35.1	IDENTIFYING INFORMATION SUPPORTED parameter data	189

Contents

3.36	REPORT LUNS command	190
3.37	REPORT SUPPORTED OPERATION CODES command	193
3.37.1	REPORT SUPPORTED OPERATION CODES command overview	193
3.37.2	All_commands parameter data format	195
3.37.3	One_command parameter data format	197
3.37.4	Command timeouts descriptor	199
3.38	REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS commands	201
3.39	REPORT TIMESTAMP command	205
3.40	REQUEST SENSE command	207
3.41	RESERVE(6) command	208
3.42	RESERVE (10) command	209
3.42.1	RESERVE (10) command introduction	209
3.42.2	Logical unit reservation	209
3.42.3	Third-party reservation	210
3.42.4	Superseding reservations	210
3.43	RESTORE ELEMENTS AND REBUILD command	211
3.44	REZERO UNIT command	212
3.45	SANITIZE command	213
3.45.1	SANITIZE command introduction	213
3.45.2	SANITIZE service actions	214
3.45.3	SANITIZE command with OVERWRITE service action	215
3.45.4	SANITIZE command with BLOCK ERASE service action	216
3.45.5	SANITIZE command with CRYPTOGRAPHIC ERASE service action	216
3.45.6	SANITIZE command with EXIT FAILURE MODE service action	216
3.46	SECURITY PROTOCOL IN command	217
3.46.1	Command description	217
3.46.2	Security protocol information description	219
3.47	SECURITY PROTOCOL OUT command	226
3.48	SEEK command	228
3.49	SEEK EXTENDED command	229
3.50	SEND DIAGNOSTIC command	230
3.51	SET IDENTIFYING INFORMATION command	232
3.52	SET TIMESTAMP command	234
3.53	START STOP UNIT command	236
3.54	STREAM CONTROL command	238
3.54.1	STREAM CONTROL command overview	238
3.54.2	STREAM CONTROL parameter data	239
3.55	SYNCHRONIZE CACHE (10) command	240
3.56	SYNCHRONIZE CACHE (16) command	242
3.57	TEST UNIT READY command	243
3.58	UNMAP command	244
3.58.1	UNMAP command overview	244
3.58.2	UNMAP parameter list	245
3.59	VERIFY (10) command	247
3.60	VERIFY (12) command	257
3.61	VERIFY (16) command	258
3.62	VERIFY (32) command	259
3.63	WRITE (6) command	261
3.64	WRITE (10) command	262
3.65	WRITE (12) command	266
3.66	WRITE (16) command	267

Contents

3.67 WRITE (32) command	268
3.68 WRITE AND VERIFY (10) command	270
3.69 WRITE AND VERIFY (12) command	271
3.70 WRITE AND VERIFY (16) command	272
3.71 WRITE AND VERIFY (32) command	273
3.72 WRITE ATOMIC (16) command	275
3.73 WRITE ATOMIC (32) command	276
3.74 WRITE BUFFER command	277
3.74.1 WRITE BUFFER command introduction	277
3.74.2 Combined header and data mode (00h)	279
3.74.3 Vendor specific mode (01h)	279
3.74.4 Data mode (02h)	279
3.74.5 Download microcode and activate mode (04h)	279
3.74.6 Download microcode, save, and activate mode (05h)	279
3.74.7 Download microcode with offsets and activate mode (06h)	280
3.74.8 Download microcode with offsets and save mode (07h)	280
3.74.9 Write data to echo buffer mode (0Ah)	280
3.74.10 Download microcode with offsets, select activation events, save, and defer activate mode (0Dh)	281
3.74.11 Download microcode with offsets, save, and defer activate mode (0Eh)	281
3.74.12 Activate deferred microcode mode (0Fh)	282
3.74.13 Enable expander communications protocol and Echo buffer mode (1Ah)	282
3.74.14 Disable expander communications protocol mode (1Bh)	282
3.74.15 Download application log mode (1Ch)	283
3.75 WRITE LONG (10) command	286
3.76 WRITE LONG (16) command	287
3.77 WRITE SAME (10) command	288
3.78 WRITE SAME (16) command	291
3.79 WRITE SAME (32) command	292
3.80 WRITE STREAM (16) command	293
3.81 WRITE STREAM (32) command	294
4. Zone Block Commands (ZBC)	295
4.1 Commands for zoned block devices overview	295
4.1.1 Summary of commands for zoned block devices	295
4.1.2 Zoned block device 16-byte CDB format with no data transfer	295
4.2 CLOSE ZONE command (94h/01h)	297
4.3 FINISH ZONE command (94h/02h)	298
4.4 OPEN ZONE command (94h/03h)	300
4.5 REPORT REALMS command (95h/06h)	302
4.5.1 REPORT REALMS parameter data	303
4.5.2 Realm descriptor	304
4.5.3 Realm Start/End descriptor	305
4.6 REPORT ZONE DOMAINS command (95h/07h)	306
4.6.1 REPORT ZONE DOMAINS parameter data	307
4.7 REPORT ZONES command (95h/00h)	310
4.7.1 REPORT ZONES parameter data	312
4.8 RESET WRITE POINTER command (94h/04h)	315
4.9 SEQUENTIALIZE ZONE command (94h/10h)	316
4.10 ZONE ACTIVATE command (95h/08h)	317
4.10.1 Identifying the candidate zones to activate and the candidate zones to deactivate	318
4.10.2 ZONE ACTIVATE parameter data and ZONE QUERY parameter data	320
4.10.3 Zone activation descriptors	321
4.11 ZONE QUERY command (95h/09h)	323

Contents

5. Parameters for direct access devices	324
5.1 Diagnostic parameters	324
5.1.1 Diagnostic page format and page codes for direct access devices	324
5.1.2 Supported diagnostic pages (00h)	326
5.1.3 Translate Address input page (40h)	327
5.1.4 Translate Address Output diagnostic page (40h)	329
5.1.5 SCSI Enclosure Services pages (01h - 2Fh)	330
5.1.6 Rebuild Assist Input diagnostic page (42h)	331
5.1.7 Rebuild Assist Output diagnostic page (42h)	332
5.2 Log parameters	334
5.2.1 Summary of log page codes	334
5.2.2 Log page structure	335
5.2.3 Application Client log page (0Fh/00h)	342
5.2.4 Background Scan log page (15h/00h)	344
5.2.5 Background Operation log page (15h/02h)	349
5.2.6 Cache Statistics page (37h/00h)	351
5.2.7 Cache Memory Statistics log page	352
5.2.8 Command Duration Limits Statistics log page	360
5.2.9 Environmental Limits log page (0Dh/02h)	364
5.2.10 Environmental Reporting log page (0Dh/01h)	368
5.2.11 Error counter log pages (WRITE, READ, and VERIFY)	372
5.2.12 Factory Log page (3Eh/00h)	374
5.2.13 Format Status log page (08h/00h)	375
5.2.14 Informational Exceptions log page (2Fh/00h)	381
5.2.15 Logical Block Provisioning log page (0Ch/00h)	383
5.2.16 Non-Medium Error log page (06h/00h)	390
5.2.17 Pending Defects log page (15h/01h)	392
5.2.18 Power Condition Transitions log page (1Ah/00h)	395
5.2.19 Protocol-Specific Port log page (18h/00h)	398
5.2.20 Self-Test Results log page (10h/00h)	405
5.2.21 Solid State Media log page (11h/00h)	408
5.2.22 Start-Stop Cycle Counter log page (0Eh/00h)	410
5.2.23 Supported Log Pages log page (00h/00h)	413
5.2.24 Supported Log Pages and Subpages log page (00h/FFh)	414
5.2.25 Supported Subpages log page	415
5.2.26 Temperature log page (0Dh/00h)	416
5.2.27 Utilization log page (0Eh/01h)	418
5.2.28 Zoned Block Device Statistics log page	421

Contents

5.3 Mode parameters.....	434
5.3.1 Mode parameters overview	434
5.3.2 Mode parameter list format	436
5.3.3 Mode parameter header formats	436
5.3.4 Mode parameter block descriptors	438
5.3.5 Mode page and subpage formats and page codes	442
5.3.6 Application Tag mode page (0Ah/02h).....	444
5.3.7 Background Control mode page (1Ch/01h)	446
5.3.8 Background Operation Control mode page (0Ah/06h).....	448
5.3.9 Caching Mode page (08h)	449
5.3.10 Command Duration Limit A mode page (0Ah/03h).....	452
5.3.11 Command Duration Limit B mode page (0Ah/04h)	454
5.3.12 Command Duration Limit T2A mode page.....	455
5.3.13 Command Duration Limit T2B mode page	460
5.3.14 Control mode page (0Ah)	461
5.3.15 Control Extension mode page (0Ah/01h)	467
5.3.16 Disconnect-Reconnect mode page (02h) for SAS.....	470
5.3.17 Format Parameters page (03h)	472
5.3.18 IO Advice Hints Grouping mode page (0Ah/05h)	475
5.3.19 Informational Exceptions Control mode page (1Ch)	477
5.3.20 Logical Block Provisioning mode page (1Ch/02h)	481
5.3.21 Power Condition mode page (1Ah)	484
5.3.22 Power Consumption Mode page (1Ah/01h).....	488
5.3.23 Read-Write Error Recovery mode page (01h)	490
5.3.24 Logical Unit mode page (18h) for SAS	495
5.3.25 Protocol-Specific Port mode page (19h) for SAS.....	496
5.3.26 Phy Control And Discover subpage (19h/01h).....	498
5.3.27 Shared Port Control mode page (19h/02h).....	502
5.3.28 Enhanced Phy Control mode page (19h/03h)	503
5.3.29 SAS – Transceiver Control (Out) subpage (19h/E5h)	506
5.3.30 SAS – Transceiver Control (In) subpage (19h/E6h)	513
5.3.31 Rigid Drive Geometry Parameters page (04h)	518
5.3.32 Seagate Specific Unit Attention parameters page (00h) for HDD.....	520
5.3.33 Seagate Specific Unit Attention parameters page (00h) for SSD.....	523
5.3.34 Verify Error Recovery mode page (07h)	525
5.3.35 Zoned Block Device Control mode page	526

Contents

5.4 Vital product data parameters.....	527
5.4.1 Vital product data parameters overview and page codes	527
5.4.2 ASCII Information VPD page (01h - 7Fh).....	528
5.4.3 Block Device Characteristics VPD page (B1h)	529
5.4.4 Block Device Characteristics Extension VPD page (B5h)	532
5.4.5 Block Limits VPD page (B0h).....	534
5.4.6 Block Limits Extension VPD page (B7h).....	539
5.4.7 Date Code page (C1h)	540
5.4.8 Device Behavior page (C3h)	541
5.4.9 Device Identification VPD page (83h)	542
5.4.10 Extended INQUIRY Data VPD page (86h).....	547
5.4.11 Firmware Numbers page (C0h)	553
5.4.12 Jumper Settings page (C2h)	555
5.4.13 Logical Block Provisioning VPD page (82h)	557
5.4.14 Mode Page Policy VPD page (87h)	560
5.4.15 Power Conditions Vital Product Data page (8Ah).....	562
5.4.16 Power Consumption Vital Product Data page (8Dh)	564
5.4.17 Protocol Specific Logical Unit Information VPD page (90h)	566
5.4.18 Protocol Specific Port Information VPD page (91h)	568
5.4.19 SCSI Feature Sets VPD page (92h).....	571
5.4.20 SCSI Ports VPD page (88h).....	572
5.4.21 Supported Vital Product Data pages (00h)	575
5.4.22 Unit Serial Number VPD page (80h).....	576
5.4.23 Zoned Block Device Characteristics VPD page (B6h).....	577

Tables

Table 1.	ISO v American Numbering Conventions	36
Table 2.	Typical CDB for 6-byte commands	38
Table 3.	Typical CDB for 10-byte commands	38
Table 4.	Typical CDB for long LBA 16-byte commands	39
Table 5.	Typical CDB for 12-byte commands	39
Table 6.	Typical variable length CDB	40
Table 7.	Typical variable length CDB for long LBA 32-byte commands	41
Table 8.	OPERATION CODE byte	42
Table 9.	Group Code values	42
Table 10.	CONTROL byte	44
Table 11.	Sense data response codes	46
Table 12.	Descriptor format sense data	47
Table 13.	Sense data descriptor format	48
Table 14.	Sense data descriptor types	48
Table 15.	Information sense data descriptor format	49
Table 16.	Command-specific information sense data descriptor format	49
Table 17.	Sense key specific sense data descriptor format	50
Table 18.	Sense key specific field definitions	51
Table 19.	Field pointer sense key specific data	51
Table 20.	Actual retry count sense key specific data	52
Table 21.	Progress indication sense key specific data	52
Table 22.	Segment pointer sense key specific data	53
Table 23.	Unit attention condition queue overflow sense key specific data	53
Table 24.	Field replaceable unit sense data descriptor format	54
Table 25.	Progress indications sense data descriptor format	54
Table 26.	Vendor specific sense data descriptor format	55
Table 27.	Fixed format sense data	56
Table 28.	Sense key descriptions	59
Table 29.	Additional Sense and Additional Sense Qualifier codes	60
Table 30.	Commands sorted by command name	65
Table 31.	Commands sorted by operation code	68
Table 32.	BACKGROUND CONTROL command	71
Table 33.	BO_CTL field	71
Table 34.	CHANGE DEFINITION command	72
Table 35.	Definition parameter field	72
Table 36.	FORMAT UNIT command	74
Table 37.	FORMAT UNIT command address descriptor usage	76
Table 38.	FFMT field description	77
Table 39.	FORMAT UNIT parameter list	78
Table 40.	Short parameter list header	79
Table 41.	Long parameter list header	79
Table 42.	FMTPIINFO field and PROTECTION FIELDS USAGE field	80

Tables

Table 43.	Initialization pattern descriptor	83
Table 44.	initialization pattern type field	83
Table 45.	Address descriptor formats	84
Table 46.	Short block format address descriptor (000b)	84
Table 47.	Bytes from index format address descriptor (100b)	85
Table 48.	Bytes from index format address descriptor (100b)	86
Table 49.	Long block format address descriptor (011b)	87
Table 50.	Bytes from index format address descriptor (100b)	87
Table 51.	Physical sector format address descriptor (101b)	88
Table 52.	GET LBA STATUS command	89
Table 53.	REPORT TYPE field	90
Table 54.	GET LBA STATUS parameter data	90
Table 55.	COMPLETION CONDITION field	91
Table 56.	LBA status descriptor format	92
Table 57.	PROVISIONING STATUS field	92
Table 58.	ADDITIONAL STATUS field	93
Table 59.	GET LBA STATUS (32) command	94
Table 60.	GET PHYSICAL ELEMENT STATUS command	95
Table 61.	FILTER field	96
Table 62.	REPORT TYPE field	96
Table 63.	GET PHYSICAL ELEMENT STATUS parameter data	97
Table 64.	Physical element status descriptor format	98
Table 65.	PHYSICAL ELEMENT TYPE field	99
Table 66.	PHYSICAL ELEMENT HEALTH field	99
Table 67.	GET STREAM STATUS command	100
Table 68.	GET STREAM STATUS parameter data	101
Table 69.	Stream status descriptor format	102
Table 70.	INQUIRY command	103
Table 71.	Standard INQUIRY data format	104
Table 72.	PERIPHERAL QUALIFIER	105
Table 73.	PERIPHERAL DEVICE TYPE	106
Table 74.	VERSION field codes	107
Table 75.	Target Port Group Support codes	108
Table 76.	BQue and CmdQue bit combinations	109
Table 77.	LOG SELECT command	111
Table 78.	Page Control (PC) field values	112
Table 79.	PAGE CODE field and SUBPAGE CODE field	113
Table 80.	PCR bit, SP bit, and PC field meanings when parameter list length is zero	114
Table 81.	LOG SENSE command	116
Table 82.	MODE SELECT(6) command	118
Table 83.	Mode page policies	118
Table 84.	MODE SELECT(10) command	120

Tables

Table 85.	MODE SENSE(6) command	121
Table 86.	Page control (PC) field	121
Table 87.	MODE SENSE(10) command	124
Table 88.	PERSISTENT RESERVE IN command	125
Table 89.	PERSISTENT RESERVE IN service action codes	125
Table 90.	PERSISTENT RESERVE IN parameter data for READ KEYS	126
Table 91.	PERSISTENT RESERVE IN data for READ RESERVATION with no reservation held	127
Table 92.	PERSISTENT RESERVE IN parameter data for READ RESERVATION with reservation	128
Table 93.	Persistent reservation scope codes	129
Table 94.	Persistent reservation type codes	129
Table 95.	PERSISTENT RESERVE IN parameter data for REPORT CAPABILITIES	130
Table 96.	ALLOW COMMANDS field	131
Table 97.	Persistent Reservation Type Mask format	132
Table 98.	PERSISTENT RESERVE IN parameter data for READ FULL STATUS	133
Table 99.	PERSISTENT RESERVE IN full status descriptor format	134
Table 100.	PERSISTENT RESERVE OUT command	136
Table 101.	PERSISTENT RESERVE OUT service action codes	137
Table 102.	PERSISTENT RESERVE OUT parameter list	138
Table 103.	PERSISTENT RESERVE OUT specify initiator ports additional parameter data	139
Table 104.	PERSISTENT RESERVE OUT service actions and valid parameters (part 1 of 2)	141
Table 105.	PERSISTENT RESERVE OUT service actions and valid parameters (part 2 of 2)	141
Table 106.	PERSISTENT RESERVE OUT command with REGISTER AND MOVE service	142
Table 107.	READ (6) command	144
Table 108.	Protection information checking for READ (6)	145
Table 109.	READ (10) command	146
Table 110.	RDPROTECT field	147
Table 111.	READ (12) command	150
Table 112.	READ (16) command	151
Table 113.	Force unit access for read operations	151
Table 114.	READ (32) command	152
Table 115.	READ BUFFER (10) command	154
Table 116.	MODE field	154
Table 117.	READ BUFFER header	155
Table 118.	READ BUFFER descriptor	156
Table 119.	Buffer offset boundary	156
Table 120.	Echo buffer descriptor	157
Table 121.	Error history BUFFER ID field	158
Table 122.	Summary of error history directory device server actions	159
Table 123.	BUFFER ID field and MODE SPECIFIC field meanings for the error history mode	159
Table 124.	Error history directory	160
Table 125.	EHS_RETRIEVED field	161
Table 126.	EHS_SOURCE field	161

Tables

Table 127. Error history directory entry	162
Table 128. BUFFER FORMAT field	162
Table 129. BUFFER SOURCE field	163
Table 130. READ BUFFER (16) command	164
Table 131. READ CAPACITY (10) command	165
Table 132. READ CAPACITY (10) parameter data	166
Table 133. READ CAPACITY (16) command	167
Table 134. READ CAPACITY (16) parameter data	168
Table 135. RC BASIS field	168
Table 136. P_TYPE FIELD and PROT_EN bit	169
Table 137. LOGICAL BLOCKS PER PHYSICAL BLOCKS EXPONENT field	169
Table 138. READ DEFECT DATA (10) command	170
Table 139. READ DEFECT DATA (10) parameter data	171
Table 140. READ DEFECT DATA (12) command	172
Table 141. READ DEFECT DATA (12) parameter data	173
Table 142. READ LONG (10) command	174
Table 143. READ LONG (16) command	176
Table 144. REASSIGN BLOCKS command	177
Table 145. REASSIGN BLOCKS parameter list	178
Table 146. REASSIGN BLOCKS short parameter list header	178
Table 147. REASSIGN BLOCKS long parameter list header	178
Table 148. RECEIVE DIAGNOSTIC RESULTS command	180
Table 149. Diagnostic Data Bytes	181
Table 150. Diagnostic Fault Codes	182
Table 151. RELEASE (6) Command	183
Table 152. RELEASE (10) Command	184
Table 153. RELEASE (10) parameter list	185
Table 154. REMOVE ELEMENT AND TRUNCATE command	186
Table 155. REPORT IDENTIFYING INFORMATION command	187
Table 156. INFORMATION TYPE	188
Table 157. REPORT IDENTIFYING INFORMATION parameter data	188
Table 158. REPORT IDENTIFYING INFORMATION SUPPORTED parameter data	189
Table 159. Identifying Information descriptor	189
Table 160. REPORT LUNS command	190
Table 161. SELECT REPORT field	191
Table 162. REPORT LUNS parameter data format	192
Table 163. REPORT SUPPORTED OPERATION CODES command	193
Table 164. REPORTING OPTIONS field	194
Table 165. All_commands parameter data	195
Table 166. Command descriptor format	195
Table 167. MLU field description	196
Table 168. CDLP field	196

Tables

Table 169. One_command parameter data	197
Table 170. Support values	198
Table 171. Command timeouts descriptor format	199
Table 172. Command timeout descriptor COMMAND SPECIFIC field usage in this manual	199
Table 173. REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command	201
Table 174. REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS parameter data	202
Table 175. REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS extended parameter data	202
Table 176. REPORT TIMESTAMP command	205
Table 177. REPORT TIMESTAMP parameter data format	206
Table 178. REQUEST SENSE command	207
Table 179. RESERVE(6) command	208
Table 180. RESERVE (10) Command	209
Table 181. RESERVE (10) ID only parameter list	210
Table 182. RESTORE ELEMENTS AND REBUILD command	211
Table 183. REZERO UNIT command (01h)	212
Table 184. SANITIZE command (48h)	213
Table 185. SANITIZE service action codes	214
Table 186. OVERWRITE service action parameter list	215
Table 187. TEST field	215
Table 188. SECURITY PROTOCOL IN command	217
Table 189. SECURITY PROTOCOL field within SECURITY PROTOCOL IN command	217
Table 190. SECURITY PROTOCOL SPECIFIC field for SECURITY PROTOCOL IN protocol 00h	219
Table 191. Supported security protocols SECURITY PROTOCOL IN parameter data	220
Table 192. Certificate data SECURITY PROTOCOL IN parameter data	221
Table 193. Certificate data SECURITY PROTOCOL IN parameter data	222
Table 194. Compliance descriptor format	223
Table 195. INFORMATION TYPE	223
Table 196. FIPS 140 Compliance descriptor	224
Table 197. REVISION field	225
Table 198. SECURITY PROTOCOL OUT command	226
Table 199. SECURITY PROTOCOL field within SECURITY PROTOCOL OUT command	227
Table 200. SEEK command (0Bh)	228
Table 201. SEEK command (2Bh)	229
Table 202. SEND DIAGNOSTIC command	230
Table 203. SELF-TEST CODE field	230
Table 204. SET IDENTIFYING INFORMATION command	232
Table 205. INFORMATION TYPE code list	233
Table 206. SET IDENTIFYING INFORMATION parameter list	233
Table 207. SET TIMESTAMP command	234
Table 208. SET TIMESTAMP parameter data format	235
Table 209. START STOP UNIT command	236
Table 210. POWER CONDITION field and POWER CONDITION MODIFIER field	236

Tables

Table 211. STREAM CONTROL command	238
Table 212. STR_CTL field	238
Table 213. STREAM CONTROL parameter data	239
Table 214. SYNCHRONIZE CACHE (10) command	240
Table 215. SYNC_PROG field description	241
Table 216. SYNCHRONIZE CACHE (16) command	242
Table 217. TEST UNIT READY command	243
Table 218. Preferred TEST UNIT READY responses	243
Table 219. UNMAP command	244
Table 220. UNMAP parameter list	245
Table 221. UNMAP block descriptor	246
Table 222. VERIFY (10) command	247
Table 223. VRPROTECT field with BYTCHK field set to 00b - medium	249
Table 224. VRPROTECT field with BYTCHK field set to 01b or 11b - medium	251
Table 225. VRPROTECT field with BYTCHK field set to one 01b or 11b - data-out buffer	253
Table 226. VRPROTECT field with BYTCHK field set to 01b or 11b - byte-by-byte comparison requirements	255
Table 227. VERIFY (12) command	257
Table 228. VERIFY (16) command	258
Table 229. VERIFY (32) command	259
Table 230. WRITE (6) command	261
Table 231. WRITE (10) command	262
Table 232. WRPROTECT field	263
Table 233. WRITE (12) command	266
Table 234. WRITE (16) command	267
Table 235. WRITE (32) command	268
Table 236. WRITE AND VERIFY (10) command	270
Table 237. WRITE AND VERIFY (12) command	271
Table 238. WRITE AND VERIFY (16) command	272
Table 239. WRITE AND VERIFY (32) command	273
Table 240. WRITE ATOMIC (16) command	275
Table 241. WRITE ATOMIC (32) command	276
Table 242. WRITE BUFFER command	277
Table 243. WRITE BUFFER MODE field	278
Table 244. MODE SPECIFIC field	281
Table 245. Application log data WRITE BUFFER format	283
Table 246. ERROR TYPE field	284
Table 247. CODE SET field	285
Table 248. ERROR LOCATION FORMAT field	285
Table 249. WRITE LONG (10) command	286
Table 250. WRITE LONG (16) command	287
Table 251. WRITE SAME (10) command	289
Table 252. ANCHOR bit, UNMAP bit, and ANC_SUP bit relationships	290

Tables

Table 253. WRITE SAME (16) command	291
Table 254. WRITE SAME (32) command	292
Table 255. WRITE STREAM (16) command	293
Table 256. WRITE STREAM (32) command	294
Table 257. Commands for host managed zoned block devices	295
Table 258. Typical 16-byte zoned block device CDB format with no data transfer	295
Table 259. CLOSE ZONE command	297
Table 260. CLOSE ZONE command processing	297
Table 261. FINISH ZONE command	298
Table 262. FINISH ZONE command processing	299
Table 263. OPEN ZONE command	300
Table 264. OPEN ZONE command processing	301
Table 265. REPORT REALMS command	302
Table 266. REPORT REALMS REPORTING OPTIONS field	302
Table 267. REPORT REALMS parameter data	303
Table 268. Realm descriptor	304
Table 269. REALM RESTRICTIONS field	305
Table 270. Realm Start/End descriptor	305
Table 271. REPORT ZONE command	306
Table 272. REPORT REALMS REPORTING OPTIONS field	306
Table 273. REPORT REALMS parameter data	307
Table 274. Zone domain descriptor	308
Table 275. REPORT ZONE command	310
Table 276. REPORT ZONES REPORTING OPTIONS field	311
Table 277. REPORT ZONES parameter data	312
Table 278. SAME field description	313
Table 279. Zone descriptor format	313
Table 280. Zone descriptor ZONE TYPE field	314
Table 281. Zone descriptor ZONE CONDITION field	314
Table 282. RESET WRITE POINTER command	315
Table 283. RESET WRITE POINTER command processing	315
Table 284. SEQUENTIALIZE ZONE command	316
Table 285. SEQUENTIALIZE ZONE command processing	316
Table 286. ZONE ACTIVATE command	317
Table 287. Selecting candidate zones to activate and deactivate with ALL bit set to zero	319
Table 288. ZONE ACTIVATE parameter data and ZONE QUERY parameter data	320
Table 289. Zone activation descriptor	322
Table 290. ZONE QUERY command	323
Table 291. Diagnostic page format	324
Table 292. Diagnostic page codes	325
Table 293. Supported diagnostic pages	326
Table 294. Translate Address page—input diagnostic page (40h)	327

Tables

Table 295. Address Field for Short Logical Block Address Format	328
Table 296. Address Field for Physical Sector Address Format	328
Table 297. Translate Address Output diagnostic page	329
Table 298. SCSI Enclosure Services page	330
Table 299. Rebuild Assist Input diagnostic page	331
Table 300. Rebuild Assist Output diagnostic page	332
Table 301. Log page codes	334
Table 302. Log page format	335
Table 303. LOG SELECT PCR bit, SP bit, and DS bit meanings when parameter list length is not zero	336
Table 304. Log parameter	337
Table 305. FORMAT AND LINKING field	338
Table 306. Parameter control byte values for bounded data counter parameters	339
Table 307. Parameter control byte values for unbounded data counter parameters	340
Table 308. Parameter control byte values for ASCII format list log parameters	340
Table 309. Parameter control byte values for binary format list log parameters	341
Table 310. Keywords for resetting or changing log parameters	341
Table 311. Application Client log page parameter codes	342
Table 312. Application client log page	342
Table 313. General usage application client parameter data	343
Table 314. Background Scan log page parameter codes	344
Table 315. Background Scan log page	344
Table 316. Background Scan Status parameter format	345
Table 317. Background Scan Status field	346
Table 318. Background Scan parameter format	347
Table 319. REASSIGN STATUS field	348
Table 320. Background Operation log page	349
Table 321. Background Operation log page parameter codes	349
Table 322. Background Operation log parameter format	350
Table 323. BO_STATUS Definitions	350
Table 324. Parameter codes	351
Table 325. Cache Statistics page (37h)	351
Table 326. Cache Memory Statistics log page parameter codes	352
Table 327. Cache Memory Statistics log page commands	352
Table 328. Cache Memory Statistics log page	353
Table 329. Read Cache Memory Hits log parameter	353
Table 330. Read to Cache Memory log parameter	354
Table 331. Write Cache Memory Hits log parameter	355
Table 332. Writes From Cache Memory log parameter	356
Table 333. Time From Last Hard Reset log parameter	357
Table 334. Time Interval log parameter	358
Table 335. Time interval descriptor	359
Table 336. Command Duration Limits Statistics log page parameter codes	360

Tables

Table 337. Command Duration Limits Statistics log page	361
Table 338. Achievable Latency Target log parameter	362
Table 339. Command Duration Limits T2A or T2B log parameter	363
Table 340. Environmental Limits log page parameter codes	364
Table 341. Environmental Limits log page	364
Table 342. Temperature Limits log parameter	365
Table 343. Relative Humidity Limits log parameter	366
Table 344. Relative humidity limit values	366
Table 345. Environmental Reporting log page parameter codes	368
Table 346. Environmental Reporting log page	368
Table 347. Temperature Report log parameter	369
Table 348. Relative Humidity Report log parameter	370
Table 349. Relative humidity reporting values	370
Table 350. Error counter log page codes	372
Table 351. Parameter codes for error counter log pages	372
Table 352. Error counter log page	373
Table 353. Factory Log page (3Eh)	374
Table 354. Format Status log page parameter codes	375
Table 355. Format Status log page	375
Table 356. Format Data Out log parameter format	376
Table 357. Grown Defects During Certification log parameter format	377
Table 358. Total Blocks Reassigned During Format log parameter format	378
Table 359. Total New Blocks Reassigned log parameter format	379
Table 360. Power On Minutes Since Format log parameter format	380
Table 361. Informational exceptions parameter codes	381
Table 362. Informational Exceptions log page	381
Table 363. Informational exceptions general parameter data	382
Table 364. Logical Block Provisioning log page parameters	383
Table 365. Logical block provisioning log page	383
Table 366. Available LBA Mapping Resource Count log parameter format	384
Table 367. SCOPE field	384
Table 368. Used LBA Mapping Resource Count log parameter format	385
Table 369. Available Provisioning Resource Percentage log parameter format	386
Table 370. RESOURCE COUNT field	386
Table 371. De-duplicated LBA Resource Count log parameter format	387
Table 372. Compressed LBA Resource Count log parameter format	388
Table 373. Total Efficiency LBA Resource Count log parameter format	389
Table 374. Non-medium error event parameter codes	390
Table 375. Non-Medium Error log page	390
Table 376. Non-Medium Error Count log parameter	391
Table 377. Pending Defects log page parameter codes	392
Table 378. Pending Defects log page	392

Tables

Table 379. Pending Defect Count log parameter format	393
Table 380. Pending Defect log parameter format	394
Table 381. Power Condition Transitions log page parameter codes	395
Table 382. Power Condition Transitions log page	396
Table 383. Power Condition Transitions log parameter format	397
Table 384. Protocol-Specific Port log page for SAS	398
Table 385. Protocol-Specific Port log parameter for SAS	399
Table 386. SAS phy log descriptor	400
Table 387. Device type field	401
Table 388. Reason field definition	402
Table 389. NEGOTIATED LOGICAL LINK RATE field	402
Table 390. Phy event descriptor	404
Table 391. Self-Test Results log page	405
Table 392. Self-test results log parameter format	405
Table 393. SELF-TEST RESULTS field	406
Table 394. Solid State Media log parameters	408
Table 395. Solid State Media log page	408
Table 396. Percentage Used Endurance Indicator log parameter format	409
Table 397. Solid State Media log parameters	410
Table 398. Start-Stop Cycle Counter log page	410
Table 399. Supported log pages	413
Table 400. Supported page descriptor	413
Table 401. Supported Log Pages and Subpages log page (00h/ FFh)	414
Table 402. Supported page/subpage descriptor	414
Table 403. Supported Subpages log page	415
Table 404. Supported subpage descriptor	415
Table 405. Temperature log page parameter codes	416
Table 406. Temperature log page	416
Table 407. Utilization log page parameter codes	418
Table 408. Utilization log page	418
Table 409. Workload Utilization log parameter format	419
Table 410. WORKLOAD UTILIZATION field	419
Table 411. Utilization Rate Based on Date and Time log parameter format	420
Table 412. DATE AND TIME BASED UTILIZATION RATE field	420
Table 413. Zoned Block Device Statistics log page parameter codes	421
Table 414. Zoned Block Device Statistics log page	421
Table 415. Maximum Open Zones log parameter	422
Table 416. Maximum Explicitly Open Zones log parameter	423
Table 417. Maximum Implicitly Open Zones log parameter	424
Table 418. Maximum Empty Zones log parameter	425
Table 419. Maximum Non-Sequential Zones log parameter	426
Table 420. Zones Emptied log parameter	427

Tables

Table 421. Suboptimal Write Commands log parameter	428
Table 422. Commands Exceeding Optimal Limit log parameter	429
Table 423. Failed Explicit Opens log parameter	430
Table 424. Read Rule Violations log parameter	431
Table 425. Write Rule Violations log parameter	432
Table 426. Maximum Implicitly Open Sequential Or Before Required Zones log parameter	433
Table 427. Mode page codes and subpage codes	434
Table 428. Mode parameter list	436
Table 429. Mode parameter header(6)	436
Table 430. Mode parameter header(10)	436
Table 431. Short LBA mode parameter block descriptor	438
Table 432. Long LBA mode parameter block descriptor	440
Table 433. Page_0 mode page format	442
Table 434. SUB_PAGE mode page format	442
Table 435. Application Tag mode page	444
Table 436. Application Tag descriptor format	445
Table 437. Background Control mode page	446
Table 438. Background Operation Control mode page	448
Table 439. BO_MODE field	448
Table 440. Caching Mode page (08h)	449
Table 441. Command Duration Limit A mode page	452
Table 442. Command Duration Limit A mode page	453
Table 443. CDLUNIT field	453
Table 444. Command Duration Limit B mode page	454
Table 445. Command Duration Limit T2A mode page	455
Table 446. PERFORMANCE VERSUS LATENCY CONTROLS field	456
Table 447. T2 command duration limit descriptor format	456
Table 448. T2CDLUNITS field	457
Table 449. Max inactive time policy field	457
Table 450. Max active time policy field	458
Table 451. COMMAND DURATION GUIDELINE POLICY field	459
Table 452. Command Duration Limit T2B mode page	460
Table 453. Control mode page	461
Table 454. Task set type (TST) field	461
Table 455. QUEUE ALGORITHM MODIFIER field	462
Table 456. Queue error management (QERR) field	463
Table 457. Unit attention interlocks control (UA_INTLCK_CTRL) field	464
Table 458. AUTOLOAD MODE field	466
Table 459. Control Extension mode page	467
Table 460. SEQUESTERED COMMANDS ORDERING field	469
Table 461. Disconnect-Reconnect mode page for SAS	470
Table 462. Format Parameters page (03h)	472

Tables

Table 463. IO Advice Hints Grouping mode page	475
Table 464. IO advice hints group descriptor	475
Table 465. IO ADVICE HINTS MODE field	476
Table 466. Informational Exceptions Control mode page	477
Table 467. Method of reporting informational exceptions (MRIE) field	479
Table 468. Use of the INTERVAL TIMER field and the REPORT COUNT field based on the MRIE field	480
Table 469. Logical Block Provisioning mode page	481
Table 470. Threshold descriptor format	482
Table 471. THRESHOLD TYPE field	482
Table 472. THRESHOLD ARMING field	483
Table 473. Power Condition mode page	484
Table 474. PM_BG_PRECEDENCE field	485
Table 475. CCF_IDLE field	487
Table 476. CCF_STANDBY field	487
Table 477. CCF_STOPPED field	487
Table 478. Power Consumption mode page	488
Table 479. ACTIVE LEVEL field	489
Table 480. Read-Write Error Recovery mode page	490
Table 481. Combined error recovery bit descriptions	492
Table 482. Protocol-Specific Logical Unit mode page for SAS	495
Table 483. Protocol-Specific Port mode page for SAS	496
Table 484. I_T NEXUS LOSS TIME values	497
Table 485. SAS - Phy Control And Discover subpage	498
Table 486. SAS phy mode descriptor	499
Table 487. The HARDWARE MINIMUM & MAXIMUM PHYSICAL LINK RATE field values	501
Table 488. The PROGRAMMED MINIMUM and MAXIMUM PHYSICAL LINK RATE field values	501
Table 489. Shared Port Control Mode Page	502
Table 490. Enhanced Phy Control mode page	503
Table 491. Enhanced phy control mode descriptor	504
Table 492. SAS Transceiver Control (Out) subpage	506
Table 493. Transceiver Controls Mode descriptor (1.5Gb, 3Gb and 6Gb Link Rate)	508
Table 494. Transceiver Controls descriptor (12Gb Link Rate)	508
Table 495. Controllable Link Rates	509
Table 496. DRIVER STRENGTH CONTROL or C1 PRE-CURSOR CONTROL (12G Mode Only) values	509
Table 497. DRIVER EMPHASIS CONTROL or C2 AMPLITUDE CONTROL (12G Mode Only)	510
Table 498. DRIVER SLEW RATE CONTROL or C3 POST CURSOR CONTROL (12G mode only)	510
Table 499. Receiver Threshold Control	511
Table 500. Receiver Equalization Gain Control field	511
Table 501. RESET and IREC bit function	512
Table 502. SAS - Transceiver Control (In) subpage	513
Table 503. Transceiver Controls descriptor (1.5Gb - 6Gb Link Rate)	515
Table 504. Transceiver Controls descriptor (1.5G, 3G, 6G and 12G)	516

Tables

Table 505. Controllable Link Rates field	516
Table 506. Rigid Drive Geometry Parameters page (04h)	518
Table 507. Seagate Specific Unit Attention parameters page (00h) for HDD	520
Table 508. Seagate Specific Unit Attention parameters page (00h) for SSD	523
Table 509. Verify Error Recovery mode page	525
Table 510. Zoned Block Device Control mode page	526
Table 511. Vital product data page codes	527
Table 512. ASCII Information VPD page	528
Table 513. Block Device Characteristics VPD page	529
Table 514. Medium Rotation Rate field	529
Table 515. WABEREQ field	530
Table 516. WACEREQ field	530
Table 517. Product Type field	530
Table 518. ZONED field	531
Table 519. Nominal Form Factor Field	531
Table 520. Block Device Characteristics Extension VPD page	532
Table 521. UTILIZATION TYPE field	532
Table 522. UTILIZATION UNITS Field	533
Table 523. UTILIZATION INTERVAL Field	533
Table 524. Block Limits VPD page	534
Table 525. Transfer limits for commands	536
Table 526. Block Limits Extension VPD page	539
Table 527. ETF Log Date Code page (C1h)	540
Table 528. Device Behavior page (C3h)	541
Table 529. Device Identification VPD page	542
Table 530. Identification Descriptor	543
Table 531. PROTOCOL IDENTIFIER values	544
Table 532. ASSOCIATION field	544
Table 533. IDENTIFIER Type field	545
Table 534. Device Identification page example	546
Table 535. Extended INQUIRY Data VPD page	547
Table 536. ACTIVATE MICROCODE field	548
Table 537. SPT field for device type value 00h	548
Table 538. SPT field for device type value 00h	549
Table 539. LU COLLECTION TYPE field	551
Table 540. Firmware Numbers page (C0h)	553
Table 541. Jumper Settings page (C2h)	555
Table 542. Drive ID bit	556
Table 543. Logical Block Provisioning VPD page	557
Table 544. LBPRZ field	558
Table 545. MINIMUM PERCENTAGE field	558
Table 546. Provisioning Type field	559

Tables

Table 547. MINIMUM PERCENTAGE field	559
Table 548. Mode Page Policy VPD page	560
Table 549. Mode page policy descriptor	560
Table 550. MODE PAGE POLICY field	561
Table 551. Power Condition VPD page	562
Table 552. Power Consumption VPD page	564
Table 553. Power consumption descriptor format	565
Table 554. POWER CONSUMPTION UNITS field	565
Table 555. Protocol Specific Logical Unit Information VPD page for SAS SSP	566
Table 556. Logical unit information descriptor for SAS SSP	567
Table 557. Protocol Specific Port Information VPD page for SAS SSP	568
Table 558. Logical unit information descriptor for SAS SSP	569
Table 559. SAS phy information descriptor for SAS SSP	570
Table 560. SCSI Feature Sets VPD page	571
Table 561. Feature set codes	571
Table 562. SCSI Ports VPD page	572
Table 563. SCSI port designation descriptor	573
Table 564. Relative Port Identifier field	574
Table 565. Target port Descriptor	574
Table 566. Supported Vital Product Data pages	575
Table 567. Unit Serial Number page (80h)	576
Table 568. Zoned Block Device Characteristics VPD page	577
Table 569. ZONED BLOCK DEVICE EXTENSION field	578

1. Definitions, Symbols, Abbreviations, Keywords, And Conventions

This clause contains the definitions, symbols, abbreviations, keywords and, conventions used throughout this manual. These items are from the American National Standards Institute T10 committee standards.

Applicable Documents:

INCITS 515 SCSI Architecture Model - 6 (SAM-6) Revision 08

INCITS 502 SCSI Primary Commands - 6 (SPC-6) Revision 06

INCITS 506 SCSI Block Commands - 5 (SBC-5) Revision 01

INCITS 536 Zoned Block Commands -2 (ZBC-2) Revision 10

INCITS 534 Serial Attached SCSI - 5 (SAS-5) Revision 01

INCITS 538 SAS Protocol Layer - 5 (SPL-5) Revision 12

1.1 Definitions

Access control list (ACL)

The data used by a SCSI target device to configure access rights for initiator ports according to the access controls state of the SCSI target device.

Access control list entry (ACE)

One entry in the access control list.

Access controls

An optional SCSI target device feature that restricts initiator port access to specific logical units and modifies the information about logical units in the parameter data of the INQUIRY and REPORT LUNS commands.

Access controls coordinator

The entity within a SCSI target device that coordinates the management and enforcement of access controls for all logical units within the SCSI target device. The access controls coordinator is always addressable through the ACCESS CONTROLS well known logical unit and LUN 0.

active power condition

When a device server is capable of responding to all of its supported commands, including media access requests, without delay.

additional sense code

A combination of the ADDITIONAL SENSE CODE and ADDITIONAL SENSE CODE QUALIFIER fields in the sense data.

Application client

An object that is the source of SCSI commands. Further definition of an application client may be found in SAM-6.

Attribute

A single unit of MAM information.

Auto contingent allegiance (ACA)

The task set condition established following the return of a CHECK CONDITION status when the NACA bit is set to one in the CONTROL byte. A detailed definition of ACA may be found in 2.2.7.

Blocked task

A task that is in the blocked state. Tasks become blocked when an ACA condition occurs. The blocked state ends when the ACA condition is cleared. A detailed definition of the blocked task state may be found in SAM-6.

Byte

A sequence of eight contiguous bits considered as a unit.

Cache

See cache memory.

Cache memory

A temporary and often volatile data storage area outside the area accessible by application clients that may contain a subset of the data stored in the non-volatile data storage area.

Check data

Information contained within a redundancy group that may allow lost or destroyed XOR-protected data to be recreated.

Command

A request describing a unit of work to be performed by a device server. A detailed definition of a command may be found in SAM-6.

Command descriptor block (CDB)

The structure used to communicate commands from an application client to a device server. A CDB may have a fixed length of up to 16 bytes or a variable length of between 12 and 260 bytes.

Command standard

A SCSI standard that defines the model, commands, and parameter data for a device type (e.g., SBC-5, SSC-3, SMC-3, MMC-5, or SES-3).

Company_id

Synonym for OUI.

Copy manager

The device server that receives an EXTENDED COPY command and performs the operation requested.

Copy target device

The name given by the EXTENDED COPY command to a source or destination logical unit (i.e., a copy target device is a logical unit, not a SCSI target device).

Cyclic redundancy check (CRC)

An error checking mechanism that checks data integrity by computing a polynomial algorithm based checksum.

Data defect list (DLIST)

A list of defects sent by the application client to the device server during a FORMAT UNIT command.

Data-in buffer

The buffer specified by the application client to receive data from the device server during the processing of a command.

Data-out buffer

The buffer specified by the application client to supply data that is sent from the application client to the device server during the processing of a command.

Default protection information

Values placed into protection information fields if an application client does not specify specific protection information values.'

Deferred error

A CHECK CONDITION status and sense data that is returned as the result of an error or exception condition that occurred during processing of a previous command for which GOOD, CONDITION MET, INTERMEDIATE, and INTERMEDIATE-CONDITION MET status has already been returned.

Device server

An object within a logical unit that processes SCSI tasks according to the rules of task management. A detailed definition of a device server may be found in SAM-6.

Device service request

A request, submitted by an application client, conveying a SCSI command to a device server. A detailed definition of a device service request may be found in SAM-6.

Device service response

The response returned to an application client by a device server on completion of a SCSI command. A detailed definition of a device service response may be found in SAM-6.

Device type

The type of peripheral device (i.e., device model) implemented by the device server and indicated by the contents of the PERIPHERAL DEVICE TYPE field in the standard INQUIRY data.

Direct-access block device

A device that is capable of containing data stored in blocks that each have a unique logical block address.

Domain

An I/O system consisting of a set of SCSI devices that interact with one another by means of a service delivery subsystem.

Element

An addressable physical component of a medium changer SCSI device that may serve as the location of a removable unit of data storage medium. A detailed definition of an element may be found in SMC-3.

Enabled task state

The only task state in which a task may make progress towards completion. A detailed definition of the enabled task state may be found in SAM-6.

Error correcting code (ECC)

An error checking mechanism that checks data integrity and enables some errors in the data to be corrected.

Error history I_T nexus

An I_T nexus for which the device server has reserved access to the error history snapshot (see SPC-6).

Error history snapshot

The contents of the error history at a specific point in time (see SPC-6).

Exclusive-or (XOR)

A Boolean arithmetic function on two binary input values that results in an output value of 1 if one and only one of the input values is 1.

Extended Unique Identifier, a 48-bit globally unique identifier (EUI-48)

The IEEE maintains a tutorial describing EUI-48 at <http://standards.ieee.org/regauth/oui/tutorials/EUI48.html>.

Extended Unique Identifier, a 64-bit globally unique identifier (EUI-64)

The IEEE maintains a tutorial describing EUI-64 at <http://standards.ieee.org/regauth/oui/tutorials/EUI64.html>.

Extent

A fixed set of logical blocks occupying contiguous logical block addresses on a single logical unit.

Faulted I_T nexus

The I_T nexus on which a CHECK CONDITION status was returned that resulted in the establishment of an ACA. The faulted I_T nexus condition is cleared when the ACA condition is cleared.

Field

A group of one or more contiguous bits, a part of a larger structure such as a CDB or sense data.

Format corrupt

a vendor-specific condition in which the application client may not be able to perform read operations, write operations, or verify operations.

Grown defect list (GLIST)

All defects sent by the application client to the device server.

Hard reset

A condition resulting from the events defined by SAM-6 in which the SCSI device performs the hard reset operations described in SAM-6, SPC-6, and the applicable command standards.

Host

A SCSI device with the characteristics of a primary computing device, typically a personal computer, workstation, server, minicomputer, main-frame computer, or auxiliary computing device. A host includes one or more SCSI initiator devices.

IEEE company_id

Synonym for OUI.

I_T nexus

A nexus between a SCSI initiator port and a SCSI target port.

I_T nexus loss

A condition resulting from the events defined by SAM-6 in which the SCSI device performs the I_T nexus loss operations described in SAM-6, SPC-6, and the applicable command standards.

I_T_L nexus

A nexus between a SCSI initiator port, a SCSI target port, and a logical unit.

I_T_L_Q nexus transaction

The information transferred between SCSI ports in a single data structure with defined boundaries (e.g., an information unit).

Idle power condition

When a device server is capable of responding to all of its supported commands, including media access requests, but commands may take longer to complete than when in the active power condition.

Implicit head of queue

An optional processing model for specified commands wherein the specified commands may be treated as if they had been received with a HEAD OF QUEUE task attribute.

Initiator device name

A SCSI device name of a SCSI initiator device or of a SCSI target/initiator device when operating as a SCSI initiator device.

Initiator port

Synonymous with SCSI initiator port.

Initiator port identifier

A value by which a SCSI initiator port is referenced within a SCSI domain.

Initiator port name

A SCSI port name of a SCSI initiator port or of a SCSI target/initiator port when operating as a SCSI initiator port.

Internet protocol domain name

The name of a computer or hierarchy of computers within the domain name system defined by the IETF (see RFC 1035 and RFC 1591). The Internet Assigned Numbers Authority maintains a list of domain name assignments at <http://www.iana.org/assignments/domain-names>.

Internet protocol number

A coded value assigned to identify protocols that layer on the Internet protocol (see RFC 791). The Internet protocol number assigned to the transmission control protocol (TCP, see RFC 793) is six. The Internet Assigned Numbers Authority maintains a list of Internet protocol number assignments at <http://www.iana.org/assignments/protocol-numbers>.

Least significant bit (LSB)

In a binary code, the bit or bit position with the smallest numerical weighting in a group of bits that, when taken as a whole, represent a numerical value (e.g., in the number 0001b, the bit that is set to one).

Left-aligned

A type of field containing ASCII data in which unused bytes are placed at the end of the field (highest offset) and are filled with ASCII space (20h) characters.

Logical block

A set of data bytes accessed and referenced as a unit.

Logical block address (LBA)

The value used to reference a logical block.

Logical unit

An externally addressable entity within a SCSI target device that implements a SCSI device model and contains a device server. A detailed definition of a logical unit may be found in SAM-6.

Logical unit access control descriptor (LUACD)

The structure within an ACE that identifies a logical unit to which access is allowed and specifies the LUN by which the logical unit is to be accessed.

Logical unit certification list (CLIST)

Defects detected by the device server during an optional certification process performed during the FORMAT UNIT command.

Logical unit inventory

The list of the logical unit numbers reported by a REPORT LUNS command.

Logical unit number (LUN)

An encoded 64-bit identifier for a logical unit. A detailed definition of a logical unit number may be found in SAM-6.

Logical unit reset

A condition resulting from the events defined by SAM-6 in which the logical unit performs the logical unit reset operations described in SAM-6, SPC-6, and the applicable command standards.

Media

Plural of Medium

Medium

A physical entity that stores data in a nonvolatile manner (i.e., retained through a power cycle) in accordance with commands processed by the device server.

Medium auxiliary memory (MAM)

An auxiliary memory residing on a medium that is accessible to the device server (e.g., a tape cartridge). Medium auxiliary memory may be nonvolatile and independent of the main function of the device server.

Most significant bit (MSB)

In a binary code, the bit or bit position with the largest numerical weighting in a group of bits that, when taken as a whole, represent a numerical value (e.g., in the number 1000b, the bit that is set to one).

Name

A label of an object that is unique within a specified context and should never change (e.g., the term name and worldwide identifier (WWID) may be interchangeable).

Network address authority (NAA)

A field within a name that specifies the format and length of that name. See FC-FS.

Nexus

A relationship between two SCSI devices, and the SCSI initiator port and SCSI target port objects within those SCSI devices.

Non-volatile cache

Cache that retains data through power cycles.

Non-volatile cache memory

Cache memory that retains data through power cycles.

Non-volatile medium

A physical storage medium that retains data written to it for subsequent read operations through power cycles (e.g., a disk within a device that stores data as magnetic field changes that do not require device power to exist).

Null-padded

A type of field in which unused bytes are placed at the end of the field (i.e., highest offset) and are filled with ASCII null (00h) characters.

Null-terminated

A type of field in which the last used byte (i.e., highest offset) is required to contain an ASCII null (00h) character.

One

The logical true condition of a variable.

Operation Code

The first byte of a SCSI CDB shall contain an operation code identifying the operation being requested by the CDB.

Organizationally unique identifier (OUI)

A numeric identifier that is assigned by the IEEE such that no assigned identifiers are identical. OUI is equivalent to company_id or IEEE company_id. The IEEE prefers OUI for EUI-48 identifiers and company_id for EUI-64 identifiers. However, the numeric identifier is called an OUI when it is assigned by the IEEE. The IEEE maintains a tutorial describing the OUI at <http://standards.ieee.org/regauth/oui/>.

Page

A regular parameter structure (or format) used by several commands. These pages are identified with a value known as a page code.

Persist through power loss

An optional capability associated with some features that allows an application client to request that a device server maintain information regarding that feature across power failures.

Persistent reservation holder

The L_T nexus(es) that are allowed to release or change a persistent reservation without preempting it.

Power cycle

Power being removed from and later applied to a SCSI device.

Power on

A condition resulting from the events defined by SAM-6 in which the SCSI device performs the power on operations described in SAM-6, SPC-6, and the applicable command standards.

Primary defect list (PLIST)

The list of defects that are considered permanent defects.

Protection information

Fields appended to each logical block that contain a cyclic redundancy check (CRC), an application tag, and a reference tag.

Protocol identifier

A coded value used in various fields to identify the protocol to which other fields apply.

Protocol specific

A requirement that is defined by a SCSI transport protocol standard. A detailed definition of protocol specific may be found in SAM-6.

Protocol standard

A SCSI standard that defines SCSI transport protocol (e.g., SAS or SBP-3).

Proxy token

An identifier for a logical unit that may be used to gain temporary access to that logical unit in the presence of access controls.

Redundancy group

A grouping of XOR-protected data and associated check data into a single type of data redundancy (see SCC-2). SPC-6 only supports the XOR type of redundancy.

Request for comment (RFC)

The name given to standards developed by the Internet Engineering Task Force.

Registered

The condition that exists for an L_T nexus following the successful completion of a PERSISTENT RESERVE OUT command with a REGISTER service action, REGISTER AND IGNORE EXISTING KEY service action, or REGISTER AND MOVE service action and lasting until the registration is removed.

Registrant

An L_T nexus that is registered.

Right-aligned

A type of field containing ASCII data in which unused bytes are placed at the start of the field (i.e., lowest offset) and are filled with ASCII space (20h) characters.

Relative port identifier

An identifier for a SCSI port that is unique within a SCSI device. Application clients may use the SCSI Ports VPD page to determine relative port identifier values.

Relative initiator port identifier

A relative port identifier for a SCSI initiator port.

Relative target port identifier

A relative port identifier for a SCSI target port.

SCSI device

A device that contains one or more SCSI ports that are connected to a service delivery subsystem and supports a SCSI application protocol.

SCSI device name

A name of a SCSI device that is world wide unique within the protocol of a SCSI domain in which the SCSI device has SCSI ports. The SCSI device name may be made available to other SCSI devices or SCSI ports in protocol specific ways.

SCSI domain

The interconnection of two or more SCSI devices and a service delivery subsystem. A detailed definition of a SCSI Domain may be found in SAM-6.

SCSI initiator device

A SCSI device containing application clients and SCSI initiator ports that originate device service and task management requests to be processed by a SCSI target device and receives device service and task management responses from SCSI target devices.

SCSI initiator port

A SCSI initiator device object acts as the connection between application clients and the service delivery subsystem through which requests and responses are routed.

SCSI port

A port of a SCSI device that connects the application client, device server or task manager to the service delivery subsystem.

SCSI port identifier

A value by which a SCSI port is referenced within a domain. The SCSI port identifier is either an initiator port identifier or a target port identifier.

SCSI port name

A name of a SCSI port that is world wide unique within the protocol of the SCSI domain of that SCSI port. The name may be made available to other SCSI devices or SCSI ports in that SCSI domain in protocol specific ways.

SCSI Ports VPD page

A VPD page that allows retrieval of information about all the SCSI ports in a SCSI target device or SCSI target/initiator device.

SCSI target device

A SCSI device containing logical units and SCSI target ports that receives device service and task management requests for processing and sends device service and task management responses to SCSI initiator devices.

SCSI target port

A SCSI target device object that acts as the connection between device servers and task managers and the service delivery subsystem through which requests and responses are routed.

SCSI transport protocol standard

A SCSI standard that defines a SCSI transport protocol (e.g., SAS, SRP, or SBP-3).

SD Association

The SD Association is an organization that establishes and maintains standards for SD memory card applications

Note 1 to entry: Note 1 to entry: See <https://www.sdcard.org/>.

Secondary target port asymmetric access state

A Secondary target port asymmetric access state is a characteristic indicating a condition that affects the way in which an individual target port participates in its assigned primary target port group (see 3.40).

Secondary target port group

Secondary target port group is one or more target ports that are in the same secondary target port asymmetric access state (see SD Association in this list).

SCSA

Secure Content Storage Association (SCSA) is an organization that develops specifications for protecting digital media content. See <http://www.vidity.com/about-us/>.

Sense data

Data describing an error or exceptional condition that a device server delivers to an application client in the same I_T_L_Q nexus transaction as a CHECK CONDITION status or in response to a REQUEST SENSE command. The format of sense data is defined in SPC-6.

Sense key

The contents of the SENSE KEY field in the sense data.

Service action

A request describing a unit of work to be performed by a device server. A service action is an extension of a command.

Service delivery subsystem

That part of a SCSI I/O system that transmits service requests to a logical unit or SCSI target device and returns logical unit or SCSI target device responses to a SCSI initiator device.

Standby power condition

When a device server is capable of accepting commands, but not capable of processing media access commands.

Status

One byte of response information sent from a device server to an application client upon completion of each command.

Storage array controller

Any combination of an initiator and application clients (see SAM-6) that originates SCSI commands, converts input LUNs to output LUNs, and converts input LBAs to output LBAs. A storage array controller organizes a group of direct-access block devices into various objects (e.g., redundancy groups and volume sets). See SCC-2.

System

One or more SCSI domains operating as a single configuration.

Target device name

A SCSI device name of a SCSI target device or of a SCSI target/initiator device when operating as a SCSI target device.

Target port

Synonymous with SCSI target port.

Target port asymmetric access state

The characteristic that defines the behavior of a target port and the allowable command set for a logical unit when commands and task management functions are routed through the target port maintaining that state.

Target port group

A set of target ports that are in the same target port asymmetric access state at all times.

Target port group asymmetric access state

The target port asymmetric access state common to the set of target ports in a target port group.

Target port identifier

A value by which a SCSI target port is referenced within a SCSI domain.

Target port name

A SCSI port name of a SCSI target port or of a SCSI target/initiator port when operating as a SCSI target port.

Task

An object within a logical unit that represents the work associated with a command or a group of linked commands. A detailed definition of a task may be found in SAM-6.

Task set

A group of tasks within a logical unit, whose interaction is dependent on the task management (queuing) and ACA rules. See SAM-6 and the Control mode page.

TCP port numbers

One of the data needed to establish a TCP connection. TCP port numbers may be assigned to protocols that layer on TCP by the Internet Assigned Numbers Authority. The Internet Assigned Numbers Authority maintains a list of TCP port number assignments at <http://www.iana.org/assignments/port-numbers>.

Third-party command

A command sent to one SCSI device requesting that an operation be performed involving two other SCSI devices (e.g., the EXTENDED COPY command may perform copy operations between two or more SCSI devices none of which are the SCSI device to which the EXTENDED COPY command was sent).

Unit attention condition

A state that a logical unit maintains while it has asynchronous status information to report to the initiator ports associated with one or more I_T nexuses. See SAM-6.

Universal time (UT)

The time at longitude zero, colloquially known as Greenwich Mean Time. See <http://aa.usno.navy.mil/faq/docs/UT.html>.

URI Schemes

The Internet Assigned Numbers Authority maintains a list of schemes for URI and URL names at <http://www.iana.org/assignments/uri-schemes>.

User data

Data contained in logical blocks that is not protection information.

UTF-8

A character set that is a transformation format of the character set defined by ISO 10646. See RFC 2279.

Vendor specific (VS)

Something (e.g., a bit, field, or code value) that is not defined by SPC-6 and may be vendor defined.

Volatile cache memory or Volatile cache

Cache memory that does not retain data through power cycles.

Volatile medium

Medium that does not retain data written to it for a subsequent read operation through power cycles (e.g., a silicon memory device that loses data written to it if device power is lost).

Well known logical unit

A logical unit that only does specific functions. Well known logical units allow an application client to issue requests to receive and manage specific information usually relating to a SCSI target device.

Well known logical unit number (W-LUN)

The logical unit number that identifies a well known logical unit.

XOR operation

Performing an XOR bitwise on two identical-sized multiple-bit input values (e.g., the current value of a logical block and the new value for that logical block). In a storage array implementing a redundancy group, the XOR operation is used in error correction algorithms and may be performed by the storage array controller or by the direct-access block devices.

XOR-protected data

Logical blocks, including user data and protection information, if any, that are part of a redundancy group.

Zero

The logical false condition of a variable.

Zero-padded

A type of field in which unused bytes are placed at the end of the field (i.e., highest offset) and are filled with zeros.

1.2 Symbols and abbreviations

See Table 1 for abbreviations of standards bodies (e.g., ISO). Additional symbols and abbreviations used in the manual include:

Abbreviation	Meaning
<	less than
>	greater than
ACE	Access Control list Entry
ACL	Access Control List
ACA	Auto Contingent Allegiance
ASC	Additional Sense Code
ASCII	American Standard Code for Information Interchange
ASCQ	Additional Sense Code Qualifier
ATA	AT Attachment (see www.t13.org)
CDB	Command Descriptor Block
CRC	Cyclic Redundancy Check
CLIST	logical unit certification list
D_ID	Destination Identifier (defined in FC-FS)
DLIST	data defect list
ECC	error correcting code
EUI-48	Extended Unique Identifier, a 48-bit globally unique identifier
EUI-64	Extended Unique Identifier, a 64-bit globally unique identifier
GLIST	grown defect list
HTTP	Hypertext Transfer Protocol (see RFC 2616)
I/O	input/output
ID	Identifier or Identification
IEC	International Electrotechnical Commission
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
IP	Internet Protocol
IPv4	Internet Protocol version 4
IPv6	Internet Protocol version 6
iSCSI	Internet SCSI
ISO	Organization for International Standards
LBA	Logical Block Address
LSB	Least Significant Bit
LUACD	Logical Unit Access Control Descriptor
LUN	Logical Unit Number
MAM	Medium Auxiliary Memory
MMC-7	SCSI Multi-Media Commands -7
MSB	Most Significant Bit
NAA	Network Address Authority
n/a	not applicable
INCITS	InterNational Committee for Information Technology Standards
OSD	Object-based Storage Devices Commands
OUI	Organizationally Unique Identifier
PLIST	primary defect list
RAID	Redundant Array of Independent Disks
RBC	SCSI Reduced Block Commands
RDMA	Remote Direct Memory Access (see SRP)
RFC	Request For Comments
RMC	SCSI Reduced Multi-Media Commands
SAM-6	SCSI Architecture Model -6
SAS-5	Serial Attached SCSI -5

SAT-5	SCSI / ATA Translation -5
SBC-5	SCSI Block Commands -5
SCSI	The architecture defined by the family of standards described in clause 1
SES-4	SCSI Enclosure Services -4
SPC-6	SCSI Primary Commands -6
SPL-5	SAS Protocol Layer -5
SRP	SCSI RDMA Protocol
SSC-5	SCSI Stream Commands -5
SSP	Serial SCSI Protocol
TCP	Transmission Control Protocol (see RFC 793)
URI	Uniform Resource Identifier (see RFC 2396 and RFC 3305)
URL	Uniform Resource Locator (see RFC 2396 and RFC 3305)
UT	Universal time
USB	Universal Serial Bus (see www.usb.org)
VPD	Vital Product Data
VS	Vendor Specific
W-LUN	Well known logical unit number
ZBC-2	Zoned Block Commands -2

1.3 Keywords

Expected

A keyword used to describe the behavior of the hardware or software in the design models assumed by this manual. Other hardware and software design models may also be implemented.

Ignored

A keyword used to describe an unused bit, byte, word, field or code value. The contents or value of an ignored bit, byte, word, field or code value shall not be examined by the receiving SCSI device and may be set to any value by the transmitting SCSI device.

Invalid

A keyword used to describe an illegal or unsupported bit, byte, word, field or code value. Receipt of an invalid bit, byte, word, field or code value shall be reported as an error.

Mandatory

A keyword indicating an item that is required to be implemented as defined in this manual.

May

A keyword that indicates flexibility of choice with no implied preference (equivalent to “may or may not”).

May not

Keywords that indicate flexibility of choice with no implied preference (equivalent to “may or may not”).

Obsolete

A keyword indicating that an item was defined in prior SCSI standards but has been removed from this manual.

Optional

A keyword that describes features that are not required to be implemented by the standard. However, if any optional feature defined in the standard is implemented, then it shall be implemented as defined in this manual.

Reserved

A keyword referring to bits, bytes, words, fields and code values that are set aside for future standardization. A reserved bit, byte, word or field shall be set to zero, or in accordance with a future extension to this manual. Recipients are not required to check reserved bits, bytes, words or fields for zero values. Receipt of reserved code values in defined fields shall be reported as an error.

Restricted

A keyword referring to bits, bytes, words, and fields that are set aside for use in other SCSI standards. A restricted bit, byte, word, or field shall be treated as a reserved bit, byte, word or field for the purposes of the requirements defined in this manual.

Shall

A keyword indicating a mandatory requirement. Designers are required to implement all such mandatory requirements to ensure interoperability with other products that conform to this manual.

Should

A keyword indicating flexibility of choice with a strongly preferred alternative; equivalent to the phrase “it is strongly recommended.”

Vendor-specific

Something (e.g., a bit, field, or code value) that is not defined by this manual and may be used differently in various implementations.

1.4 Conventions

Certain words and terms used in this manual have a specific meaning beyond the normal English meaning. These words and terms are defined either in this clause or in the text where they first appear. Names of commands, status codes, sense keys, and additional sense codes are in all uppercase (e.g., REQUEST SENSE).

If there is more than one CDB length for a particular command (e.g., MODE SENSE(6) and MODE SENSE(10) and the name of the command is used in a sentence without any CDB length descriptor (e.g., MODE SENSE), then the condition specified in the sentence applies to all CDB lengths for that command.

Names of fields and state variables are in uppercase (e.g. NAME). When a field or state variable name contains acronyms, uppercase letters may be used for readability. Normal case is used when the contents of a field or state variable are being discussed. Fields or state variables containing only one bit are usually referred to as the NAME bit instead of the NAME field.

Normal case is used for words having the normal English meaning.

A binary number is represented in this manual by any sequence of digits comprised of only the Western-Arabic numerals 0 and 1 immediately followed by a lower-case b (e.g., 0101b). Underscores or spaces may be included between characters in binary number representations to increase readability or delineate field boundaries (e.g., 0 0101 1010b or 0_0101_1010b).

A hexadecimal number is represented in this manual by any sequence of digits comprised of only the Western-Arabic numerals 0 through 9 and/or the upper-case English letters A through F immediately followed by a lower-case h (e.g., FA23h). Underscores or spaces may be included in hexadecimal number representations to increase readability or delineate field boundaries (e.g., B FD8CFA23h or B_FD8C_FA23h).

A decimal number is represented in this manual by any sequence of digits comprised of only the Western-Arabic numerals 0 through 9 not immediately followed by a lower-case b or lower-case h (e.g., 25).

When the value of the bit or field is not relevant, x or xx appears in place of a specific value.

This manual uses the ISO convention for representing decimal numbers (e.g., the thousands and higher multiples are separated by a space and a comma is used as the decimal point). Table 1 shows some examples of decimal numbers represented using the ISO and American conventions.

Table 1 ISO v American Numbering Conventions

ISO	American
0,6	0.6
3,141 592 65	3.14159265
1 000	1,000
1 323 462	1,323,462.95

Lists sequenced by letters (e.g., a) red, b) blue, c) green) show no ordering relationship between the listed items. Lists sequenced by numbers (e.g., 1) red, 2) blue, 3) green) show an ordering relationship between the listed items.

If a conflict arises between text, tables or figures, the order of precedence to resolve the conflicts is text, then tables, and finally figures. Not all tables or figures are fully described in the text. Tables show data format and values. Notes do not constitute any requirements for implementors.

2. General Concepts

This manual defines behaviors that are common to all Seagate SCSI device models. This manual defines the SCSI commands that are basic to more than one disk drive model and the SCSI commands that may apply to any SCSI Interface and Serial Attached SCSI (SAS).

2.1 Command Descriptor Block (CDB)

2.1.1 CDB usage and structure

A command is communicated by sending a command descriptor block (CDB) to the device server. For several commands, the CDB is accompanied by a list of parameters in the Data-Out Buffer. See the specific commands for detailed information.

If a logical unit validates reserved CDB fields and receives a reserved field within the CDB that is not zero, then the logical unit shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If a logical unit receives a reserved CDB code value in a field other than the OPERATION CODE field, then the logical unit shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The fixed length CDB formats are described in 2.1.2 The variable length CDB formats are described in 2.1.3. The CDB fields that are common to most commands are described in 2.2. The fields shown in 2.1.2 and 2.1.3 and described in 2.2 are used consistently by most commands. However, the actual usage of any field (except OPERATION CODE and CONTROL) is described in the subclause defining that command. If a device server receives a CDB containing an operation code that is invalid or not supported, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID COMMAND OPERATION CODE.

For all commands, if there is an invalid parameter in the CDB, the device server shall terminate the command without altering the medium.

2.1.2 The fixed length CDB formats

All fixed length CDBs shall have an OPERATION CODE field as their first byte and a CONTROL byte as their last byte. Table 2 shows the typical format of a 6-byte CDB. Table 3 shows the typical format of a 10-byte CDB. Table 4 shows the typical format of a 12-byte CDB. Table 5 shows the format of a 16-byte CDB for commands that provide for a long LBA.

Table 2 Typical CDB for 6-byte commands

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE							
1	Miscellaneous CDB information			(MSB)				
2	LOGICAL BLOCK ADDRESS (if required)							
3								
4	TRANSFER LENGTH (if required) PARAMETER LIST LENGTH (if required) ALLOCATION LENGTH (if required)							
5	CONTROL							

Table 3 Typical CDB for 10-byte commands

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE							
1	Miscellaneous CDB information			SERVICE ACTION (if required)				
2	LOGICAL BLOCK ADDRESS (if required)							
...								
5	(LSB)							
6	Miscellaneous CDB information							
7	TRANSFER LENGTH (if required) PARAMETER LIST LENGTH (if required) ALLOCATION LENGTH (if required)							
8								
9	CONTROL							

Table 4 Typical CDB for 12-byte commands

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE							
1	Miscellaneous CDB information			SERVICE ACTION (if required)				
2	(MSB)							
...	LOGICAL BLOCK ADDRESS (if required)							
5	(LSB)							
6	(MSB)							
...	TRANSFER LENGTH (if required) PARAMETER LIST LENGTH (if required) ALLOCATION LENGTH (if required)							
9	(LSB)							
10	Miscellaneous CDB information							
11	CONTROL							

Table 5 Typical CDB for long LBA 16-byte commands

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE							
1	Miscellaneous CDB information							
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	TRANSFER LENGTH (if required) PARAMETER LIST LENGTH (if required) ALLOCATION LENGTH (if required)							
13	(LSB)							
14	Miscellaneous CDB information							
15	CONTROL							

2.1.3 The variable length CDB formats

The first byte of a variable length CDB shall contain the operation code 7Fh. The CONTROL byte is the second byte in the variable length CDB (see table 6)

Table 6 Typical variable length CDB

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Miscellaneous CDB information							
3	Miscellaneous CDB information							
4	Miscellaneous CDB information							
5	Miscellaneous CDB information							
6	Miscellaneous CDB information							
7	ADDITIONAL CDB LENGTH (n-7)							
8	(MSB)	SERVICE ACTION						(LSB)
9								
10	(MSB)	Service Action specific fields						
...								
n								(LSB)

ADDITIONAL CDB LENGTH field

The ADDITIONAL CDB LENGTH field specifies the number of additional CDB bytes. This value in the ADDITIONAL CDB LENGTH field shall be a multiple of 4. If the number of CDB bytes delivered by the service delivery subsystem is not sufficient to contain the number of bytes specified by the ADDITIONAL CDB LENGTH field, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

SERVICE ACTION field

The SERVICE ACTION field specifies the action being requested by the application client. The SERVICE ACTION field is required in the variable length CDB format and is described in 4.3.4.2. Each service action code description defines a number of service action specific fields that are needed for that service action.

A 32-byte variable length CDB format is defined for long LBA operations (see table 7)

Table 7 Typical variable length CDB for long LBA 32-byte commands

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Miscellaneous CDB information							
3	Miscellaneous CDB information							
4	Miscellaneous CDB information							
5	Miscellaneous CDB information							
6	Miscellaneous CDB information							
7	Additional CDB Length (n-7) [9]							
8	(MSB)	SERVICE ACTION						(LSB)
9								
10	Miscellaneous CDB information		DPO	FUA	Miscellaneous CDB information			
11	Miscellaneous CDB information							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
...								
19								
20	(MSB)	Miscellaneous CDB information						(LSB)
...								
27								
28	(MSB)	TRANSFER LENGTH (if required) PARAMETER LIST LENGTH (if required) ALLOCATION LENGTH (if required)						(LSB)
...								
31								

2.2 Common CDB fields

2.2.1 OPERATION CODE

The first byte of a SCSI CDB shall contain an operation code identifying the operation being requested by the CDB. Some operation codes provide for modification of their operation based on a service action (see 2.2.2). In such cases, the operation code and service action code combine to identify the operation being requested. The location of the SERVICE ACTION field in the CDB varies depending on the operation code value.

The OPERATION CODE (see table 9) of the CDB has a GROUP CODE field and a COMMAND CODE field. The three-bit GROUP CODE field provides for eight groups of command codes. The five-bit COMMAND CODE field provides for thirty-two command codes in each group. A total of 256 possible operation codes exist. Operation codes are defined in this manual and other command standards. The group code value shall determine the length of the CDB (see table 10).

Table 8 OPERATION CODE byte

Bit	7	6	5	4	3	2	1	0
	GROUP CODE			COMMAND CODE				

The value in the GROUP CODE field specifies one of the groups shown in Table 9.

Table 9 Group Code values

Group Code	Meaning	Typical CDB Format
000b	6 byte commands	see Table 2
001b	10 byte commands	see Table 3
010b	10 byte commands	see Table 3
011b	Reserved [a]	
100b	16 byte commands	see Table 5 and Table 6
101b	12 byte commands	see Table 4
110b	Vendor Specific	
111b	Vendor Specific	

[a] The format of the commands using operation code 7Fh is described in 2.1.3. With the exception of operation code 7Fh, all group code 011b operation codes are reserved.

2.2.2 SERVICE ACTION

All CDB formats except the 6-byte format provide for a SERVICE ACTION field containing a coded value identifying a function to be performed under the more general command function specified in the OPERATION CODE field. While the SERVICE ACTION field is defined for CDB formats, it is used as described in this subclause only in those CDB formats that contain a SERVICE ACTION field. When the specific field SERVICE ACTION is not defined in a CDB format, the bits identified as the SERVICE ACTION field in a CDB shall be used or reserved as specified by the particular CDB format.

2.2.3 LOGICAL BLOCK ADDRESS

The logical block addresses on a logical unit or within a volume or partition shall begin with block zero and be contiguous up to the last logical block of that logical unit or within that volume or partition.

A six-byte CDB may contain a 21-bit LOGICAL BLOCK ADDRESS field. The ten-byte and the twelve-byte CDBs may contain 32-bit LOGICAL BLOCK ADDRESS fields. The sixteen-byte CDB has two formats: one allows a 32-bit LOGICAL BLOCK ADDRESS field (see table 5) and the other allows a 64-bit LOGICAL BLOCK ADDRESS field (see table 6). LOGICAL BLOCK ADDRESS fields in additional parameter data have their length specified for each occurrence. See the specific command descriptions.

2.2.4 TRANSFER LENGTH

The TRANSFER LENGTH field specifies the amount of data to be transferred, usually the number of blocks. Some commands use transfer length to specify the requested number of bytes to be sent as defined in the command description.

Commands that use one byte for the TRANSFER LENGTH field may allow up to 256 blocks or 256 bytes of data to be transferred by one command.

In commands that use multiple bytes for the TRANSFER LENGTH field, a transfer length of zero specifies that no data transfer shall take place. A value of one or greater specifies the number of blocks or bytes that shall be transferred. Refer to the specific command description for further information.

2.2.5 PARAMETER LIST LENGTH

The PARAMETER LIST LENGTH field is used to specify the number of bytes sent from the Data-Out Buffer. This field is typically used in CDBs for parameters that are sent to a device server (e.g., mode parameters, diagnostic parameters, log parameters). A parameter list length of zero specifies that no data shall be transferred. This condition shall not be considered as an error, unless otherwise specified.

2.2.6 ALLOCATION LENGTH

The ALLOCATION LENGTH field specifies the maximum number of bytes that an application client has allocated in the Data-In Buffer. An allocation length of zero specifies that no data shall be transferred. This condition shall not be considered as an error. The device server shall terminate transfers to the Data-In Buffer when the number of bytes specified by the ALLOCATION LENGTH field have been transferred or when all available data have been transferred, whichever is less. The allocation length is used to limit the maximum amount of variable length data (e.g., mode data, log data, diagnostic data) returned to an application client. If the information being transferred to the Data-In Buffer includes fields containing counts of the number of bytes in some or all of the data, then the contents of these fields shall not be altered to reflect the truncation, if any, that results from an insufficient ALLOCATION LENGTH value, unless this manual describes the Data-In Buffer format states otherwise.

If the amount of information to be transferred exceeds the maximum value that the ALLOCATION LENGTH field is capable of specifying, the device server shall transfer no data and terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

2.2.7 CONTROL

The CONTROL byte has the same definition for all commands.

All CDBs shall contain a CONTROL byte (see table 10). The location of the CONTROL byte within a CDB depends on the CDB format (see 2.1.2 and 2.1.3).

Table 10 CONTROL byte

Bit	7	6	5	4	3	2	1	0
	Vendor Specific		Reserved			NACA	Obsolete	Obsolete

All SCSI transport protocol standards shall define the functionality needed for a logical unit to implement the NACA bit.

NACA (Normal ACA) bit

The NACA (Normal ACA) bit specifies whether an auto contingent allegiance (ACA) is established if the command returns with CHECK CONDITION status. An NACA bit set to one specifies that an ACA shall be established.

- 0** An NACA bit set to zero specifies that an ACA shall not be established. The actions for ACA are specified in SAM-6. Actions that may be required when an ACA is not established are described in SAM-6. All logical units shall implement support for the NACA value of zero and may support the NACA value of one (i.e., ACA). The ability to support a NACA value of one is indicated with the NORMACA bit in the standard INQUIRY data (see clause 3.8.2)
- 1** If the NACA bit is set to one but the logical unit does not support ACA, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

2.2.8 GROUPING FUNCTION

A grouping function is a function that collects information about attributes associated with commands (i.e., information about commands with the same group value are collected into the specified group). The definition of the attributes and the groups is outside the scope of this manual. Groups are identified with the GROUP NUMBER field in the CDB of certain commands (e.g., the WRITE (10) command (see 3.64)).

The collection of this information is outside the scope of this manual (e.g., the information may not be transmitted using any SCSI protocols).

Support for the grouping function is indicated in the GROUP_SUP bit in the Extended INQUIRY Data VPD page (see 5.4.10).

2.3 Parameter Rounding

Certain parameters sent to a SCSI target port with various commands contain a range of values. Targets may choose to implement only selected values from this range. When the target receives a value that it does not support, it either rejects the command (CHECK CONDITION status with Illegal Request Sense key) or it rounds the value received to a supported value. The target shall reject unsupported values unless rounding is permitted in the description of the parameter.

Rounding of parameter values, when permitted (Rounding is enabled by MODE SELECT command, page code 00h, byte 2, bit 2) shall be performed as follows:

a SCSI target port that receives a parameter value that is not an exact supported value shall adjust the value to one that it supports and shall return CHECK CONDITION status with a sense key of Recovered Error. The additional sense code shall be set to Rounded Parameter. The initiator is responsible to issue an appropriate command to learn what value the target has selected.

Implementor's Note: Generally, the target should adjust maximum-value fields down to the next lower supported value than the one specified by the initiator. Minimum-value fields should be rounded up to the next higher supported value than the one specified by the initiator. In some cases, the type of rounding (up or down) is explicitly specified in the description of the parameter.

2.4 Sense data

2.4.1 Sense data introduction

Sense data shall be returned in the same I_T_L_Q nexus transaction as a CHECK CONDITION status and as parameter data in response to the REQUEST SENSE command. Sense data returned in the same I_T_L_Q nexus transaction as a CHECK CONDITION status shall be either fixed or descriptor format sense data format based on the value of the D_SENSE bit in the Control mode page. The REQUEST SENSE command may be used to request either the fixed format sense data or the descriptor format sense data.

The first byte of all sense data contains the RESPONSE CODE field that indicates the error type and format of the sense data (see table 11).

Table 11 Sense data response codes

Response Code	Error type		Sense data format	
	Description	Reference	Description	Reference
00h - 6Fh	Reserved			
70h	Current	2.4.1.3	Fixed	2.4.1.2
71h	Deferred	2.4.1.4	Fixed	2.4.1.2
72h	Current	2.4.1.3	Descriptor	2.4.1.1
73h	Deferred	2.4.1.4	Descriptor	2.4.1.1
74h - 7Eh	Reserved			
7Fh	Vendor specific			

The RESPONSE CODE field shall be set to 70h in all unit attention sense data in which:

- a) The ADDITIONAL SENSE CODE field is set to 29h; or
- b) The additional sense code is set to MODE PARAMETERS CHANGED.

2.4.1.1 Descriptor format sense data

2.4.1.1.1 Descriptor format sense data overview

The descriptor format sense data for response codes 72h (current errors) and 73h (deferred errors) is defined in table 12.

Table 12 Descriptor format sense data

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved	RESPONSE CODE (72h or 73h)						
1	Reserved				SENSE KEY			
2	ADDITIONAL SENSE CODE							
3	ADDITIONAL SENSE CODE QUALIFIER							
4								
...	Reserved							
6								
7	ADDITIONAL SENSE LENGTH (n-7)							
Sense Data Descriptor(s)								
8	(MSB)	Sense Data Descriptor (first) (see table 13)						(LSB)
...								
...	(MSB)	Sense Data Descriptor (last) (see table 13)						(LSB)
n								

RESPONSE CODE field

The contents of the RESPONSE CODE field indicate the error type and format of the sense data (see 2.4.1). For descriptor format sense data, the RESPONSE CODE field shall be set to 72h or 73h.

SENSE KEY, ADDITIONAL SENSE CODE and ADDITIONAL SENSE CODE QUALIFIER fields

The SENSE KEY, ADDITIONAL SENSE CODE and ADDITIONAL SENSE CODE QUALIFIER fields provide a hierarchy of information. The hierarchy provides a top-down approach for an application client to determine information relating to the error and exception conditions.

SENSE KEY field

The SENSE KEY field indicates generic information describing an error or exception condition. The sense keys are defined in 2.4.1.5.

ASC (ADDITIONAL SENSE CODE) field

The ADDITIONAL SENSE CODE (ASC) field indicates further information related to the error or exception condition reported in the SENSE KEY field. Support of the additional sense codes not required by this manual is optional. A list of additional sense codes is in 2.4.1.5. If the device server does not have further information related to the error or exception condition, the additional sense code shall be set to zero.

ASCQ (ADDITIONAL SENSE CODE QUALIFIER) field

The ADDITIONAL SENSE CODE QUALIFIER (ASCQ) field indicates detailed information related to the additional sense code. If the error or exception condition is reported by the device server, the value returned shall be as specified in 2.4.1.5. If the device server does not have detailed information related to the error or exception condition, the additional sense code qualifier shall be set to zero.

ADDITIONAL SENSE LENGTH field

The ADDITIONAL SENSE LENGTH field indicates the number of additional sense bytes that follow. The additional sense length shall be less than or equal to 244 (i.e., limiting the total length of the sense data to 252 bytes). If the sense data is being returned as parameter data by a REQUEST SENSE command, then the relationship between the ADDITIONAL SENSE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

SENSE DATA DESCRIPTORS field

Sense data descriptors (see table 13) provide specific sense information. A given type of sense data descriptor shall be included in the sense data only when the information it contains is valid.

Table 13 Sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE							
1	ADDITIONAL LENGTH (n-1)							
2	(MSB)							
...	SENSE DATA DESCRIPTOR SPECIFIC							
n								(LSB)

DESCRIPTOR TYPE field

The DESCRIPTOR TYPE field contains a type code (see table 14) that identifies the type of sense data descriptor. No more than one sense data descriptor of each type shall be included in the descriptor format sense data.

Table 14 Sense data descriptor types

Type	Description	Reference
00h	Information	2.4.1.1.2
01h	Command specific information	2.4.1.1.3
02h	Sense key specific	2.4.1.1.4
03h	Field replaceable unit	2.4.1.1.5
04h	Stream commands	SSC-3
05h	Block commands	SBC-5
06h	OSD object identification	OSD
07h	OSD response integrity check value	OSD
08h	OSD attribute identification	OSD
09h	ATA Return	SAT
0Ah	Another Progress indication	2.4.1.1.6
0Bh - 7Fh	Reserved	
80h - FFh	Vendor specific	2.4.1.1.7

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field indicates the number of sense data descriptor specific bytes that follow in the sense data descriptor.

2.4.1.1.2 Information sense data descriptor

The information sense data descriptor (see table 15) provides information that is device-type or command specific and is defined in a command standard.

Table 15 Information sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE (00h)							
1	ADDITIONAL LENGTH (0Ah)							
2	VALID (1b)	Reserved						
3	Reserved							
4	(MSB)							
...	INFORMATION							
11								(LSB)

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE and ADDITIONAL LENGTH fields are described in 2.4.1.1.1. For the information sense data descriptor, the DESCRIPTOR TYPE field shall be set to 00h and the ADDITIONAL LENGTH field shall be set to 0Ah.

VALID bit

The VALID bit shall be set to one.

NOTE In the fixed format sense data, the VALID bit indicates whether the contents of the INFORMATION field is valid as defined by a command standard. Since the contents of the INFORMATION field are valid whenever an information sense data descriptor is included in the sense data, the only legal value for the VALID bit is set to one.

INFORMATION field

The contents of the INFORMATION field are device-type or command specific and are defined in a command standard. When a four byte quantity is stored in the INFORMATION field, the first four bytes shall be zero.

2.4.1.1.3 Command-specific information sense data descriptor

The command-specific information sense data descriptor (see table 16) provides information that depends on the command on which the exception condition occurred.

Table 16 Command-specific information sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE (01h)							
1	ADDITIONAL LENGTH (0Ah)							
2	Reserved							
3	Reserved							
4	(MSB)							
...	COMMAND SPECIFIC INFORMATION							
11								(LSB)

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE and ADDITIONAL LENGTH fields are described in 2.4.1.1.1. For the command-specific information sense data descriptor, the DESCRIPTOR TYPE field shall be set to 01h and the ADDITIONAL LENGTH field shall be set to 0Ah.

COMMAND-SPECIFIC INFORMATION field

The COMMAND-SPECIFIC INFORMATION field contains information that depends on the command on which the exception condition occurred. When a four byte quantity is stored in the COMMAND-SPECIFIC INFORMATION field, the first four bytes shall be zero.

Further meaning for the COMMAND-SPECIFIC INFORMATION field is defined within the command description in the appropriate command standard (e.g., see SBC-5 for the REASSIGN BLOCKS commands, or SPC-6 for the EXTENDED COPY command).

2.4.1.1.4 Sense key specific sense data descriptor**2.4.1.1.4.1 Sense key specific sense data descriptor introduction**

The sense key specific sense data descriptor (see table 17) provides additional information about the exception condition. The format and content of the sense-key specific data depends on the value in the SENSE KEY field (see 2.4.1.1.1).

Table 17 Sense key specific sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE (02h)							
1	ADDITIONAL LENGTH (06h)							
2	Reserved							
3	Reserved							
4	SKSV (1b)							
5	SENSE KEY SPECIFIC							
6								
7	Reserved							

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE and ADDITIONAL LENGTH fields are described in 2.4.1.1.1. For the sense-key specific sense data descriptor, the DESCRIPTOR TYPE field shall be set to 01h and the ADDITIONAL LENGTH field shall be set to 06h.

SKSV (Sense-key specific valid) bit

The sense-key specific valid (SKSV) bit shall be set to one.

NOTE In the fixed format sense data, the SKSV bit indicates whether the contents of the SENSE KEY SPECIFIC field are valid as defined by a command standard. Since the contents of the SENSE KEY SPECIFIC field are valid whenever a sense key specific sense data descriptor is included in the sense data, the only legal value for the SKSV bit is set to one.

The definition of the SENSE KEY SPECIFIC field (see table 18) is determined by the value of the SENSE KEY field (see 2.4.1.1.1).

Table 18 Sense key specific field definitions

Sense Key	Sense Key Specific Field Definition	Reference
ILLEGAL REQUEST	Field pointer	2.4.1.1.4.2
HARDWARE ERROR, MEDIUM ERROR, or RECOVERED ERROR	Actual retry count	2.4.1.1.4.3
NO SENSE or NOT READY	Progress indication	2.4.1.1.4.4
COPY ABORTED	Segment pointer	2.4.1.1.4.5
UNIT ATTENTION	Unit attention condition queue overflow	2.4.1.1.4.6
All other sense keys	The sense key specific sense data descriptor shall not appear in the descriptor format sense data and the SKSV bit (see 2.4.1.2) shall be set to zero in the fixed format sense data.	

2.4.1.1.4.2 Field pointer sense key specific data

If the SENSE KEY is ILLEGAL REQUEST, then the SENSE KEY SPECIFIC field shall be as shown in table 19.

Table 19 Field pointer sense key specific data

Bit Byte	7	6	5	4	3	2	1	0
0	SKSV (1b)	C/D	Reserved		BPV	BIT POINTER		
1	(MSB) _____							
2	FIELD POINTER							(LSB)

SKSV bit

The SKSV bit is described in 2.4.1.1.4.1 for descriptor format sense data and in 2.4.1.2 for fixed format sense data.

C/D (Command Data) bit

- 0** A C/D bit set to zero indicates that the illegal parameter is in the data parameters sent by the application client in the Data-Out Buffer.
- 1** A C/D bit set to one indicates that the illegal parameter is in the CDB.

BPV (Bit Pointer Valid) bit

- 0** A BPV bit set to zero indicates that the value in the BIT POINTER field is not valid.
- 1** A BPV bit set to one indicates that the BIT POINTER field specifies which bit of the byte designated by the FIELD POINTER field is in error. When a multiple-bit field is in error, the BIT POINTER field shall point to the first bit (i.e., the left-most bit) of the field.

FIELD POINTER field

The FIELD POINTER field indicates which byte of the CDB or of the parameter data was in error. Bytes are numbered starting from zero, as shown in the tables describing the commands and parameters. When a multiple-byte field is in error, the field pointer shall point to the first byte (i.e., the left-most byte) of the field. If several consecutive bytes are reserved, each shall be treated as a single-byte field.

NOTE The bytes identified as being in error are not necessarily the bytes that need to be changed to correct the problem.

2.4.1.1.4.3 Actual retry count sense key specific data

If the sense key is HARDWARE ERROR, MEDIUM ERROR, or RECOVERED ERROR, then the SENSE KEY SPECIFIC field shall be as shown in table 20.

Table 20 Actual retry count sense key specific data

Bit Byte	7	6	5	4	3	2	1	0
0	SKSV (1b)	Reserved						
1	(MSB)	ACTUAL RETRY COUNT						
2		(LSB)						

SKSV bit

The SKSV bit is described in 2.4.1.1.4.1 for descriptor format sense data and in 2.4.1.2 for fixed format sense data.

ACTUAL RETRY COUNT field

The ACTUAL RETRY COUNT field returns vendor specific information on the number of retries of the recovery algorithm used in attempting to recover an error or exception condition.

NOTE This field should be computed in the same way as the retry count fields within the Read-Write Error Recovery mode page.

2.4.1.1.4.4 Progress indication sense key specific data

If the sense key is NO SENSE or NOT READY, the SENSE KEY SPECIFIC field shall be as shown in table 21.

Table 21 Progress indication sense key specific data

Bit Byte	7	6	5	4	3	2	1	0
0	SKSV (1b)	Reserved						
1	(MSB)	PROGRESS INDICATION						
2		(LSB)						

SKSV bit

The SKSV bit is described in 2.4.1.1.4.1 for descriptor format sense data and in 2.4.1.2 for fixed format sense data.

PROGRESS INDICATION field

The PROGRESS INDICATION field is a percent complete indication in which the returned value is a numerator that has 65 536 (10000h) as its denominator. The progress indication shall be based upon the total operation.

NOTE The progress indication should be time related, however this is not an absolute requirement. (E.g., since format time varies with the number of defects encountered, etc., it is reasonable for the device server to assign values to various steps within the process. The granularity of these steps should be small enough to provide reasonable assurances to the application client that progress is being made.)

2.4.1.1.4.5 Segment pointer sense key specific data

If the sense key is COPY ABORTED, the SENSE KEY SPECIFIC field shall be as shown in table 22.

Table 22 Segment pointer sense key specific data

Bit Byte	7	6	5	4	3	2	1	0
0	SKSV (1b)	Reserved	SD	Reserved	BPV	BIT POINTER		
1	(MSB) _____							
2	FIELD POINTER							_____ (LSB)

SKSV bit

The SKSV bit is described in 2.4.1.1.4.1 for descriptor format sense data and in 2.4.1.2 for fixed format sense data.

SD (SEGMENT DESCRIPTOR) bit

The SD bit indicates whether the field pointer is relative to the start of the parameter list or to the start of a segment descriptor.

- 0** An SD bit set to zero indicates that the field pointer is relative to the start of the parameter list.
- 1** An SD bit set to one indicates that the field pointer is relative to the start of the segment descriptor indicated by the third and fourth bytes of the COMMAND-SPECIFIC INFORMATION field.

BPV (BIT POINTER VALID) bit

- 0** A BPV bit set to zero indicates that the value in the BIT POINTER field is not valid.
- 1** A BPV bit set to one indicates that the BIT POINTER field specifies which bit of the byte designated by the FIELD POINTER field is in error.

When a multiple-bit field is in error, the BIT POINTER field shall point to the most-significant (i.e., left-most) bit of the field.

FIELD POINTER field

The FIELD POINTER field indicates which byte of the parameter list or segment descriptor was in error.

If the parameter list is in excess of 65 528 bytes in length and SD is set to zero, the FIELD POINTER value may not fit in two bytes provided by the sense key specific sense data descriptor.

2.4.1.1.4.6 Unit attention condition queue overflow sense key specific data

If the sense key is UNIT ATTENTION, the SENSE KEY SPECIFIC field shall be as shown in table 23

Table 23 Unit attention condition queue overflow sense key specific data

Bit Byte	7	6	5	4	3	2	1	0
0	SKSV (1b)	Reserved						OVERFLOW
1	Reserved							
2	Reserved							

SKSV bit

The SKSV bit is described in 2.4.1.1.4.1 for descriptor format sense data and in 2.4.1.2 for fixed format sense data.

OVERFLOW bit

- 0** An OVERFLOW bit set to zero indicates that the unit attention condition queue has not overflowed.
- 1** An OVERFLOW bit set to one indicates that the unit attention condition queue has overflowed.

2.4.1.1.5 Field replaceable unit sense data descriptor

The field replaceable unit sense data descriptor (see table 24) provides information about a component that has failed.

Table 24 Field replaceable unit sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE (03h)							
1	ADDITIONAL LENGTH (02h)							
2	Reserved							
3	FIELD REPLACEABLE UNIT CODE							

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE and ADDITIONAL LENGTH fields are described in 2.4.1.1.1. For the field replaceable unit sense data descriptor, the DESCRIPTOR TYPE field shall be set to 03h and the ADDITIONAL LENGTH field shall be set to 02h.

FIELD REPLACEABLE UNIT CODE field

Non-zero values in the FIELD REPLACEABLE UNIT CODE field are used to identify a component that has failed. A value of zero in this field indicates that no specific component has been identified to have failed or that the data is not available. The format of this information is not specified by this manual. Additional information about the field replaceable unit may be available in the ASCII Information VPD page, if supported by the device server.

2.4.1.1.6 Progress indication sense data descriptor

If the sense key is set to NO SENSE or NOT READY, the progress indication sense data descriptor (see table 25) may be used to provide a progress indication for one operation other than the one described by the non-descriptor fields in 2.4.1.1.1. The sense data should include one progress indication sense data descriptor for each operation for which the device server is able to report progress other than the operation described by the non-descriptor fields in 2.4.1.1.1.

Table 25 Progress indications sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0	
0	DESCRIPTOR TYPE (0Ah)								
1	ADDITIONAL LENGTH (06h)								
2	sense key								
3	additional sense code								
4	additional sense code qualifier								
5	Reserved								
6	MSB	progress indication						LSB	
7									

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE field and ADDITIONAL LENGTH field are described in 2.4.1.1.1.

For the progress indications sense data descriptor:

- the DESCRIPTOR TYPE field shall be set to 0Ah; and
- the ADDITIONAL LENGTH field shall be set to 06h.

SENSE KEY field

The SENSE KEY field indicates the operation for which this progress indication sense data descriptor provides a progress indication. A list of sense key values is in 2.4.1.5.

ADDITIONAL SENSE CODE field

The ADDITIONAL SENSE CODE (ASC) field indicates the operation for which this progress indication sense data descriptor provides a progress indication. A list of additional sense codes is in 2.4.1.6.

ADDITIONAL SENSE CODE QUALIFIER field

The ADDITIONAL SENSE CODE QUALIFIER (ASCQ) field indicates detailed information related to the additional sense code for the operation for which this progress indication sense data descriptor provides a progress indication. The value returned in the ADDITIONAL SENSE CODE QUALIFIER (ASCQ) field shall be as specified in 2.4.1.6.

PROGRESS INDICATION field

The PROGRESS INDICATION field indicates a percent complete for the operation indicated by the SENSE KEY field, the ADDITIONAL SENSE CODE field, and the ADDITIONAL SENSE CODE QUALIFIER field. The value in the PROGRESS INDICATION field shall be as defined in 2.4.1.1.4.4.

2.4.1.1.7 Vendor specific sense data descriptors

Vendor specific sense data descriptors (see table 26) contain vendor specific data that further defines the nature of the exception condition.

Table 26 Vendor specific sense data descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	DESCRIPTOR TYPE (80h - FFh)							
1	ADDITIONAL LENGTH (n-1)							
2	(MSB)							
...	VENDOR SPECIFIC							
n								(LSB)

DESCRIPTOR TYPE and ADDITIONAL LENGTH fields

The DESCRIPTOR TYPE and ADDITIONAL LENGTH fields are described in 2.4.1.1.1. For the vendor specific sense data descriptor, the DESCRIPTOR TYPE field shall be set to a value between 80h and FFh, inclusive.

2.4.1.2 Fixed format sense data

The fixed format sense data for response codes 70h (current errors) and 71h (deferred errors) is defined in table 27.

Table 27 Fixed format sense data

Bit Byte	7	6	5	4	3	2	1	0
0	VALID	RESPONSE CODE (70h OR 71h)						
1	Obsolete							
2	FILEMARK	EOM	ILI	Reserved	SENSE KEY			
3	(MSB)							
...	INFORMATION							
6	(LSB)							
7	ADDITIONAL SENSE LENGTH (n-7)							
8	(MSB)							
...	COMMAND-SPECIFIC INFORMATION							
11	(LSB)							
12	ADDITIONAL SENSE CODE							
13	ADDITIONAL SENSE CODE QUALIFIER							
14	FIELD REPLACEABLE UNIT CODE							
15	SKSV	(MSB)						
...	SENSE KEY SPECIFIC							
17	(LSB)							
18	(MSB)							
...	ADDITIONAL SENSE BYTES							
n	(LSB)							

VALID bit

- 0** A VALID bit set to zero indicates that the INFORMATION field is not defined in this manual or any command standard.
- 1** A VALID bit set to one indicates the INFORMATION field contains valid information as defined in this manual or a command standard.

RESPONSE CODE field

The contents of the RESPONSE CODE field indicate the error type and format of the sense data (see 2.4.1). For fixed format sense data, the RESPONSE CODE field shall be set to 70h or 71h.

FILE MARK bit

See the SSC-3 READ and SPACE commands for examples of FILEMARK bit usage.

EOM (End-of-Medium) bit

See the SSC-3 READ, SPACE, and WRITE commands for examples of end-of-medium (EOM) bit usage.

ILI (Incorrect length indicator) Bit

See the SBC-5 READ LONG, SBC-5 WRITE LONG, and SSC-3 READ commands and for examples of incorrect length indicator (ILI) bit usage.

SENSE KEY, ADDITIONAL SENSE CODE, and ADDITIONAL SENSE CODE QUALIFIER fields

The SENSE KEY, ADDITIONAL SENSE CODE, and ADDITIONAL SENSE CODE QUALIFIER fields are described in 4.5.2.1.

INFORMATION field

The contents of the INFORMATION field is device-type or command specific and is defined within the appropriate standard for the device type or command of interest. targets shall implement the INFORMATION field. Unless specified otherwise, this field contains:

- a) the unsigned LOGICAL BLOCK ADDRESS associated with the sense key, for direct-access devices (device type 0), write-once devices (device type 4), CD-ROM devices (device type 5), and optical memory devices (device type 7);
- b) the difference (residue) of the requested length minus the actual length in either bytes or blocks, as determined by the command, for sequential-access devices (device type 1), printer devices (device type 2), processor devices (device type 3) and some direct access device commands, except as defined for d) below. Negative values are indicated by two's complement notation;
- c) the difference (residue) of the requested number of blocks minus the actual number of blocks copied or compared for the current segment descriptor of a COPY, COMPARE, COPY AND VERIFY, or Extended COPY command; or
- d) for sequential-access devices operating in buffered modes 1h or 2h that detect an unrecoverable write error when unwritten data blocks, filemarks, or setmarks remain in the buffer, the value of the information field for all commands shall be:
 - A) the total number of data blocks, filemarks, and setmarks in the buffer if the device is in fixed block mode (block length field of the MODE SENSE block descriptor is non-zero and the fixed bit of the WRITE command is one); or
 - B) the number of bytes in the buffer, including filemarks and setmarks, if the device is in variable mode (the fixed bit of the WRITE command is zero).

ADDITIONAL SENSE LENGTH field

The ADDITIONAL SENSE LENGTH field indicates the number of additional sense bytes that follow. The additional sense length shall be less than or equal to 244 (i.e., limiting the total length of the sense data to 252 bytes). If the sense data is being returned as parameter data by a REQUEST SENSE command, then the relationship between the ADDITIONAL SENSE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

COMMAND-SPECIFIC INFORMATION field

The COMMAND-SPECIFIC INFORMATION field contains information that depends on the command on which the exception condition occurred.

FIELD REPLACEABLE UNIT CODE field

The FIELD REPLACEABLE UNIT CODE field is described in 2.4.1.1.5.

SKSV (Sense-key Specific Valid) bit

- 1** A sense-key specific valid (SKSV) bit set to one indicates the SENSE KEY SPECIFIC field contains valid information as defined in this manual.
- 0** An SKSV bit set to zero indicates that the SENSE KEY SPECIFIC field is not as defined by this manual.

SENSE KEY SPECIFIC field

The SENSE KEY SPECIFIC field is described in 2.4.1.1.4.

The additional sense bytes may contain vendor specific data that further defines the nature of the exception condition.

2.4.1.3 Current errors

Response codes 70h and 72h (current error) indicate that the sense data returned is the result of an error or exception condition on the task that returned the CHECK CONDITION status or a protocol specific failure condition. This includes errors generated during processing of the command. It also includes errors not related to any command that are detected during processing of a command (e.g., disk servo-mechanism failure, off-track errors, or power-up test errors).

2.4.1.4 Deferred errors

Response codes 71h and 73h (deferred error) indicate that the sense data returned is the result of an error or exception condition that occurred during processing of a previous command for which GOOD, CONDITION MET, INTERMEDIATE, and INTERMEDIATE-CONDITION MET status has already been returned. Such commands are associated with the use of the immediate bit and with some forms of caching. Device servers that implement these features shall implement deferred error reporting.

The deferred error may be indicated by returning CHECK CONDITION status to an application client accessed through a defined I_T nexus as described in this subclause.

If the task terminates with CHECK CONDITION status and the sense data describes a deferred error, the command for the terminated task shall not have been processed. After the device server detects a deferred error condition, it shall return a deferred error according to the following rules:

- a) If no external intervention is necessary to recover a deferred error, a deferred error indication shall not be returned unless required by the error handling parameters of a MODE SELECT command. The occurrence of the error may be logged;
- b) If it is possible to associate a deferred error with an I_T nexus and with a particular function or a particular subset of data, and the error is either unrecovered or required to be reported by the mode parameters, then a deferred error indication shall be returned for a command received on the I_T nexus associated with the deferred error. If an application client request received on an I_T nexus other than the I_T nexus associated with the deferred error attempts to access the particular function or subset of data associated with the deferred error and the TST field equals 000b, then the device server shall respond to the command with a BUSY or ACA ACTIVE status according to the requirements in SAM-6. If an application client request received on an I_T nexus other than the I_T nexus associated with the deferred error attempts to access the particular function or subset of data associated with the deferred error and the TST field equals 001b, then the command attempting the access shall not be blocked by the deferred error and the cause of the deferred error may result in an error being reported for the command attempting the access;
- b) If the device server is unable to associate a deferred error with an I_T nexus or with a particular subset of data, the device server shall return a deferred error for one command received on each I_T nexus. If multiple deferred errors have accumulated for an I_T nexus, only the last error shall be returned;
- b) If the SCSI target device is unable to associate a deferred error with a particular logical unit, it shall establish a deferred error for every logical unit and shall return the deferred error for one command for each logical unit received on each appropriate I_T nexus; or
- b) If a task has never entered the enabled task state, and a deferred error occurs, the task shall be terminated with CHECK CONDITION status and deferred error information returned in the sense data. If a deferred error occurs after a task has entered the enabled task state and the task is affected by the error, the task shall be terminated with CHECK CONDITION status and the current error information shall be returned in the sense data. In this case, if the current error information does not adequately define the deferred error condition, a deferred error may be returned after the current error information has been returned. If a deferred error occurs after a task has entered the enabled task state and the task completes successfully, the device server may choose to return the deferred error information after the completion of the current command in conjunction with a subsequent command that has not begun processing.

NOTE A deferred error may indicate that an operation was unsuccessful long after GOOD status was returned. If the application client is unable to replicate or recover from other sources the data that is being written using cached or buffered write operations, then synchronization commands should be performed before the critical data is destroyed. This is necessary for actions taken when deferred errors occur in the storing of the data. The synchronizing process should provide the necessary commands to allow returning CHECK CONDITION status and subsequent returning of deferred error sense information after all cached or buffered operations are completed.

2.4.1.5 Sense key and sense code definitions

The sense keys are defined in table 28.

Table 28 Sense key descriptions

Sense Key	Description
0h	NO SENSE: Indicates that there is no specific sense key information to be reported. This may occur for a successful command or for a command that receives CHECK CONDITION status because one of the FILEMARK, EOM, or ILI bits is set to one.
1h	RECOVERED ERROR: Indicates that the command completed successfully, with some recovery action performed by the device server. Details may be determined by examining the additional sense bytes and the INFORMATION field. When multiple recovered errors occur during one command, the choice of which error to report (e.g., first, last, most severe) is vendor specific.
2h	NOT READY: Indicates that the logical unit is not accessible. Operator intervention may be required to correct this condition.
3h	MEDIUM ERROR: Indicates that the command terminated with a non-recovered error condition that may have been caused by a flaw in the medium or an error in the recorded data. This sense key may also be returned if the device server is unable to distinguish between a flaw in the medium and a specific hardware failure (i.e., sense key 4h).
4h	HARDWARE ERROR: Indicates that the device server detected a non-recoverable hardware failure (e.g., controller failure, device failure, or parity error) while performing the command or during a self test.
5h	<p>ILLEGAL REQUEST: Indicates that:</p> <ul style="list-style-type: none"> a) The command was addressed to an incorrect logical unit number (see SAM-6); b) The command had an invalid task attribute (see SAM-6); c) The command was addressed to a logical unit whose current configuration prohibits processing the command; d) There was an illegal parameter in the CDB; or e) There was an illegal parameter in the additional parameters supplied as data for some commands (e.g., PERSISTENT RESERVE OUT). <p>If the device server detects an invalid parameter in the CDB, it shall terminate the command without altering the medium. If the device server detects an invalid parameter in the additional parameters supplied as data, the device server may have already altered the medium.</p>
6h	UNIT ATTENTION: Indicates that a unit attention condition has been established (e.g., the removable medium may have been changed, a logical unit reset occurred). See SAM-6.
7h	DATA PROTECT: Indicates that a command that reads or writes the medium was attempted on a block that is protected. The read or write operation is not performed.
8h	BLANK CHECK: Indicates that a write-once device or a sequential-access device encountered blank medium or format-defined end-of-data indication while reading or that a write-once device encountered a non-blank medium while writing.
9h	VENDOR SPECIFIC: This sense key is available for reporting vendor specific conditions.
Ah	COPY ABORTED: Indicates an EXTENDED COPY command was aborted due to an error condition on the source device, the destination device, or both.
Bh	ABORTED COMMAND: Indicates that the device server aborted the command. The application client may be able to recover by trying the command again.
Ch	Reserved
Dh	VOLUME OVERFLOW: Indicates that a buffered SCSI device has reached the end-of-partition and data may remain in the buffer that has not been written to the medium. One or more RECOVER BUFFERED DATA command(s) may be issued to read the unwritten data from the buffer. (See SSC-3.)
Eh	MISCOMPARE: Indicates that the source data did not match the data read from the medium.
Fh	COMPLETED: Indicates there is command completed sense data (see SAM-6) to be reported. This may occur for a successful command.

2.4.1.6 Additional Sense and Additional Sense Qualifier codes

Table 29 lists the Additional Sense (ASC) and Additional Sense Qualifier (ASCQ) codes. Code values are in hexadecimal. ANSI standard SPC-6 lists a more complete table.

NOTE Table 29 is for reference only, as not all drives covered by this manual support all of the codes listed. Codes without sense key references may or may not be supported.

Table 29 Additional Sense and Additional Sense Qualifier codes

ASC (byte 12)	ASCQ (byte 13)	Description	Sense Key
00	00	No Additional Sense Information	0
01	00	No Index/Logical Block Signal	4
02	00	No SEEK Complete	4
03	00	Peripheral Device Write Fault	1, 3, 4
03	86	Write Fault Data Corruption	
04	00	Logical Unit Not Ready, Cause Not Reportable	2
04	01	Logical Unit Not Ready, Becoming Ready	2
04	02	Logical Unit Not Ready, START UNIT Required	2
04	03	Logical Unit Not Ready, Manual Intervention Required	2
04	04	Logical Unit Not Ready, Format in Progress	2
04	09	Logical Unit Not Ready, Self Test in Progress	2
04	0A	Logical Unit Not Ready, NVC recovery in progress after and exception event	2
04	11	Logical Unit Not Ready, Notify (Enable Spinup) required	2
04	22	Logical unit not ready, power cycle required	2
04	F0	Logical unit not ready, super certify in progress	2
08	00	Logical Unit Communication Failure	9, B
08	01	Logical Unit Communication Time-Out	B
08	02	Logical Unit Communication Parity Error	
09	00	Track Following Error	1, 3, 4
09	01	Servo Fault	1, 4
09	04	Head Select Fault	3, 4
09	0D	Write to at least one copy of a redundant file failed	1
09	0E	Redundant files have < 50% good copies	1
09	F8	Calibration is needed but the QST is set without the Recal Only bit	1
09	FF	Servo Cal completed as part of self-test	1
0A	00	Error Log Overflow	
0A	01	Failed to write super certify log file	3
0A	02	Failed to read super certify log file	3
0B	00	Aborted Command	B
0B	01	Warning—Specified Temperature Exceeded	1, 6
0B	02	Warning, Enclosure Degraded	1
0C	00	Write Error	3
0C	01	Write Error Recovered With Auto-Reallocation	1
0C	02	Write Error—Auto Reallocation Failed	3
0C	03	Write Error—Recommend Reassignment	3

Table 29 Additional Sense and Additional Sense Qualifier codes

ASC (byte 12)	ASCQ (byte 13)	Description	Sense Key
0C	FF	Write Error—Too many error recovery revs	3
0D	00	Volume Overflow Constants	D
0E	00	Data Miscompare	E
10	00	ID CRC Or ECC Error	
11	00	Unrecovered Read Error	1, 3
11	01	Read Retries Exhausted	
11	02	Error Too Long To Correct	
11	04	Unrecovered Read Error—Auto Reallocation Failed	3
11	FF	Unrecovered Read Error—Too many error recovery revs	3
12	00	Address Mark Not Found For ID Field	
12	01	Recovered Data Without ECC Using Previous Logical Block ID	
12	02	Recovered Data With ECC Using Previous Logical Block ID	
14	00	Logical Block Not Found	
14	01	Record Not Found	3
15	00	Random Positioning Error	
15	01	Mechanical Positioning Error	1, 3, 4
15	02	Positioning Error Detected By Read Of Medium	
16	00	Data Synchronization Mark Error	1, 3, 4
17	00	Recovered Data With No Error Correction Applied	
17	01	Recovered Data Using Retries	1
17	02	Recovered Data Using Positive Offset	1
17	03	Recovered Data Using Negative Offset	1
17	05	Recovered Data Using Previous Logical Block ID	
17	06	Recovered Data Without ECC—Data Auto Reallocated	
18	00	Recovered Data With ECC	1
18	01	Recovered Data With ECC And Retries Applied	1
18	02	Recovered Data With ECC And/Or Retries, Data Auto-Reallocated	1
18	05	Recovered Data—Recommand Reassignment	
18	06	Recovered Data Using ECC and Offsets	
18	07	Recovered Data With ECC—Data Rewritten	1
19	00	Defect List Error	1, 4
19	01	Defect List Not Available	
19	02	Defect List Error In Primary List	
19	03	Defect List Error in Grown List	
19	0E	Fewer than 50% Defect List Copies	
1A	00	Parameter List Length Error	5
1B	00	Synchronous Data Transfer Error	
1C	00	Defect List Not Found	1, 4
1C	01	Primary Defect List Not Found	
1C	02	Grown Defect List Not Found	

Table 29 Additional Sense and Additional Sense Qualifier codes

ASC (byte 12)	ASCQ (byte 13)	Description	Sense Key
1C	83	Seagate Unique Diagnostic Code	
1D	00	Miscompare During Verify Operation	E
1F	00	Number of Defects Overflows the Allocated Space That The Read Defect Command Can Handle	1
20	00	Invalid Command Operation Code	5
20	F3	Invalid linked command operation code	5
21	00	Logical Block Address Out Of Range	D
24	00	Invalid Field In CDB	5
24	01	Illegal Queue Type for CDB (Low priority commands must be SIMPLE queue)	5
24	F0	Invalid LBA in linked command	5
24	F2	Invalid linked command operation code	5
24	F3	Illegal G->P operation request	5
25	00	Logical Unit Not Supported	5
26	00	Invalid Field In Parameter List	5
26	01	Parameter Not Supported	5
26	02	Parameter Value Invalid	5
26	03	Invalid Field Parameter—Threshold Parameter	5
26	04	Invalid Release of Active Persistent Reserve	5
26	05	Fail to read valid log dump data	5
26	97	Invalid Field Parameter—TMS Firmware Tag	
26	98	Invalid Field Parameter—Check Sum	
26	99	Invalid Field Parameter—Firmware Tag	
27	00	Write Protected	7
29	00	Flashing LED occurred	4
29	00	Power On, Reset, Or Bus Device Reset Occurred	6
29	01	Power-On Reset Occurred	6
29	02	SCSI Bus Reset Occurred	6
29	03	Bus Device Reset Function Occurred	6
29	04	Internal Reset Occurred	6
29	05	Transceiver Mode Changed To Single-Ended	6
29	06	Transceiver Mode Changed To LVD	6
29	07	Write Log Dump data to disk successful OR IT Nexus Loss	6
29	08	Write Log Dump data to disk fail	6
29	09	Write Log Dump Entry information fail	6
29	0A	Reserved disk space is full	6
29	0B	SDBP test service contained an error, examine status packet(s) for details	6
29	0C	SDBP incoming buffer overflow (incoming packet too big)	6
29	CD	Flashing LED occurred. (Cold reset)	6
29	CE	Flashing LED occurred. (Warm reset)	6
2A	01	Mode Parameters Changed	6
2A	02	Log Parameters Changed	6

Table 29 Additional Sense and Additional Sense Qualifier codes

ASC (byte 12)	ASCQ (byte 13)	Description	Sense Key
2A	03	Reservations preempted	6
2A	04	Reservations Released	6
2A	05	Registrations Preempted	6
2C	00	Command Sequence Error	5
2F	00	Tagged Commands Cleared By Another Initiator	6
31	00	Medium Format Corrupted	3
31	01	Corruption in R/W format request	3
31	91	Corrupt World Wide Name (WWN) in drive information file	3
32	00	No Defect Spare Location Available	4
32	01	Defect List Update Error	3, 4, 5
32	02	No Spares Available—Too Many Defects On One Track	
32	03	Defect list longer than allocated memory	3
33	00	Flash not ready for access	3
35	00	Unspecified Enclosure Services Failure	4
35	01	Unsupported Enclosure Function	5
35	02	Enclosure Services Unavailable	2
35	03	Enclosure Transfer Failure	4
35	04	Enclosure Transfer Refused	4
37	00	Parameter Rounded	1
3D	00	Invalid Bits In Identify Message	
3E	03	Logical Unit Failed Self Test	4
3E	00	Logical Unit Has Not Self Configured Yet	
3F	00	Target Operating Conditions Have Changed	6
3F	01	Device internal reset occurred	6
3F	02	Changed Operating Definition	6
3F	05	Device Identifier Changed	6
3F	0F	Echo buffer overwritten	B
3F	80	Buffer contents have changed	1
3F	90	Invalid APM Parameters	
3F	91	World Wide Name (WWN) Mismatch	6
40	01	DRAM Parity Error	1, 4
40	02	Spinup Error recovered with retries	1
42	00	Power-On Or Self-Test Failure	4
42	0A	Port A failed loopback test	4
42	0B	Port B failed loopback test	4
43	00	Message Reject Error	B
44	00	Internal Target Failure	1, 3, 4
44	F2	Data Integrity Check Failed on verify	4
44	F6	Data Integrity Check Failed during write	4
44	FF	XOR CDB check error	4

Table 29 Additional Sense and Additional Sense Qualifier codes

ASC (byte 12)	ASCQ (byte 13)	Description	Sense Key
45	00	Select/Reselection Failure	B
47	00	SCSI Parity Error	B
47	03	Information Unit CRC Error	B
48	00	Initiator Detected Error Message Received	B
49	00	Invalid Message Received	B
4B	00	Data Phase Error	B
4B	01	Invalid transfer tag	B
4B	02	Too many write data	B
4B	03	ACK NAK Timeout	B
4B	04	NAK received	B
4B	05	Data Offset error	B
4B	06	Initiator response timeout	B
4C	00	Logical Unit Failed Self-Configuration	
4E	00	Overlapped Commands Attempted	B
55	01	XOR Cache is Not Available	
55	04	PRKT table is full	5
5B ¹	00	Log Exception	
5B*	01	Threshold Condition Met	
5B*	02	Log Counter At Maximum	
5B*	03	Log List Codes Exhausted	
5C	00	RPL Status Change	6
5C	01	Spindles Synchronized	
5C	02	Spindles Not Synchronized	
5D	00	Failure Prediction Threshold Exceeded	1, 6
5D	FF	False Failure Prediction Threshold Exceeded	1, 6
65	00	Voltage Fault	4
80	00	General Firmware Error Qualifier	9
80	86	IOEDC Error on Read	9
80	87	IOEDC Error on Write	9
80	88	Host Parity Check Failed	9
80	89	IOEDC Error on Read Detected by Formatter	9
80	8A	Host FIFO Parity Error detected by Common Buffer	9
80	8B	Host FIFO Parity Error detected by frame buffer logic	9
80	8C	Host Data Frame Buffer Parity Error	9
81	00	Reassign Power—Fail Recovery Failed	
81	00	LA Check Error, LCM bit = 0	4
81	00	LA Check Error	B
B4	00	Unreported Deferred Errors have been logged on log page 34h	6

[1] Can be supported, but is a factory installed option.

3. Direct Access Block commands (SPC-6 and SBC-5)

This clause describes the commands supported by Seagate Disk Drives.

Commands that have been supported prior to this manual being produced and that are now indicated as obsolete will be described in this clause as obsolete. However, a description will be provided for such commands.

Commands that have been declared obsolete by the T10 committee and were never supported by Seagate are not included in this manual. Commands that have not been supported in the past, but may be supported in the near future will be included in this manual.

This clause contains information about the commands used by Serial Attached SCSI disk drives. This clause is organized to provide rapid access to command information.

Two types of commands are supported by the drive: commands for all devices; and commands for direct access devices. The individual Product Manuals for each Seagate model drive list the Commands and parameter pages that the particular drive supports.

Table 30 Commands sorted by command name

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
BACKGROUND CONTROL	9Eh/15h		x	3.1
CHANGE DEFINITION ^[2]	40h	x		3.2
FORMAT UNIT	04h		x	3.3
GET LBA STATUS (16)	9Eh/12h		x	3.4
GET LBA STATUS (32)	7Fh/0012h		x	3.5
GET PHYSICAL ELEMENT STATUS	9Eh/17h		x	3.6
GET STREAM STATUS	9Eh/16h		x	3.7
INQUIRY	12h	x		3.8
LOG SELECT	4Ch	x		3.9
LOG SENSE	4Dh	x		3.10
MODE SELECT (6)	15h	x		3.11
MODE SELECT (10)	55h	x		3.12
MODE SENSE (6)	1Ah	x		3.13
MODE SENSE (10)	5Ah	x		3.14
PERSISTENT RESERVE IN	5Eh	x		3.15
PERSISTENT RESERVE OUT	5Fh	x		3.16
READ (6) ^[2]	08h		x	3.17
READ (10)	28h		x	3.18
READ (12)	A8h		x	3.19
READ (16)	88h		x	3.20
READ (32)	7Fh/0009h		x	3.21
READ BUFFER (10)	3Ch	x		3.22
READ BUFFER (16)	9Bh	x		3.23

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
READ CAPACITY (10)	25h		x	3.24
READ CAPACITY (16)	9Eh/10h		x	3.25
READ DEFECT DATA (10)	37h		x	3.26
READ DEFECT DATA (12)	B7h		x	3.27
READ LONG (10) ^[2]	3Eh		x	3.28
READ LONG (16) ^[2]	9Eh/11h		x	3.29
REASSIGN BLOCKS	07h		x	3.30
RECEIVE DIAGNOSTIC RESULTS	1Ch	x		3.31
RELEASE (6) ^[2]	17h	x		3.32
RELEASE (10) ^[2]	57h	x		3.33
REMOVE ELEMENT AND TRUNCATE	9Eh/18h		x	3.34
REPORT IDENTIFYING INFORMATION	A3h/05h	x		3.35
REPORT LUNS	A0h	x		3.36
REPORT SUPPORTED OPERATIONS CODES	A3h/0Ch	x		3.37
REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS	A3h/0Dh	x		3.38
REPORT TIMESTAMP	A3h/0Fh	x		3.39
REQUEST SENSE	03h	x		3.40
RESERVE (6) ^[2]	16h	x		3.41
RESERVE (10) ^[2]	56h	x		3.42
RESTORE ELEMENTS AND REBUILD	9Eh/19h		x	3.43
REZERO UNIT ^[2]	01h		x	3.44
SANITIZE	48h		x	3.45
SECURITY PROTOCOL IN	A2h	x		3.46
SECURITY PROTOCOL OUT	B5h	x		3.47
SEEK (6) ^[2]	0Bh		x	3.48
SEEK EXTENDED (10) ^[2]	2Bh		x	3.49
SEND DIAGNOSTIC	1Dh	x		3.50
SET IDENTIFYING INFORMATION	A4h/06h	x		3.51
SET TIMESTAMP	A4h/0Fh	x		3.52
START/STOP UNIT	1Bh		x	3.53
STREAM CONTROL	9Eh/14h		x	3.54
SYNCHRONIZE CACHE (10)	35h		x	3.55
SYNCHRONIZE CACHE (16)	91h		x	3.56

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
TEST UNIT READY	00h	x		3.57
UNMAP	42h		x	3.58
VERIFY(10)	2Fh		x	3.59
VERIFY (12)	AFh		x	3.60
VERIFY (16)	8Fh		x	3.61
VERIFY (32)	7Fh/000Ah		x	3.62
WRITE (6) ^[2]	0Ah		x	3.63
WRITE (10)	2Ah		x	3.64
WRITE (12)	AAh		x	3.65
WRITE (16)	8Ah		x	3.66
WRITE (32)	7Fh/000Bh		x	3.67
WRITE AND VERIFY (10)	2Eh		x	3.68
WRITE AND VERIFY (12)	A Eh		x	3.69
WRITE AND VERIFY (16)	8Eh		x	3.70
WRITE AND VERIFY (32)	7Fh/000Ch		x	3.71
WRITE ATOMIC (16)	9Ch		x	3.72
WRITE ATOMIC (32)	7Fh/0018h		x	3.73
WRITE BUFFER	3Bh	x		3.74
WRITE LONG	3Fh		x	3.75
WRITE LONG (16)	9Fh/11h		x	3.76
WRITE SAME (10)	41h		x	3.77
WRITE SAME (16)	93h		x	3.78
WRITE SAME (32)	7Fh/000Dh		x	3.79
WRITE STREAM (16)	9Ah		x	3.80
WRITE STREAM (32)	7Fh		x	3.81

[1] Some commands are defined by a combination of operation code and service action.
The operation code value is shown preceding the slash and the service action value is shown after the slash.

[2] Command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

Table 31 Commands sorted by operation code

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
TEST UNIT READY	00h	x		3.57
REZERO UNIT ^[2]	01h		x	3.43
REQUEST SENSE	03h	x		3.40
FORMAT UNIT	04h		x	3.3
REASSIGN BLOCKS	07h		x	3.30
READ (6) ^[2]	08h		x	3.17
WRITE (6) ^[2]	0Ah		x	3.63
SEEK (6) ^[2]	0Bh		x	3.48
INQUIRY	12h	x		3.8
MODE SELECT (6)	15h	x		3.11
RESERVE (6) ^[2]	16h	x		3.41
RELEASE (6) ^[2]	17h	x		3.32
MODE SENSE (6)	1Ah	x		3.13
START/STOP UNIT	1Bh		x	3.53
RECEIVE DIAGNOSTIC RESULTS	1Ch	x		3.31
SEND DIAGNOSTIC	1Dh	x		3.50
READ CAPACITY (10)	25h		x	3.24
READ (10)	28h		x	3.18
WRITE (10)	2Ah		x	3.64
SEEK EXTENDED (10) ^[2]	2Bh		x	3.49
WRITE AND VERIFY (10)	2Eh		x	3.68
VERIFY(10)	2Fh		x	3.59
SYNCHRONIZE CACHE (10)	35h		x	3.55
READ DEFECT DATA (10)	37h		x	3.26
WRITE BUFFER	38h	x		3.74
READ BUFFER (10)	3Ch	x		3.22
READ LONG (10) ^[2]	3Eh		x	3.28
WRITE LONG	3Fh		x	3.75
CHANGE DEFINITION ^[2]	40h	x		3.2
WRITE SAME (10)	41h		x	3.77
UNMAP	42h		x	3.58
SANITIZE	48h		x	3.45

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
LOG SELECT	4Ch	x		3.9
LOG SENSE	4Dh	x		3.10
MODE SELECT (10)	55h	x		3.12
RESERVE (10) ^[2]	56h	x		3.42
RELEASE (10) ^[2]	57h	x		3.33
MODE SENSE (10)	5Ah	x		3.14
PERSISTENT RESERVE IN	5Eh	x		3.15
PERSISTENT RESERVE OUT	5Fh	x		3.16
WRITE STREAM (32)	7Fh		x	3.81
READ (32)	7Fh/0009h		x	3.21
VERIFY (32)	7Fh/000Ah		x	3.62
WRITE (32)	7Fh/000Bh		x	3.67
WRITE AND VERIFY (32)	7Fh/000Ch		x	3.71
WRITE SAME (32)	7Fh/000Dh		x	3.79
GET LBA STATUS (32)	7Fh/0012h		x	3.5
WRITE ATOMIC (32)	7Fh/0018h		x	3.73
READ (16)	88h		x	3.20
WRITE (16)	8Ah		x	3.66
WRITE AND VERIFY (16)	8Eh		x	3.70
VERIFY (16)	8Fh		x	3.61
SYNCHRONIZE CACHE (16)	91h		x	3.56
WRITE SAME (16)	93h		x	3.78
WRITE STREAM (16)	9Ah		x	3.80
READ BUFFER (16)	9Bh	x		3.23
WRITE ATOMIC (16)	9Ch		x	3.72
READ CAPACITY (16)	9Eh/10h		x	3.25
READ LONG (16) ^[2]	9Eh/11h		x	3.29
GET LBA STATUS (16)	9Eh/12h		x	3.4
STREAM CONTROL	9Eh/14h		x	3.54
BACKGROUND CONTROL	9Eh/15h		x	3.1
GET STREAM STATUS	9Eh/16h		x	3.7
GET PHYSICAL ELEMENT STATUS	9Eh/17h		x	3.6
REMOVE ELEMENT AND TRUNCATE	9Eh/18h		x	3.34

Command name	OP code ^[1]	Command type		Clause Reference
		All devices	Direct access devices	
RESTORE ELEMENTS AND REBUILD	9Eh/19h		x	3.43
WRITE LONG (16)	9Fh/11h		x	3.76
REPORT LUNS	A0h	x		3.36
SECURITY PROTOCOL IN	A2h	x		3.46
REPORT IDENTIFYING INFORMATION	A3h/05h	x		3.34
REPORT SUPPORTED OPERATIONS CODES	A3h/0Ch	x		3.37
REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS	A3h/0Dh	x		3.38
REPORT TIMESTAMP	A3h/0Fh	x		3.39
SET IDENTIFYING INFORMATION	A4h/06h	x		3.51
SET TIMESTAMP	A4h/0Fh	x		3.52
READ (12)	A8h		x	3.19
WRITE (12)	AAh		x	3.65
WRITE AND VERIFY (12)	A Eh		x	3.69
VERIFY (12)	A Fh		x	3.60
SECURITY PROTOCOL OUT	B5h	x		3.47
READ DEFECT DATA (12)	B7h		x	3.27

- [1] Some commands are defined by a combination of operation code and service action. The operation code value is shown preceding the slash and the service action value is shown after the slash.
- [2] Command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

3.1 BACKGROUND CONTROL command

The BACKGROUND CONTROL command (see table 32) is used to request that the device server start or stop host initiated advanced background operations (see 5.3.8), if any.

This command uses the SERVICE ACTION IN (16) CDB format (see SBC-5 - Annex A.2).

Table 32 BACKGROUND CONTROL command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (15h)				
2	BO_CTL		Reserved					
3	BO_TIME							
4	Reserved							
...								
14	CONTROL							
15								

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 32.

SERVICE ACTION field

The SERVICE ACTION field is defined in defined in 2.2.2 and set to the value defined in table 32.

BO_CTL field

The background operation control (BO_CTL) field specifies that the device server shall control host initiated advanced background operations as described in SBC-5. The BO_CTL field is described in Table 33.

Table 33 BO_CTL field

Code	Description
00b	Do not change host initiated advanced background operations.
01b	Start host initiated advanced background operations.
10b	Stop host initiated advanced background operations.
11b	Reserved

BO_TIME field

The background operation time (BO_TIME) field specifies the maximum time that the device server shall have to perform host initiated advanced background operations in units of 100 ms (see SBC-5). The BO_TIME field is ignored if the BO_CTL field is not set to 01b. A BO_TIME field set to 00h specifies that there is no limit to the time that the device server may perform host initiated advanced background operations.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.2 CHANGE DEFINITION command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The CHANGE DEFINITION command (see table) is used to modify the operating definition of the device server(s) with respect to commands from the sending initiator or with respect to commands from all initiators.

Table 34 CHANGE DEFINITION command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (40h)							
1	Reserved							
2	Reserved							SAVE
3	Reserved	DEFINITION PARAMETER						
4	Reserved							
5	Reserved							
6	Reserved							
7	Reserved							
8	PARAMETER DATA LENGTH							
9	CONTROL							

If reservations are active, they shall affect the execution of the CHANGE DEFINITION command as follows. If the SCSI device does not allow different operating definitions for each initiator, a reservation conflict shall occur when a CHANGE DEFINITION command is received from an initiator other than the one holding a logical unit reservation. If any initiator has an extent or element reservation on an SCSI device, no other initiator may affect the operating definition of the initiator holding the reservation by use of the CHANGE DEFINITION command.

SAVE bit

- 0** A save control bit (SAVE) of zero indicates that the device server shall not save the operating definition.
- 1** A Save bit of one indicates that the device server shall save the operating definition in non-volatile memory.

The definition parameter field is defined in Table 35.

Table 35 Definition parameter field

Value	Meaning of definition parameter
00h	Use current operating definition
03h	SCSI-2 operating definition
04h	SCSI-3 operating definition
01 - 02h	Reserved for historical uses
05 - 3Eh	Reserved
3Fh	Manufacturer default definition
40 - 7Fh	Vendor specific

The current operating definition parameter values establish operating definitions compatible with the applicable SCSI standard.

PARAMETER DATA LENGTH field

The parameter data length field specifies the length in bytes of the parameter data that shall be transferred from the application client to the device server. A parameter data length of zero indicates that no data shall be transferred. This condition shall not be considered as an error. Parameter data length values greater than zero indicate the number of bytes of parameter data that shall be transferred.

The parameter data is vendor-specific.

- 1) The parameter data may be used to specify a password to validate an operating definition change.

The CHANGE DEFINITION command causes one of the operating definition modifications listed below:

- a) Change the operating definition of a logical unit relative to all initiators in the system: In this case, the target is capable of maintaining a separate operating definition for each logical unit relative to all initiators in the system; or
- b) Change the operating definition of all logical units in the target relative to all initiators in the system: In this case, the target is capable of maintaining only one operating definition.
- 2) This manual does not provide a direct means to determine which of the above methods has been implemented. An indirect means of determining which method is implemented exists in that the device server is required to inform affected initiators of operating definition changes via the unit attention condition.
- 3) The modifications listed c) and d) above may result in incompatibilities if other initiators are using a different SCSI version.

The operating definition is modified after successful completion of the command. The application client should verify the new operating definition by issuing an INQUIRY command requesting the implemented operating definition page (see SCSI -3).

- 4) The method of changing the operating definition is vendor-specific. Some implementations may require that the target's operating mode be reinitialized as if a power-up or hard reset had occurred. Other implementations may modify only those operating definitions that are affected by the CHANGE DEFINITION command.

If the CHANGE DEFINITION command is not executed successfully for any reason, the operating definition shall remain the same as it was before the CHANGE DEFINITION command was attempted. If it is impossible to return to the previous operating definition, a unit attention condition shall be generated.

- 5) The present operating definition of the target may always be interrogated through the INQUIRY command. When an SCSI-3 target has its operating definition changed to an older SCSI operating definition, certain changes are needed to promote compatibility with preexisting older SCSI initiators.

After a power-on condition or a hard reset condition, the target shall set its initial operating definition of the device server(s) to the last saved value (if saving is implemented), or its default value (if saving is not implemented).

CONTROL byte

The CONTROL byte is defined in 2.2.7..

3.3 FORMAT UNIT command

3.3.1 FORMAT UNIT command overview

The FORMAT UNIT command (see table 36) requests that the device server format the medium into application client accessible logical blocks as specified in the number of blocks and block length values received in the last mode parameter block descriptor (see 5.3.4) in a MODE SELECT command (see 3.11 and 3.12). In addition, the device server may certify the medium and create control structures for the management of the medium and defects. The degree that the medium is altered by this command is vendor-specific.

If a device server receives a FORMAT UNIT command before receiving a MODE SELECT command with a mode parameter block descriptor the device server shall use the number of blocks and block length at which the logical unit is currently formatted (i.e., no change is made to the number of blocks and the block length of the logical unit during the format operation).

Table 36 FORMAT UNIT command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (04h)							
1	FMTINFO		LONG-LIST	FMTDATA	CMPLIST	DEFECT LIST FORMAT		
2	Vendor Specific							
3	Reserved							
4	Reserved					FFMT		
5	CONTROL							

While performing a format operation, the device server shall respond to commands attempting to enter into the task set except INQUIRY commands, REPORT LUNS commands, and REQUEST SENSE commands with CHECK CONDITION status with the sense key set to NOT READY and the additional sense code set to LOGICAL UNIT NOT READY, FORMAT IN PROGRESS. Handling of commands already in the task set is vendor-specific. If the device server receives an INQUIRY command, a REPORT LUNS command, or a REQUEST SENSE command, then the device server shall process the command. The device server shall return data for an INQUIRY command based on the condition of the SCSI target device before beginning the FORMAT UNIT command (i.e., INQUIRY data shall not change until after successful completion of a format operation). The processing of commands in the task set when a FORMAT UNIT command is received is vendor specific.

FMTPINFO (Format Protection Information) field

The format protection information (FMTPINFO) field (see table 42) in combination with the PROTECTION FIELD USAGE field (see 3.3.3) specifies whether or not the device server enables or disables the use of protection information.

When protection information is written during a FORMAT UNIT command (i.e., the FMTPINFO bit is set to one) protection information shall be written to a default value of FFFFFFFF_FFFFFFFFh.

LONGLIST bit

If the FMTDATA bit is set to zero, the LONGLIST bit shall be ignored.

- 0** A LONGLIST bit set to zero specifies that the parameter list, if any, contains a short parameter list header as defined in table 40.
- 1** A LONGLIST bit set to one specifies that the parameter list, if any, contains a long parameter list header as defined in table 41.

FMTDATA (Format Data)

- 0** A format data (FMTDATA) bit set to zero specifies that no parameter list be transferred from the data-out buffer.
- 1** A FMTDATA bit set to one specifies that the FORMAT UNIT parameter list (see table 39) shall be transferred from the data-out buffer. The parameter list consists of a parameter list header, followed by an optional initialization pattern descriptor, followed by an optional defect list.

CMPLST (Complete List)

If the FMTDATA bit is set to zero, the CMPLIST bit shall be ignored.

- 0** A complete list (CMPLST) bit set to zero specifies that the defect list included in the FORMAT UNIT parameter list shall be used in an addition to the existing list of defects. As a result, the device server shall construct a new GLIST that contains:
 - a) the existing GLIST;
 - b) the DLIST, if it is sent by the application client; and
 - c) the CLIST, if certification is enabled (i.e., the device server may add any defects it detects during the format operation).
- 1** A CMPLST bit set to one specifies that the defect list included in the FORMAT UNIT parameter list is a complete list of defects. Any existing GLIST shall be discarded by the device server. As a result, the device server shall construct a new GLIST that contains:
 - a) the DLIST, if it is sent by the application client; and
 - b) the CLIST, if certification is enabled (i.e., the device server may add any defects it detects during the format operation).

DEFECT LIST FORMAT field

The DEFECT LIST FORMAT field specifies the format of the address descriptors in the defect list if the FMTDATA bit is set to one (see table 37).

Table 37 defines the address descriptor usage for the FORMAT UNIT command.

Table 37 FORMAT UNIT command address descriptor usage (Sheet 1 of 2)

Field in the FORMAT UNIT CDB			DEFECT LIST LENGTH field in the parameter list header	Type [a]	Comments [f]
FMTDATA	CMPLST	DEFECT LIST FORMAT			
0	Any	000b	Not available	M	Vendor-specific defect information
1	0	000b (short block)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]
1	0	001b (long block)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]
1	0	010b (long block)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]
1	0	011b (long block)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]
1	0	100b (bytes from index)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]

[a] M = implementation is mandatory. O = implementation is optional.

[b] No DLIST is included in the parameter list.

[c] A DLIST is included in the parameter list. The device server shall add the DLIST defects to the new GLIST.

[d] The device server shall add existing GLIST defects to the new GLIST (i.e., use the existing GLIST).

[e] The device server shall not add existing GLIST defects to the new GLIST (i.e., discard the existing GLIST).

[f] All the options described in this table cause a new GLIST to be created during processing of the FORMAT UNIT command as described in the text.

Table 37 FORMAT UNIT command address descriptor usage (Sheet 2 of 2)

Field in the FORMAT UNIT CDB			DEFECT LIST LENGTH field in the parameter list header	Type [a]	Comments [f]
FMTDATA	CMPLST	DEFECT LIST FORMAT			
1	0	101b (physical sector)	Zero	O	See [b] and [d]
	1			O	See [b] and [e]
	0		Nonzero	O	See [c] and [d]
	1			O	See [c] and [e]
1	0	110b (vendor specific)	Vendor specific	O	
	1			O	
All others				Reserved.	
<p>[a] M = implementation is mandatory. O = implementation is optional.</p> <p>[b] No DLIST is included in the parameter list.</p> <p>[c] A DLIST is included in the parameter list. The device server shall add the DLIST defects to the new GLIST.</p> <p>[d] The device server shall add existing GLIST defects to the new GLIST (i.e., use the existing GLIST).</p> <p>[e] The device server shall not add existing GLIST defects to the new GLIST (i.e., discard the existing GLIST).</p> <p>[f] All the options described in this table cause a new GLIST to be created during processing of the FORMAT UNIT command as described in the text.</p>					

FFMT field

The fast format (FFMT) field is described in table 38.

Table 38 FFMT field description

Code	Description	Support
00b	The device server initializes the medium as specified in the CDB and parameter list before completing the format operation. After successful completion of the format operation, read commands and verify commands are processed as described in SBC-5.	Mandatory
01b	The device server initializes the medium without overwriting the medium (i.e., resources for managing medium access are initialized and the medium is not written) before completing the format operation. After successful completion of the format operation, read commands and verify commands are processed as described in SBC-5. If the device server determines that the options specified in this FORMAT UNIT command are incompatible with the read command and verify command requirements described in SBC-5, then the device server shall not perform the format operation and shall terminate the FORMAT UNIT command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FAST FORMAT COMBINATION.	Optional
10b	The device server initializes the medium without overwriting the medium (i.e., resources for managing medium access are initialized and the medium is not written) before completing the format operation. After successful completion of the format operation, read commands and verify commands are processed as described in SBC-5.	Optional
11b	Reserved	

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.3.2 FORMAT UNIT parameter list

3.3.2.1 FORMAT UNIT parameter list overview

Table 39 defines the FORMAT UNIT parameter list.

Table 39 FORMAT UNIT parameter list

Bit Byte	7	6	5	4	3	2	1	0
	Parameter List Header (see table 40 or table 41 in 3.3.3)							
	Initialization Pattern Descriptor (if any) (see table 43, in 3.3.4)							
	Defect List (if any)							

PARAMETER LIST HEADER field

The PARAMETER LIST HEADER is defined in 3.3.3.

INITIALIZATION PATTERN DESCRIPTOR field

The INITIALIZATION PATTERN DESCRIPTOR, if any, is defined in 3.3.4.

DEFECT LIST field

The DEFECT LIST, if any, contains address descriptors (see table 37) each specifying a location on the medium that the device server shall exclude from the application client accessible part. This is called the DLIST.

3.3.3 Parameter list header

The parameter list headers (see table 40 and table 41) provide several optional format control parameters. Device servers that implement these headers provide the application client additional control over the use of the four defect sources, and the format operation. If the application client attempts to select any function not implemented by the device server, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

The short parameter list header (see table 40) is used if the LONGLIST bit is set to zero in the FORMAT UNIT CDB.

Table 40 Short parameter list header

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved					PROTECTION FIELDS USAGE			
1	FOV	DPRY	DCRT	STPF	IP	Obsolete	IMMED	Vendor specific	
2	(MSB) _____								
3	DEFECT LIST LENGTH							(LSB)	

The long parameter list header (see table 41) is used if the LONGLIST bit is set to one in the FORMAT UNIT CDB.

Table 41 Long parameter list header

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved					PROTECTION FIELDS USAGE			
1	FOV	DPRY	DCRT	STPF	IP	Obsolete	IMMED	Vendor specific	
2	Reserved								
3	P_I_INFORMATION				PROTECTION INTERVAL EXPONENT				
4	(MSB) _____								
...	DEFECT LIST LENGTH							_____	
7								(LSB)	

The PROTECTION FIELD USAGE field in combination with the FMTPINFO field (see table 42) specifies the requested protection type (see SBC-5).

Table 42 FMTPINFO field and PROTECTION FIELDS USAGE field (Sheet 1 of 2)

Device server indication		Application client specification		Description
SPT ^[a]	PROTECT ^[b]	FMTPI INFO	PROTECTION FIELD USAGE	
xxx b	0	00 b	000 b	The logical unit shall be formatted to type 0 protection ^[c] (see SBC-5) resulting in the P_TYPE field ^[d] being set to 000b.
xxx b	0	00 b	>000 b	Illegal ^[e]
xxx b	0	01 b	xxx b	Illegal ^[f]
xxx b	0	1x b	xxx b	Illegal ^[f]
xxx b	1	00 b	000 b	The logical unit shall be formatted to type 0 protection ^[c] (see SBC-5) resulting in the P_TYPE field ^[d] being set to 000b.
xxx b	1	00 b	>000 b	Illegal ^[e]
xxx b	1	0 b	xxx b	Illegal ^[f]
000 b 001 b 011 b 111 b	1	10 b	000 b	The logical unit shall be formatted to type 1 protection ^[g] (see SBC-5) resulting in the P_TYPE field ^[d] being set to 000b.
000 b 001 b 011 b 111 b	1	10 b	>000 b	Illegal ^[e]
000 b	1	11 b	xxx b	Illegal ^[f]
000 b 001 b 011 b 111 b	1	11 b	000 b	The logical unit shall be formatted to type 2 protection ^[g] (see SBC-5) resulting in the P_TYPE field ^[d] being set to 001b.
001 b 010 b	1	11 b	>000 b	Illegal ^[e]
011 b 100 b	1	11 b	000 b	Illegal ^[e]
011 b 100 b 101 b 111 b	1	11 b	001 b	The logical unit shall be formatted to type 3 protection. ^[g] (see SBC-5) resulting in the P_TYPE field ^[d] being set to 010b.
011 b 100 b 101 b 111 b	1	11 b	>001 b	Illegal ^[e]
110 b	1	1x b	xxx b	Reserved

Table 42 FMTPINFO field and PROTECTION FIELDS USAGE field (Sheet 2 of 2)

Device server indication		Application client specification		Description
SPT ^[a]	PROTECT ^[b]	FMT PINFO	PROTECTION FIELD USAGE	
[a]	See the Extended INQUIRY Data VPD page (see 5.4.10) for the definition of the SPT field.			
[b]	See the standard INQUIRY data (see 3.8.2) for the definition of the PROTECT bit.			
[c]	The device server shall format the medium to the block length specified in the mode parameter block descriptor of the mode parameter header (see 5.3.3).			
[d]	See the READ CAPACITY command (see 3.24.1) for the definition of the P_TYPE field.			
[e]	The device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.			
[f]	The device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.			
[g]	The device server shall format the medium to the block length specified in the mode parameter block descriptor of the mode parameter header plus eight (e.g., if the block length is 512, then the formatted block length is 520). Following a successful format, the PROT_EN bit in the READ CAPACITY (16) parameter data (see 3.25.2) indicates whether protection information (see SBC-5) is enabled.			

FOV (Format Options Valid) bit

- 0** A format options valid (FOV) bit set to zero specifies that the device server shall use its default settings for the DPRY, DCRT, STPF, and IP bits. If the FOV bit is set to zero, the application client shall set these bits to zero. If the FOV bit is set to zero and any of the other bits listed in this paragraph are not set to zero, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.
- 1** A FOV bit set to one specifies that the device server shall examine the values of the DPRY, DCRT, STPF, and IP bits. When the FOV bit is set to one, the DPRY, DCRT, STPF, and IP bits are defined as follows.

DPRY (Disable Primary) bit

- 0** A disable primary (DPRY) bit set to zero specifies that the device server shall not use parts of the medium identified as defective in the PLIST for application client accessible logical blocks. If the device server is not able to locate the PLIST or it is not able to determine whether a PLIST exists, it shall take the action specified by the STPF bit.
- 1** A DPRY bit set to one specifies that the device server shall not use the PLIST to identify defective areas of the MEDIUM. The PLIST shall not be deleted.

DCRT (disable certification) bit

- 0** A disable certification (DCRT) bit set to zero specifies that the device server shall perform a vendor-specific medium certification operation to generate a CLIST.
- 1** A DCRT bit set to one specifies that the device server shall not perform any vendor-specific medium certification process or format verification operation.

STPF (Stop Format) bit

The stop format (STPF) bit controls the behavior of the device server if one of the following events occurs:

- a) The device server has been requested to use the PLIST (i.e., the DPRY bit is set to zero) or the GLIST (i.e., the CMLST bit is set to zero) and the device server is not able to locate the list or determine whether the list exists; or
- b) The device server has been requested to use the PLIST (i.e., the DPRY bit is set to zero) or the GLIST (i.e., the CMLST bit is set to zero), and the device server encounters an error while accessing the defect list.
- 0** A STPF bit set to zero specifies that, if one or both of these events occurs, the device server shall continue to process the FORMAT UNIT command. The device server shall return CHECK CONDITION status at the completion of the FORMAT UNIT command with the sense key set to RECOVERED ERROR and the additional sense code set to either DEFECT LIST NOT FOUND if the condition described in item a) occurred, or DEFECT LIST ERROR if the condition described in item b) occurred.
- 1** A STPF bit set to one specifies that, if one or both of these events occurs, the device server shall terminate the FORMAT UNIT command with CHECK CONDITION status and the sense key shall be set to MEDIUM ERROR with the additional sense code set to either DEFECT LIST NOT FOUND if the condition described in item a) occurred, or DEFECT LIST ERROR if the condition described in item b) occurred.

NOTE The use of the FMTDATA bit, the CMPLST bit, and the parameter list header allow the application client to control the source of the defect lists used by the FORMAT UNIT command. Setting the DEFECT LIST LENGTH field to zero allows the application client to control the use of PLIST and CLIST without having to specify a DLIST.

IP (initialization pattern) bit

- 0** An initialization pattern (IP) bit set to zero specifies that an initialization pattern descriptor is not included and that the device server shall use its default initialization pattern.
- 1** An IP bit set to one specifies that an initialization pattern descriptor (see 3.3.4) is included in the FORMAT UNIT parameter list following the parameter list header.

IMMED (Immediate) bit

- 0** An immediate (IMMED) bit set to zero specifies that the device server shall return status after the format operation has completed.
- 1** An IMMED bit value set to one specifies that the device server shall return status after the entire parameter list has been transferred.

P_I_INFORMATION field

The P_I_INFORMATION field shall be set to zero.

PROTECTION INTERVAL EXPONENT field

For a type 1 protection information request, if the PROTECTION INTERVAL EXPONENT field is not set to zero, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

For a type 2 protection or a type 3 protection format request, the protection interval exponent determines the length of user data to be sent before protection information is transferred (i.e., the protection information interval).

The protection information interval is calculated as follows:

$$\text{Equation 1 protection information interval} = \text{logical block length} / 2^{(\text{protection interval exponent})}$$

where:

logical block length is the length in bytes of a logical block as specified in the mode parameter block descriptor (see 5.3.4.1)

protection interval exponent is the contents of the PROTECTION INTERVAL EXPONENT field

If the protection information interval calculates to a value that is not an even number (e.g., $520/2^3 = 65$) or not a whole number (e.g., $520/2^4 = 32.5$ and $520/2^{10} = 0.508$), then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

DEFECT LIST LENGTH field

The DEFECT LIST LENGTH field specifies the total length in bytes of the defect list (i.e., the address descriptors) that follows and does not include the initialization pattern descriptor, if any. The formats for the address descriptor(s) are shown in table 45.

Address descriptors should be in ascending order. More than one physical or logical block may be affected by each address descriptor. If the address descriptors are not in the required order, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

3.3.4 Initialization pattern descriptor

The initialization pattern descriptor specifies that the device server initialize logical blocks to a specified pattern. The initialization pattern descriptor (see table 43) is sent to the device server as part of the FORMAT UNIT parameter list.

Table 43 Initialization pattern descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	OBSOLETE		SI	Reserved				
1	INITIALIZATION PATTERN TYPE							
2	(MSB)	INITIALIZATION PATTERN LENGTH (n - 3)						(LSB)
3	INITIALIZATION PATTERN							
4								
...								
n								

SI (Security Initialize) bit

This bit is not supported on Seagate products. Customers should use the SANITIZE command to satisfy secure initialization requirements.

INITIALIZATION PATTERN TYPE field

The INITIALIZATION PATTERN TYPE field (see table 44) specifies the type of pattern the device server shall use to initialize each logical block within the application client accessible part of the medium. All bytes within a logical block shall be written with the initialization pattern. The initialization pattern is modified by the IP MODIFIER field as described in table 44.

Table 44 INITIALIZATION PATTERN TYPE field

Code	Description
00h	Use a default initialization pattern [a]
01h	Repeat the pattern specified in the INITIALIZATION PATTERN field as required to fill the logical block [b]
02h - 7Fh	Reserved
80h - FFh	Vendor-specific
[a]	If the INITIALIZATION PATTERN LENGTH field is not set to zero, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.
[b]	If the INITIALIZATION PATTERN LENGTH field is set to zero, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

INITIALIZATION PATTERN LENGTH field

The INITIALIZATION PATTERN LENGTH field specifies the number of bytes contained in the INITIALIZATION PATTERN field. If the initialization pattern length exceeds the current block length the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

INITIALIZATION PATTERN field

The INITIALIZATION PATTERN field specifies the initialization pattern.

3.3.5 Address descriptor formats

3.3.5.1 Address descriptor formats overview

This subclause describes the address descriptor formats used in the FORMAT UNIT command, the READ DEFECT DATA commands (see 3.26 and 3.27), and the Translate Address diagnostic pages (see 5.1.3) of the SEND DIAGNOSTIC command and the RECEIVE DIAGNOSTIC RESULTS command.

The format type of an address descriptor is specified with:

- the DEFECT LIST FORMAT field in the CDB, for the FORMAT UNIT command and the READ DEFECT DATA commands;
- the SUPPLIED FORMAT field, for the SEND DIAGNOSTIC command Translate Address diagnostic page; or
- the TRANSLATE FORMAT field, for the RECEIVE DIAGNOSTIC RESULTS command Translate Address diagnostic page.

Table 45 defines the types of address descriptors.

Table 45 Address descriptor formats

Format type	Description	Reference
000b	Short block format address descriptor	3.3.5.2
001b	Extended bytes from index address descriptor ^[a]	3.3.5.3
010b	Extended physical sector address descriptor ^[a]	3.3.5.4
011b	Long block format address descriptor	3.3.5.5
100b	Bytes from index format address descriptor	3.3.5.6
101b	Physical sector format address descriptor	3.3.5.7
110b	Vendor-specific	
All others	Reserved	

[a] This address descriptor format type is defined for direct access block devices using rotating media (see SBC-5).

3.3.5.2 Short block format address descriptor

A format type of 000b specifies the short block format address descriptor defined in table 46.

Table 46 Short block format address descriptor (000b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	SHORT BLOCK ADDRESS							
3	(LSB)							

SHORT BLOCK ADDRESS field

For the FORMAT UNIT command, the SHORT BLOCK ADDRESS field contains the four-byte LBA of a defect. For the READ DEFECT DATA commands, the SHORT BLOCK ADDRESS field contains a vendor-specific four-byte value. For the Translate Address diagnostic pages, the SHORT BLOCK ADDRESS field contains a four-byte LBA or a vendor-specific four byte value that is greater than the capacity of the medium.

3.3.5.3 Extended bytes from index address descriptor

A format type of 001b specifies the extended bytes from index address descriptor defined in table 47. For the FORMAT UNIT command and the READ DEFECT DATA command, this descriptor specifies the location of a defect that is either:

- the length of one track;
- is less than the length of a physical block; or
- a defect that starts from one address descriptor and extends to the next address descriptor.

For the Translate Address diagnostic pages, this descriptor specifies the location of an LBA. If format type 001b is used in the SUPPLIED FORMAT field of a Translate Address Output diagnostic page (see 5.1.4), and the MADS bit in the ADDRESS TO TRANSLATE field is set to one, then the device server shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Table 47 Bytes from index format address descriptor (100b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	CYLINDER NUMBER							
2	(LSB)							
3	HEAD NUMBER							
4	MADS	Reserved			(MSB)			
...	BYTES FROM INDEX							
7	(LSB)							

CYLINDER NUMBER field

The CYLINDER NUMBER field contains the cylinder number.

HEAD NUMBER field

The HEAD NUMBER field contains the head number.

MADS bit

A multi-address descriptor start (MADS) bit set to one specifies that this descriptor defines the beginning of a defect that spans multiple address descriptors. The defect may be a number of sequential physical blocks on the same cylinder and head (i.e., a track) or may be a number of sequential tracks on the same head. A MADS bit set to zero specifies that:

- this descriptor defines the end of a defect if the previous address descriptor has the MADS bit set to one; or
- this descriptor defines a single defective physical track (i.e., the BYTES FROM INDEX field contains FFF_FFFFh) or a single defective physical block (i.e., the BYTES FROM INDEX field does not contain FFF_FFFFh).

See SBC-5 for valid combinations of two address descriptors that describe a defect.

BYTES FROM INDEX field

- if not set to FFF_FFFFh, contains the number of bytes from the index (e.g., from the start of the track) to the location being described; or
- if set to FFF_FFFFh, specifies that the entire track is being described.

For sorting bytes from index format address descriptors, the cylinder number is the most significant part of the address and the bytes from index is the least significant part of the address. More than one logical block may be described by this descriptor.

3.3.5.4 Extended physical sector address descriptor

A format type of 010b specifies the extended physical sector address descriptor defined in table 48. For the FORMAT UNIT command and the READ DEFECT DATA command, this descriptor specifies the location of a defect that is either:

- a) the length of one track;
- b) is less than the length of a physical block; or
- c) a defect that starts from one address descriptor and extends to the next address descriptor.

For the Translate Address diagnostic pages, this descriptor specifies the location of an LBA. If format type 010b is used in the SUPPLIED FORMAT field of a Translate Address Output diagnostic page (see 5.1.4), and the MADS bit in the ADDRESS TO TRANSLATE field is set to one, then the device server shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Table 48 Bytes from index format address descriptor (100b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	CYLINDER NUMBER							
2								
3	HEAD NUMBER							
4	MADS	Reserved			(MSB)			
...	SECTOR NUMBER							
7								

CYLINDER NUMBER field

The CYLINDER NUMBER field contains the cylinder number.

HEAD NUMBER field

The HEAD NUMBER field contains the head number.

MADS bit

A multi-address descriptor start (MADS) bit set to one specifies that this descriptor defines the beginning of a defect that spans multiple address descriptors. The defect may be a number of sequential physical blocks on the same cylinder and head (i.e., a track) or may be a number of sequential tracks on the same head. A MADS bit set to zero specifies that:

- a) this descriptor defines the end of a defect if the previous address descriptor has the MADS bit set to one; or
- b) this descriptor defines a single defective physical track (i.e., the BYTES FROM INDEX field contains FFF_FFFFh) or a single defective physical block (i.e., the BYTES FROM INDEX field does not contain FFF_FFFFh).

See SBC-5 for valid combinations of two address descriptors that describe a defect.

The SECTOR NUMBER field contains the sector number. A SECTOR NUMBER field set to FFF_FFFFh specifies that the entire track is being described.

SECTOR NUMBER field

- a) if not set to FFF_FFFFh, contains the sector number of the location being described; or
- b) if set to FFF_FFFFh, specifies that the entire track is being described.

For sorting extended physical sector address descriptors, the cylinder number is the most significant part of the address and the sector number is the least significant part of the address. More than one logical block may be described by this descriptor.

3.3.5.5 Long block format address descriptor

A format type of 011b specifies the long block format address descriptor defined in table 49.

Table 49 Long block format address descriptor (011b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	LONG BLOCK ADDRESS							
7	(LSB)							

LONG BLOCK ADDRESS field

For the FORMAT UNIT command, the LONG BLOCK ADDRESS field contains the eight-byte logical block address of a defect. If multiple logical blocks are contained within a physical block, then the device server may consider logical blocks in addition to the one specified by this descriptor as containing defects. For the READ DEFECT DATA commands, the LONG BLOCK ADDRESS field contains a vendor-specific eight-byte value. For the Translate Address diagnostic pages, the LONG BLOCK ADDRESS field contains a four-byte LBA or a vendor-specific four byte value that is greater than the capacity of the medium.

3.3.5.6 Bytes from index format address descriptor

A format type of 100b specifies the bytes from index address descriptor defined in table 50. For the FORMAT UNIT command and the READ DEFECT DATA commands, this descriptor specifies the location of a defect that is either the length of one track or is no more than eight bytes long. For the Translate Address diagnostic pages, this descriptor specifies the location of a track or the first byte or last byte of an area.

Table 50 Bytes from index format address descriptor (100b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	CYLINDER NUMBER							
2	(LSB)							
3	HEAD NUMBER							
4	(MSB)							
...	BYTES FROM INDEX							
7	(LSB)							

CYLINDER NUMBER field

The CYLINDER NUMBER field contains the cylinder number.

HEAD NUMBER field

The HEAD NUMBER field contains the head number.

BYTES FROM INDEX field

The BYTES FROM INDEX field contains the number of bytes from the index (e.g., from the start of the track) to the location being described. A BYTES FROM INDEX field set to FFFFFFFFh specifies that the entire track is being described.

For sorting bytes from index format address descriptors, the cylinder number is the most significant part of the address and the bytes from index is the least significant part of the address. More than one logical block may be described by this descriptor.

3.3.5.7 Physical sector format address descriptor

A format type of 101b specifies the physical sector address descriptor defined in table 51. For the FORMAT UNIT command and the READ DEFECT DATA commands, this descriptor specifies the location of a defect that is either the length of one track or the length of one sector. For the Translate Address diagnostic pages, this descriptor specifies the location of a track or a sector.

Table 51 Physical sector format address descriptor (101b)

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	CYLINDER NUMBER							
2	(LSB)							
3	HEAD NUMBER							
4	(MSB)							
...	SECTOR NUMBER							
7	(LSB)							

CYLINDER NUMBER field

The CYLINDER NUMBER field contains the cylinder number.

HEAD NUMBER field

The HEAD NUMBER field contains the head number.

SECTOR NUMBER field

The SECTOR NUMBER field contains the sector number. A SECTOR NUMBER field set to FFFFFFFh specifies that the entire track is being described.

For sorting physical sector format address descriptors, the cylinder number is the most significant part of the address and the sector number is the least significant part of the address. More than one logical block may be described by this descriptor.

3.4 GET LBA STATUS (16) command

3.4.1 GET LBA STATUS (16) command overview

The GET LBA STATUS (16) command (see table 52) requests that the device server transfer parameter data describing the logical block provisioning status (see SBC-5) for the specified LBA and zero or more subsequent LBAs to the Data-In Buffer.

The device server may or may not process this command as an uninterrupted sequence of actions (e.g., if concurrent operations are occurring that affect the logical block provisioning status, then the returned parameter data may be inconsistent or out of date).

This command uses the SERVICE ACTION IN (16) CDB format (see SBC-5 - Annex A.2).

Table 52 GET LBA STATUS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (12h)				
2	(MSB)							
...	STARTING LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	ALLOCATION LENGTH							
13	(LSB)							
14	REPORT TYPE							
15	CONTROL							

OPERATION CODE field

The OPERATION CODE field is defined in SPC-6 and shall be set to the value shown in table 52 for the GET LBA STATUS (16) command.

SERVICE ACTION field

The SERVICE ACTION field is defined in 2.2.2 and shall be set to the value shown in table 52 for the GET LBA STATUS (16) command.

STARTING LOGICAL BLOCK ADDRESS field

The STARTING LOGICAL BLOCK ADDRESS field specifies the LBA of the first logical block addressed by this command. If the specified starting LBA exceeds the capacity of the medium (see SPC-6), then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. In response to a GET LBA STATUS command, the device server may send less data to the Data-In Buffer than is specified by the allocation length. If, in response to a single GET LBA STATUS command, the device server does not send sufficient data to the Data-In Buffer to satisfy the requirement of the application client, then, to retrieve additional information, the application client may send additional GET LBA STATUS commands with different starting LBA values.

REPORT TYPE field

The REPORT TYPE field specifies the type of LBA status descriptors to return as shown in (see table 53).

Table 53 REPORT TYPE field

Code	Description
0h	Return descriptors for all LBAs
1h	Return descriptors for all LBAs using only non-zero provisioning status (see 3.4.2.2)
2h	Return descriptors for all LBAs that are mapped (see SBC-5)
3h	Return descriptors for all LBAs that are deallocated (see SBC-5)
4h	Return descriptors for all LBAs that are anchored (see SBC-5)
10h	Return descriptors for LBAs that may return an unrecovered error
All others	Reserved

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.4.2 GET LBA STATUS parameter data**3.4.2.1 GET LBA STATUS parameter data overview**

The GET LBA STATUS parameter data (see table 54) contains an eight-byte header followed by one or more LBA status descriptors.

Table 54 GET LBA STATUS parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	PARAMETER DATA LENGTH (n-3)							
3								
4	Reserved							
...								
6								
7	Reserved				COMPLETION CONDITION		RTP	
LBA status descriptors								
8	LBA status descriptor [first] (see 3.4.2.2)							
...								
23								
...								
n-15	LBA status descriptor [last] (see 3.4.2.2) (if any)							
...								
n								

PARAMETER DATA LENGTH field

The PARAMETER DATA LENGTH field indicates the number of bytes of parameter data that follow. The value in the PARAMETER DATA LENGTH field shall be:

- a) set to 4, if there are no status descriptors to report;
- b) at least 20 (i.e., the available parameter data shall contain at least one LBA status descriptor); and
- c) four added to a multiple of 16 (i.e., the available parameter data shall end on a boundary between LBA Status descriptors).

As a result of processing considerations not defined by this standard, two GET LBA STATUS commands with identical values in all CDB fields may result in two different values in the PARAMETER DATA LENGTH field

The relationship between the PARAMETER DATA LENGTH field and the ALLOCATION LENGTH field in the CDB is defined in 2.2.6.

COMPLETION CONDITION field

The COMPLETION CONDITION field indicates the condition that caused completion of the GET LBA STATUS command. The COMPLETION CONDITION field is described in table 55.

Table 55 **COMPLETION CONDITION field**

Code	Description
000b	No indication of the completion condition.
001b	The command completed as a result of meeting the allocation length.
010b^a	The command completed as a result of completing the scan length.
011b	The command completed as a result of reaching the capacity of the medium (see SBC-5).
All others	Reserved
a This only applies to the GET LBA STATUS (32) command	

If the command completes by reaching the capacity of the medium and any other condition at the same time, then the COMPLETION CONDITION field shall be set to 011b.

Report Type Processed (RTP) bit

The report type processed (RTP) bit indicates whether the value in the REPORT TYPE field was processed. If the RTP bit is set to zero, then the REPORT TYPE field was not processed (i.e., the GET LBA STATUS parameter data is returned as if the REPORT TYPE field was set to 00h). If the RTP bit is set to one, then the REPORT TYPE field was processed. If a device server supports the REPORT TYPE field set to a non-zero value, then the RTP bit shall be set to one.

3.4.2.2 LBA status descriptor

The LBA status descriptor (see table 56) contains LBA status information for one or more LBAs.

Table 56 LBA status descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	LBA STATUS LOGICAL BLOCK ADDRESS							
7	(LSB)							
8	(MSB)							
...	NUMBER OF LOGICAL BLOCKS							
11	(LSB)							
12	Reserved				PROVISIONING STATUS			
13	Reserved							
...								
15								

LBA STATUS LOGICAL BLOCK ADDRESS field

The LBA STATUS LOGICAL BLOCK ADDRESS field contains the first LBA of the LBA extent for which this descriptor reports LBA status.

NUMBER OF LOGICAL BLOCKS field

The NUMBER OF LOGICAL BLOCKS field contains the number of logical blocks in that LBA extent. The device server should return the largest possible value in the NUMBER OF LOGICAL BLOCKS field.

PROVISIONING STATUS field

The PROVISIONING STATUS field is defined in table 57.

Table 57 PROVISIONING STATUS field

Code	Description	Allowed for report types
0h	Each LBA in the LBA extent is mapped (see SBC-5) or has an unknown state.	00h
1h	Each LBA in the LBA extent is deallocated (see SBC-5).	00h, 01h, 03h, 10h
2h	Each LBA in the LBA extent is anchored (see SBC-5).	00h, 01h, 04h, 10h
3h	Each LBA in the LBA extent is mapped.	01h, 02h, 10h
4h	Each LBA in the LBA extent has an unknown provisioning status.	01h, 10h
All others	Reserved	

If the logical unit is fully provisioned (see SBC-5), then the PROVISIONING STATUS field for all LBAs shall be set to:

- 0h (i.e., mapped or unknown), if the RTP bit is set to zero;
- 0h (i.e., mapped or unknown), if the REPORT TYPE field is set to 00h in the CDB and the RTP bit is set to one; or
- 3h (i.e., mapped), if the REPORT TYPE field is not set to 00h in the CDB and the RTP bit is set to one.

ADDITIONAL STATUS field

The ADDITIONAL STATUS field shall be set to 00h if the REPORT TYPE field is set to 00h in the CDB and shall be as shown in table 58 for all other values of report type.

Table 58 ADDITIONAL STATUS field

Code	Description
00h	No additional status to report.
01h	The device server has detected that each LBA in the LBA extent may return an unrecovered error.
All others	Reserved

3.4.2.3 LBA status descriptor relationships

The LBA STATUS LOGICAL BLOCK ADDRESS field in the first LBA status descriptor returned in the GET LBA STATUS parameter data shall contain the lowest numbered LBA that is greater than or equal to the starting logical block address specified in the CDB that meets the requirements for the specified report type. For subsequent LBA status descriptors, the contents of the LBA STATUS LOGICAL BLOCK ADDRESS field shall contain:

- a) for a non-zero report type, the value of the lowest numbered LBA meeting the requirements for the specified report type that is greater than or equal to the sum of the values in:
 - A) the LBA STATUS LOGICAL BLOCK ADDRESS field in the previous LBA status descriptor;
 - and
 - B) the NUMBER OF LOGICAL BLOCKS field in the previous LBA status descriptor;

or

- b) for report type 0h, the sum of the values in:
 - A) the LBA STATUS LOGICAL BLOCK ADDRESS field in the previous LBA status descriptor;
 - and
 - B) the NUMBER OF LOGICAL BLOCKS field in the previous LBA status descriptor.

Adjacent LBA status descriptors may have the same values for the PROVISIONING STATUS field.

3.5 GET LBA STATUS (32) command

The GET LBA STATUS (32) command (see table 59) requests that the device server transfer parameter data describing the logical block provisioning status (see 4.7) and additional status for the specified LBA and zero or more subsequent LBAs to the Data-In Buffer.

The device server may or may not process this command as an uninterrupted sequence of actions (e.g., if concurrent operations are occurring that affect the logical block provisioning status, then the returned parameter data may be inconsistent or out of date).

This command uses the variable length CDB format (see SBC-5 clause A.1).

Table 59 GET LBA STATUS (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
...								
6								
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0012h)						(LSB)
9								
10	REPORT TYPE							
11	Reserved							
12	(MSB)	STARTING LOGICAL BLOCK ADDRESS						(LSB)
...								
19								
20	(MSB)	SCAN LENGTH						(LSB)
...								
23								
24	ELEMENT IDENTIFIER							
...								
27								
28	(MSB)	ALLOCATION LENGTH						(LSB)
...								
31								

OPERATION CODE field, ADDITIONAL CDB LENGTH field, and SERVICE ACTION

The OPERATION CODE field, ADDITIONAL CDB LENGTH field, and SERVICE ACTION field are defined in 2.2.2 and shall be set to the values shown in table 59 for the GET LBA STATUS (32) command.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

SCAN LENGTH field

The SCAN LENGTH field specifies the maximum number of contiguous logical blocks to be scanned for logical blocks that meet the specified report type. A value of 0000_0000h in the SCAN LENGTH field specifies that there is no limit on the number of logical blocks to be scanned (e.g., scan to the end of the media, or scan until the allocation length is met).

ELEMENT IDENTIFIER field

The ELEMENT IDENTIFIER field specifies the element identifier of the physical element (see SBC-5) for which LBAs shall be reported based on the value in the REPORT TYPE field. If the ELEMENT IDENTIFIER field is set to 0000_0000h, then LBAs for all physical elements shall be reported based on the value in the REPORT TYPE field.

See the GET LBA STATUS (16) command for the description of the STARTING LOGICAL BLOCK ADDRESS field, the ALLOCATION LENGTH field, the REPORT TYPE field, and the returned parameter data (see 3.4.2).

3.6 GET PHYSICAL ELEMENT STATUS command

The GET PHYSICAL ELEMENT STATUS command (see table 60) requests that the device server return status information for physical elements within the logical unit.

This command uses the SERVICE ACTION IN (16) CDB format (see SBC-5 clause A.2).

Table 60 GET PHYSICAL ELEMENT STATUS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (17h)				
2	Reserved							
...								
5								
6	(MSB)	STARTING ELEMENT						(LSB)
...	ALLOCATION LENGTH							
9								
10								
...	CONTROL							
13								
14								
15								

OPERATION CODE field and the SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in SPC-6 and shall be set to the values shown in table 60 for the GET PHYSICAL ELEMENT STATUS command.

STARTING ELEMENT field

The STARTING ELEMENT field specifies the element identifier of the first physical element addressed by this command.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. In response to a GET PHYSICAL ELEMENT STATUS command, the device server may send less data to the Data-In Buffer than is specified by the allocation length. If, in response to a GET PHYSICAL ELEMENT STATUS command, the device server does not send sufficient data to the Data-In Buffer to satisfy the requirement of the application client, then, to retrieve additional information, the application client may send additional GET PHYSICAL ELEMENT STATUS commands with different starting element values.

FILTER field

The FILTER field restricts the physical element status descriptors to return, as shown in table 61.

Table 61 FILTER field

Code	Description
00b	All physical status descriptors as specified by the other fields in the CDB.
01b	Only physical element status descriptors for which the value of the PHYSICAL ELEMENT HEALTH field (see 5.8.2.2) is: <ul style="list-style-type: none"> a) greater than or equal to 65h and less than or equal to CFh (i.e., outside manufacturer's specification limit); b) equal to FDh (i.e., all operations associated with storage element depopulation have completed and one or more completed with error); c) equal to FEh (i.e., an operation associated with storage element depopulation is in progress); or d) equal to FFh (i.e., all operations associated with storage element depopulation have completed without error).
All others	Reserved

REPORT TYPE field

The REPORT TYPE field specifies the type of physical element status descriptors to return as shown in table 62.

Table 62 REPORT TYPE field

Code	Description
0h	Return descriptors for physical elements, based on the FILTER field
1h	Return descriptors for storage elements, based on the FILTER field
All others	Reserved

CONTROL byte

The CONTROL byte is defined in 2.2.7

3.6.1 GET PHYSICAL ELEMENT STATUS parameter data

The GET PHYSICAL ELEMENT STATUS parameter data (see table 59) contains a 32-byte header followed by zero or more physical element status descriptors.

Table 63 GET PHYSICAL ELEMENT STATUS parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	NUMBER OF DESCRIPTORS							
3	(LSB)							
4	(MSB)							
...	NUMBER OF DESCRIPTORS RETURNED							
7	(LSB)							
8	(MSB)							
...	IDENTIFIER OF ELEMENT BEING DEPOPULATED							
11	(LSB)							
12	(MSB)							
...	Reserved							
31	(LSB)							
Physical element status descriptor list								
32								
...	Physical element status descriptor [first] (see 3.6.2)							
63								
...								
n-32								
...	Physical element status descriptor [last] (see 3.6.2)							
n								

NUMBER OF DESCRIPTORS field

The NUMBER OF DESCRIPTORS field shall contain the number of descriptors in the element descriptors list. The element descriptors list is a list of physical elements that:

- meet the requirements of the REPORTING OPTIONS field;
- meet the requirements of the FILTER field; and
- have an element identifier that is greater than or equal to the element identifier specified by the STARTING ELEMENT field in the CDB.

The contents of the NUMBER OF DESCRIPTORS field are not altered based on the allocation length.

NUMBER OF DESCRIPTORS RETURNED field

The NUMBER OF DESCRIPTORS RETURNED field contains the number of valid physical element status descriptors returned in the parameter data.

IDENTIFIER OF ELEMENT BEING DEPOPULATED field

The IDENTIFIER OF ELEMENT BEING DEPOPULATED field contains the element identifier of the element that has a physical element health set to FEh (i.e., an operation associated with storage element depopulation is in progress). If the value of this field is set to zero, then no operation associated with storage element depopulation is in progress.

As a result of processing considerations not defined by this standard, two GET PHYSICAL ELEMENT STATUS commands with identical values in all CDB fields may result in two different values in the NUMBER OF DESCRIPTORS field.

The physical element status descriptors shall be sorted in ascending order of the element identifier.

3.6.2 Physical element status descriptor

The physical element status descriptor (see table 64) contains status information for a physical element.

Table 64 Physical element status descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
...								
3								
4	(MSB)	ELEMENT IDENTIFIER						(LSB)
...	Reserved							
7								
8								
...	Reserved							
12								
13								
14	PHYSICAL ELEMENT TYPE							
15	PHYSICAL ELEMENT HEALTH							
16	(MSB)	ASSOCIATED CAPACITY						(LSB)
...	Reserved							
23								
24								
...	Reserved							
31								

ELEMENT IDENTIFIER field

The ELEMENT IDENTIFIER field contains the non-zero identifier of the physical element (e.g., storage element) associated with this physical element status descriptor.

RALWD bit

A restoration allowed (RALWD) bit set to:

- 1** indicates that this storage element has been depopulated and is a candidate for being restored.
- 0** indicates that this storage element:
 - a) has not been depopulated; or
 - b) has been depopulated and is not a candidate for being restored.

PHYSICAL ELEMENT TYPE field

The PHYSICAL ELEMENT TYPE field indicates the type of the physical element associated with this physical element status descriptor, as described in table 65.

Table 65 PHYSICAL ELEMENT TYPE field

Code	Description
01h	Storage element
All others	Reserved

PHYSICAL ELEMENT HEALTH field

The PHYSICAL ELEMENT HEALTH field indicates the health of the physical element associated with this physical element status descriptor, as described in table 66.

Table 66 PHYSICAL ELEMENT HEALTH field

Code	Description
00h	Not reported.
01h to 63h^a	The physical element health is within manufacturer's specification limits.
64h	The physical element health is at manufacturer's specification limit.
65h to 63CF^a	The physical element health is outside manufacturer's specification limit.
D0h to FCh	Reserved
FDh	All operations associated with storage element depopulation have completed and one or more completed with error.
FEh	An operation associated with storage element depopulation is in progress.
FFh	All operations associated with storage element depopulation have completed without error.

a The device server may implement a subset of these values.

ASSOCIATED CAPACITY field

The ASSOCIATED CAPACITY field indicates the number of logical blocks by which the capacity of the device is reduced if the physical element associated with this physical element status descriptor becomes depopulated. A value of FFFF_FFFF_FFFF_FFFFh indicates that the number of logical blocks by which the capacity is reduced is not specified.

3.7 GET STREAM STATUS command

The GET STREAM STATUS command (see table 67) requests that the device server transfer parameter data describing the status of streams (see SBC-5) for the logical unit to the Data-In Buffer.

The device server may or may not process this command as an uninterrupted sequence of actions (e.g., if concurrent operations are occurring that affect the status of streams, then the returned parameter data may be inconsistent or out of date).

Table 67 GET STREAM STATUS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (16h)				
2	Reserved							
3	Reserved							
4	STARTING STREAM IDENTIFIER							
5	Reserved							
6	Reserved							
...	Reserved							
9	Reserved							
10	(MSB)	ALLOCATION LENGTH						(LSB)
...	ALLOCATION LENGTH							
13	(LSB)							
14	Reserved							
15	CONTROL							

The OPERATION CODE field and the SERVICE ACTION field shall be set to the values shown in table 67 for the GET STREAM STATUS command.

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 67.

SERVICE ACTION field

The SERVICE ACTION field is defined in 2.2.2 and set to the value defined in table 67.

STARTING STREAM IDENTIFIER field

The STARTING STREAM IDENTIFIER field specifies the stream identifier of the first stream addressed by this command (see 3.7.1.2). If the specified starting stream identifier exceeds the value indicated by the MAXIMUM NUMBER OF STREAMS field of the Block Limits VPD page (see 5.4.5), then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to ILLEGAL FIELD IN CDB.

The ALLOCATION LENGTH field is defined in 2.2.6. If, in response to a single GET STREAM STATUS command, the device server does not send sufficient data to the Data-In Buffer to satisfy the requirement of the application client, then the application client may send additional GET STREAM STATUS commands with different starting stream identifier values to retrieve additional information.

3.7.1 GET STREAM STATUS parameter data

The GET STREAM STATUS parameter data (see table 68) contains an eight-byte header followed by zero or more stream status descriptors.

Table 68 GET STREAM STATUS parameter data

Bit Byte	7	6	5	4	3	2	1	0	
0	PARAMETER DATA LENGTH (n-7)								
...									
3									
4	Reserved								
5	NUMBER OF OPEN STREAMS								
6									(MSB)
7									(LSB)
Stream status descriptors									
8	(MSB)	Stream status descriptor [first]						(LSB)	
...									
15	(LSB)								
...									
n-7	(MSB)	Stream status descriptor [last]						(LSB)	
...									
n	(LSB)								

PARAMETER DATA LENGTH field

The PARAMETER DATA LENGTH field shall contain the length in bytes of the stream list. The stream list length is the number of open streams in the logical unit multiplied by eight. The contents of the STREAM LIST LENGTH field are not altered based on the allocation length.

Due to processing considerations outside the scope of this standard, two GET STREAM STATUS commands with identical values in all CDB fields may result in two different values in the PARAMETER DATA LENGTH field.

The relationship between the PARAMETER DATA LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

NUMBER OF OPEN STREAMS field

The NUMBER OF OPEN STREAMS field indicates the number of streams that are currently open in the logical unit.

3.7.1.1 Stream status descriptor

The stream status descriptor (see table 69) contains stream status information for one open stream.

Table 69 Stream status descriptor format

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1	Reserved								
2	(MSB)	STREAM IDENTIFIER							
3							(LSB)		
4	Reserved								
...	Reserved								
7	Reserved								

STREAM IDENTIFIER field

The STREAM IDENTIFIER field contains the stream identifier of an open stream.

3.7.1.2 Stream status descriptor relationships

The STREAM IDENTIFIER field in the first stream status descriptor returned in the GET STREAM STATUS parameter data shall contain:

- a) the value specified in the STARTING STREAM IDENTIFIER field of the CDB if that stream is open; or
- b) the value of the next greater stream identifier of an open stream.

If the value specified in the STARTING STREAM IDENTIFIER field of the CDB is greater than the highest stream identifier of an open stream, then the device server shall not return any stream status descriptors. For subsequent stream status descriptors, the contents of the STREAM IDENTIFIER field shall contain the value of the next greater stream identifier of an open stream.

3.8 INQUIRY command

3.8.1 INQUIRY command introduction

The INQUIRY command (see table 70) requests that information regarding the logical unit and SCSI target device be sent to the application client.

Table 70 INQUIRY command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (12h)								
1	Reserved						Obsolete	EVPD	
2	PAGE CODE								
3	(MSB)	ALLOCATION LENGTH						(LSB)	
4									
5	CONTROL								

EVPD (Enable Vital Product Data) bit

An enable vital product data (EVPD) bit set to one specifies that the device server shall return the vital product data specified by the PAGE CODE field (see 5.4). If the device server does not support (see 5.4.21) the requested vital product data page, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

An EVPD bit set to zero specifies that the device server shall return the standard INQUIRY data (see 3.8.2). If the PAGE CODE field is not set to zero and the EVPD bit is set to zero, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If the EVPD bit is set to one, the PAGE CODE field specifies which page of vital product data information the device server shall return (see 5.4).

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. If EVPD is set to zero, the allocation length should be at least five, so that the ADDITIONAL LENGTH field in the parameter data (see 3.8.2) is returned. If EVPD is set to one, the allocation length should be at least four, so that the PAGE LENGTH field in the parameter data (see 5.4) is returned.

In response to an INQUIRY command received by an incorrect logical unit, the SCSI target device shall return the INQUIRY data with the peripheral qualifier set to the value defined in 3.8.2. The INQUIRY command shall return CHECK CONDITION status only when the device server is unable to return the requested INQUIRY data.

If an INQUIRY command is received from an initiator port with a pending unit attention condition (i.e., before the device server reports CHECK CONDITION status), the device server shall perform the INQUIRY command and shall not clear the unit attention condition (see SAM-6).

The device server should be able to process the INQUIRY command even when an error occurs that prohibits normal command completion.

INQUIRY data (i.e., standard INQUIRY data (see 3.8.2) and all VPD pages (see 5.4) should be returned even though the device server is not ready for other commands. Standard INQUIRY data, the Extended INQUIRY Data VPD page (see 5.4.10), and the Device Identification VPD page (see 5.4.9) should be available without incurring any media access delays. If reporting INQUIRY data requires a delay (e.g., the device server stores some of the standard INQUIRY data or VPD data on the media), then the device server may return ASCII spaces (20h) in ASCII fields and zeros in other fields until the data is available from the media.

INQUIRY data may change as the SCSI target device and its logical units perform their initialization sequence.

EXAMPLE – Logical units may provide a minimum command set from nonvolatile memory until they load the final firmware from the media. After the firmware has been loaded, more options may be supported and therefore different INQUIRY data may be returned.

If the INQUIRY data changes for any reason, the device server shall establish a unit attention condition for the initiator port associated with every I_T nexus (see SAM-6), with the additional sense code set to INQUIRY DATA HAS CHANGED.

NOTE The INQUIRY command may be used by an application client after a hard reset or power on condition to determine the device types for system configuration.

CONTROL byte

The CONTROL byte is defined in 2.2.7

3.8.2 Standard INQUIRY data

The standard INQUIRY data (see table 71) shall contain at least 36 bytes

Table 71 Standard INQUIRY data format

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	RMB	Reserved						
2	VERSION							
3	Obsolete	Obsolete	NORMACA	HISUP	RESPONSE DATA FORMAT			
4	ADDITIONAL LENGTH (N-4)							
5	SCCS	ACC	TPGS		3PC	Reserved		PROTECT
6	Obsolete	ENC SERV	VS	MULTIP	Obsolete	Obsolete	Obsolete	Obsolete
7	Obsolete	Obsolete	Obsolete	Obsolete	Obsolete	Obsolete	CMDQUE	VS
8	(MSB)							
...	T10 VENDOR IDENTIFICATION							
15	(LSB)							
16	(MSB)							
...	PRODUCT IDENTIFICATION							
31	(LSB)							
32	(MSB)							
...	PRODUCT REVISION LEVEL							
35	(LSB)							
36	DRIVE SERIAL NUMBER							
...	DRIVE SERIAL NUMBER							
43	DRIVE SERIAL NUMBER							
44	Vendor Unique							
...	Seagate fills this field with 00h.							
55	Seagate fills this field with 00h.							
56	Reserved			Reserved		Reserved	Reserved	
57	Reserved							
58	(MSB)							
59	VERSION DESCRIPTOR 1							
...	...							
72	(MSB)							
73	VERSION DESCRIPTOR 8							
74	(LSB)							
...	Reserved							
95	Reserved							
Vendor specific parameters								
96	(MSB)							
...	Copyright Notice (Vendor specific)							
n	(LSB)							

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE field identify the peripheral device connected to the logical unit. If the SCSI target device is not capable of supporting a peripheral device connected to this logical unit, the device server shall set these fields to 7Fh (i.e., PERIPHERAL QUALIFIER field set to 011b and PERIPHERAL DEVICE TYPE field set to 1Fh).

The peripheral qualifier is defined in table 72 and the peripheral device type is defined in table 73

Table 72 PERIPHERAL QUALIFIER

Qualifier	Description
000b	A peripheral device having the specified peripheral device type is connected to this logical unit. If the device server is unable to determine whether or not a peripheral device is connected, it also shall use this peripheral qualifier. This peripheral qualifier does not mean that the peripheral device connected to the logical unit is ready for access.
001b	A peripheral device having the specified peripheral device type is not connected to this logical unit. However, the device server is capable of supporting the specified peripheral device type on this logical unit.
010b	Reserved
011b	The device server is not capable of supporting a peripheral device on this logical unit. For this peripheral qualifier the peripheral device type shall be set to 1Fh. All other peripheral device type values are reserved for this peripheral qualifier.
100b - 111b	Vendor specific

Table 73 PERIPHERAL DEVICE TYPE

Code	Doc. [a]	Description
00h	SBC-5	Direct access block device (e.g., magnetic disk)
01h	SSC-3	Sequential-access device (e.g., magnetic tape)
02h	SSC	Printer device
03h	SPC-2	Processor device
04h	SBC-5	Write-once device (e.g., some optical disks)
05h	MMC-5	CD/DVD device
06h		Scanner device (obsolete)
07h	SBC-5	Optical memory device (e.g., some optical disks)
08h	SMC-3	Medium changer device (e.g., jukeboxes)
09h		Communications device (obsolete)
0Ah - 0Bh		Obsolete
0Ch	SCC-2	Storage array controller device (e.g., RAID)
0Dh	SES	Enclosure services device
0Eh	RBC	Simplified direct-access device (e.g., magnetic disk)
0Fh	OCRW	Optical card reader/writer device
10h	BCC	Bridge Controller Commands
11h	OSD	Object-based Storage Device
12h	ADC-2	Automation/Drive Interface
13h - 1Dh		Reserved
1Eh		Well known logical unit [b]
1Fh		Unknown or no device type

[a] All standards are subject to revision, and parties to agreements based on the standard are encouraged to investigate the possibility of applying the most recent editions of the listed standards.

[b] All well known logical units use the same peripheral device type code.

RMB (Removable Media) bit

- 0** A removable medium (RMB) bit set to zero indicates that the medium is not removable.
- 1** A RMB bit set to one indicates that the medium is removable.

VERSION field

The VERSION field indicates the implemented version of the SPC standard and is defined in table 74 .

Table 74 VERSION field codes

Code	Description		
00h	The device does not claim conformance to any standard.		
02h	Obsolete		
03h	The device complies to ANSI INCITS 301-1997 (SPC).		
04h	The device complies to ANSI INCITS 351-2001 (SPC-2).		
05h	The device complies to ANSI INCITS 408-2005 (SPC-3).		
06h	The device complies to ANSI INCITS 513-2015 (SPC-4)		
07h	The device complies to T10/BSR INCITS 503 (SPC-6)		
Code	Description	Code	Description
01h	Obsolete (SCSI=001b)	07h	Reserved
08h - 0Ch	Obsolete (ECMA=001b)	0Dh - 3Fh	Reserved
40h - 44h	Obsolete (ISO=01b)	45h - 47h	Reserved
48h - 4Ch	Obsolete (ISO=01b & ECMA=001b)	4Dh - 7Fh	Reserved
80h - 84h	Obsolete (ISO=10b)	85h - 87h	Reserved
88h - 8Ch	Obsolete (ECMA=001b)	8Dh - FFh	Reserved

NORMACA (Normal ACA Supported)

- 1** The Normal ACA Supported (NORMACA) bit set to one indicates that the device server supports a NACA bit set to one in the CDB CONTROL byte and supports the ACA task attribute (see 2.2.7).
- 0** A NORMACA bit set to zero indicates that the device server does not support a NACA bit set to one and does not support the ACA task attribute.

HISUP (Hierarchical Support) bit

- 0** A hierarchical support (HISUP) bit set to zero indicates the SCSI target device does not use the hierarchical addressing model to assign LUNs to logical units.
- 1** A HISUP bit set to one indicates the SCSI target device uses the hierarchical addressing model to assign LUNs to logical units.

RESPONSE DATA FORMAT field

A RESPONSE DATA FORMAT field value of two indicates that the data shall be in the format defined in this manual. Response data format values less than two are obsolete. Response data format values greater than two are reserved.

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field indicates the length in bytes of the remaining standard INQUIRY data. The relationship between the ADDITIONAL LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

SCCS (SCC Supported) bit

- 1** An SCC Supported (SCCS) bit set to one indicates that the SCSI target device contains an embedded storage array controller component. See SCC-2 for details about storage array controller devices.
- 0** An SCCS bit set to zero indicates that the SCSI target device does not contain an embedded storage array controller component.

ACC (Access Controls Coordinator) bit

- 1** An Access Controls Coordinator (ACC) bit set to one indicates that the SCSI target device contains an access controls coordinator that may be addressed through this logical unit.
- 0** An ACC bit set to zero indicates that no access controls coordinator may be addressed through this logical unit. If the SCSI target device contains an access controls coordinator that may be addressed through any logical unit other than the ACCESS CONTROLS well known logical unit, then the ACC bit shall be set to one for LUN 0.

TPGS (Target Port Group Support) field

The contents of the target port group support (TPGS) field (see table 75) indicate the support for asymmetric logical unit access.

Table 75 Target Port Group Support codes

Code	Description
00b	The SCSI target device does not support asymmetric logical unit access or supports a form of asymmetric access that is vendor specific. Neither the REPORT TARGET GROUPS nor the SET TARGET GROUPS commands is supported.
01b	Only implicit asymmetric logical unit access (see SPC-6) is supported. The SCSI target device is capable of changing target port asymmetric access states without a SET TARGET PORT GROUPS command. The REPORT TARGET PORT GROUPS command is supported and the SET TARGET PORT GROUPS command is not supported.
10b	Only explicit asymmetric logical unit access (i.e., the TPGS field contains 10b or 11b) is supported. The SCSI target device only changes target port asymmetric access states as requested with the SET TARGET PORT GROUPS command. Both the REPORT TARGET PORT GROUPS command and the SET TARGET PORT GROUPS command are supported.
11b	Both explicit and implicit asymmetric logical unit access are supported. Both the REPORT TARGET PORT GROUPS command and the SET TARGET PORT GROUPS commands are supported.

3PC (Third-Party Copy) bit

- 1** A Third-Party Copy (3PC) bit set to one indicates that the SCSI target device supports third-party copy commands such as the EXTENDED COPY command.
- 0** A 3PC bit set to zero indicates that the SCSI target device does not support such commands.

PROTECT bit

- 0** A PROTECT bit set to zero indicates that the logical unit does not support protection information (i.e. type 0) (see SPC-6 and SBC-5).
- 1** A PROTECT bit set to one indicates that the logical unit supports type 1 protection, type 2 protection, or type 3 protection (see SBC-5). The SPT field in the Extended INQUIRY Data VPD page (see 5.4.10) indicates which type of protection the logical unit supports.

ENCSEV (Enclosure Services) bit

- 1** An Enclosure Services (ENCSEV) bit set to one indicates that the SCSI target device contains an embedded enclosure services component. See SES for details about enclosure services, including a device model for an embedded enclosure services device.
- 0** An ENCSEV bit set to zero indicates that the SCSI target device does not contain an embedded enclosure services component.

MULTIP (Multi Port) bit

- 1** A Multi Port (MULTIP) bit set to one indicates that this is a multi-port (two or more ports) SCSI target device and conforms to the SCSI multi-port device requirements found in the applicable standards (e.g., SAM-6, a SCSI transport protocol standard and possibly provisions of a command standard).
- 0** A MULTIP bit set to zero indicates that this SCSI target device has a single port and does not implement the multi-port requirements.

CMDQUE (Command Queuing) bit

If the logical unit does not support the BQUE bit, CMDQUE bit shall be set to one indicating that the logical unit supports the task management model (see SAM-6).

If the logical unit supports the BQUE bit, the CMDQUE bit and BQUE bit indicate whether the logical unit supports the full task management model as described in table 76.

Table 76 BQue and CmdQue bit combinations

BQue	CmdQue	Description
0	0	Obsolete
0	1	Full task management model supported
1	0	Basic task management model supported
1	1	Illegal combination of BQUE and CMDQUE bits

T10 VENDOR IDENTIFICATION field

The T10 VENDOR IDENTIFICATION field contains eight bytes of left-aligned ASCII data (see 5.4.2) identifying the vendor of the product. The T10 vendor identification shall be one assigned by INCITS. Bytes 8 through 15 contain the ASCII characters that represent "SEAGATE" (53h 45h 41h 47h 41h 54h 45h 20h (space)).

PRODUCT IDENTIFICATION

The PRODUCT IDENTIFICATION field contains sixteen bytes of left-aligned ASCII data (see 5.4.2) defined by Seagate. Bytes 16 through 31 indicate the drive model with 20h (space) used as a filler. The table below is an example of drive test data returned by the drive. Bytes 16 and 17 will contain 53 54 for all drive models.

Refer to the applicable Seagate product manual to get the actual text string.

PRODUCT REVISION LEVEL field

The PRODUCT REVISION LEVEL field contains four bytes of left-aligned ASCII data defined by Seagate. Bytes 32 through 35 contain the four ASCII digits representing the last four digits of the product Firmware Release number.

VERSION DESCRIPTOR fields

The VERSION DESCRIPTOR fields provide for identifying up to eight standards to which the SCSI target device claims conformance. The value in each VERSION DESCRIPTOR field shall be selected from the Version Descriptor Values Table in the current SPC standard. All version descriptor values not listed in table 74 are reserved. Technical Committee T10 of INCITS maintains an electronic copy of the information in the Version Descriptor Values Table on its world wide web site (<http://www.t10.org/>). In the event that the T10 world wide web site is no longer active, access may be possible via the INCITS world wide web site (<http://www.incits.org/>), the ANSI world wide web site (<http://www.ansi.org/>), the IEC site (<http://www.iec.ch/>), the ISO site (<http://www.iso.ch/>), or the ISO/IEC JTC 1 web site (<http://www.iso.ch/>). It is recommended that the first version descriptor be used for the SCSI architecture standard, followed by the physical transport standard if any, followed by the SCSI transport protocol standard, followed by the appropriate SPC version, followed by the device type command set, followed by a secondary command set if any. Refer to the latest SPC version for a complete list of descriptor values.

Copyright Notice field

Seagate uses bytes 96 - 143 to provide a copyright notice that begins "Copyright (c) XXXX Seagate All rights reserved," where "XXXX" indicates the year the drive's firmware code was built (for example: 2016).

3.8.3 Vital product data

The application client requests the vital product data information by setting the EVPD bit to one and specifying the page code of a vital product data. See 5.4 for details about vital product data. The information returned consists of configuration data (e.g., vendor identification, product identification, model, serial number), manufacturing data (e.g., plant and date of manufacture), field replaceable unit data and other vendor specific or device specific data. If the device server does not implement the requested page, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The device server should have the ability to process the INQUIRY command even when an error occurs that prohibits normal command completion. In such a case, CHECK CONDITION status should be returned for commands other than INQUIRY or REQUEST SENSE. The sense data returned may contain the field replaceable unit code. The vital product data may be obtained for the failing device using the INQUIRY command.

This manual defines a format that allows device-independent application client software to display the vital product data returned by the INQUIRY command. The contents of the data may be vendor specific, and may be unusable without detailed information about the device.

This manual does not define the location or method of storing the vital product data. The retrieval of the data may require completion of initialization operations within the device, that may induce delays before the data is available to the application client. Time-critical requirements are an implementation consideration and are not addressed in the standard.

3.9 LOG SELECT command

The LOG SELECT command (see table 77) provides a means for an application client to manage statistical information maintained by the SCSI target device about the SCSI target device or its logical units. Device servers that implement the LOG SELECT command shall also implement the LOG SENSE command. Structures in the form of log parameters within log pages are defined as a way to manage the log data. The LOG SELECT command provides for sending zero or more log pages via the Data-Out Buffer. This manual defines the format of the log pages (see 5.2.2), but does not define the conditions and events that are logged. Application clients should issue LOG SENSE commands prior to issuing LOG SELECT commands to determine supported log pages and page lengths.

Table 77 LOG SELECT command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (4Ch)							
1	Reserved						PCR	SP
2	PC	PAGE CODE						
3	SUBPAGE CODE							
4	(MSB)	Reserved						
...								
6		(LSB)						
7	(MSB)	PARAMETER LIST LENGTH						
8								
9	CONTROL							

PCR (Parameter Code Reset) bit

The parameter code reset (PCR) bit instructs a device server whether or not to set parameters to their vendor specific default values (e.g., zero) as described in table 80.

SP (Save Parameters) bit

The save parameters (SP) bit instructs a device server whether or not to save parameters to non-volatile memory as described in table 80.

PC (Page Control) field

The page control (PC) field specifies which data counter parameter values (i.e., when the FORMAT AND LINKING field (see 5.2.2) contains 00b or 10b) shall be processed by a device server in response to a LOG SELECT command as described in table 78. The PC field shall be ignored for list parameters (i.e., when the FORMAT AND LINKING field contains 01b or 11b).

Table 78 Page Control (PC) field values

Values	Description
00b	Threshold values
01b	Cumulative values
10b	Default threshold values
11b	Default cumulative values

The threshold values and cumulative values for data counter parameters are:

- 1) the current values if there has been an update to a cumulative parameter value (e.g., by a LOG SELECT command or by a device specific event) in the specified page or pages since the last logical unit reset occurred;
- 2) the saved values, if saved parameters are implemented, current values have been saved, and an update has not occurred since the last logical unit reset; or
- 3) the vendor specific default values, if saved values are not available or not implemented.

When evaluated together, the combination of the values in the PCR bit, the SP bit, and the PC field specify the actions that a SCSI target device performs while processing a LOG SELECT command (see table 80).

PARAMETER LIST LENGTH field

If the PARAMETER LIST LENGTH field is set to zero, the PAGE CODE field and SUBPAGE CODE field specify the log page or log pages to which the other CDB fields apply (see 3.9.1).

Since each log page in the parameter list contains a PAGE CODE field and SUBPAGE CODE field (see 5.2.2), the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB, if:

- a) the PARAMETER LIST LENGTH field contains a value other than zero, and:
 - A) the PAGE CODE field contains a value other than zero; or
 - B) the SUBPAGE CODE field contains a value other than zero.

The PARAMETER LIST LENGTH field specifies the length in bytes of the parameter list that shall be located in the Data-Out Buffer.

If the PARAMETER LIST LENGTH field contains zero, no log pages shall be transferred. This condition shall not be considered an error. The LOG SELECT command shall be processed as described in 3.9.1.

3.9.1 Processing LOG SELECT when the parameter list length is zero

If the PARAMETER LIST LENGTH field is set to zero (i.e., when there is no parameter data being sent with a LOG SELECT command), the SCSI target device responds by processing the log parameter values as described in this subclause.

PAGE CODE field and SUBPAGE CODE field

The PAGE CODE field and SUBPAGE CODE field (see table 79) specify the log page or log pages to which the other CDB fields apply (see table 79).

Table 79 PAGE CODE field and SUBPAGE CODE field

PAGE CODE field	SUBPAGE CODE field	Description
00h	00h	All log parameters in all log pages ^[a]
00h to 3Fh	01h to FEh	All log parameters in the log page specified by the page code and subpage code
00h to 3Fh	FFh	All log parameters in the log pages specified by page code and all subpage codes
01h to 3Fh	00h	All log parameters in the log page specified by the page code
[a] This is equivalent to the LOG SELECT command operation specified by previous versions of this standard.		

Table 80 defines the meaning of the combinations of values for the PCR bit, the SP bit, and the PC field.

Table 80 PCR bit, SP bit, and PC field meanings when parameter list length is zero (Sheet 1 of 2)

PCR bit	SP bit	PC field	Description
0b	0b	0xb	This is not an error. The device server shall make no changes to any log parameter values and shall not save any values to non-volatile media.
0b	1b	00b	The device server shall make no changes to any log parameter values and shall process the optional saving of current parameter values as follows: <ul style="list-style-type: none"> a) if the values are current threshold data counter parameters, then: <ul style="list-style-type: none"> A) if the device server implements saving of the current threshold values, the device server shall save all current threshold values to non-volatile media; or B) if the device server does not implement saving of the current threshold values, the device server shall terminate the command. ^[a] or b) if the values are current list parameters, then: <ul style="list-style-type: none"> A) if the device server implements saving of the current list parameters, the device server shall save all current list parameters to non-volatile media; or B) if the device server does not implement saving of the current list parameters, the device server shall terminate the command. ^[a]
0b	1b	01b	The device server shall make no change to any log parameter values and shall process the optional saving of current parameter values as follows: <ul style="list-style-type: none"> a) if the values are current cumulative data counter parameters, then: <ul style="list-style-type: none"> A) if the device server implements saving of the current cumulative values, the device server shall save all current cumulative values to non-volatile media; or B) if the device server does not implement saving of the current cumulative values, the device server shall terminate the command. ^[a] or b) if the values are current list parameters, then: <ul style="list-style-type: none"> A) if the device server implements saving of the current list parameters, the device server shall save all current list parameters to non-volatile media; or B) if the device server does not implement saving of the current list parameters, the device server shall terminate the command. ^[a]
0b	xb	10b	The device server shall set all current threshold values to the vendor specific default threshold values ^[b] and shall not save any values to non-volatile media.
0b	xb	11b	The device server shall set all current cumulative values to the vendor specific default cumulative values ^[b] and shall not save any values to non-volatile media.
1b	0b	xxb	The device server shall: <ul style="list-style-type: none"> a) set all current threshold values to the vendor specific default threshold values; ^[b] b) set all current cumulative values to the vendor specific default cumulative values; ^[b] c) set all list parameters to their vendor specific default values; and d) not save any values to non-volatile media.
			^[a] The command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.
			^[b] Vendor specific default threshold values and vendor specific default cumulative values may be zero.

Table 80 PCR bit, SP bit, and PC field meanings when parameter list length is zero (Sheet 2 of 2)

PCR bit	SP bit	PC field	Description
1b	1b	00b	The device server shall process the optional saving of current threshold values as follows: a) if the device server implements saving of the current threshold values, the device server shall: 1) save all current threshold values to non-volatile media; 2) set all current threshold values to the vendor specific default threshold values ^[b] ; 3) set all current cumulative values to the vendor specific default cumulative values ^[b] , and 4) set all list parameters to their vendor specific default values. or b) if the device server does not implement saving of the current threshold values, the device server shall terminate the command. ^[a]
1b	1b	01b	The device server shall process the optional saving of current cumulative values as follows: a) if the device server implements saving of the current cumulative values, the device server shall: 1) save all current cumulative values to non-volatile media; 2) set all current threshold values to the vendor specific default threshold values ^[b] ; 3) set all current cumulative values to the vendor specific default cumulative values ^[b] , and 4) set all list parameters to their vendor specific default values. or b) if the device server does not implement saving of the current cumulative values, the device server shall terminate the command. ^[a]
1b	1b	1xb	The device server shall: a) set all current threshold values to the vendor specific default threshold values ^[b] ; b) set all current cumulative values to the vendor specific default cumulative values ^[b] ; c) set all list parameters to their vendor specific default values; and d) not save any values to non-volatile media.
[a] The command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.			
[b] Vendor specific default threshold values and vendor specific default cumulative values may be zero.			

The current cumulative values may be updated by the device server as defined for the specific log page or by the application client using the LOG SELECT command. The current threshold values may only be modified by the application client via the LOG SELECT command.

NOTE Log pages or log parameters that are not available may become available at some later time (e.g., after the logical unit has become ready).

Additional information about the LOG SELECT command is in Clause 3.9.

The application client should send log pages in ascending order by page code value if the Data-Out Buffer contains multiple log pages. If the Data-Out Buffer contains multiple log parameters within a log page, then they should be sent in ascending order by parameter code value. If the application client sends log pages out of order or parameter codes out of order, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

3.10 LOG SENSE command

The LOG SENSE command (see table 81) provides a means for the application client to retrieve statistical or other operational information maintained by the SCSI target device about the SCSI target device or its logical units. It is a complementary command to the LOG SELECT command. See clause 4.2 of this manual for more information on returned log pages.

Table 81 LOG SENSE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (4Dh)							
1	Reserved						Obsolete	SP
2	PC		PAGE CODE					
3	SUBPAGE CODE							
4	Reserved							
5	(MSB)							
6	PARAMETER POINTER						(LSB)	
7	(MSB)							
8	ALLOCATION LENGTH						(LSB)	
9	CONTROL							

SP (Saving Parameters) bit

- 1 If saving log parameters is implemented, an SP bit set to one specifies that the device server shall perform the specified LOG SENSE command and shall save all log parameters identified as saveable by the DS bit to a nonvolatile, vendor specific location. Saving parameters is an optional function of the LOG SENSE command. If the logical unit does not implement saving log parameters and if the save parameters (SP) bit is set to one, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.
- 0 An SP bit set to zero specifies the device server shall perform the specified LOG SENSE command and shall not save any log parameters.

For data counter log parameters (i.e., when the FORMAT AND LINKING field in the parameter control byte in the log parameter structure (see 5.2.2.2) contains 00b or 10b), the page control (PC) table 78 specifies which log parameter values are to be returned by a device server in response to a LOG SENSE command.

For list parameters (i.e., when the FORMAT AND LINKING field in the parameter control byte in the log parameter structure (see 5.2.2.2) contains 01b or 11b), the PC field shall be ignored. If the parameters specified by the PAGE CODE field and SUBPAGE CODE field in the CDB are list parameters, then the parameter values returned by a device server in response to a LOG SENSE command are determined as follows:

- 1) the current list parameter values, if there has been an update to a list parameter value (e.g., by a LOG SELECT command or by a device specific event) in the specified page or pages since the last logical unit reset occurred;
- 2) the saved list parameter values, if saved parameters are implemented and an update has not occurred since the last logical unit reset; or
- 3) the vendor specific default list parameter values, if saved values are not available or not implemented and an update has not occurred since the last logical unit reset.

PAGE CODE and SUBPAGE CODE Fields

The PAGE CODE field and SUBPAGE CODE field specify which log page of data is being requested. If the log page specified by the page code and subpage code combination is reserved or not supported, then the device server shall terminate with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

PARAMETER POINTER field

The PARAMETER POINTER field allows the application client to request parameter data beginning from a specific parameter code to the maximum allocation length or the maximum parameter code supported by the logical unit, whichever is less. If the value of the PARAMETER POINTER field is larger than the largest available parameter code known to the device server for the specified log page, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

Log parameters within the specified log page shall be transferred in ascending order according to parameter code. Additional information about the LOG SENSE command is in 5.2.

3.11 MODE SELECT(6) command

The MODE SELECT(6) command (see table 82) provides a means for the application client to specify medium, logical unit, or peripheral device parameters to the device server. Device servers that implement the MODE SELECT(6) command shall also implement the MODE SENSE(6) command. Application clients should issue MODE SENSE(6) prior to each MODE SELECT(6) to determine supported mode pages, page lengths, and other parameters.

Table 82 MODE SELECT(6) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (15h)							
1	Reserved			PF	Reserved		RTD	SP
2	Reserved							
3	Reserved							
4	PARAMETER LIST LENGTH							
5	CONTROL							

Logical units shall share mode parameter header and block descriptor values across all I_T nexuses. I_T nexus loss shall not affect mode parameter header, block descriptor, and mode page values.

Logical units shall maintain current and saved values of each mode page based on any of the policies listed in table 83. The mode page policy used for each mode page may be reported in the Mode Page Policy VPD page (see 5.4.14).

Table 83 Mode page policies

Mode page policy	Number of mode page copies
Shared	One copy of the mode page that is shared by all I_T nexuses.
Per target port	A separate copy of the mode page for each target port with each copy shared by all initiator ports.
Per I_T nexus	A separate copy of the mode page for each I_T nexus

After a logical unit reset, each mode parameter header, block descriptor, and mode page shall revert to saved values if supported or default values if saved values are not supported.

If an application client sends a MODE SELECT command that changes any parameters applying to other I_T nexuses, the device server shall establish a unit attention (see SAM-6) condition for the initiator port associated with every I_T nexus except the I_T nexus on which the MODE SELECT command was received, with the additional sense code set to MODE PARAMETERS CHANGED.

PF (Page Format) bit

- 0** A page format (PF) bit set to zero specifies that all parameters after the block descriptors are vendor specific.
- 1** A PF bit set to one specifies that the MODE SELECT parameters following the header and block descriptor(s) are structured as pages of related parameters and are as defined in this manual. If the RTD bit is set to one then the PF bit is ignored.

RTD (revert to defaults) bit

- 0** An RTD bit set to zero specifies that the device server shall process the MODE SELECT command based on the other fields in the CDB and parameter data.
- 1** An RTD_SUP bit (see SPC-6) set to one and an RTD bit set to one specifies that the device server shall revert:
 - a) current mode page values for all mode pages to their default values, if the SP bit is set to zero; and
 - b) current mode page values and saved mode page values for all pages to their default values, if the SP bit is set to one.

SP (save pages) bit

- 0** A save pages (SP) bit set to zero specifies that the device server shall perform the specified MODE SELECT operation, and shall not save any mode pages. If the logical unit implements no distinction between current and saved mode pages and the SP bit is set to zero, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB. An SP bit set to one specifies that the device server shall perform the specified MODE SELECT operation, and shall save to a nonvolatile vendor specific location all the saveable mode pages including any sent in the Data-Out Buffer. Mode pages that are saved are specified by the parameter saveable (PS) bit that is returned in the first byte of each mode page by the MODE SENSE command.
- 1** If the PS bit is set to one in the MODE SENSE data, then the mode page shall be saveable by issuing a MODE SELECT command with the SP bit set to one. If the logical unit does not implement saved mode pages and the SP bit is set to one, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the mode parameter list that shall be contained in the Data-Out Buffer. A parameter list length of zero specifies that the Data-Out Buffer shall be empty. This condition shall not be considered as an error.

If the parameter list length results in the truncation of any mode parameter header, mode parameter block descriptor(s), or mode page, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to PARAMETER LIST LENGTH ERROR.

The mode parameter list for the MODE SELECT and MODE SENSE commands is defined in 3.13. Parts of each mode parameter list are defined in a device-type dependent manner. Definitions for the parts of each mode parameter list that are unique for each device-type may be found in the applicable command standards.

The device server shall terminate the MODE SELECT command with CHECK CONDITION status, set the sense key to ILLEGAL REQUEST, set the additional sense code to INVALID FIELD IN PARAMETER LIST, and shall not change any mode parameters in response to any of the following conditions:

- a) If the application client sets any field that is reported as not changeable by the device server to a value other than its current value;
- b) If the application client sets any field in the mode parameter header or block descriptor(s) to an unsupported value;
- c) If an application client sends a mode page with a page length not equal to the page length returned by the MODE SENSE command for that mode page;
- d) If the application client sends an unsupported value for a mode parameter and rounding is not implemented for that mode parameter;
or
- e) If the application client sets any reserved field in the mode parameter list to a non-zero value and the device server checks reserved fields.

If the application client sends a value for a mode parameter that is outside the range supported by the device server and rounding is implemented for that mode parameter, the device server handles the condition by either:

- a) Rounding the parameter to an acceptable value and terminating the command as described in 2.3; or
- b) Terminating the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

A device server may alter any mode parameter in any mode page, even those reported as non-changeable, as a result of changes to other mode parameters.

The device server validates the non-changeable mode parameters against the current values that existed for those mode parameters prior to the MODE SELECT command.

NOTE The current values calculated by the device server may affect the application client's operation. The application client may issue a MODE SENSE command after each MODE SELECT command, to determine the current values.

3.12 MODE SELECT (10) command

The MODE SELECT(10) command (see table 84) provides a means for the application client to specify medium, logical unit, or peripheral device parameters to the device server. See the MODE SELECT(6) command (see 3.11) for a description of the fields and operation of this command. Application clients should issue MODE SENSE(10) prior to each MODE SELECT(10) to determine supported mode pages, page lengths, and other parameters. Device servers that implement the MODE SELECT(10) command shall also implement the MODE SENSE(10) command.

Table 84 MODE SELECT(10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (55h)							
1	Reserved			PF	Reserved			SP
2	Reserved							
...								
6								
7	(MSB)	PARAMETER LIST LENGTH						(LSB)
8								
9	CONTROL							

3.13 MODE SENSE(6) command

3.13.1 MODE SENSE(6) command introduction

The MODE SENSE(6) command (see table 85) provides a means for a device server to report parameters to an application client. It is a complementary command to the MODE SELECT(6) command. Device servers that implement the MODE SENSE(6) command shall also implement the MODE SELECT(6) command.

Table 85 MODE SENSE(6) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (1Ah)							
1	Reserved				DBD	Reserved		
2	PC		PAGE CODE					
3	SUBPAGE CODE							
4	ALLOCATION LENGTH							
5	CONTROL							

DBD (disable block descriptors) bit

- 0** A disable block descriptors (DBD) bit set to zero specifies that the device server may return zero or more block descriptors in the returned MODE SENSE data.
- 1** A DBD bit set to one specifies that the device server shall not return any block descriptors in the returned MODE SENSE data.

PC (Page Control) field

The page control (PC) field specifies the type of mode parameter values to be returned in the mode pages. The PC field is defined in table 86.

Table 86 Page control (PC) field

Code	Type of parameter	Reference
00b	Current values	3.13.1.1
01b	Changeable values	3.13.1.2
10b	Default values	3.13.1.3
11b	Saved values	3.13.1.4

The PC field only affects the mode parameters within the mode pages, however the PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field should return current values (i.e., as if PC is set to 00b). The mode parameter header and mode parameter block descriptor should return current values.

Some SCSI target devices may not distinguish between current and saved mode parameters and report identical values in response to a PC field of either 00b or 11b. See also the description of the save pages (SP) bit in the MODE SELECT command.

PAGE CODE and SUBPAGE CODE fields

The PAGE CODE and SUBPAGE CODE fields specify which mode pages and subpages to return (see table 401).

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

An application client may request any one or all of the supported mode pages from the device server. If an application client issues a MODE SENSE command with a page code or subpage code value not implemented by the logical unit, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

If an application client requests all supported mode pages, the device server shall return the supported pages in ascending page code order beginning with mode page 01h. If mode page 00h is implemented, the device server shall return mode page 00h after all other mode pages have been returned.

If the PC field and the PAGE CODE field are both set to zero, the device server should return a mode parameter header and block descriptor, if applicable.

The mode parameter list for direct access devices for MODE SELECT and MODE SENSE is defined in 5.3. Parts of the mode parameter list are specifically defined for each device type. Definitions for the parts of each mode parameter list that are unique for each device-type may be found in the applicable command standards.

3.13.1.1 Current values

A PC field value of 00b requests that the device server return the current values of the mode parameters. The current values returned are:

- a) The current values of the mode parameters established by the last successful MODE SELECT command;
- b) The saved values of the mode parameters if a MODE SELECT command has not successfully completed since the mode parameters were restored to their saved values (see 3.9); or
- c) The default values of the mode parameters if a MODE SELECT command has not successfully completed since the mode parameters were restored to their default values (see 3.9).

3.13.1.2 Changeable values

A PC field value of 01b requests that the device server return a mask denoting those mode parameters that are changeable. In the mask, the bits in the fields of the mode parameters that are changeable all shall be set to one and the bits in the fields of the mode parameters that are non-changeable (i.e., defined by the logical unit) all shall be set to zero.

If the logical unit does not implement changeable parameters mode pages and the device server receives a MODE SENSE command with 01b in the PC field, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

An attempt to change a non-changeable mode parameter using the MODE SELECT command shall result in an error condition (see 3.9).

The application client should issue a MODE SENSE command with the PC field set to 01b and the PAGE CODE field set to 3Fh to determine which mode pages are supported, which mode parameters within the mode pages are changeable, and the supported length of each mode page prior to issuing any MODE SELECT commands.

3.13.1.3 Default values

A PC field value of 10b requests that the device server return the default values of the mode parameters. Unsupported parameters shall be set to zero. Default values should be accessible even if the logical unit is not ready.

3.13.1.4 Saved values

A PC field value of 11b requests that the device server return the saved values of the mode parameters. Mode parameters not supported by the logical unit shall be set to zero. If saved values are not implemented, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to SAVING PARAMETERS NOT SUPPORTED.

The method of saving parameters is vendor specific. The parameters are preserved in such a manner that they are retained when the device is powered down. All saveable mode pages should be considered saved when a MODE SELECT command issued with the SP bit set to one has returned a GOOD status or after the successful completion of a FORMAT UNIT command.

3.13.1.5 Initial responses

After a logical unit reset, the device server shall respond in the following manner:

- a) If default values are requested, report the default values;
- b) If saved values are requested, report valid restored mode parameters, or restore the mode parameters and report them. If the saved values of the mode parameters are not able to be accessed from the nonvolatile vendor specific location, the command shall be terminated with CHECK CONDITION status, with the sense key set to NOT READY. If saved parameters are not implemented, respond as defined in 3.13.1.4; or
- c) If current values are requested and the current values have been sent by the application client via a MODE SELECT command, the current values shall be returned. If the current values have not been sent, the device server shall return:
 - a) The saved values, if saving is implemented and saved values are available; or
 - b) The default values.

3.14 MODE SENSE(10) command

The MODE SENSE(10) command (see table 87) provides a means for a device server to report parameters to an application client. It is a complementary command to the MODE SELECT(10) command. Device servers that implement the MODE SENSE(10) command shall also implement the MODE SELECT(10) command.

Table 87 MODE SENSE(10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (5Ah)							
1	Reserved			LLBAA	DBD	Reserved		
2	PC		PAGE CODE					
3	SUBPAGE CODE							
4	Reserved							
...								
6								
7	(MSB)	ALLOCATION LENGTH						
8							(LSB)	
9	CONTROL							

LLBAA (Long LBA Accepted) bit

- 1** If the Long LBA Accepted (LLBAA) bit is set to one, the device server is allowed to return parameter data with the LONGLBA bit equal to one.
- 0** If LLBAA bit is set to zero, the LONGLBA bit shall be zero in the parameter data returned by the device server.

See the MODE SENSE(6) command (3.13) for a description of the other fields and operation of this command.

3.15 PERSISTENT RESERVE IN command

3.15.1 PERSISTENT RESERVE IN command introduction

The PERSISTENT RESERVE IN command (see table 88) is used to obtain information about persistent reservations and reservation keys (i.e., registrations) that are active within a device server. This command is used in conjunction with the PERSISTENT RESERVE OUT command (see 3.16).

Table 88 PERSISTENT RESERVE IN command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (5Eh)							
1	Reserved			SERVICE ACTION				
2	Reserved							
...								
6								
7	(MSB)	ALLOCATION LENGTH						(LSB)
8								
9	CONTROL							

The service action codes for the PERSISTENT RESERVE IN command are defined in table 89.

Table 89 PERSISTENT RESERVE IN service action codes

Code	Name	Description	Reference
00h	READ KEYS	Reads all registered reservation keys (i.e., registrations) as described in SPC-6.	3.15.2
01h	READ RESERVATION	Reads the current persistent reservations as described in SPC-6.	3.15.3
02h	REPORT CAPABILITIES	Returns capability information	3.15.4
03h	READ FULL STATUS	Reads complete information about all registrations and the persistent reservations, if any	3.15.5
04h - 1Fh	Reserved	Reserved	

3.15.2 READ KEYS service action

The READ KEYS service action requests that the device server return a parameter list containing a header and a list of each currently registered I_T nexus' reservation key. If multiple I_T nexuses have registered with the same key, then that key value shall be listed multiple times, once for each such registration.

For more information on READ KEYS see SPC-6.

The format for the parameter data provided in response to a PERSISTENT RESERVE IN command with the READ KEYS service action is shown in table 90.

Table 90 PERSISTENT RESERVE IN parameter data for READ KEYS

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	PRGENERATION							
3	(LSB)							
4	(MSB)							
...	ADDITIONAL LENGTH (N-7)							
7	(LSB)							
Reservation key list								
8	(MSB)							
...	Reservation key [first]							
15	(LSB)							
n-7	(MSB)							
...	Reservation key [last]							
n	(LSB)							

PRGENERATION (Persistent Reservations Generation) field

The Persistent Reservations Generation (PRGENERATION) field shall contain a 32-bit counter maintained by the device server that shall be incremented every time a PERSISTENT RESERVE OUT command requests a REGISTER service action, a REGISTER AND IGNORE EXISTING KEY service action, a REGISTER AND MOVE service action, a CLEAR service action, a PREEMPT service action, or a PREEMPT AND ABORT service action. The counter shall not be incremented by a PERSISTENT RESERVE IN command, by a PERSISTENT RESERVE OUT command that performs a RESERVE or RELEASE service action, or by a PERSISTENT RESERVE OUT command that is terminated due to an error or reservation conflict. Regardless of the APTPL bit value the PRGENERATION value shall be set to zero by a power on.

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field contains a count of the number of bytes in the Reservation key list. The relationship between the ADDITIONAL LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

The reservation key list contains the 8-byte reservation keys for all I_T nexuses that have been registered (see SPC-6).

3.15.3 READ RESERVATION service action

3.15.3.1 READ RESERVATION service action introduction

The READ RESERVATION service action requests that the device server return a parameter list containing a header and the persistent reservation, if any, that is present in the device server.

For more information on READ RESERVATION see SPC-6.

3.15.3.2 PERSISTENT RESERVE IN parameter data for READ RESERVATION

When no persistent reservation is held, the format for the parameter data provided in response to a PERSISTENT RESERVE IN command with the READ RESERVATION service action is shown in table 91.

Table 91 PERSISTENT RESERVE IN data for READ RESERVATION with no reservation held

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	PRGENERATION							
3	(LSB)							
4	(MSB)							
...	ADDITIONAL LENGTH (0000_0000h)							
7	(LSB)							

PRGENERATION field

The PRGENERATION field shall be as defined for the PERSISTENT RESERVE IN command with READ KEYS service action parameter data (see 3.15.2).

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field shall be set to zero, indicating that no persistent reservation is held.

When a persistent reservation is held, the format for the parameter data provided in response to a PERSISTENT RESERVE IN command with the READ RESERVATION service action is shown in table 92.

Table 92 PERSISTENT RESERVE IN parameter data for READ RESERVATION with reservation

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	PRGENERATION							
3	(LSB)							
4	(MSB)							
...	ADDITIONAL LENGTH (0000-0010h)							
7	(LSB)							
8	(MSB)							
...	RESERVATION KEY							
15	(LSB)							
16	Obsolete							
...	Obsolete							
19	Obsolete							
20	Reserved							
21	SCOPE				TYPE			
22	Obsolete							
23	Obsolete							

PRGENERATION field

The PRGENERATION field shall be as defined for the PERSISTENT RESERVE IN command with READ KEYS service action parameter data.

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field contains a count of the number of bytes to follow and shall be set to 16. The relationship between the ADDITIONAL LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

RESERVATION KEY field

The RESERVATION KEY field shall contain the reservation key under which the persistent reservation is held (see SPC-6).

SCOPE field

The SCOPE field shall be set to LU_SCOPE (see 3.15.3.3).

TYPE field

The TYPE field shall contain the persistent reservation type (see 3.15.3.4) specified in the PERSISTENT RESERVE OUT command that created the persistent reservation.

The obsolete fields in bytes 16 through 19, byte 22, and byte 23 were defined in a previous standard.

3.15.3.3 Persistent reservations scope

The SCOPE field (see table 93) shall be set to LU_SCOPE, specifying that the persistent reservation applies to the entire logical unit.

Table 93 Persistent reservation scope codes

Code	Name	Description
0h	LU_SCOPE	Persistent reservation applies to the full logical unit
1h - 2h		Obsolete
3h - Fh		Reserved

The LU_SCOPE scope shall be implemented by all device servers that implement PERSISTENT RESERVE OUT.

3.15.3.4 Persistent reservations type

The TYPE field (see table 94) specifies the characteristics of the persistent reservation being established for all logical blocks within the logical unit. SPC-6 defines the persistent reservation types under which each command defined in that standard is allowed to be processed. Each other command standard (e.g., SBC-5, SSC-3, SMC-3, MMC-5, or SES-3) defines the persistent reservation types under which each command defined in that command standard is allowed to be processed.

Table 94 Persistent reservation type codes

Code	Name	Description
0h		Obsolete
1h	Write Exclusive	Access Restrictions: Some commands (e.g., media-access write commands) are only allowed for the persistent reservation holder (see SPC-6). Persistent Reservation Holder: There is only one persistent reservation holder.
2h		Obsolete
3h	Exclusive Access	Access Restrictions: Some commands (e.g., media-access commands) are only allowed for the persistent reservation holder (see SPC-6). Persistent Reservation Holder: There is only one persistent reservation holder.
4h		Obsolete
5h	Write Exclusive – Registrants Only	Access Restrictions: Some commands (e.g., media-access write commands) are only allowed for registered I_T nexuses. Persistent Reservation Holder: There is only one persistent reservation holder (see SPC-6).
6h	Exclusive Access – Registrants Only	Access Restrictions: Some commands (e.g., media-access commands) are only allowed for registered I_T nexuses. Persistent Reservation Holder: There is only one persistent reservation holder (see SPC-6).
7h	Write Exclusive – All Registrants	Access Restrictions: Some commands (e.g., media-access write commands) are only allowed for registered I_T nexuses. Persistent Reservation Holder: Each registered I_T nexus is a persistent reservation holder (see SPC-6).
8h	Exclusive Access – All Registrants	Access Restrictions: Some commands (e.g., media-access commands) are only allowed for registered I_T nexuses. Persistent Reservation Holder: Each registered I_T nexus is a persistent reservation holder (see SPC-6).
9h - Fh	Reserved	

3.15.4 REPORT CAPABILITIES service action

The REPORT CAPABILITIES service action requests that the device server return information on persistent reservation features.

The format for the parameter data provided in response to a PERSISTENT RESERVE IN command with the REPORT CAPABILITIES service action is shown in table 95.

Table 95 PERSISTENT RESERVE IN parameter data for REPORT CAPABILITIES

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	LENGTH (0008h)							(LSB)
2	RLR_C	Reserved		CRH	SIP_C	ATP_C	Reserved	PTPL_C
3	TMV	ALLOW COMMANDS			Reserved			PTPL_A
4	_____							
5	PERSISTENT RESERVATION TYPE MASK							
6	_____							
7	Reserved							

LENGTH field

The LENGTH field indicates the length in bytes of the parameter data. The relationship between the LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

RLR_C (Replace Lost Reservation Capable) bit

- 1** Indicates that the device server supports the REPLACE LOST RESERVATION service action in the PERSISTENT RESERVE OUT command.
- 0** Indicates that the device server does not support the REPLACE LOST RESERVATION service action in the PERSISTENT RESERVE OUT command. If set to 0 then the device server shall not terminate any commands with CHECK CONDITION status with the sense key set to DATA PROTECT and the additional sense code set to PERSISTENT RESERVATION INFORMATION LOST as described in SPC-6.

CRH (Compatible Reservation Handling) field

- 1** A Compatible Reservation Handling (CRH) bit set to one indicates that the device server supports the exceptions to the RESERVE and RELEASE commands described in SPC-6.
- 0** A CRH bit set to zero indicates that RESERVE(6) command, RESERVE(10) command, RELEASE(6) command, and RELEASE(10) command are processed as defined in SPC-6.

SIP_C (Specify Initiator Ports Capable) bit

- 1** A Specify Initiator Ports Capable (SIP_C) bit set to one indicates that the device server supports the SPEC_I_PT bit in the PERSISTENT RESERVE OUT command parameter data (see 3.16.3).
- 0** An SIP_C bit set to zero indicates that the device server does not support the SPEC_I_PT bit in the PERSISTENT RESERVE OUT command parameter data.

ATP_C (Target Ports Capable) bit

- 1** An All Target Ports Capable (ATP_C) bit set to one indicates that the device server supports the ALL_TG_PT bit in the PERSISTENT RESERVE OUT command parameter data.
- 0** An ATP_C bit set to zero indicates that the device server does not support the ALL_TG_PT bit in the PERSISTENT RESERVE OUT command parameter data.

PTPL_C (Persist Through Power Loss Capable) bit

- 1** A Persist Through Power Loss Capable (PTPL_C) bit set to one indicates that the device server supports the persist through power loss capability see SPC-6 for persistent reservations and the APTPL bit in the PERSISTENT RESERVE OUT command parameter data.
- 0** An PTPL_C bit set to zero indicates that the device server does not support the persist through power loss capability.

TMV (Type Mask Valid) bit

- 1** A Type Mask Valid (TMV) bit set to one indicates that the PERSISTENT RESERVATION TYPE MASK field contains a bit map indicating which persistent reservation types are supported by the device server.
- 0** A TMV bit set to zero indicates that the PERSISTENT RESERVATION TYPE MASK field shall be ignored.

The ALLOW COMMANDS (see table 96) indicates whether certain commands are allowed through certain types of persistent reservations.

Table 96 ALLOW COMMANDS field

Code	Description
000b	No information is provided about whether certain commands are allowed through certain types of persistent reservations.
001b	The device server allows the TEST UNIT READY command (see 3.57) through Write Exclusive and Exclusive Access persistent reservations and does not provide information about whether the following commands are allowed through Write Exclusive persistent reservations: <ul style="list-style-type: none"> a) the MODE SENSE, READ ATTRIBUTE, READ BUFFER, RECEIVE DIAGNOSTIC RESULTS, REPORT SUPPORTED OPERATION CODES, and REPORT SUPPORTED TASK MANAGEMENT FUNCTION commands (see 3.38); and b) the READ DEFECT DATA command (see 3.27).
010b	The device server allows the TEST UNIT READY command through Write Exclusive and Exclusive Access persistent reservations and does not allow the following commands through Write Exclusive persistent reservations: <ul style="list-style-type: none"> a) the MODE SENSE, READ ATTRIBUTE, READ BUFFER, RECEIVE DIAGNOSTIC RESULTS, REPORT SUPPORTED OPERATION CODES, and REPORT SUPPORTED TASK MANAGEMENT FUNCTION commands; and b) the READ DEFECT DATA command. The device server does not allow the RECEIVE COPY RESULTS command through Write Exclusive or Exclusive Access persistent reservations.
011b	The device server allows the TEST UNIT READY command through Write Exclusive and Exclusive Access persistent reservations and allows the following commands through Write Exclusive persistent reservations: <ul style="list-style-type: none"> a) the MODE SENSE, READ ATTRIBUTE, READ BUFFER, RECEIVE DIAGNOSTIC RESULTS, REPORT SUPPORTED OPERATION CODES, and REPORT SUPPORTED TASK MANAGEMENT FUNCTION commands; and b) the READ DEFECT DATA command. The device server does not allow the RECEIVE COPY RESULTS command through Write Exclusive or Exclusive Access persistent reservations.
100b	The device server allows the TEST UNIT READY command and the RECEIVE COPY RESULTS command through Write Exclusive and Exclusive Access persistent reservations and allows the following commands through Write Exclusive persistent reservations: <ul style="list-style-type: none"> a) the MODE SENSE command, READ ATTRIBUTE command, READ BUFFER command, RECEIVE DIAGNOSTIC RESULTS command, REPORT SUPPORTED OPERATION CODES command, and REPORT SUPPORTED TASK MANAGEMENT FUNCTION command; and b) the READ DEFECT DATA command.
101b to 111b	Reserved

PTPL_A (Persist Through Power Loss Activated) bit

- 1** A Persist Through Power Loss Activated (PTPL_A) bit set to one indicates that the persist through power loss capability is activated (see SPC-6).
- 0** A PTPL_A bit set to zero indicates that the persist through power loss capability is not activated.

PERSISTENT RESERVATION TYPE MASK field

The PERSISTENT RESERVATION TYPE MASK field (see table 97) contains a bit map that indicates the persistent reservation types that are supported by the device server.

Table 97 Persistent Reservation Type Mask format

Bit Byte	7	6	5	4	3	2	1	0
4	WR_EX_AR	EX_AC_RO	WR_EX_RO	Reserved	EX_AC	Reserved	WR_EX	Reserved
5	Reserved							EX_AC_AR

WR_EX_AR (Write Exclusive – All Registrants) bit

- 1** A Write Exclusive – All Registrants (WR_EX_AR) bit set to one indicates that the device server supports the Write Exclusive – All Registrants persistent reservation type.
- 0** An WR_EX_AR bit set to zero indicates that the device server does not support the Write Exclusive – All Registrants persistent reservation type.

EX_AC_RO (Exclusive Access – Registrants Only) bit

- 1** An Exclusive Access – Registrants Only (EX_AC_RO) bit set to one indicates that the device server supports the Exclusive Access – Registrants Only persistent reservation type.
- 0** An EX_AC_RO bit set to zero indicates that the device server does not support the Exclusive Access – Registrants Only persistent reservation type.

WR_EX_RO (Write Exclusive – Registrants Only) bit

- 1** A Write Exclusive – Registrants Only (WR_EX_RO) bit set to one indicates that the device server supports the Write Exclusive – Registrants Only persistent reservation type.
- 0** An WR_EX_RO bit set to zero indicates that the device server does not support the Write Exclusive – Registrants Only persistent reservation type.

EX_AC (Exclusive Access) bit

- 1** An Exclusive Access (EX_AC) bit set to one indicates that the device server supports the Exclusive Access persistent reservation type.
- 0** An EX_AC bit set to zero indicates that the device server does not support the Exclusive Access persistent reservation type.

WR_EX (Write Exclusive) bit

- 1** A Write Exclusive (WR_EX) bit set to one indicates that the device server supports the Write Exclusive persistent reservation type.
- 0** An WR_EX bit set to zero indicates that the device server does not support the Write Exclusive persistent reservation type.

EX_AC_AR (Exclusive Access – All Registrants)

- 1** An Exclusive Access – All Registrants (EX_AC_AR) bit set to one indicates that the device server supports the Exclusive Access – All Registrants persistent reservation type.
- 0** An EX_AC_AR bit set to zero indicates that the device server does not support the Exclusive Access – All Registrants persistent reservation type.

3.15.5 READ FULL STATUS service action

The READ FULL STATUS service action requests that the device server return a parameter list describing the registration and persistent reservation status of each currently registered I_T nexus for the logical unit.

For more information on READ FULL STATUS see SPC-6.

The format for the parameter data provided in response to a PERSISTENT RESERVE IN command with the READ FULL STATUS service action is shown in table 98.

Table 98 PERSISTENT RESERVE IN parameter data for READ FULL STATUS

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	PRGENERATION							
3								
4	(MSB)							
...	ADDITIONAL LENGTH (N-7)							
7								
Full status descriptors								
8	Full status descriptor [first] (see table 99)							
...	Full status descriptor [last] (see table 99)							
n								

PRGENERATION field

The PRGENERATION field shall be as defined for the PERSISTENT RESERVE IN command with READ KEYS service action parameter data (see 3.15.2).

ADDITIONAL LENGTH field

The ADDITIONAL LENGTH field contains a count of the number of bytes to follow in the full status descriptors. The relationship between the ADDITIONAL LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

The format of the full status descriptors is shown in table 99. Each full status descriptor describes one or more registered I_T nexuses. The device server shall return persistent reservations status information for every registered I_T nexus.

Table 99 PERSISTENT RESERVE IN full status descriptor format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)	RESERVATION KEY							
...									
7									(LSB)
8		Reserved							
...									
11									
12		Reserved					ALL_TG_PT	R HOLDER	
13		SCOPE			TYPE				
14		Reserved							
...									
17									
18	(MSB)	RELATIVE TARGET PORT IDENTIFIER							
19									(LSB)
20	(MSB)	ADDITIONAL DESCRIPTOR LENGTH (N-23)							
...									
23									(LSB)
24		TRANSPORTID							
...									
n									

RESERVATION KEY field

The RESERVATION KEY field contains the reservation key.

R HOLDER (Reservation Holder) bit

- 1** A Reservation Holder (R HOLDER) bit set to one indicates that all I_T nexuses described by this full status descriptor are registered and are persistent reservation holders.
- 0** A R HOLDER bit set to zero indicates that all I_T nexuses described by this full status descriptor are registered but are not persistent reservation holders.

ALL_TG_PT (All Target Ports) bit

- 0** An All Target Ports (ALL_TG_PT) bit set to zero indicates that this full status descriptor represents a single I_T nexus.
- 1** An ALL_TG_PT bit set to one indicates that:
 - a) This full status descriptor represents all the I_T nexuses that are associated with both:
 1. The initiator port specified by the TRANSPORTID field; and
 2. Every target port in the SCSI target device;
 - b) All the I_T nexuses are registered with the same reservation key; and
 - c) All the I_T nexuses are either reservation holders or not reservation holders as indicated by the R_HOLDER bit.

The device server is not required to return an ALL_TG_PT bit set to one. Instead, it may return separate full status descriptors for each I_T nexus.

R_HOLDER bit

- 1** If the R_HOLDER bit is set to one (i.e., if the I_T nexus described by this full status descriptor is a reservation holder), the SCOPE field and the TYPE field are as defined in the READ RESERVATION service action parameter data (see 3.15.3).
- 0** If the R_HOLDER bit is set to zero, the contents of the SCOPE field and the TYPE field are not defined by this manual.

ALL_TG_PT bit

- 0** If the ALL_TG_PT bit set to zero, the RELATIVE TARGET PORT IDENTIFIER field contains the relative port identifier (see SPC-6) of the target port that is part of the I_T nexus described by this full status descriptor.
- 1** If the ALL_TG_PT bit is set to one, the contents of the RELATIVE TARGET PORT IDENTIFIER field are not defined by this manual.

ADDITIONAL DESCRIPTOR LENGTH field

The ADDITIONAL DESCRIPTOR LENGTH field contains a count of the number of bytes that follow in the descriptor (i.e., the size of the TRANSPORTID).

TRANSPORTID field

The TRANSPORTID field contains a TRANSPORTID (see SPC-6) identifying the initiator port that is part of the I_T nexus or I_T nexuses described by this full status descriptor.

3.16 PERSISTENT RESERVE OUT command

3.16.1 PERSISTENT RESERVE OUT command introduction

The PERSISTENT RESERVE OUT command (see table 100) is used to request service actions that reserve a logical unit for the exclusive or shared use of a particular I_T nexus. The command uses other service actions to manage and remove such persistent reservations.

I_T nexuses performing PERSISTENT RESERVE OUT service actions are identified by a registered reservation key provided by the application client. An application client may use the PERSISTENT RESERVE IN command to obtain the reservation key, if any, for the I_T nexus holding a persistent reservation and may use the PERSISTENT RESERVE OUT command to preempt that persistent reservation.

Table 100 PERSISTENT RESERVE OUT command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (5Fh)							
1	Reserved			SERVICE ACTION				
2	SCOPE				TYPE			
3	Reserved							
4	Reserved							
5	(MSB)							
...	PARAMETER LIST LENGTH							
8								(LSB)
9	CONTROL							

If a PERSISTENT RESERVE OUT command is attempted, but there are insufficient device server resources to complete the operation, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INSUFFICIENT REGISTRATION RESOURCES.

The PERSISTENT RESERVE OUT command contains fields that specify a persistent reservation service action, the intended scope of the persistent reservation, and the restrictions caused by the persistent reservation. The TYPE and SCOPE fields are defined in 3.15.3.4 and 3.15.3.3. If a SCOPE field specifies a scope that is not implemented, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

Fields contained in the PERSISTENT RESERVE OUT parameter list specify the information required to perform a particular persistent reservation service action.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the number of bytes of parameter data for the PERSISTENT RESERVE OUT command.

The parameter list shall be 24 bytes in length and the PARAMETER LIST LENGTH field shall contain 24 (18h), if the following conditions are true:

- a) The SPEC_I_PT bit (see 3.16.3) is set to zero; and
- b) The service action is not REGISTER AND MOVE.

If the SPEC_I_PT bit is set to zero, the service action is not REGISTER AND MOVE, and the parameter list length is not 24, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to PARAMETER LIST LENGTH ERROR.

If the parameter list length is larger than the device server is able to process, the command should be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to PARAMETER LIST LENGTH ERROR.

3.16.2 PERSISTENT RESERVE OUT service actions

When processing the PERSISTENT RESERVE OUT service actions, the device server shall increment the PRGENERATION value as specified in 3.15.2.

The PERSISTENT RESERVE OUT command service actions are defined in table 101.

Table 101 PERSISTENT RESERVE OUT service action codes

Code	Name	Description	PRGENERATION field incremented (see 3.15.2)	Parameter list format
00h	REGISTER	Register a reservation key with the device server (see SPC-6) or unregister a reservation key (see SPC-6).	Yes	Basic (see 3.16.3)
01h	RESERVE	Creates a persistent reservation having a specified SCOPE and TYPE (see SPC-6). The SCOPE and TYPE of a persistent reservation are defined in 3.15.3.3 and 3.15.3.4.	No	Basic (see 3.16.3)
02h	RELEASE	Releases the selected persistent reservation (see SPC-6).	No	Basic (see 3.16.3)
03h	CLEAR	Clears all reservation keys (i.e., registrations) and all persistent reservations (see SPC-6).	Yes	Basic (see 3.16.3)
04h	PREEMPT	Preempts persistent reservations and/or removes registrations (see SPC-6).	Yes	Basic (see 3.16.3)
05h	PREEMPT AND ABORT	Preempts persistent reservations and/or removes registrations and aborts all tasks for all preempted I_T nexuses (see SPC-6)	Yes	Basic (see 3.16.3)
06h	REGISTER AND IGNORE EXISTING KEY	Register a reservation key with the device server (see SPC-6) or unregister a reservation key (see SPC-6).	Yes	Basic (see 3.16.3)
07h	REGISTER AND MOVE	Register a reservation key for another I_T nexus with the device server and move a persistent reservation to that I_T nexus (see SPC-6)	Yes	Register and move (see 3.16.4)
08h	REPLACE LOST RESERVATION	Replace lost persistent reservation information (see SPC-6)	Yes	Basic (see 3.16.3)
09h - 1Fh	Reserved			

3.16.3 Basic PERSISTENT RESERVE OUT parameter list

The parameter list format shown in table 102 shall be used by the PERSISTENT RESERVE OUT command with any service action except the REGISTER AND MOVE service action. All fields shall be sent, even if the field is not required for the specified service action and scope values.

Table 102 PERSISTENT RESERVE OUT parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	RESERVATION KEY							
7	(LSB)							
8	(MSB)							
...	SERVICE ACTION RESERVATION KEY							
15	(LSB)							
16	Obsolete							
...								
19								
20	Reserved			SPEC_I_PT	ALL_TG_PT	Reserved	APTPL	
21	Reserved							
22	Obsolete							
23								
24	Additional parameter data							
...								
n								

The obsolete fields in bytes 16 through 19, byte 22 and byte 23 were defined in a previous standard.

RESERVATION KEY field

The RESERVATION KEY field contains an 8-byte value provided by the application client to the device server to identify the I_T nexus that is the source of the PERSISTENT RESERVE OUT command. The device server shall verify that the contents of the RESERVATION KEY field in a PERSISTENT RESERVE OUT command parameter data matches the registered reservation key for the I_T nexus from which the command was received, except for:

- a) The REGISTER AND IGNORE EXISTING KEY service action where the RESERVATION KEY field shall be ignored; and
- b) The REGISTER service action for an unregistered I_T nexus where the RESERVATION KEY field shall contain zero; and
- c) The REPLACE LOST RESERVATION service action where the RESERVATION KEY field shall contain zero.

Except as noted above, when a PERSISTENT RESERVE OUT command specifies a RESERVATION KEY field other than the reservation key registered for the I_T nexus the device server shall return a RESERVATION CONFLICT status. Except as noted above, the reservation key of the I_T nexus shall be verified to be correct regardless of the SERVICE ACTION and SCOPE field values.

SERVICE ACTION RESERVATION KEY field

The SERVICE ACTION RESERVATION KEY field contains information needed for the following service actions: REGISTER, REGISTER AND IGNORE EXISTING KEY, PREEMPT, PREEMPT AND ABORT, and REPLACE LOST RESERVATION. The SERVICE ACTION RESERVATION KEY field is ignored for the following service actions: RESERVE, RELEASE, and CLEAR.

For the REGISTER service action and REGISTER AND IGNORE EXISTING KEY service action, the SERVICE ACTION RESERVATION KEY field contains:

- a) The new reservation key to be registered in place of the registered reservation key specified in the RESERVATION KEY field; or
- b) Zero to unregister the registered reservation key specified in the RESERVATION KEY field.

For the PREEMPT service action and PREEMPT AND ABORT service action, the SERVICE ACTION RESERVATION KEY field contains the reservation key of:

- a) The registrations to be removed; and
- b) If the SERVICE ACTION RESERVATION KEY field identifies a persistent reservation holder (see SPC-6), persistent reservations that are to be preempted.

For the REPLACE LOST RESERVATION service action, the SERVICE ACTION RESERVATION KEY field contains the new reservation key to be registered.

SPEC_I_PT (Specify Initiator Ports) bit

- 0 If the Specify Initiator Ports (SPEC_I_PT) bit is set to zero, the device server shall apply the registration only to the I_T nexus that sent the PERSISTENT RESERVE OUT command.
- 1 If the SPEC_I_PT bit is set to one for the REGISTER service action or the REGISTER AND IGNORE EXISTING KEY service action, then the additional parameter data shall include a list of transport IDs (see table 103) and the device server shall also apply the registration to the I_T nexus for each initiator port specified by a TRANSPORTID. If a registration fails for any initiator port (e.g., if the logical unit does not have enough resources available to hold the registration information), no registrations shall be made, and the command shall be terminated with CHECK CONDITION status.

Table 103 PERSISTENT RESERVE OUT specify initiator ports additional parameter data

Bit Byte	7	6	5	4	3	2	1	0
24	TRANSPORTID PARAMETER DATA LENGTH (N - 27)							
...								
27								
TransportIDs List								
28	TransportID [first]							
...	TransportID [last]							
...								
n								

TRANSPORTID PARAMETER DATA LENGTH field

The TRANSPORTID PARAMETER DATA LENGTH field specifies the number of bytes of TRANSPORTIDs that follow.

The command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST:

- a) If the value in the parameter list length field in the CDB does not include all of the additional parameter list bytes specified by the TRANSPORTID PARAMETER DATA LENGTH field; or
- b) If the value in the TRANSPORTID PARAMETER DATA LENGTH field results in the truncation of a TRANSPORTID.

The format of a TRANSPORTID is specified in SPC-6.

ALL_TG_PT (All Target Ports) bit

The All Target Ports (ALL_TG_PT) bit is valid only for the REGISTER service action and the REGISTER AND IGNORE EXISTING KEY service action, and shall be ignored for all other service actions. Support for the ALL_TG_PT bit is optional.

- 1** If the device server receives a REGISTER service action or a REGISTER AND IGNORE EXISTING KEY service action with the ALL_TG_PT bit set to one, it shall create the specified registration on all target ports in the SCSI target device known to the device server (i.e., as if the same registration request had been received individually through each target port).
- 0** If the device server receives a REGISTER service action or a REGISTER AND IGNORE EXISTING KEY service action with the ALL_TG_PT bit set to zero, it shall apply the registration only to the target port through which the PERSISTENT RESERVE OUT command was received.

APTPL (Activate Persist Through Power Loss) bit

- 1** The Activate Persist Through Power Loss (APTPL) bit is valid only for the REGISTER service action and the REGISTER AND IGNORE EXISTING KEY service action, and shall be ignored for all other service actions. Support for an APTPL bit equal to one is optional. If a device server that does not support an APTPL bit set to one receives that value in a REGISTER service action or a REGISTER AND IGNORE EXISTING KEY service action, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. If the last valid APTPL bit value received by the device server is one, the logical unit shall retain any persistent reservation(s) that may be present and all reservation keys (i.e., registrations) for all I_T nexuses even if power is lost and later returned (see SPC-6).
- 0** If the last valid APTPL bit value received by the device server is zero, the loss of power in the SCSI target device shall release the persistent reservation for the logical unit and remove all registered reservation keys (see SPC-6).

Table 104 summarizes which fields are set by the application client and interpreted by the device server for each service action and scope value.

Table 104 PERSISTENT RESERVE OUT service actions and valid parameters (part 1 of 2)

Service action	Allowed SCOPE	Parameters (part 1 of 2)			
		TYPE	RESERVATION KEY	SERVICE ACTION RESERVATION KEY	APTPL
REGISTER	ignored	ignored	valid	valid	valid
REGISTER AND IGNORE EXISTING KEY	ignored	ignored	ignored	valid	valid
RESERVE	LU_SCOPE	valid	valid	ignored	ignored
RELEASE	LU_SCOPE	valid	valid	ignored	ignored
CLEAR	ignored	ignored	valid	ignored	ignored
PREEMPT	LU_SCOPE	valid	valid	valid	ignored
PREEMPT AND ABORT	LU_SCOPE	valid	valid	valid	ignored
REGISTER AND MOVE	LU_SCOPE	valid	valid	valid	not applicable [a]
REPLACE LOST RESERVATION	LU_SCOPE	valid	valid	valid	valid

[a] The parameter list format for the REGISTER AND MOVE service action is described in 3.16.4.

Table 105 PERSISTENT RESERVE OUT service actions and valid parameters (part 2 of 2)

Service action	Allowed SCOPE	Parameters (part 2 of 2)	
		ALL_TG_PT	SPEC_I_PT
REGISTER	ignored	valid	valid
REGISTER AND IGNORE EXISTING KEY	ignored	valid	invalid
RESERVE	LU_SCOPE	ignored	invalid
RELEASE	LU_SCOPE	ignored	invalid
CLEAR	ignored	ignored	invalid
PREEMPT	LU_SCOPE	ignored	invalid
PREEMPT AND ABORT	LU_SCOPE	ignored	invalid
REGISTER AND MOVE	LU_SCOPE	not applicable [a]	invalid
REPLACE LOST RESERVATION	LU_SCOPE	invalid	invalid

[a] The parameter list format for the REGISTER AND MOVE service action is described in 3.16.4.

3.16.4 Parameter list for the PERSISTENT RESERVE OUT command with REGISTER AND MOVE service

The parameter list format shown in table 106 shall be used by the PERSISTENT RESERVE OUT command with REGISTER AND MOVE service action.

Table 106 PERSISTENT RESERVE OUT command with REGISTER AND MOVE service

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)								
...	RESERVATION KEY								
7	(LSB)								
8	(MSB)								
...	SERVICE ACTION RESERVATION KEY								
15	(LSB)								
16	Reserved								
17	Reserved						UNREG	APTPL	
18	(MSB)								
19	RELATIVE TARGET PORT IDENTIFIER								
20	(MSB)								
...	TRANSPORTID PARAMETER DATA LENGTH (N - 23)								
23	(LSB)								
24	(MSB)								
...	TRANSPORTID								
n	(LSB)								

RESERVATION KEY field

The RESERVATION KEY field contains an 8-byte value provided by the application client to the device server to identify the I_T nexus that is the source of the PERSISTENT RESERVE OUT command. The device server shall verify that the contents of the RESERVATION KEY field in a PERSISTENT RESERVE OUT command parameter data matches the registered reservation key for the I_T nexus from which the command was received. If a PERSISTENT RESERVE OUT command specifies a RESERVATION KEY field other than the reservation key registered for the I_T nexus, the device server shall return a RESERVATION CONFLICT status.

SERVICE ACTION RESERVATION KEY field

The SERVICE ACTION RESERVATION KEY field contains the reservation key to be registered to the specified I_T nexus.

APTPL (Activate Persist Through Power Loss) bit

- 1 The Activate Persist Through Power Loss (APTPL) bit set to one is optional. If a device server that does not support an APTPL bit set to one receives that value, it shall return CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. If the last valid APTPL bit value received by the device server is one, the logical unit shall retain any persistent reservation(s) that may be present and all reservation keys (i.e., registrations) for all I_T nexuses even if power is lost and later returned (see SPC-6).
- 0 If the last valid APTPL bit value received by the device server is zero, the loss of power in the SCSI target device shall release the persistent reservation for the logical unit and remove all registered reservation keys (see SPC-6).

UNREG (Unregister) bit

- 0 The unregister (UNREG) bit set to zero specifies that the device server shall not unregister the I_T nexus on which the PERSISTENT RESERVE OUT command REGISTER AND MOVE service action was received.
- 1 An UNREG bit set to one specifies that the device server shall unregister the I_T nexus on which the PERSISTENT RESERVE OUT command REGISTER AND MOVE service action was received.

RELATIVE TARGET PORT IDENTIFIER field

The RELATIVE TARGET PORT IDENTIFIER field specifies the relative port identifier of the target port in the I_T nexus to which the persistent reservation is to be moved.

TRANSPORTID DESCRIPTOR LENGTH field

The TRANSPORTID DESCRIPTOR LENGTH field specifies the number of bytes of the TRANSPORTID that follows, shall be a minimum of 24 bytes, and shall be a multiple of 4.

TRANSPORTID field

The TRANSPORTID field specifies the initiator port in the I_T nexus to which the persistent reservation is to be moved. The format of the TransportID is defined in SPC-6.

The command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST:

- a) If the value in the PARAMETER LIST LENGTH field in the CDB does not include all of the parameter list bytes specified by the TRANSPORTID PARAMETER DATA LENGTH field; or
- b) If the value in the TRANSPORTID PARAMETER DATA LENGTH field results in the truncation of a TransportID.

3.17 READ (6) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The READ (6) command (see table 107) requests that the device server read the specified logical block(s) and transfer them to the data-in buffer. Each logical block read includes user data and, if the medium is formatted with protection information enabled, protection information. Each logical block transferred includes user data but does not include protection information. The most recent data value written, or to be written if cached, in the addressed logical blocks shall be returned.

Table 107 READ (6) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (08h)							
1	Reserved			(MSB)				
2	LOGICAL BLOCK ADDRESS							
3								(LSB)
4	TRANSFER LENGTH							
5	CONTROL							

The cache control bits are not provided for this command. Direct-access block devices with cache may have values for the cache control bits that affect the READ (6) command; however, no default values are defined by this manual. If explicit control is required, the READ (10) command should be used.

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field specifies the first logical block accessed by this command. If the logical block address exceeds the capacity of the medium the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

TRANSFER LENGTH field

The TRANSFER LENGTH field specifies the number of contiguous logical blocks of data that shall be read and transferred to the data-in buffer, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A TRANSFER LENGTH field set to zero specifies that 256 logical blocks shall be read. Any other value specifies the number of logical blocks that shall be read. If the logical block address plus the transfer length exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page.

- a) For the READ (10) command, READ (12) command, READ (16) command, and READ (32) command, a TRANSFER LENGTH field set to zero specifies that no logical blocks are read.
- b) Although the READ (6) command is limited to addressing logical blocks up to a capacity of 2 Gigabytes, for block lengths of 512 bytes, this command has been maintained since some system initialization routines require that the READ (6) command be used. System initialization routines should migrate from the READ (6) command to the READ (10) command, which is capable of addressing 2 Terabytes with block lengths of 512 bytes, or the READ (16) command to address more than 2 Terabytes.

The device server shall check the protection information read from the medium before returning status for the command as described in table 108.

Table 108 Protection information checking for READ (6)

Logical unit formatted with protection information	Shall device server transmit protection information?	Field in protection information [e]	Extended INQUIRY Data VPD page bit value [d]	If check fails [b] [c], additional sense code
Yes	No	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [a]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [f] [g]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
No	No protection information available to check			

[a] The device server checks the logical block application tag only if it has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field. The method for acquiring this knowledge is not defined by this manual.

[b] If an error is reported, the sense key shall be set to ABORTED COMMAND.

[c] If multiple errors occur, the selection of which error to report is not defined by this manual.

[d] See the Extended INQUIRY Data VPD page (see 5.4.10) for the definitions of the GRD_CHK bit, APP_CHK bit, and REF_CHK bit.

[e] If the device server detects a:

- LOGICAL BLOCK APPLICATION TAG field set to FFFFh and type 1 protection (see SBC-5) or type 2 protection (see SBC-5) is enabled; or
- LOGICAL BLOCK APPLICATION TAG field set to FFFFh, LOGICAL BLOCK REFERENCE TAG field set to FFFF FFFFh, and type 3 protection (see SBC-5) is enabled,

then the device server shall not check any protection information in the associated logical block.

[f] If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block.

[g] If type 2 protection or type 3 protection is enabled, the device server checks the logical block reference tag only if it has knowledge of the contents of the LOGICAL BLOCK REFERENCE TAG field. The method for acquiring this knowledge is not defined by this manual.

3.18 READ (10) command

The READ (10) command (see table 109) requests that the device server read the specified logical block(s) and transfer them to the data-in buffer. Each logical block read includes user data and, if the medium is formatted with protection information enabled, protection information. Each logical block transferred includes user data and may include protection information, based on the RDPROTECT field and the medium format. The most recent data value written in the addressed logical block shall be returned.

Table 109 READ (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (28h)							
1	RDPROTECT			DPO	FUA	RARC	Obsolete	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	(MSB)							
8	TRANSFER LENGTH							
8	(LSB)							
9	CONTROL							

RDPROTECT field

The device server shall check the protection information read from the medium before returning status for the command based on the RDPROTECT field as described in table 110.

Table 110 RDPROTECT field (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Shall device server transmit protection information?	Field in protection information [h]	Extended INQUIRY Data VPD page bit value [g]	If check fails [d] [f], additional sense code
000b	Yes [d]	No	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
				GRD_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [i]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
				REF_CHK = 0	NO CHECK PERFORMED
	No	No protection information available to check			
001b 101b [b]	Yes	Yes [e]	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
				GRD_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK REFERENCE TAG [j]	REF_CHK = 1 [i]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
				REF_CHK = 0	NO CHECK PERFORMED
	No [a]	No protection information available to transmit to the data-in buffer or for checking			
010b [b]	Yes	Yes [e]	LOGICAL BLOCK GUARD	NO CHECK PERFORMED	
			LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
				APP_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [i]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
				REF_CHK = 0	NO CHECK PERFORMED
			No [a]	No protection information available to transmit to the data-in buffer or for checking	
	011b [b]	Yes	Yes [e]	LOGICAL BLOCK GUARD	NO CHECK PERFORMED
LOGICAL BLOCK APPLICATION TAG				NO CHECK PERFORMED	
LOGICAL BLOCK REFERENCE TAG				NO CHECK PERFORMED	
No [a]		No protection information available to transmit to the data-in buffer or for checking			

Table 110 RDPROTECT field (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Shall device server transmit protection information?	Field in protection information [h]	Extended INQUIRY Data VPD page bit value [g]	If check fails [d] [f], additional sense code
100b [b]	Yes	Yes [e]	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
				GRD_CHK = 0	NO CHECK PERFORMED
			LOGICAL BLOCK APPLICATION TAG	NO CHECK PERFORMED	
	LOGICAL BLOCK REFERENCE TAG	NO CHECK PERFORMED			
No [a]	No protection information available to transmit to the data-in buffer or for checking				
101b - 111b	Reserved				

[a] A read operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[b] If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[c] If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field, then the device server shall check each logical block application tag. If the ATO bit in the Control mode page (see 5.3.14) is set to one, then this knowledge is acquired from:

- 1) the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a READ (32) command (see 3.21) is received by the device server;
- 2) the Application Tag mode page (see 5.3.6), if a command other than READ (32) is received by the device server, and the ATMPE bit in the Control mode page (see 5.3.14) is set to one; or
- 3) a method not defined by this standard, if a command other than READ (32) is received by the device server, and the ATMPE bit is set to zero.

[d] If an error is reported, the sense key shall be set to ABORTED COMMAND.

[e] Transmit protection information to the data-in buffer.

[f] If multiple errors occur, the selection of which error to report is not defined by this manual.

[g] See the Extended INQUIRY Data VPD page (see 5.4.10) for the definitions of the GRD_CHK bit, the APP_CHK bit, and the REF_CHK bit.

[h] If the device server detects:

- 1) a LOGICAL BLOCK APPLICATION TAG field set to FFFFh and type 1 protection (see SBC-5) or type 2 protection (see SBC-5) is enabled; or
- 2) a LOGICAL BLOCK APPLICATION TAG field set to FFFFh, LOGICAL BLOCK REFERENCE TAG field set to FFFF FFFFh, and type 3 protection (see SBC-5) is enabled, then the device server shall not check any protection information in the associated protection information interval.

[i] If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block. If type 2 protection or type 3 protection is enabled, the device server checks the LOGICAL BLOCK REFERENCE TAG if it has knowledge of the contents of the logical block reference tag field. If type 2 protection is enabled, then this knowledge may be acquired through the expected INITIAL LOGICAL BLOCK REFERENCE TAG field in a READ (32) command (see 3.21). If type 3 protection is enabled, then the method for acquiring this knowledge is not defined by this manual.

[j] If the DPICZ bit in the Control mode page (see 5.3.14) is set to one, then protection information shall not be checked.

DPO (Disable Page Out) bit

- 0** A Disable Page Out (DPO) bit set to zero specifies that the retention priority shall be determined by the RETENTION PRIORITY fields in the Caching mode page (see 5.3.9).
- 1** A DPO bit set to one specifies that the device server shall assign the logical blocks accessed by this command the lowest retention priority for being fetched into or retained by the cache. A DPO bit set to one overrides any retention priority specified in the Caching mode page. All other aspects of the algorithm implementing the cache replacement strategy are not defined by this manual.

NOTE The DPO bit is used to control replacement of logical blocks in the cache when the application client has information on the future usage of the logical blocks. If the DPO bit is set to one, the application client is specifying that the logical blocks accessed by the command are not likely to be accessed again in the near future and should not be put in the cache nor retained by the cache. If the DPO bit is set to zero, the application client is specifying that the logical blocks accessed by this command are likely to be accessed again in the near future.

FUA bit

- 0** A Force unit Access (FUA) bit set to zero specifies that the device server may read the logical blocks from the volatile cache (if any), the specified data pattern for that LBA (e.g., the data pattern for unmapped data), the non-volatile cache, or the medium.
- 1** An FUA bit set to one specifies that the device server shall read the logical blocks from the specified data pattern for that LBA, the non-volatile cache (if any), or the medium. If a volatile cache contains a more recent version of a logical block, then the device server shall write that logical block to non-volatile cache or the medium before reading the logical block.

RARC bit

If rebuild assist mode is supported and not enabled, then the rebuild assist recovery control (RARC) bit is ignored. If rebuild assist mode is supported and enabled, then the RARC bit specifies that read operations are processed as defined in SBC-5.

If the rebuild assist mode is not supported and the RARC bit is set to one, then the device server should terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field specifies the first logical block accessed by this command. If the logical block address exceeds the capacity of the medium the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

GROUP NUMBER field

The GROUP NUMBER field specifies the group into which attributes associated with the command should be collected. A GROUP NUMBER field set to zero specifies that any attributes associated with the command shall not be collected into any group.

TRANSFER LENGTH field

The TRANSFER LENGTH field specifies the number of contiguous logical blocks of data that shall be read and transferred to the data-in buffer, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A TRANSFER LENGTH field set to zero specifies that no logical blocks shall be read. This condition shall not be considered an error. Any other value specifies the number of logical blocks that shall be read. If the logical block address plus the transfer length exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page.

3.19 READ (12) command

The READ (12) command (see table 111) requests that the device server read the specified logical block(s) and transfer them to the data-in buffer. Each logical block read includes user data and, if the medium is formatted with protection information enabled, protection information. Each logical block transferred includes user data and may include protection information, based on the RDPROTECT field and the medium format.

Table 111 READ (12) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A8h)							
1	RDPROTECT			DPO	FUA	RARC	Obsolete	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	(MSB)							
...	TRANSFER LENGTH							
9	(LSB)							
10	RESTRICTED FOR MMC-6	Reserved		GROUP NUMBER				
11	CONTROL							

See the READ (10) command for the definitions of the fields in this command.

3.20 READ (16) command

The READ (16) command (see table 112) requests that the device server read the specified logical block(s) and transfer them to the data-in buffer. Each logical block read includes user data and, if the medium is formatted with protection information enabled, protection information. Each logical block transferred includes user data and may include protection information, based on the RDPROTECT field and the medium format.

Table 112 READ (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (88h)							
1	RDPROTECT			DPO	FUA	RARC	Obsolete	DLD2
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	TRANSFER LENGTH							
13	(LSB)							
14	DLD1	DLD0	GROUP NUMBER					
15	CONTROL							

DLD2, DLD1 and DLD0 bits

The command duration time (see SAM-6) is specified by the command duration limit descriptor (see 5.3.10 and 5.3.11) specified by the DLD2 bit, the DLD1 bit, and the DLD0 bit, as shown in table 113. The CDLP field in the REPORT SUPPORTED OPERATION CODES parameter data (see SPC-6) indicates that the command duration limit descriptor is in the Command Duration Limit A mode page or the Command Duration Limit B mode page (see 5.3.10 and 5.3.11).

Table 113 Force unit access for read operations

Duration limit descriptor value bits			Command duration limit descriptor specifying command duration time
DLD2	DLD1	DLD0	
0b	0b	0b	Command is not a duration limited command (see SAM-6)
0b	0b	1b	First command duration limit descriptor
0b	1b	0b	Second command duration limit descriptor
0b	1b	1b	Third command duration limit descriptor
1b	0b	0b	Fourth command duration limit descriptor
1b	0b	1b	Fifth command duration limit descriptor
1b	1b	0b	Sixth command duration limit descriptor
1b	1b	1b	Seventh command duration limit descriptor

CONTROL byte

The CONTROL byte is defined in 2.2.7

See the READ (10) command for the definitions of the other fields in this command.

3.21 READ (32) command

The READ (32) command (see table 114) requests that the device server read the specified logical block(s) and transfer them to the data-in buffer. Each logical block read includes user data and, if the medium is formatted with protection information enabled, protection information. Each logical block transferred includes user data and may include protection information, based on the RDPROTECT field and the medium format.

The READ (32) command shall only be processed if type 2 protection is enabled (see SBC-5).

Table 114 READ (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
...								
5								
6	Reserved		GROUP NUMBER					
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0009h)						(LSB)
9								
10	RDPROTECT		DPO	FUA	RARC	Obsolete	Reserved	
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
...								
19								
20	(MSB)	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG						(LSB)
...								
23								(LSB)
24	(MSB)	EXPECTED LOGICAL BLOCK APPLICATION TAG						(LSB)
25								
26	(MSB)	LOGICAL BLOCK APPLICATION TAG MASK						(LSB)
27								
28	(MSB)	TRANSFER LENGTH						(LSB)
...								
31								

See the READ (10) command for the definitions of the GROUP NUMBER field, the RDPROTECT field, the DPO bit, the FUA bit, the RARC bit, the LOGICAL BLOCK ADDRESS field, and the TRANSFER LENGTH field.

EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field

When checking of the LOGICAL BLOCK REFERENCE TAG field is enabled (see table 110), the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field contains the value of the LOGICAL BLOCK REFERENCE TAG field expected in the protection information of the first logical block accessed by the command instead of a value based on the LBA.

EXPECTED LOGICAL BLOCK APPLICATION TAG and LOGICAL BLOCK APPLICATION TAG MASK fields

If the ATO bit in the Control mode page (see 5.3.14) is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is enabled (see table 110), the LOGICAL BLOCK APPLICATION TAG MASK field contains a value that is a bit mask for enabling the checking of the LOGICAL BLOCK APPLICATION TAG field in the protection information for each logical block accessed by the command. A LOGICAL BLOCK APPLICATION TAG MASK field bit set to one enables the checking of the corresponding bit of the EXPECTED LOGICAL BLOCK APPLICATION TAG field with the corresponding bit of the LOGICAL BLOCK APPLICATION TAG field in the protection information.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see table 110), or if the ATO bit is set to zero, the LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored.

3.22 READ BUFFER (10) command

3.22.1 READ BUFFER (10) command introduction

The READ BUFFER (10) command (see table 115) is used in conjunction with the WRITE BUFFER command as a diagnostic function for testing memory in the SCSI device and the integrity of the service delivery subsystem. This command shall not alter the medium.

Table 115 READ BUFFER (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (3Ch)							
1	MODE SPECIFIC			MODE				
2	BUFFER ID							
3	(MSB)							
...	BUFFER OFFSET							
5	(LSB)							
6	(MSB)							
...	ALLOCATION LENGTH							
8	(LSB)							
9	CONTROL							

MODE SPECIFIC field

The usage of the MODE SPECIFIC field depends on the value in the MODE field.

MODE field

The function of this command and the meaning of fields within the CDB depend on the contents of the MODE field. The MODE field is defined in table 116.

Table 116 MODE field

MODE	Description
00h	Combined header and data ^[a]
01h	Not supported ^[a]
02h	Data
03h	Descriptor
04h - 09h	Reserved
0Ah	Echo buffer
0Bh	Echo buffer descriptor
0Ch - 19h	Reserved
1Ah	Obsolete
1Bh	Reserved
1Ch	Error history
1Dh - 1Fh	Reserved

[a] Mode 00h and 01h are not recommended.

ALLOCATION LENGTH field

If the MODE field is not set to one, the ALLOCATION LENGTH field is defined in 2.2.6.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.22.2 Combined header and data mode (00h)

The four-byte READ BUFFER header (see table 117) is followed by data bytes from the buffer.

Table 117 READ BUFFER header

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1	(MSB)	BUFFER CAPACITY							
...									
3									(LSB)
4	DATA								
...									
n									

BUFFER CAPACITY field

The BUFFER CAPACITY field specifies the total number of data bytes available in the buffer. The buffer capacity is not reduced to reflect the actual number of bytes written using the WRITE BUFFER command with combined header and data mode. The relationship between the BUFFER CAPACITY field and the CDB ALLOCATION LENGTH field is defined in 2.2.6. Following the READ BUFFER header, the device server shall transfer data from the buffer.

3.22.3 Vendor specific mode (01h)

This mode is not supported by Seagate products. If used, the drive will return CHECK CONDITION and report an ILLEGAL REQUEST/INVALID FIELD IN CDB error.

3.22.4 Data mode (02h)

In this mode, the Data-In Buffer is filled only with logical unit buffer data. The BUFFER ID field specifies a buffer within the logical unit from which data shall be transferred. Seagate assigns buffer ID codes to buffers within the logical unit. Buffer ID zero shall be supported. If more than one buffer is supported, then additional buffer ID codes shall be assigned contiguously, beginning with one. Buffer ID code assignments for the READ BUFFER command shall be the same as for the WRITE BUFFER command. If an unsupported buffer ID code is selected, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The BUFFER OFFSET field contains the byte offset within the specified buffer from which data shall be transferred. The application client should conform to the offset boundary requirements returned in the READ BUFFER descriptor (see 3.22.5). If the device server is unable to accept the specified buffer offset, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.22.5 Descriptor mode (03h)

In this mode, a maximum of four bytes of READ BUFFER descriptor information is returned. The device server shall return the descriptor information for the buffer specified by the BUFFER ID field (see the description of the buffer ID in 3.22.4). If there is no buffer associated with the specified buffer ID, the device server shall return all zeros in the READ BUFFER descriptor. The BUFFER OFFSET field is reserved in this mode. The allocation length should be set to four or greater. The READ BUFFER descriptor is defined as shown in table 118.

Table 118 READ BUFFER descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	OFFSET BOUNDARY							
1	(MSB)							
...	BUFFER CAPACITY							
3								(LSB)

OFFSET BOUNDARY field

The OFFSET BOUNDARY field returns the boundary alignment within the selected buffer for subsequent WRITE BUFFER and READ BUFFER commands. The value contained in the OFFSET BOUNDARY field shall be interpreted as a power of two.

For READ BUFFER commands, the OFFSET BOUNDARY field (see table 119) applies to the following modes:

- data (i.e., 02h) (see 3.22.4); and
- error history (i.e., 1Ch) (see 3.22.8)

The value contained in the BUFFER OFFSET field of subsequent WRITE BUFFER and READ BUFFER commands should be a multiple of $2^{\text{offset boundary}}$ as shown in table 119.

Table 119 Buffer offset boundary

Offset boundary	$2^{\text{Offset boundary}}$	Buffer offsets
0h	$2^0 = 1$	Byte boundaries
1h	$2^1 = 2$	Even-byte boundaries
2h	$2^2 = 4$	Four-byte boundaries
3h	$2^3 = 8$	Eight-byte boundaries
4h	$2^4 = 16$	16-byte boundaries
.	.	.
FFh	Not applicable	0 is the only supported buffer offset

BUFFER CAPACITY field

The BUFFER CAPACITY field shall return the maximum size of the selected buffer in bytes. This capacity value only applies to data mode (i.e., MODE field set to 02h).

NOTE In a system employing multiple application clients, a buffer may be altered between the WRITE BUFFER and READ BUFFER commands by another application client. Buffer testing applications should ensure that only a single application client is active. Use of reservations to all logical units on the device or linked commands may be helpful in avoiding buffer alteration between these two commands.

3.22.6 Echo buffer mode (0Ah)

In this mode the device server transfers data to the application client from the echo buffer that was written by the most recent WRITE BUFFER command with the mode field set to echo buffer received on the same I_T nexus. The READ BUFFER command shall return the same number of bytes of data as received in the prior WRITE BUFFER command with the mode field set to echo buffer, limited by the allocation length. The BUFFER ID and BUFFER OFFSET fields are ignored in this mode.

If no WRITE BUFFER command with the mode set to echo buffer received on this I_T nexus has completed without an error, then the READ BUFFER command shall terminate with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to COMMAND SEQUENCE ERROR. If the data in the echo buffer has been overwritten by another I_T nexus, the READ BUFFER command shall be terminated with CHECK CONDITION status, with the sense key set to ABORTED COMMAND, and the additional sense code set to ECHO BUFFER OVERWRITTEN.

After a WRITE BUFFER command with the mode set to echo buffer has completed without an error, the application client may send multiple READ BUFFER commands with the mode set to echo buffer in order to read the echo buffer data multiple times.

3.22.7 Echo buffer descriptor mode (0Bh)

In this mode, a maximum of four bytes of READ BUFFER descriptor information is returned. The device server shall return the descriptor information for the echo buffer. If there is no echo buffer implemented, the device server shall return all zeros in the READ BUFFER descriptor. The BUFFER ID field and BUFFER OFFSET field are reserved in this mode. The allocation length should be set to four or greater. The READ BUFFER descriptor is defined as shown in table 120.

Table 120 Echo buffer descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							EBOS
1	Reserved							
2	Reserved			(MSB)				
3	BUFFER CAPACITY							(LSB)

BUFFER CAPACITY field

The BUFFER CAPACITY field shall return the size of the echo buffer in bytes aligned to a four-byte boundary. The maximum echo buffer size is 4 096 bytes.

If the echo buffer is implemented, the echo buffer descriptor shall be implemented.

EBOS bit

- 1** An echo buffer overwritten supported (EBOS) bit set to one indicates either:
 - a) The device server returns the ECHO BUFFER OVERWRITTEN additional sense code if the data being read from the echo buffer is not the data previously written by the same I_T nexus, or
 - b) The device server ensures echo buffer data returned to each I_T nexus is the same as that previously written by that I_T nexus.
- 0** An EBOS bit set to zero specifies that the echo buffer may be overwritten by any intervening command received on any I_T nexus.

A READ BUFFER command with the mode set to echo buffer descriptor may be used to determine the echo buffer capacity and supported features before a WRITE BUFFER command with the mode set to echo buffer is sent.

3.22.8 Error history mode (1Ch)

3.22.8.1 Error history overview

This mode is used to manage and retrieve error history (see SPC-6).

If the device server is unable to process a READ BUFFER command with the MODE field set to 1Ch because of a vendor specific condition, then the device server shall terminate the READ BUFFER command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to COMMAND SEQUENCE ERROR.

The BUFFER ID field (see table 121) specifies the action that the device server shall perform, and the parameter data, if any, that the device server shall return.

Table 121 Error history BUFFER ID field

Code	Description	Buffer offset	Error history I_T nexus constrained	Reference
00h	Return error history directory	0000h	Yes	3.22.8.2
01h	Return error history directory and create new error history snapshot (see 1.1 and SPC-6)	0000h	Yes	3.22.8.2
02h	Return error history directory and establish new error history I_T nexus (see 1.1 and SPC-6)	0000h	No	3.22.8.2
03h	Return error history directory, establish new error history I_T nexus, and create new error history snapshot	0000h	No	3.22.8.2
04h to 0Fh	Reserved		Yes	
10h to EFh	Return error history	0000h to FFFFh	Yes	3.22.8.3
F0h to FDh	Reserved		Yes	
FEh	Clear error history I_T nexus	Ignored	Yes	3.22.8.4
FFh	Clear error history I_T nexus and release error history snapshot	Ignored	Yes	3.22.8.5

The command shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to OPERATION IN PROGRESS if the device server receives a READ BUFFER command:

- a) with the MODE field set to 1Ch;
- b) with the BUFFER ID field set to a value that table 121 shows as constrained by error history I_T nexus;
- c) if an error history I_T nexus exists and the command is received from an I_T nexus that is different that I_T nexus; and
- d) an error history snapshot exists.

BUFFER OFFSET field

The BUFFER OFFSET field specifies the byte offset from the start of the buffer specified by the BUFFER ID field from which the device server shall return data. The application client should conform to the offset boundary requirements indicated in the READ BUFFER descriptor (see 3.22.5). If the buffer offset is not one of those shown in table 121 or the device server is unable to accept the specified buffer offset, then the device server shall terminate the READ BUFFER command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.22.8.2 Error history directory

Whenever allowed by established error history I_T nexus constraints (see 3.22.8.1), if any, all error history device server actions return an error history directory (see table 124). Some error history device server actions also discard the existing error history snapshot (see SPC-6) and create a new error history snapshot (see table 122).

Table 122 Summary of error history directory device server actions

BUFFER ID field	Establish new error history I_T nexus (see SPC-6)	Error history snapshot (see SPC-6)	
		Preserved (if exists)	Created
00h	No [a]	Yes	No [b]
01h	No [a]	No	Yes
02h	Yes	Yes	No [b]
03h	Yes	No	Yes

[a] If no error history I_T nexus is established, a new one is established.
[b] If no error history snapshot exists, a new one is created.

Table 123 defines the meaning of the combinations of values for the BUFFER ID field and the MODE SPECIFIC field for the error history mode.

Table 123 BUFFER ID field and MODE SPECIFIC field meanings for the error history mode

BUFFER ID field	MODE SPECIFIC field	Description
00h to 03h	000b	If a new error history snapshot is created (see table 122), vendor specific parameter data shall be created (i.e., at least one error history directory entry (see table 127) shall contain a BUFFER FORMAT field that is set to 00h).
	001b	If a new error history snapshot is created (see table 122), current internal status parameter data shall be created (i.e., at least one error history directory entry (see table 127) shall contain a BUFFER FORMAT field that is set to 01h).
	010b to 111b	Reserved
All others	000b to 111b	Reserved

The error history directory is defined in table 124.

Table 124 Error history directory

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	T10 VENDOR IDENTIFICATION							
7	(LSB)							
8	VERSION							
9	Reserved			EHS_RETRIEVED		EHS_SOURCE		CLR_SUP
10	Reserved							
...								
29								
30	(MSB)							
31	DIRECTORY LENGTH (n-31)							
	(LSB)							
Error history directory list								
32	Error history directory entry [first] (see table 127)							
...								
39								
	...							
n-7	Error history directory entry [last] (see table 127)							
...								
n								

T10 VENDOR IDENTIFICATION field

The T10 VENDOR IDENTIFICATION field contains eight bytes of left-aligned ASCII data identifying the manufacturer of the logical unit. The T10 vendor identification shall be one assigned by INCITS.

NOTE The T10 VENDOR IDENTIFICATION field may contain a different value than the VENDOR IDENTIFICATION field in the standard INQUIRY data (see 3.8.2) (e.g., this field may indicate a disk drive component vendor while the standard INQUIRY data indicates the original equipment manufacturer).

VERSION field

The VERSION field indicates the version and format of the vendor specific error history. The VERSION field is assigned by the vendor indicated in the T10 VENDOR IDENTIFICATION field.

EHS_RETRIEVED (error history retrieved) field

The error history retrieved (EHS_RETRIEVED) field (see table 125) indicates whether a clear error history device server action has been requested for the error history snapshot. EHS_RETRIEVED field shall be set to 00b or 10b when the error history snapshot is created.

Table 125 EHS_RETRIEVED field

Code	Description
00b	No information
01b	The error history I_T nexus has requested buffer ID FEh (i.e., clear error history I_T nexus) or buffer ID FFh (i.e., clear error history I_T nexus and release snapshot) for the current error history snapshot.
10b	An error history I_T nexus has not requested buffer ID FEh (i.e., clear error history I_T nexus) or buffer ID FFh (i.e., clear error history I_T nexus and release snapshot) for the current error history snapshot.
11b	Reserved

EHS_SOURCE (error history source) field

The error history source (EHS_SOURCE) field (see table 126) indicates the source of the error history snapshot.

Table 126 EHS_SOURCE field

Code	Description
00b	The error history snapshot was created by the device server and was not created due to processing a READ BUFFER command.
01b	Error history snapshot was created due to processing of the current READ BUFFER command
10b	Error history snapshot was created due to processing of a previous READ BUFFER command
11b	Reserved

CLR_SUPC (clear support) bit

- 1** A clear support (CLR_SUP) bit set to one indicates that the CLR bit is supported in the WRITE BUFFER command download error history mode (see 3.74).
- 0** A CLR_SUP bit set to zero indicates that the CLR bit is not supported.

DIRECTORY LENGTH field

The DIRECTORY LENGTH field indicates the number of error history directory list bytes available to be transferred. This value shall not be altered even if the allocation length is not sufficient to transfer the entire error history directory list.

The error history directory list contains an error history directory entry (see table 127) for each supported buffer ID in the range of 00h to EFh. The first entry shall be for buffer ID 00h and the entries shall be in order of ascending buffer IDs. The supported buffer IDs are not required to be contiguous. There shall not be any entries for buffer IDs greater than or equal to F0h.

Table 127 Error history directory entry

Bit Byte	7	6	5	4	3	2	1	0
0	SUPPORTED BUFFER ID							
1	BUFFER FORMAT							
2	Reserved				BUFFER SOURCE			
3	Reserved							
4	(MSB)							
...	MAXIMUM AVAILABLE LENGTH							
7	(LSB)							

SUPPORTED BUFFER ID field

The SUPPORTED BUFFER ID field indicates the error history buffer ID associated with this entry.

BUFFER FORMAT field

If the SUPPORTED BUFFER ID field is set to 10h to EFh, the BUFFER FORMAT field (see table 128) indicates the format of the parameter data for the error history buffer indicated by the SUPPORTED BUFFER ID field. If the SUPPORTED BUFFER ID field is not set to 10h to EFh, the BUFFER FORMAT field should be ignored by the application client.

Table 128 BUFFER FORMAT field

Code	Description	Format Reference
00h	Contains vendor specific data	
01h	Contains current internal status parameter data	see SPC-6
02h	Contains saved internal status parameter data	see SPC-6
All others	Reserved	

BUFFER SOURCE field

If the SUPPORTED BUFFER ID field is set to 10h to EFh, the BUFFER SOURCE field (see table 129) indicates the source field the error history buffer indicated by the SUPPORTED BUFFER ID field. If the SUPPORTED BUFFER ID field is set to 10h to EFh, the BUFFER SOURCE field should be ignored by the application client.

Table 129 BUFFER SOURCE field

Code	Description
0h	The source is indicated in the EHS_SOURCE field in the error history directory (see table 124).
1h	The source is unknown.
2h	The error history information was: a) created by the device server as the result of a vendor specific event; and b) not created due to processing of a READ BUFFER command.
3h	The error history information was created due to the processing of the current READ BUFFER command.
4h	The error history information was created due to the processing of a previous READ BUFFER command.
All others	Reserved

MAXIMUM AVAILABLE LENGTH

The MAXIMUM AVAILABLE LENGTH field indicates the maximum number of data bytes contained in the buffer indicated by the SUPPORTED BUFFER ID field. The actual number of bytes available for transfer may be smaller.

3.22.8.3 Error history data buffer**3.22.8.3.1 Overview**

Unless an error is encountered, the device server shall return parameter data that contains error history from the error history snapshot from the specified buffer at the specified buffer offset. The parameter data shall be formatted as indicated by the BUFFER FORMAT field in the error history directory entry (see table 127) associated with the buffer ID specified by the READ BUFFER command.

If the device server receives a READ BUFFER command with the MODE field set to 1Ch from the established error history I_T nexus and the BUFFER ID field is set to a value that the error history directory (see 3.22.8.2) shows as not supported, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

If the value in the BUFFER OFFSET field is not supported, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

The amount of error history in the specified buffer shall be less than or equal to the number of bytes indicated by the MAXIMUM AVAILABLE LENGTH field in the error history directory (see 3.22.8.2).

3.22.8.4 Clear error history I_T nexus

If the BUFFER ID field is set to FEh, the device server shall:

- a) clear the error history I_T nexus, if any; and
- b) not transfer any data.

3.22.8.5 Clear error history I_T nexus and release snapshot

If the BUFFER ID field is set to FFh, the device server shall:

- a) clear the error history I_T nexus, if any,
- b) release the error history snapshot, if any; and
- c) not transfer any data.

3.23 READ BUFFER (16) command

The READ BUFFER (16) command (see table 130) requests that the device server perform the actions defined for the READ BUFFER (10) command (see 3.22).

Table 130 READ BUFFER (16) command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (9Bh)								
1	MODE SPECIFIC			MODE					
2	(MSB)	BUFFER OFFSET							(LSB)
...									
9	(MSB)	ALLOCATION LENGTH							(LSB)
...									
10									
13									
14	BUFFER ID								
15	CONTROL								

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 130.

MODE SPECIFIC field, MODE field, BUFFER OFFSET field, ALLOCATION LENGTH field, and BUFFER ID field

The MODE SPECIFIC field, MODE field, BUFFER OFFSET field, ALLOCATION LENGTH field, and BUFFER ID field are defined in 3.22.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.24 READ CAPACITY (10) command

3.24.1 READ CAPACITY (10) overview

The READ CAPACITY (10) command (see table 131) requests that the device server transfer 8 bytes of parameter data describing the capacity and medium format of the direct-access block device to the data-in buffer. This command may be processed as if it has a HEAD OF QUEUE task attribute. If the logical unit supports protection information, the application client should use the READ CAPACITY (16) command instead of the READ CAPACITY (10) command.

Table 131 READ CAPACITY (10) command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (25h)								
1	Reserved							Obsolete	
2	(MSB)	LOGICAL BLOCK ADDRESS (Obsolete)						(LSB)	
...									
5									
6	Reserved								
7	Reserved								
8	Reserved							PMI (Obsolete)	
9	CONTROL								

For the definition of the LOGICAL BLOCK ADDRESS field see 2.2.3.

LOGICAL BLOCK ADDRESS field

This field has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The LOGICAL BLOCK ADDRESS field shall be set to zero if the PMI bit is set to zero. If the PMI bit is set to zero and the LOGICAL BLOCK ADDRESS field is not set to zero, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

PMI (Partial Medium Indicator) bit

This bit has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

- 0** A partial medium indicator (PMI) bit set to zero specifies that the device server return information on the last logical block on the direct-access block device.
- 1** A PMI bit set to one specifies that the device server return information on the last logical block after that specified in the LOGICAL BLOCK ADDRESS field before a substantial vendor-specific delay in data transfer may be encountered.

This function is intended to assist storage management software in determining whether there is sufficient space starting with the logical block address specified in the CDB to contain a frequently accessed data structure (e.g., a file directory or file index) without incurring an extra delay.

3.24.2 READ CAPACITY (10) parameter data

The READ CAPACITY (10) parameter data is defined in table 132. Any time the READ CAPACITY (10) parameter data changes, the device server should establish a unit attention condition as described in SBC-5.

Table 132 READ CAPACITY (10) parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	RETURNED LOGICAL BLOCK ADDRESS							
3								
4	(MSB)							
...	BLOCK LENGTH IN BYTES							
7								

RETURNED LOGICAL BLOCK ADDRESS field

If the number of logical blocks exceeds the maximum value that is able to be specified in the RETURNED LOGICAL BLOCK ADDRESS field, the device server shall set the RETURNED LOGICAL BLOCK ADDRESS field to FFFFFFFFh. The application client should then issue a READ CAPACITY (16) command (see 3.26) to retrieve the READ CAPACITY (16) parameter data.

- 0** If the PMI bit is set to zero, the device server shall set the RETURNED LOGICAL BLOCK ADDRESS field to the lower of:
 - a) the LBA of the last logical block on the direct-access block device; or
 - b) FFFFFFFFh.
- 1** If the PMI bit is set to one, the device server shall set the RETURNED LOGICAL BLOCK ADDRESS field to the lower of:
 - a) the last LBA after that specified in the LOGICAL BLOCK ADDRESS field of the CDB before a substantial vendor-specific delay in data transfer may be encountered; or
 - b) the LBA of the last logical block on the direct-access block device.

The RETURNED LOGICAL BLOCK ADDRESS shall be greater than or equal to that specified by the LOGICAL BLOCK ADDRESS field in the CDB.

BLOCK LENGTH IN BYTES field

The BLOCK LENGTH IN BYTES field contains the number of bytes of user data in the logical block indicated by the RETURNED LOGICAL BLOCK ADDRESS field. This value does not include protection information or additional information (e.g., ECC bytes) recorded on the medium.

3.25 READ CAPACITY (16) command

3.25.1 READ CAPACITY (16) command overview

The READ CAPACITY (16) command (see table 133) requests that the device server transfer parameter data describing the capacity and medium format of the direct-access block device to the data-in buffer. This command is mandatory if the logical unit supports protection information and optional otherwise (see SBC-5). This command is implemented as a service action of the SERVICE ACTION IN operation code. This command may be processed as if it has a HEAD OF QUEUE task attribute.

Table 133 READ CAPACITY (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (10h)				
2	(MSB)							
...	LOGICAL BLOCK ADDRESS (Obsolete)							
9	(LSB)							
10	(MSB)							
...	ALLOCATION LENGTH							
13	(LSB)							
14	Reserved							PMI (Obsolete)
15	CONTROL							

LOGICAL BLOCK ADDRESS field and PMI bit

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

See the READ CAPACITY (10) command (see 3.24) for the definition of the PMI bit.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field (see 2.2.6) specifies the maximum number of bytes that the application client has allocated for returned parameter data. An allocation length of zero indicates that no data shall be transferred. This condition shall not be considered as an error. The device server shall terminate transfers to the data-in buffer when the number of bytes specified by the ALLOCATION LENGTH field have been transferred or when all available data has been transferred, whichever is less. The contents of the parameter data shall not be altered to reflect the truncation, if any, that results from an insufficient allocation length.

3.25.2 READ CAPACITY (16) parameter data

The READ CAPACITY (16) parameter data is defined in table 134. Any time the READ CAPACITY (16) parameter data changes, the device server should establish a unit attention condition as described in SPC-6.

Table 134 READ CAPACITY (16) parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	RETURNED LOGICAL BLOCK ADDRESS							
7	(LSB)							
8	(MSB)							
...	LOGICAL BLOCK LENGTH IN BYTES							
11	(LSB)							
12	Reserved		RC BASIS		P_TYPE		PROT_EN	
13	P_I_EXPONENT				LOGICAL BLOCKS PER PHYSICAL BLOCK EXPONENT			
14	LBPME	LBPRZ	(MSB)					
15	LOWEST ALIGNED LOGICAL BLOCK ADDRESS							
16	(LSB)							
...	Reserved							
31								

RETURNED LOGICAL BLOCK ADDRESS field

The RETURNED LOGICAL BLOCK ADDRESS field and LOGICAL BLOCK LENGTH IN BYTES field of the READ CAPACITY (16) parameter data are the same as the in the READ CAPACITY (10) parameter data (see 3.24.1). The maximum value that shall be returned in the RETURNED LOGICAL BLOCK ADDRESS field is FFFFFFFF_FFFFFFFEh.

LOGICAL BLOCK LENGTH IN BYTES field

The LOGICAL BLOCK LENGTH IN BYTES field contains the number of bytes of user data in the logical block indicated by the RETURNED LOGICAL BLOCK ADDRESS field. This value does not include protection information or additional information (e.g., ECC bytes) recorded on the medium.

RC BASIS field

The RC BASIS field indicates the meaning of the value returned by the RETURNED LOGICAL BLOCK ADDRESS field in the READ CAPACITY (16) parameter data and is described in table 135.

Table 135 RC BASIS field

Code	DESCRIPTION
00b	The RETURNED LOGICAL BLOCK ADDRESS field indicates the highest LBA of a contiguous range of zones that are not sequential write required zones starting with the first zone.
01b	The RETURNED LOGICAL BLOCK ADDRESS field indicates the LBA of the last logical block on the logical unit.
10b	Reserved
11	Reserved

P_TYPE (Protection Type) field and PROT_EN bit

The protection type (P_TYPE) field and the PROT_EN bit (see table 136) indicate the logical unit's current type of protection.

Table 136 P_TYPE FIELD and PROT_EN bit

PROT_EN	P_TYPE	DESCRIPTION
0	XXXb	The logical unit is formatted to type 0 protection (see SBC-5)
1	000b	The logical unit is formatted to type 1 protection (see SBC-5)
1	001b	The logical unit is formatted to type 2 protection (see SBC-5)
1	010b	The logical unit is formatted to type 3 protection (see SBC-5)
1	011b - 111b	Reserved

P_I_EXPONENT field

The P_I_EXPONENT field may be used to determine the number of protection information intervals placed within each logical block (see 3.3.2).

The number of protection information intervals is calculated as follows:

$$\text{number of protection information intervals} = 2^{(\text{p}_i \text{ exponent})}$$

where: $\text{p}_i \text{ exponent}$ is the contents of the P_I_EXPONENT field

LOGICAL BLOCKS PER PHYSICAL BLOCKS EXPONENT field

The LOGICAL BLOCKS PER PHYSICAL BLOCKS EXPONENT field is defined in table 137.

Table 137 LOGICAL BLOCKS PER PHYSICAL BLOCKS EXPONENT field

Code	Description
0	One or more physical blocks per logical block ^[a]
$n > 0$	2^n logical blocks per physical block
[a] The number of physical blocks per logical block is not reported.	

Logical Block Provisioning Management Enabled (LBPME) bit

- 1** If the thin provisioning enabled (TPE) bit is set to one, then the logical unit implements logical block provisioning management (see SBC-5).
- 0** If the TPE bit is set to zero, then the logical unit does not implement logical block provisioning management (see SBC-5).

Logical Block Provisioning Read Zeros (LBPRZ) bit

- 1** If the logical block provisioning read zeros (LBPRZ) bit is set to one, then, for an unmapped LBA specified by a read operation, the device server shall send user data with all bits set to zero to the data-in buffer.
- 0** If the TPRZ bit is set to zero, then, for an unmapped LBA specified by a read operation, the device server may send user data with all bits set to any value to the data-in buffer.

LOWEST ALIGNED LOGICAL BLOCK ADDRESS field

The LOWEST ALIGNED LOGICAL BLOCK ADDRESS field indicates the LBA of the first logical block that is located at the beginning of a physical block (SBC-5).

3.26 READ DEFECT DATA (10) command

3.26.1 READ DEFECT DATA (10) command overview

The READ DEFECT DATA (10) command (see table 138) requests that the device server transfer the medium defect data to the data-in buffer.

Table 138 READ DEFECT DATA (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (37h)							
1	Reserved							
2	Reserved		REQ_PLIST	REQ_GLIST	DEFECT LIST FORMAT			
3	Reserved							
...								
6								
7	(MSB)	ALLOCATION LENGTH						(LSB)
8								
9	CONTROL							

If the device server is unable to access the medium defect data, it shall terminate the command with CHECK CONDITION status. The sense key shall be set to either MEDIUM ERROR, if a medium error occurred, or NO SENSE, if medium defect data does not exist. The additional sense code shall be set to DEFECT LIST NOT FOUND.

REQ_PLIST (request primary defect list) bit

- 0 A request primary defect list (REQ_PLIST) bit set to zero specifies that the device server shall not return the PLIST.
- 1 A REQ_PLIST bit set to one specifies that the device server shall return the PLIST, if any.

REQ_GLIST (request grown defect list) bit

- 0 A request grown defect list (REQ_GLIST) bit set to zero specifies that the device server shall not return the GLIST.
- 1 A REQ_GLIST bit set to one specifies that the device server shall return the GLIST, if any.

A REQ_PLIST bit set to zero and a REQ_GLIST bit set to zero specifies that the device server shall return only the defect list header (i.e., the first four bytes of the defect list).

A REQ_PLIST bit set to one and a REQ_GLIST bit set to one specifies that the device server shall return both the PLIST and GLIST, if any. The order the lists are returned in is vendor-specific. Whether the lists are merged or not is vendor-specific.

DEFECT LIST FORMAT field

The DEFECT LIST FORMAT field specifies the preferred format for the defect list. This field is intended for those device servers capable of returning more than one format, as defined in the FORMAT UNIT command (see 3.3.5). A device server unable to return the requested format shall return the defect list in its default format and indicate that format in the DEFECT LIST FORMAT field in the defect list header (see table 138).

If the requested defect list format and the returned defect list format are not the same, the device server shall transfer the defect data and then terminate the command with CHECK CONDITION status with the sense key set to RECOVERED ERROR and the additional sense code set to DEFECT LIST NOT FOUND.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. The application client is responsible for comparing the allocation length requested in the CDB with the defect list length returned in the parameter data to determine whether a partial list was received. If the number of address descriptors the device server has to report exceeds the maximum value that is able to be specified in the ALLOCATION LENGTH field, the device server shall transfer no data and return CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

3.26.2 READ DEFECT DATA (10) parameter data

The READ DEFECT DATA (10) parameter data (see table 139) contains a four-byte header, followed by zero or more address descriptors.

Table 139 READ DEFECT DATA (10) parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
1	Reserved			PLISTV	GLISTV	DEFECT LIST FORMAT		
2	(MSB) _____							
3	DEFECT LIST LENGTH (N - 3)							(LSB)
Defect List (if any)								
4	_____							
...	ADDRESS DESCRIPTOR(S) (IF ANY)							
n	_____							

PLISTV (PLIST valid) bit

- 0** A PLIST valid (PLISTV) bit set to zero indicates that the data returned does not contain the PLIST.
- 1** A PLISTV bit set to one indicates that the data returned contains the PLIST.

GLISTV (GLIST valid) bit

- 0** A GLIST valid (GLISTV) bit set to zero indicates that the data returned does not contain the GLIST.
- 1** A GLISTV bit set to one indicates that the data returned contains the GLIST.

DEFECT LIST FORMAT field

The DEFECT LIST FORMAT field indicates the format of the address descriptors returned by the device server. This field is defined in the FORMAT UNIT command (see 3.3.5).

If the device server returns short block format address descriptors or long block format address descriptors, the address descriptors contain vendor-specific values.

NOTE The use of the short block format and the long block format is not recommended for this command. There is no standard model that defines the meaning of the block address of a defect. In the usual case, a defect that has been reassigned no longer has an LBA.

If the device server returns physical sector format address descriptors (see 3.3.5.7), it may or may not include defects in parts of the medium not accessible to the application client. If the device server returns bytes from index format address descriptors (see 3.3.5.6), it shall return a complete list of the defects. A complete list of the defects may include defects in areas not within the capacity returned in the READ CAPACITY command.

DEFECT LIST LENGTH field

The DEFECT LIST LENGTH field indicates the length in bytes of the address descriptors that follow. The DEFECT LIST LENGTH is equal to four or eight times the number of the address descriptors, depending on the format of the returned address descriptors.

The address descriptors may or may not be sent in ascending order.

3.27 READ DEFECT DATA (12) command

3.27.1 READ DEFECT DATA (12) command overview

The READ DEFECT DATA (12) command (see table 140) requests that the device server transfer the medium defect data to the data-in buffer.

Table 140 READ DEFECT DATA (12) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (B7h)							
1	Reserved			REQ_PLIST	REQ_GLIST	DEFECT LIST FORMAT		
2	ADDRESS DESCRIPTOR INDEX							
...								
5								
6	(MSB)		ALLOCATION LENGTH					
...								
9	(LSB)							
10	Reserved							
11	CONTROL							

See the READ DEFECT DATA (10) command (see 3.26) for the definitions of the fields in this command that are not described in this clause.

ADDRESS DESCRIPTOR INDEX field

The ADDRESS DESCRIPTOR INDEX field specifies the index of the first address descriptor (see 3.3.5.1) in the defect list that the device server shall return. If the ADDRESS DESCRIPTOR INDEX field is set to:

- a value less than the number of available address descriptors, then the device server shall transfer a defect list beginning with the address descriptor that is at the ADDRESS DESCRIPTOR INDEX field value multiplied by the size of the address descriptor; or
- a value greater than or equal to the number of available address descriptors, then the device server shall return a zero length defect list.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. The application client is responsible for comparing the allocation length requested in the CDB with the DEFECT LIST LENGTH field value returned in the parameter data to determine whether a partial list was received. If the length of all the address descriptors that are available is greater than FFFF_FFFFh, then the device server shall transfer the length of address descriptors specified by the allocation length or the DEFECT LIST LENGTH field value plus eight, whichever is less, and complete the command with GOOD status.

3.27.2 READ DEFECT DATA (12) parameter data

The READ DEFECT DATA (12) parameter data (see table 141) contains an eight byte header, followed by zero or more address descriptors.

Table 141 READ DEFECT DATA (12) parameter data

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1	Reserved			PLISTV	GLISTV	DEFECT LIST FORMAT			
2	Reserved								
3	Reserved								
4	(MSB)	DEFECT LIST LENGTH (N - 7)						(LSB)	
...									
7									
Defect List (if any)									
8	Address descriptor(s) (if any)								
...									
n									

See the READ DEFECT DATA (10) command (see 3.26.2) for the definitions of the fields in the defect list header that are not described in this clause.

DEFECT LIST LENGTH field

The DEFECT LIST LENGTH field indicates the length in bytes of address descriptors from the beginning address descriptor specified by the ADDRESS DESCRIPTOR INDEX field to the last address descriptor available to be returned. A value of FFFF_FFFFh in the DEFECT LIST LENGTH field indicates that more than FFFF_FFFFh bytes are available.

3.28 READ LONG (10) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The READ LONG (10) command (see table 142) requests that the device server transfer data from a single logical block to the data-in buffer. The data transferred during the READ LONG (10) command is vendor-specific, but shall include the following items recorded on the medium:

- a) if a logical block is being transferred, then:
 - A) user data or transformed user data for the logical block;
 - B) protection information or transformed protection information, if any, for the logical block; and
 - C) any additional information (e.g., ECC bytes) for all the physical blocks in the logical block.
- or
- b) if a physical block is being transferred, then:
 - A) user data or transformed user data for all the logical blocks in the physical block;
 - B) protection information or transformed protection information, if any, for all the logical blocks in the physical block; and
 - C) any additional information (e.g., ECC bytes).

If a cache contains a more recent version of a logical block, the device server shall write the logical block to the medium before reading it. The values in the Read-Write Error Recovery mode page (see 5.3.23) do not apply to this command. The device server may perform retries while processing this command.

Table 142 READ LONG (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (3Eh)							
1	Reserved					PBLOCK	CORRCT	Obsolete
2	(MSB)	LOGICAL BLOCK ADDRESS						
...								
5	(LSB)							
6	Reserved							
7	(MSB)	BYTE TRANSFER LENGTH						
8	(LSB)							
9	CONTROL							

LOGICAL BLOCK ADDRESS field

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

PBLOCK bit

If there is more than one logical block per physical block (i.e., the LOGICAL BLOCKS PER PHYSICAL BLOCK EXPONENT field in the READ CAPACITY (16) data is set to a non-zero value), then the device server shall support the physical block (PBLOCK) bit.

- 1** a PBLOCK bit set to one specifies that the device server shall return the entire physical block containing the specified logical block, and
- 0** a PBLOCK bit set to zero specifies that the device server shall return bytes representing only the specified logical block.

If there are one or more physical blocks per logical block (i.e., the LOGICAL BLOCKS PER PHYSICAL BLOCK EXPONENT field in the READ CAPACITY (16) data is set to zero) and the PBLOCK bit is set to one, then the device server shall return CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

CORRCT (correct) bit

- 0** A correct (CORRCT) bit set to zero specifies that a logical block be read without any correction made by the device server. A CORRCT bit set to zero should result in GOOD status unless data is not transferred for some reason other than that the data is non-correctable. In this case the appropriate status and sense data shall be returned.
- 1** A CORRCT bit set to one specifies that the data be corrected by ECC before being transferred to the data-in buffer.

BYTE TRANSFER LENGTH field

The BYTE TRANSFER LENGTH field specifies the number of bytes of data that shall be read from the specified logical block and transferred to the data-in buffer. If the BYTE TRANSFER LENGTH field is not set to zero and does not match the available data length, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB. In the sense data (see SPC-6), the VALID and ILI bits shall each be set to one and the INFORMATION field shall be set to the difference (i.e., residue) of the requested byte transfer length minus the actual available data length in bytes. Negative values shall be indicated by two's complement notation.

A BYTE TRANSFER LENGTH field set to zero specifies that no bytes shall be read. This condition shall not be considered an error.

3.29 READ LONG (16) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The READ LONG (16) command (see table 143) requests that the device server transfer data from a single logical block to the data-in buffer. The data transferred during the READ LONG (16) command is vendor-specific, but shall include the following items recorded on the medium:

- a) if a logical block is being transferred, then:
 - A) user data or transformed user data for the logical block;
 - B) protection information or transformed protection information, if any, for the logical block; and
 - C) any additional information (e.g., ECC bytes) for all the physical blocks in the logical block.
- or
- b) if a physical block is being transferred, then:
 - A) user data or transformed user data for all the logical blocks in the physical block;
 - B) protection information or transformed protection information, if any, for all the logical blocks in the physical block; and
 - C) any additional information (e.g., ECC bytes).

If a cache contains a more recent version of a logical block, the device server shall write the logical block to the medium before reading it. The values in the Read-Write Error Recovery mode page (see 5.3.23) do not apply to this command. The device server may perform retries while processing this command. This command is implemented as a service action of the SERVICE ACTION IN operation code.

Table 143 READ LONG (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (11h)				
2	(MSB)	LOGICAL BLOCK ADDRESS						
...								
9	(LSB)							
10	Reserved							
11	Reserved							
12	(MSB)	BYTE TRANSFER LENGTH						
13	(LSB)							
14	Reserved						PBLOCK	CORRCT
15	CONTROL							

See the READ LONG (10) command (see 3.28) for the definitions of the fields in this command.

3.30 REASSIGN BLOCKS command

3.30.1 REASSIGN BLOCKS command overview

The REASSIGN BLOCKS command (see table 144) requests that the device server reassign defective logical blocks to another area on the medium set aside for this purpose. The device server should also record the location of the defective logical blocks in the GLIST, if supported. This command shall not alter the contents of the PLIST.

The parameter list provided in the data-out buffer contains a defective LBA list that contains the LBAs of the logical blocks to be reassigned. The device server shall reassign the parts of the medium used for each logical block in the defective LBA list. More than one physical block may be relocated by each LBA. If the device server is able to recover user data and protection information, if any, from the original logical block, it shall write the recovered user data and any protection information to the reassigned logical block. If the LBA is unmapped, then the device server shall cause the LBA to become mapped and write the data that was retrieved during a read operation specifying the LBA that was reassigned to the logical block (see SBC-5). If the device server is unable to recover user data and protection information, if any, it shall write vendor-specific data as the user data and shall write a default value of FFFFFFFF_FFFFFFFFh as the protection information, if enabled. The data in all other logical blocks on the medium shall be preserved.

NOTE The effect of specifying a logical block to be reassigned that previously has been reassigned is to reassign the logical block again. Although not likely, over the life of the medium, a logical block may be assigned to multiple physical block addresses until no more spare locations remain on the medium.

Table 144 REASSIGN BLOCKS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (07h)							
1	Reserved						LONGLBA	ONGLIST
2	Reserved							
...								
4								
5	CONTROL							

LONGLBA (Long LBA) bit

- 0** A long LBA (LONGLBA) bit set to zero specifies that the REASSIGN BLOCKS defective LBA list contains four byte LBAs.
- 1** A LONGLBA bit set to one specifies that the REASSIGN BLOCKS defective LBA list contains eight byte LBAs.

3.30.2 REASSIGN BLOCKS parameter list

The REASSIGN BLOCKS parameter list (see table 145) contains a four-byte parameter list header followed by a defective LBA list containing one or more LBAs.

Table 145 REASSIGN BLOCKS parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	Parameter list header (see table 146 or table 147)							
...								
3								
4	DEFECTIVE LBA LIST (if any)							
...								
n								

LOGLIST bit

0 If LOGLIST is set to zero, the parameter list header is defined in table 146.

Table 146 REASSIGN BLOCKS short parameter list header

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
1								
2	(MSB)	DEFECT LIST LENGTH						(LSB)
3								

1 If LOGLIST is set to one, the parameter list header is defined in table 147.

Table 147 REASSIGN BLOCKS long parameter list header

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	DEFECT LIST LENGTH						(LSB)
...								
3								

DEFECT LIST LENGTH field

The DEFECT LIST LENGTH field indicates the total length in bytes of the DEFECTIVE LBA LIST field. The DEFECT LIST LENGTH field does not include the parameter list header length and is equal to either:

- a) four times the number of LBAs, if the LONGLBA bit is set to zero; or
- b) eight times the number of LBAs, if the LONGLBA bit is set to one.

DEFECTIVE LBA LIST field

The DEFECTIVE LBA LIST field contains a list of defective LBAs. Each LBA is a four-byte field if the LONGLBA bit is set to zero or an eight-byte field if the LONGLBA bit is set to one. The LBAs shall be in ascending order.

If the direct-access block device has insufficient capacity to reassign all of the specified logical blocks, the device server shall terminate the command with CHECK CONDITION status with the sense key set to HARDWARE ERROR and the additional sense code set to NO DEFECT SPARE LOCATION AVAILABLE.

If the direct-access block device is unable to successfully complete a REASSIGN BLOCKS command, the device server shall terminate the command with CHECK CONDITION status with the appropriate sense data (see SPC-6). The first LBA not reassigned shall be returned in the COMMAND-SPECIFIC INFORMATION field of the sense data. If information about the first LBA not reassigned is not available, or if all the defects have been reassigned, the COMMAND-SPECIFIC INFORMATION field shall be set to FFFFFFFFh if fixed format sense data is being used or FFFFFFFF_FFFFFFFFh if descriptor format sense data is being used.

If the REASSIGN BLOCKS command failed due to an unexpected unrecoverable read error that would cause the loss of data in a logical block not specified in the defective LBA list, the LBA of the unrecoverable block shall be returned in the INFORMATION field of the sense data and the VALID bit shall be set to one.

If the REASSIGN BLOCKS command returns CHECK CONDITION status and the sense data COMMAND-SPECIFIC INFORMATION field contains a valid LBA, the application client should remove all LBAs from the defective LBA list prior to the one returned in the COMMAND-SPECIFIC INFORMATION field. If the sense key is MEDIUM ERROR and the INFORMATION field contains the valid LBA, the application client should insert that new defective LBA into the defective LBA list and reissue the REASSIGN BLOCKS command with the new defective LBA list. Otherwise, the application client should perform any corrective action indicated by the sense data and then reissue the REASSIGN BLOCKS command with the new defective LBA list.

3.31 RECEIVE DIAGNOSTIC RESULTS command

The RECEIVE DIAGNOSTIC RESULTS command (see table 148) requests analysis data be sent to the application client Data-In Buffer after completion of a SEND DIAGNOSTIC command (see 3.50), or, optionally, SCSI-3 Enclosure Services (SES) pages be sent to the initiator. Support for SES is indicated in the drive product manual.

If no data in the optional Page format was requested by the SEND DIAGNOSTIC command (0 in bit 4 of Table 202), the data returned to the initiator is in the format shown in Table 149.

All FRU and error code definitions are unique to the product and intended for factory/field maintenance personnel.

Table 148 RECEIVE DIAGNOSTIC RESULTS command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (1Ch)								
1	Reserved							PCV	
2	PAGE CODE								
3	(MSB)	ALLOCATION LENGTH							
4								(LSB)	
5	CONTROL								

PCV (Page Code Valid) bit

- 0** A page code valid (PCV) bit set to zero specifies that the device server return parameter data based on the most recent SEND DIAGNOSTIC command (e.g., the diagnostic page with the same page code as that specified in the most recent SEND DIAGNOSTIC command). The response to a RECEIVE DIAGNOSTIC RESULTS command with the PCV bit set to zero is vendor-specific if:
 - a) The most recent SEND DIAGNOSTIC command was not a SEND DIAGNOSTIC command defining parameter data to return;
 - b) A RECEIVE DIAGNOSTIC RESULTS command with a PCV bit set to one has been processed since the last SEND DIAGNOSTIC command was processed; or
 - c) No SEND DIAGNOSTIC command defining parameter data to return has been processed since power on, hard reset, or logical unit reset.
- 1** A page code valid (PCV) bit set to one specifies that the device server return the diagnostic page specified in the PAGE CODE field. Page code values are defined in Table 292.

PAGE CODE field

The PAGE CODE field identifies which diagnostic page is requested as a result of a RECEIVE DIAGNOSTIC RESULTS command with the PCV bit equal to one, or returned as a result of a RECEIVE DIAGNOSTIC RESULTS parameter data.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field (see 2.2.6) shall specify the number of bytes the initiator has allocated for returned data. An ALLOCATION LENGTH of zero indicates that no data shall be transferred. Any other value indicates the maximum number of bytes that shall be transferred. The drive terminates the DATA IN phase when ALLOCATION LENGTH bytes have been transferred or when all available data has been transferred to the initiator, whichever is less.

Table 149 Diagnostic Data Bytes

Code	Byte	Description
00h	0	ADDITIONAL LENGTH (MSB) [1]
28h	1	ADDITIONAL LENGTH (LSB) [1]
XXh	2	FRU CODE (most probable) [2]
XXh	3	FRU CODE [2]
XXh	4	FRU CODE [2]
XXh	5	FRU CODE (least probable) [2]
XXh	6	ERROR CODE (MSB) [3]
V.U.	7	ERROR CODE (LSB) [4]
V.U.	8 thru n	Additional vendor unique fault information (if any) (not available)

- [1] ADDITIONAL LENGTH. This two byte value indicates the number of additional bytes included in the diagnostic data list. For example, if no product unique byte (byte 7) is available, this value would be 0006h. A value of 0000h means that there are no additional bytes.
- [2] A FIELD REPLACEABLE UNIT (FRU) Code is a byte that identifies an assembly that may have failed. The codes will be listed in probability order, with the most probable assembly listed first and the least probable listed last. A code of 00h indicates there is no FRU information and a code of 01h indicates the entire unit should be replaced. Seagate drives return 00h in these bytes.
- [3] The ERROR CODE is a two byte value that provides information designating which part of a diagnostic operation has failed. The LSB of the error code is vendor unique and defined in note [4]. Usually, Seagate drives support only some subset of the list given in note [4].
- [4] Vendor Unique codes supported by Seagate devices are listed in table 150.

Table 150 Diagnostic Fault Codes

Code	Fault description
01h	Formatter Diagnostic Error
02h	Microprocessor RAM Diagnostic Error
04h	No Drive Ready
08h	No Sector or Index Detected
09h	Fatal Hardware Error While Doing Drive Diagnostics
0Ch	No Drive Command Complete
10h	Unable to Set Drive Sector Size
14h	Unable to Clear Drive Attention
18h	Unable to Start Spindle Motor
20h	Unable to Recal Drive
30h	Unable to Send Write Current Data to Drive
34h	Unable to Issue Drive SEEK Command
40h	Unable to Read User Table From Drive
41h	Ran Out of Sectors While Doing Drive Diagnostics
42h	Unable to Read Reallocation Table
43h	Unable to Read ETF Log
45h	Firmware Read from disk or Sent by Host has an Invalid Checksum
60h	Thermal Calibration Failure
70h	Microprocessor Internal Timer Error
80h	Buffer Controller Diagnostic Error
81h	Buffer RAM Diagnostic Error
C1h	Data Miscompare While Doing Drive Diagnostics

3.32 RELEASE (6) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The RELEASE(6) command (see table 151) is used to release a previously reserved logical unit. This subclause describes only those instances where the RELEASE(6) command differs from the RELEASE(10) command. Except for the instances described in this subclause, the RELEASE(6) command shall function exactly like the RELEASE(10) command (see 3.33).

Table 151 RELEASE (6) Command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (17h)							
1	Reserved			Obsolete				
2	Obsolete							
3	Reserved							
4	Reserved							
5	CONTROL							

The RELEASE(6) command shall not release third-party reservations.

3.33 RELEASE (10) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

3.33.1 RELEASE (10) command introduction

The RELEASE(10) command (see table 152) is used to release a previously reserved logical unit.

Table 152 RELEASE (10) Command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (57h)								
1	Reserved			3RDPTY		Reserved		LONGID	Obsolete
2	Obsolete								
3	THIRD-PARTY DEVICE ID								
4	Reserved								
5	Reserved								
6	Reserved								
7	(MSB)	PARAMETER LIST LENGTH							
8									(LSB)
9	CONTROL								

The RESERVE and RELEASE commands provide a basic mechanism for contention resolution in multiple-initiator systems. See 5.5.1 for a general description of reservations and the commands that manage them. A reservation may only be released by a RELEASE command from the initiator that made it. It is not an error for an application client to attempt to release a reservation that is not currently valid, or is held by another initiator. In this case, the device server shall return GOOD status without altering any other reservation.

Byte 1 Bit 0 and Byte 2 provide an obsolete way to release previously reserved extents within a logical unit. If Byte 1, Bit 0 is equal to one, device servers not implementing the obsolete capability shall terminate the command with CHECK CONDITION status and the sense key shall be set to ILLEGAL REQUEST.

3.33.2 Logical unit release

Logical unit reservation release is mandatory if the RELEASE(10) command is implemented. This command shall cause the device server to terminate all non-third-party logical unit reservations that are active from the initiator to the specified logical unit.

3.33.3 Third-party release

Third-party reservation release is optional if the RELEASE(10) command is implemented. Third-party release allows an application client to release a logical unit that was previously reserved using third-party reservation.

3RDPTY (third-party) bit

- 0** If the third-party (3RDPTY) bit is zero, then a third-party release is not requested. If the 3RDPTY bit is zero then the LONGID bit and the PARAMETER LIST LENGTH field shall be ignored.
- 1** If the 3RDPTY bit is one then the device server shall release the specified logical unit, but only if the initiator ID, 3RDPTY bit, and THIRD-PARTY DEVICE ID are identical when compared to the RESERVE command that established the reservation. The device server shall not modify the mode parameters for commands received from the third-party device even if the device server implements the transfer of mode parameters with a third-party RESERVE command.

THIRD-PARTY DEVICE ID field and LONGID bit

If the THIRD-PARTY DEVICE ID value associated with the reservation release is smaller than 255, the LONGID bit may be zero and the ID value sent in the CDB THIRD-PARTY DEVICE ID field. Device ID formats are protocol specific. If the LONGID bit is zero, the PARAMETER LIST LENGTH field shall be set to zero. If the THIRD-PARTY DEVICE ID is greater than 255, the LONGID bit shall be one.

Device servers that support device IDs greater than 255 shall accept commands with LONGID equal to one. Device servers whose devices IDs are limited to 255 or smaller may reject commands with LONGID equal to one with CHECK CONDITION status and a sense key of ILLEGAL REQUEST.

If the LONGID bit is one, the parameter list length shall be eight, and the parameter list shall have the format shown in table 96. If the LONGID bit is one, the THIRD-PARTY DEVICE ID field in the CDB shall be ignored. If the LONGID bit is one and the parameter list length is not eight, the device server shall return a CHECK CONDITION status with a sense key of ILLEGAL REQUEST.

Table 153 RELEASE (10) parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	THIRD-PARTY DEVICE ID							
...								
7								

3.34 REMOVE ELEMENT AND TRUNCATE command

The REMOVE ELEMENT AND TRUNCATE command (see table 154) requests that the device server perform a storage element depopulation (see SBC-5).

If deferred microcode has been saved and not activated (see SPC-6), then the device server shall terminate this command with CHECK CONDITION status with the sense key set to NOT READY and the additional sense code set to LOGICAL UNIT NOT READY, MICROCODE ACTIVATION REQUIRED.

This command uses the SERVICE ACTION IN (16) CDB format (see SBC-5 - Annex A.2).

Table 154 REMOVE ELEMENT AND TRUNCATE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (18h)				
2	(MSB)							
...	REQUESTED CAPACITY							
9	(LSB)							
10	(MSB)							
...	ELEMENT IDENTIFIER							
13	(LSB)							
14	Reserved							
15	CONTROL							

OPERATION CODE field and the SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in SPC-6 and shall be set to the values shown in table 154 for the REMOVE ELEMENT AND TRUNCATE command.

REQUESTED CAPACITY field

The REQUESTED CAPACITY field specifies the capacity in logical blocks (i.e. one greater than the number of logical blocks returned by the READ CAPACITY command) of the media upon completion of the command. A value of zero specifies that the device server shall choose the resultant capacity of the media. If the device server is unable to set the capacity of the medium to the specified value, then the device server shall:

- a) not change the capacity of the media; and
- b) terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

ELEMENT IDENTIFIER field

The ELEMENT IDENTIFIER field specifies the element identifier associated with the storage element (see SBC-5) to be depopulated. If the ELEMENT IDENTIFIER field specifies a physical element that is not a storage element, (i.e. the PHYSICAL ELEMENT TYPE field (see SBC-5) is not set to 01h in the corresponding physical element status descriptor) or specifies a physical element not supported by the device (see SBC-5), then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

If the ELEMENT IDENTIFIER field specifies an element identifier for which the device server does not support depopulation, then the device server shall terminate this command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

If the ELEMENT IDENTIFIER field specifies an element identifier that is associated with a storage element that is depopulated, then the device server shall make no changes and not consider this an error.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

After successful command completion, further processing may occur as described in SBC-5.

3.35 REPORT IDENTIFYING INFORMATION

The REPORT IDENTIFYING INFORMATION command requests that the device server send device identification information to the application client.

The device server shall return the same identifying information regardless of the I_T nexus being used to retrieve the identifying information.

Processing a REPORT IDENTIFYING INFORMATION command may require the enabling of a nonvolatile memory within the logical unit. If the nonvolatile memory is not ready, the command shall be terminated with CHECK CONDITION status, rather than wait for the nonvolatile memory to become ready. The sense key shall be set to NOT READY and the additional sense code shall be set as described in table 218. This information should allow the application client to determine the action required to cause the device server to become ready.

Table 155 REPORT IDENTIFYING INFORMATION command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A3h)							
1	Reserved			SERVICE ACTION (05h)				
2	Reserved							
3	Reserved							
4	RESTRICTED (see SCC-2)							
5	Reserved							
6	(MSB)							
...	ALLOCATION LENGTH							
9	(LSB)							
10	INFORMATION TYPE							Reserved
11	CONTROL							

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

INFORMATION TYPE field

The INFORMATION TYPE field (see table 156) specifies the type of information to be reported.

Table 156 INFORMATION TYPE

Code	Description	Length	Reference
0000000b	Peripheral device identifying information	0 to 64 bytes	Table 34
0000010b	Peripheral device text identifying information.	65 to 512bytes	Table 34
1111111b	Identifying information supported. The parameter data contains a list of supported identifying information types and the maximum length of each.	0 to 256 bytes	3.35.1
xxxxxx1b	Restricted.		SCC-2
All other	Reserved.		

The REPORT IDENTIFYING INFORMATION parameter data format used when the INFORMATION TYPE field is set to 0000000b or 0000010b is shown in table 157.

Table 157 REPORT IDENTIFYING INFORMATION parameter data

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1									
2	(MSB)	INFORMATION LENGTH (n - 3)							
3	(LSB)								
4									
...	INFORMATION								
n									

INFORMATION LENGTH

The INFORMATION LENGTH field indicates the length in bytes of the INFORMATION field. The relationship between the INFORMATION LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

INFORMATION

The INFORMATION field contains the identifying information that has the specified information type (see table 156).

3.35.1 IDENTIFYING INFORMATION SUPPORTED parameter data

The REPORT IDENTIFYING INFORMATION parameter data format used when the INFORMATION TYPE field is set to 1111111b is shown in table 158.

Table 158 REPORT IDENTIFYING INFORMATION SUPPORTED parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
1	Reserved							
2	(MSB)	IDENTIFYING INFORMATION LENGTH (n - 3)						(LSB)
3								
Identifying information descriptor list								
4	Identifying information descriptor [first] (see table 159)							
...								
7								
n - 3	Identifying information descriptor [last]							
...								
n								

IDENTIFYING INFORMATION LENGTH field

The IDENTIFYING INFORMATION LENGTH field indicates the length in bytes of the identifying information descriptor list. The relationship between the IDENTIFYING INFORMATION LENGTH field and the ALLOCATION LENGTH field is defined in 2.2.6.

Identifying information descriptor list

The Identifying information descriptor list contains an identifying information descriptor (see table 159) for each identifying information type supported by the device server. The identifying information descriptors shall be sorted in increasing order by information type.

Table 159 Identifying Information descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	INFORMATION TYPE							Reserved
1	Reserved							
2	(MSB)	MAXIMUM INFORMATION LENGTH						(LSB)
3								

INFORMATION TYPE field

The INFORMATION TYPE field indicates the information type (see table 156).

MAXIMUM LENGTH field

The MAXIMUM LENGTH field indicates the maximum number of bytes supported for identifying information that has the indicated information type.

3.36 REPORT LUNS command

The REPORT LUNS command (see table 160) requests the device server to return the logical unit inventory accessible to the I_T nexus. The logical unit inventory returned to the application client is a list that shall include the logical unit numbers of all logical units having a PERIPHERAL QUALIFIER value of 000b (see 3.8.2) based on the SELECT REPORT field. Logical unit numbers for logical units with PERIPHERAL QUALIFIER values other than 000b and 011b may be included in the logical unit inventory. Logical unit numbers for logical units with a PERIPHERAL QUALIFIER value of 011b shall not be included in the logical unit inventory.

Table 160 REPORT LUNS command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (A0h)								
1	Reserved								
2	SELECT REPORT								
3	Reserved								
...									
5									
6	(MSB)	ALLOCATION LENGTH						(LSB)	
...									
9									
10	Reserved								
11	CONTROL								

OPERATION CODE field

The OPERATION CODE field is defined in 2.2.1 and shall be set as shown in table 160 for the REPORT LUNS command.

SELECT REPORT field

The SELECT REPORT field (see table 161) specifies the types of logical unit addresses that shall be reported.

Table 161 SELECT REPORT field

Code	Description
00h	The list shall contain the logical units accessible to the I_T nexus with the following addressing methods (see SAM-6): <ul style="list-style-type: none"> a) simple logical unit addressing method; b) logical unit addressing method; c) peripheral device addressing method; d) flat space addressing method; e) extended flat space addressing method; and f) long extended flat space addressing method. If there are no logical units to report, the LUN LIST LENGTH field shall be set to zero.
01h	The list shall contain only well known logical units, if any. If there are no well known logical units, the LUN LIST LENGTH field shall be zero.
02h	The list shall contain all logical units accessible to the I_T nexus.
10h	If the device server processing the command is in LUN 0 or the REPORT LUNS well known logical unit, then the list shall contain only administrative logical units (see SAM-6). The LUN LIST LENGTH field shall be set to zero if the device server processing the command is not in: <ul style="list-style-type: none"> a) LUN 0; or b) the REPORT LUNS well known logical unit. If there are no logical units to report, the LUN LIST LENGTH field shall be set to zero.
11h	If the device server processing the command is in LUN 0 or the REPORT LUNS well known logical unit, then the list shall contain only: <ul style="list-style-type: none"> a) administrative logical units (see SAM-6); b) logical units with the logical unit addressing method at level 1; and c) logical units with single level LUN structure with the following addressing methods (see SAM-6): <ul style="list-style-type: none"> A) peripheral device addressing method; B) flat space addressing method; C) extended flat space addressing method; and D) long extended flat space addressing method. The LUN LIST LENGTH field shall be set to zero if the device server processing the command is not in: <ul style="list-style-type: none"> a) LUN 0; or b) the REPORT LUNS well known logical unit. If there are no logical units to report, the LUN LIST LENGTH field shall be set to zero.
12h	If the device server processing the command is in an administrative logical unit, the list shall contain: <ul style="list-style-type: none"> a) the logical unit processing the command; and b) subsidiary logical units that are contained in the same logical unit conglomerate that contains the logical unit processing the command. The LUN LIST LENGTH field shall be set to zero if the device server processing the command is not in an administrative logical unit. If there are no logical units to report, the LUN LIST LENGTH field shall be set to zero.
F8h to FFh	Vendor specific
All others	Reserved

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. The allocation length should be at least 16.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The REPORT LUNS command shall return CHECK CONDITION status only when the device server is unable to return the requested report of the logical unit inventory.

If a REPORT LUNS command is received from an I_T nexus with a pending unit attention condition (i.e., before the device server reports CHECK CONDITION status), the device server shall perform the REPORT LUNS command (see SAM-6).

The REPORT LUNS parameter data should be returned even though the device server is not ready for other commands. The report of the logical unit inventory should be available without incurring any media access delays. If the device server is not ready with the logical unit inventory or if the inventory list is null for the requesting I_T nexus and the SELECT REPORT field set to 02h, then the device server shall provide a default logical unit inventory that contains at least LUN 0 or the REPORT LUNS well known logical unit. A non-empty peripheral device logical unit inventory that does not contain either LUN 0 or the REPORT LUNS well known logical unit is valid.

If a REPORT LUNS command is received for a logical unit that the SCSI target device does not support and the device server is not capable of returning the logical unit inventory, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to LOGICAL UNIT NOT SUPPORTED.

The device server shall report those devices in the logical unit inventory using the format shown in table 162.

Table 162 REPORT LUNS parameter data format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	LUN LIST LENGTH (n-7)							
3								
4	Reserved							
...								
7								
LUN list								
8	LUN [first]							
...								
15	...							
...								
n-7	LUN [last]							
...								
n								

LUN LIST LENGTH field

The LUN LIST LENGTH field shall contain the length in bytes of the LUN list that is available to be transferred. The LUN list length is the number of logical unit numbers in the logical unit inventory multiplied by eight. The relationship between the LUN LIST LENGTH field and the ALLOCATION LENGTH field is defined in 2.2.6.

3.37 REPORT SUPPORTED OPERATION CODES command

3.37.1 REPORT SUPPORTED OPERATION CODES command overview

The REPORT SUPPORTED OPERATION CODES command (see table 163) requests the device server to return information on commands the addressed logical unit supports. This command uses the MAINTENANCE IN CDB format (see SPC-6). An application client may request a list of all operation codes and service actions supported by the logical unit or the command support data for a specific command.

Table 163 REPORT SUPPORTED OPERATION CODES command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A3h)							
1	Reserved			SERVICE ACTION (0Ch)				
2	RCTD	Reserved				REPORTING OPTIONS		
3	REQUESTED OPERATION CODE							
4	(MSB)	REQUESTED SERVICE ACTION						(LSB)
5								
6	(MSB)	ALLOCATION LENGTH						(LSB)
...								
9								
10	Reserved							
11	CONTROL							

OPERATION CODE field

The OPERATION CODE field is defined in Clause 2.2.1 and shall be set as shown in table 163 for the REPORT SUPPORTED OPERATION CODES command.

SERVICE ACTION field

The SERVICE ACTION field is defined in Clause 2.2.2 and shall be set as shown in table 163 for the REPORT SUPPORTED OPERATION CODES command.

RCTD (Return Command Timeouts Descriptor) bit

- 0** A RCTD bit set to zero specifies that the command timeouts descriptor shall not be returned.
- 1** A RCTD bit set to one specifies that the command timeouts descriptor (see 3.37.4) shall be included in each command descriptor (see 3.37.2) that is returned or in the one_command parameter data (see 3.37.3) that is returned.

REPORTING OPTIONS field

The REPORTING OPTIONS field (see table 164) specifies the information to be returned in the parameter data.

Table 164 REPORTING OPTIONS field

Code	Descriptions	Parameter Data Reference
000b	A list of all operation codes and service actions ^a supported by the logical unit shall be returned in the all_commands parameter data format. The REQUESTED OPERATION CODE CDB field and REQUESTED SERVICE ACTION CDB field shall be ignored.	3.37.2
001b	The command support data for the operation code specified in the REQUESTED OPERATION CODE field shall be returned in the one_command parameter data format. The REQUESTED SERVICE ACTION CDB field shall be ignored. If the REQUESTED OPERATION CODE field specifies an operation code that has service actions ^a , then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.	3.37.3
010b	The command support data for the operation code and service action ^a specified in the REQUESTED OPERATION CODE CDB field and REQUESTED SERVICE ACTION CDB field shall be returned in the one_command parameter data format. If the REQUESTED OPERATION CODE CDB field specifies an operation code that does not have service actions ^a , then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.	3.37.3
011b	The command support data for the operation code and service action ^a specified in the REQUESTED OPERATION CODE field and REQUESTED SERVICE ACTION field shall be returned in the one_command parameter data format. If: <ul style="list-style-type: none"> a) the operation code specified by the REQUESTED OPERATION CODE field specifies an operation code for which the device server does not implement service actions, the REQUESTED SERVICE ACTION field is set to 00h, and the command is supported; or b) the operation code specified by the REQUESTED OPERATION CODE field specifies an operation code for which the device server implements service actions and the value in the REQUESTED SERVICE ACTION field is supported, then the command support data shall indicate that the command is supported (i.e., the SUPPORT field (see table 256) is set to 011b or 101b). Otherwise, the command support data shall indicate that the command is not supported (i.e., the SUPPORT field is set to 001b).	3.37.3
100b - 111b	Reserved.	
<p>a The device server should also process the following fields in the following commands as specifying service actions (i.e., the specified field should be processed as a SERVICE ACTION field):</p> <ul style="list-style-type: none"> a) the MODE field in the READ BUFFER command (see 3.22); and b) the MODE field in the WRITE BUFFER command (see 3.64). 		

REQUESTED OPERATION CODE field

The REQUESTED OPERATION CODE field specifies the operation code of the command to be returned in the one_command parameter data format (see 3.37.3).

REQUESTED SERVICE ACTION field

The REQUESTED SERVICE ACTION field specifies the service action of the command to be returned in the one_command parameter data format.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

3.37.2 All_commands parameter data format

The REPORT SUPPORTED OPERATION CODES all_commands parameter data format (see table 165) begins with a four-byte header that contains the length in bytes of the parameter data followed by a list of supported commands. Each command descriptor contains information about a single supported command CDB (i.e., one operation code and service action combination, or one non-service-action operation code). The list of command descriptors shall contain all commands supported by the logical unit.

Table 165 All_commands parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	COMMAND DATA LENGTH (n - 3)							
3	(LSB)							
Command descriptors								
4	Command descriptor (see table 166) [first]							
...	...							
...	Command descriptor (see table 166) [last]							
n								

COMMAND DATA LENGTH field

The COMMAND DATA LENGTH field indicates the length in bytes of the command descriptor list. The contents of the COMMAND DATA LENGTH field are not altered based on the allocation length.

Each command descriptor (see table 166) contains information about a single supported command CDB.

Table 166 Command descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE							
1	Reserved							
2	(MSB)							
3	SERVICE ACTION							
4	(LSB)							
4	Reserved							
5	Reserved	RWCDLP	MLU	CDLP	CTDP	SERVACTV		
6	(MSB)							
7	CDB LENGTH							
8	(LSB)							
...	Command timeouts descriptor, if any (see table 171)							
19								

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit.

SERVICE ACTION field

The SERVICE ACTION field contains a supported service action of the supported operation code indicated by the OPERATION CODE field. If the operation code indicated in the OPERATION CODE field does not have a service action, the SERVICE ACTION field shall be set to 00h.

Multiple Logical Units (MLU) field

The multiple logical units (MLU) field is described in Table 167.

Table 167 MLU field description

Code	Description
00b	The effect of this command on other logical units is not reported.
01b	This command affects only this logical unit.
10b	This command affects more than one but not all logical units contained in this SCSI target device.
11b	This command affects all of the logical units contained in this SCSI target device.

Read Write Command Duration Limits Page (RWCDLP) bit and Command Duration Limit Page (CDLP) field

The read write command duration limits page (RWCDLP) bit and the command duration limit page (CDLP) field (see table 168) indicate the mode page, if any, that specifies the command duration limit for the command.

Table 168 CDLP field

RWCDLP bit	CDLP field	Description
0b	00b	No command duration limit mode page is indicated for this command
1b	00b	Reserved
0b ^a	01b ^a	Command Duration Limit A mode page
0b ^b	10b ^b	Command Duration Limit B mode page
1b ^c	01b ^c	Command Duration Limit T2A mode page
1b ^d	10b ^d	Command Duration Limit T2B mode page
0b or 1b	11b	Reserved

a If this value is returned, the Command Duration Limit A mode page (see 5.3.10) shall be supported.
b If this value is returned, the Command Duration Limit B mode page (see 5.3.11) shall be supported.
c If these values are returned, the Command Duration Limit T2A mode page (see 5.3.12) shall be supported.
d If these values are returned, the Command Duration Limit T2B mode page (see 5.3.13) shall be supported.

Command Timeouts Descriptor Present (CTDP) bit

- 0** A CTDP bit set to zero indicates that the command timeouts descriptor is not included in this command descriptor.
- 1** A CTDP bit set to one indicates that the command timeouts descriptor is included in this command descriptor.

Service Action Valid (SERVACTV) bit

- 0** A service action valid (SERVACTV) bit set to zero indicates the operation code indicated by the OPERATION CODE field does not have service actions and the SERVICE ACTION field contents are reserved.
- 1** A SERVACTV bit set to one indicates the operation code indicated by the OPERATION CODE field has service actions and the contents of the SERVICE ACTION field are valid.

CDB LENGTH field

The CDB LENGTH field indicates the length of the command CDB in bytes for the operation code indicated in the OPERATION CODE field, and if the SERVACTV bit is set to one the service action indicated by the SERVICE ACTION field.

Report Command Timeout Descriptor (RCTD) bit

- 0** If the RCTD bit is set to zero, the command timeouts descriptor shall not be included.
- 1** If the RCTD bit is set to one in the REPORT SUPPORTED OPERATION CODES CDB, the command timeouts descriptor shall be included.

Command Timeouts descriptor

The command timeouts descriptor is described in 3.37.4.

3.37.3 One_command parameter data format

The REPORT SUPPORTED OPERATION CODES one_command parameter data format contains information about the CDB and a usage map for bits in the CDB for the command specified by the REPORTING OPTIONS, REQUESTED OPERATION CODE, and REQUESTED SERVICE ACTION fields in the REPORT SUPPORTED OPERATION CODES CDB.

Table 169 One_command parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							RWCDLP
1	CTDP	MLU		CDLP		SUPPORT		
2	(MSB)							
3	CDB SIZE (n - 3)							(LSB)
4	CDB USAGE DATA							
...								
n								
n+1	Command timeouts descriptor, if any (see table 171)							
...								
n+12								

Command Timeout Descriptor Present (CTDP) bit

- 0** A CTDP bit set to zero indicates that the command timeouts descriptor is not included in the parameter data.
- 1** A CTDP bit set to one indicates that the command timeouts descriptor is included in the parameter data.

Multiple Logical Units (MLU) field

The multiple logical units (MLU) field is described in Table 167.

Read Write Command Duration Limits Page (RWCDLP) bit and Command Duration Limit Page (CDLP) field

The read write command duration limits page (RWCDLP) bit and the command duration limit page (CDLP) field (see table 168) indicate the mode page, if any, that specifies the command duration limit for the command.

SUPPORT field

The SUPPORT field is defined in Table 170.

Table 170 Support values

Support	Description
000b	Data about the requested SCSI command is not currently available. All data after byte 1 is not valid. A subsequent request for command support data may be successful.
001b	The device server does not support the requested command. All data after byte 1 is undefined.
010b	Reserved.
011b	The device server supports the requested command in conformance with a SCSI standard. The parameter data format conforms to the definition in table 169.
100b	Reserved.
101b	The device server supports the requested command in a vendor specific manner. The parameter data format conforms to the definition in table 169.
110b - 111b	Reserved.

CDB SIZE field

The CDB SIZE field contains the size of the CDB USAGE DATA field in the parameter data, and the number of bytes in the CDB for command being queried (i.e., the command specified by the REPORTING OPTIONS, REQUESTED OPERATION CODE, and REQUESTED SERVICE ACTION fields in the REPORT SUPPORTED OPERATION CODES CDB).

CDB USAGE DATA field

The CDB USAGE DATA field contains information about the CDB for the command being queried. The first byte of the CDB USAGE DATA field shall contain the operation code for the command being queried. If the command being queried contains a service action, then that service action code shall be placed in the CDB USAGE DATA field in the same location as the SERVICE ACTION field of the command CDB. All other bytes of the CDB USAGE DATA field shall contain a usage map for bits in the CDB for the command being queried.

The bits in the usage map shall have a one-for-one correspondence to the CDB for the command being queried. If the device server evaluated a bit in the CDB for the command being queried, the usage map shall contain a one in the corresponding bit position. If any bit representing part of a field is returned as one, all bits for the field shall be returned as one. If the device server ignores or treats as reserved a bit in the CDB for the command being queried, the usage map shall contain a zero in the corresponding bit position. The usage map bits for a given CDB field all shall have the same value.

For example, the CDB usage bit map for the REPORT SUPPORTED OPERATION CODES command is: A3h, 0Ch, 87h, FFh, FFh, FFh, FFh, FFh, FFh, 00h, 07h. This example assumes that the logical unit only supports the low-order three bits of the CDB CONTROL byte. The first byte contains the operation code, and the second byte contains three reserved bits and the service action. The remaining bytes contain the usage map.

Command Timeouts descriptor

The command timeouts descriptor is described in 3.37.4.

3.37.4 Command timeouts descriptor

3.37.4.1 Overview

The command timeouts descriptor (see table 171) returns timeout information for commands supported by the logical unit based on the time from the start of processing for the command to its reported completion.

Values returned in the command timeouts descriptor do not include times that are outside the control of the device server (e.g., prior commands with the IMMED bit set to one in the CDB, concurrent commands from the same or different I_T nexuses, manual unloads, power-on self tests, prior aborted commands, commands that force cache synchronization, delays in the service delivery subsystem).

For commands that cause a change in power condition, values returned in the command timeouts descriptor do not include the power condition transition time (e.g., the time to spinup rotating media).

Values returned in the command timeouts descriptor should not be used to compare products.

Table 171 Command timeouts descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	DESCRIPTOR LENGTH (000Ah)						(LSB)
1								
2		Reserved						
3		COMMAND SPECIFIC						
4	(MSB)	NOMINAL COMMAND PROCESSING TIMEOUT						(LSB)
...								
7								
8	(MSB)	RECOMMEND COMMAND TIMEOUT						(LSB)
...								
11								

DESCRIPTOR LENGTH field

The DESCRIPTOR LENGTH field indicates the number of bytes that follow in the command timeouts descriptor.

COMMAND SPECIFIC field

The COMMAND SPECIFIC field contains timeout information (see table 172) that is specific to one or more commands. If no command specific timeout information is defined by this or the applicable command standard the COMMAND SPECIFIC field is reserved.

Table 172 Command timeout descriptor COMMAND SPECIFIC field usage in this manual

Command	Reference
WRITE BUFFER	3.37.4.2

NOMINAL COMMAND PROCESSING TIMEOUT field

A non-zero value in the NOMINAL COMMAND PROCESSING TIMEOUT field indicates the minimum amount of time in seconds the application client should wait prior to querying for the progress of the command identified by the parameter data that contains this command timeouts descriptor. A value of zero in the NOMINAL COMMAND PROCESSING TIMEOUT field indicates that no timeout is indicated.

NOTE The value contained in the NOMINAL COMMAND PROCESSING TIMEOUT field may include time required for typical device error recovery procedures expected to occur on a regular basis.

RECOMMENDED COMMAND TIMEOUT field

A non-zero value in the RECOMMENDED COMMAND TIMEOUT field specifies the recommended time in seconds the application client should wait prior to timing out the command identified by the parameter data that contains this command timeouts descriptor. A value of zero in the RECOMMENDED COMMAND TIMEOUT field indicates that no time is indicated.

The device server should set the recommended command timeout to a value greater than or equal to the nominal command processing timeout.

3.37.4.2 WRITE BUFFER command timeouts descriptor COMMAND SPECIFIC field usage

For the WRITE BUFFER command, the COMMAND SPECIFIC field usage is reserved for all modes except the following:

- a) download microcode and activate mode (04h);
- b) download microcode, save, and activate mode (05h);
- c) download microcode with offsets and activate mode (06h);
- d) download microcode with offsets, save, and activate mode (07h);
- e) download microcode with offsets, select activation events, save, and defer activate mode (0Dh) only if the microcode is activated by an event other than the activate deferred microcode mode;
- f) download microcode with offsets, save, and defer activate mode (0Eh) only if the microcode is activated by an event other than an activate deferred microcode mode;
and
- g) activate deferred microcode mode (0Fh).

If the command timeouts descriptor describes one of the WRITE BUFFER modes listed in this subclause, then the COMMAND SPECIFIC field indicates the maximum time, in one second increments, that access to the SCSI device is limited or not possible through any SCSI ports associated with a logical unit that processes a WRITE BUFFER command that specifies one of the named modes. A value of zero in the COMMAND SPECIFIC field indicates that the no maximum time is indicated.

3.38 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS commands

The REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command (see table 173) requests the device server to return on task management functions (see SAM-6) the addressed logical unit supports. This command uses the MAINTENANCE IN CDB format (see SPC-6).

Table 173 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A3h)							
1	Reserved			SERVICE ACTION (0Dh)				
2	REPD							
...	Reserved							
5								
6	(MSB)							
...	ALLOCATION LENGTH (4h or larger)							
9								(LSB)
10	Reserved							
11	CONTROL							

OPERATION CODE field

The OPERATION CODE field shall be set as shown in table 173 for the REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command.

SERVICE ACTION field

The SERVICE ACTION field shall be set as shown in table 173 for the REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command.

REPD bit

- 1** A return extended parameter data (REPD) bit set to one specifies that the task management timeout information shall be included in the parameter data that is returned.
- 0** A REPD bit set to zero specifies that the task management timeout information shall not be returned.

The format of the parameter data for the REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS command depends on the value of the REPD bit as follows:

- 0** if the REPD bit is set to zero, the REPORT SUPPORTED TASK MANAGEMENT FUNCTION parameter data returned is shown in table 174; and
- 1** if the REPD bit is set to one, the REPORT SUPPORTED TASK MANAGEMENT FUNCTION parameter data returned is shown in table 175.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. The allocation length should be at least four.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS basic parameter data format is shown in table 174.

Table 174 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	ATS	ATSS	CACAS	CTSS	LURS	QTS	Obsolete	Obsolete
1	Reserved					QAES	QTSS	ITNRS
2	Reserved							
3	REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS ADDITIONAL DATA LENGTH (00h)							

The REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS extended parameter data format is shown in Table 175.

Table 175 REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS extended parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	ATS	ATSS	CACAS	CTSS	LURS	QTS	Obsolete	Obsolete
1	Reserved					QAES	QTSS	ITNRS
2	Reserved							
3	REPORT SUPPORTED TASK MANAGEMENT FUNCTIONS ADDITIONAL DATA LENGTH (0Ch)							
4	Reserved							TMFTMOV
5	Reserved							
6	ATS	ATSTS	CACATS	CTSTS	LURTS	QTTS	Reserved	Reserved
7	Reserved					QAETS	QTSTS	ITNRTS
8	(MSB)							
...	TASK MANAGEMENT FUNCTIONS LONG TIMEOUT							
11	(LSB)							
12	(MSB)							
...	TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT							
15	(LSB)							

ATS (ABORT TASK Supported) bit

- 1 An ATS bit set to one indicates the ABORT TASK task management functions (see SAM-6) is supported by the logical unit
- 0 An ATS bit set to zero indicates the ABORT TASK task management function is not supported.

ATSS (ABORT TASK Set Supported) bit

- 1 ATS bit set to one indicates the ABORT TASK SET task management function (see SAM-6) is supported by the logical unit.
- 0 ATS bit set to zero indicates the ABORT TASK SET task management function is not supported.

CACAS (CLEAR ACA Supported) bit

- 1 A CACAS bit set to one indicates the CLEAR ACA task management function (see SAM-6) is supported by the logical unit.
- 0 A CACAS bit set to zero indicates the CLEAR ACA task management function is not supported.

CTSS (CLEAR TASK SET Supported) bit

- 1 A CTSS bit set to one indicates the CLEAR TASK SET task management function (see SAM-6) is supported by the logical unit.
- 0 A CTSS bit set to zero indicates the CLEAR TASK SET task management function is not supported.

LURS (LOGICAL UNIT RESET Supported) bit

- 1 A LURS bit set to one indicates the LOGICAL UNIT RESET task management function (see SAM-6) is supported by the logical unit.
- 0 A LURS bit set to zero indicates the LOGICAL UNIT RESET task management function is not supported.

QTS (QUERY TASK Supported) bit

- 1** A QTS bit set to one indicates the QUERY TASK task management function (see SAM-6) is supported by the logical unit.
- 0** A QTS bit set to zero indicates the QUERY TASK task management function is not supported.

TRS (TARGET RESET Supported) bit

- 1** A TRS bit set to one indicates the TARGET RESET task management function (See SAM-2) is supported by the logical unit.
- 0** A TRS bit set to zero indicates the TARGET RESET task management function is not supported.

WAKES (WAKEUP Supported) bit

- 1** A WAKES bit set to one indicates the WAKEUP task management function (see SAM-2) is supported by the logical unit.
- 0** A WAKES bit set to zero indicates the WAKEUP task management function is not supported.

QAES (QUERY ASYNCHRONOUS EVENT Supported) bit

- 1** A QAES bit set to one indicates the QUERY ASYNCHRONOUS EVENT task management function (see SAM-6) is supported by the logical unit.
- 0** A QAES bit set to zero indicates the QUERY ASYNCHRONOUS EVENT task management function is not supported.

QTSS (QUERY TASK SET Supported) bit

- 1** A QUERY TASK SET supported (QTSS) bit set to one indicates the QUERY TASK SET task management function (see SAM-6) is supported by the logical unit.
- 0** A QTSS bit set to zero indicates the QUERY TASK SET task management function is not supported.

ITNRS (I-T NEXUS RESET Supported) bit

- 1** An ITNRS bit set to one indicates the I_T NEXUS RESET task management function (see SAM-6) is supported by the logical unit.
- 0** An ITNRS bit set to zero indicates the I_T NEXUS RESET task management function is not supported.

TMFTMOV (Task Management Function Timeouts Valid) bit

- 1** A TMFTMOV bit set to one indicates the contents of the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field and TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field are valid.
- 0** A TMFTMOV bit set to zero indicates the contents of the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field and TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field are not valid and should be ignored.

ATTS (ABORT TASK Timeout Selector) bit

- 1** An ATTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the ABORT TASK task management function.
- 0** An ATTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the ABORT TASK task management function.

ATSTS (ABORT TASK SET Timeout Selector) bit

- 1** An ATSTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the ABORT TASK SET task management function.
- 0** An ATSTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the ABORT TASK SET task management function.

CACATS (CLEAR ACA Timeout Selector) bit

- 1** A CACATS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the CLEAR ACA task management function.
- 0** A CACATS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the CLEAR ACA task management function.

CTSTS (CLEAR TASK SET Timeout Selector) bit

- 1** A CTSTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the CLEAR TASK SET task management function.
- 0** A CTSTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the CLEAR TASK SET task management function.

LURTS (LOGICAL UNIT RESET Timeout Selector) bit

- 1** A LURTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the LOGICAL UNIT RESET task management function.
- 0** A LURTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the LOGICAL UNIT RESET task management function.

QTTS (QUERY TASK Timeout Selector) bit

- 1** A QTTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the QUERY TASK task management function.
- 0** A QTTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the QUERY TASK task management function.

QAETS (QUERY ASYNCHRONOUS EVENT Timeout Selector) bit

- 1** A QAETS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the QUERY ASYNCHRONOUS EVENT task management function.
- 0** A QAETS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the QUERY ASYNCHRONOUS EVENT task management function.

QTSTS (QUERY TASK SET Timeout Selector) bit

- 1** A QTSTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the QUERY TASK SET task management function.
- 0** A QTSTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the QUERY TASK SET task management function.

ITNRTS (I_T NEXUS RESET timeout selector) bit

- 1** An ITNRTS bit set to one indicates that the value in the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field applies to the I_T NEXUS RESET task management function.
- 0** An ITNRTS bit set to zero indicates that the value in the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field applies to the I_T NEXUS RESET task management function.

TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field

If the TMFTMOV bit is set to one and the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field is not set to zero, then the contents of the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field indicate the recommended time in 100 millisecond increments that the application client should wait prior to timing out a task management function for which the applicable selector bit is set to zero. If the TMFTMOV bit is set to zero or the TASK MANAGEMENT FUNCTIONS LONG TIMEOUT field is set to zero, then the recommended timeout is unspecified for any task management function for which the applicable selector bit is set to zero.

TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field

If the TMFTMOV bit is set to one and the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field is not set to zero, then the contents of the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field indicate the recommended time in 100 millisecond increments that the application client should wait prior to timing out a task management function for which the applicable selector bit is set to one. If the TMFTMOV bit is set to zero or the TASK MANAGEMENT FUNCTIONS SHORT TIMEOUT field is set to zero, then the recommended timeout is unspecified for any task management function for which the applicable selector bit is set to one.

3.39 REPORT TIMESTAMP command

The REPORT TIMESTAMP command (see table 176) requests the device server to return the current value of a device clock (see SPC-6). This command uses the MAINTENANCE IN CDB format (see SPC-6).

Table 176 REPORT TIMESTAMP command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A3h)							
1	Reserved			SERVICE ACTION (0Fh)				
2	Reserved							
...								
5								
6	(MSB)	ALLOCATION LENGTH						
...								
9	(LSB)							
10	Reserved							
11	CONTROL							

OPERATION CODE field

The OPERATION CODE field shall be set as shown in table 176 for the REPORT TIMESTAMP command.

SERVICE ACTION field

The SERVICE ACTION field shall be set as shown in table 176 for the REPORT TIMESTAMP command.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The format for the parameter data returned by the REPORT TIMESTAMP command is shown in table 177.

Table 177 REPORT TIMESTAMP parameter data format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	TIMESTAMP PARAMETER DATA LENGTH (0Ah)							_____ (LSB)
2	Reserved				TIMESTAMP ORIGIN			
3	Reserved							
4	Reserved							
...	TIMESTAMP _____							
9	_____							
10	Reserved							
11	Reserved							

TIMESTAMP PARAMETER DATA LENGTH field

The TIMESTAMP PARAMETER DATA LENGTH field indicates the number of bytes of parameter data that follow. The contents of the TIMESTAMP PARAMETER DATA LENGTH field are not altered based on the allocation length (see 2.2.6).

TIMESTAMP ORIGIN field

The TIMESTAMP ORIGIN field indicates the most recent event that initialized the returned device clock (see SPC-6).

TIMESTAMP field

The TIMESTAMP field contains the current value of a device clock (see SPC-6).

3.40 REQUEST SENSE command

The REQUEST SENSE command (see table 178) requests that the device server transfer sense data to the application client.

Table 178 REQUEST SENSE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (03h)							
1	Reserved							DESC
2	Reserved							
3	Reserved							
4	ALLOCATION LENGTH							
5	CONTROL							

DESC (Descriptor Format) bit

The descriptor format (DESC) bit specifies which sense data format shall be returned.

- 0** If DESC is set to zero, fixed format sense data shall be returned (see 2.4.1.2).
- 1** If DESC is set to one and descriptor format sense data is supported, descriptor format sense data shall be returned (see 2.4.1.1).

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. Application clients should request 252 bytes of sense data to ensure they retrieve all the sense data. If fewer than 252 bytes are requested, sense data may be lost since the REQUEST SENSE command with any allocation length clears the sense data.

Sense data shall be available and cleared under the conditions defined in SAM-6. If the device server has no other sense data available to return, it shall:

- 1) return the sense key set to NO SENSE, additional sense code set to NO ADDITIONAL SENSE INFORMATION and;
- 2) complete the REQUEST SENSE command with GOOD status.
- 3) On completion of the command the logical unit shall return to the same power condition that was active before the REQUEST SENSE command was received. A REQUEST SENSE command shall not reset any power condition timers.

The device server shall return CHECK CONDITION status for a REQUEST SENSE command only to report exception conditions specific to the REQUEST SENSE command itself.

Examples of conditions that cause a REQUEST SENSE command to return a CHECK CONDITION status are:

- a) An invalid field value is detected in the CDB;
- b) The device server does not support the REQUEST SENSE command (see 3.40);
- c) An unrecovered error is detected by the service delivery subsystem; or
- d) A malfunction prevents return of the sense data.

Device servers shall return at least 18 bytes of parameter data in response to a REQUEST SENSE command if the allocation length is 18 or greater and the DESC bit is set to zero. Application clients may determine how much sense data has been returned by examining the ALLOCATION LENGTH field in the CDB and the ADDITIONAL SENSE LENGTH field in the sense data. Device servers shall not adjust the additional sense length to reflect truncation if the allocation length is less than the sense data available.

3.41 RESERVE(6) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The RESERVE(6) command (see table 179) is used to reserve a logical unit. This subclause describes only those instances where the RESERVE(6) command differs from the RESERVE(10) command. Except for the instances described in this subclause, the RESERVE(6) command shall function exactly like the RESERVE(10) command (see 3.42).

Table 179 RESERVE(6) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (16h)							
1	Reserved			Obsolete				
2	Obsolete							
3	Obsolete							
4	Obsolete							
5	CONTROL							

Obsolete Bits 1 through 4 of Byte 1 provided a method, limited to device addresses 0 through 7, to handle third-party reservations in earlier versions of the SCSI standard. The obsolete method has been replaced by the RESERVE(10) and RELEASE(10).

Byte 1 Bit 0 and Bytes 2 through 4 provide an obsolete way to reserve extents within a logical unit. The Seagate device server does not support the feature—if it is set, it will be rejected with an ILLEGAL REQUEST/INVALID BIT IN THE CDB. The Seagate device server ignores the Obsolete field for the Reservation ID.

3.42 RESERVE (10) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

3.42.1 RESERVE (10) command introduction

The RESERVE(10) command (see table 180) is used to reserve a logical unit.

Table 180 RESERVE (10) Command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (56h)							
1	Reserved			3RDPTY	Reserved		LONGID	Obsolete
2	Obsolete							
3	THIRD-PARTY DEVICE ID							
4	Reserved							
5	Reserved							
6	Reserved							
7	(MSB)	PARAMETER LIST LENGTH						(LSB)
8								
9	CONTROL							

The RESERVE and RELEASE commands provide a basic mechanism for contention resolution in multiple-initiator systems. The third-party reservation allows logical units to be reserved for another specified SCSI device. See 5.5.1 for a general description of reservations and the commands that manage them.

If the RESERVE(10) command is implemented, then the RELEASE(10) also shall be implemented.

Byte 1 Bit 0 and Byte 2 provide an obsolete way to reserve extents within a logical unit. If Byte 1, Bit 0 is equal to one, device servers not implementing the obsolete capability shall terminate the command with CHECK CONDITION status and the sense key shall be set to ILLEGAL REQUEST.

3.42.2 Logical unit reservation

Logical unit reservations are mandatory if the RESERVE(10) command is implemented. This command shall request that the entire logical unit be reserved for the exclusive use of the initiator until the reservation is superseded by another valid RESERVE command from the same initiator or until released by a RELEASE command from the same initiator that made the reservation, by a TARGET RESET task management function performed by any initiator, by a hard reset condition, or by a power on cycle. A logical unit reservation shall not be granted if the logical unit is reserved by another initiator. It shall be permissible for an initiator to reserve a logical unit that is currently reserved by that initiator. If the LONGID bit or the 3RDPTY bit is zero then the PARAMETER LIST LENGTH field shall be ignored.

If the logical unit is reserved for another initiator, the device server shall return RESERVATION CONFLICT status. After honoring a logical unit reservation, the device server shall check each newly received command for reservation conflicts.

For multiple port implementations, devices on other ports (i.e., the ports that do not include the initiator to which the reservation has been granted) also shall be denied access to the logical unit as described in the preceding clause.

3.42.3 Third-party reservation

Third-party reservations are mandatory if the RESERVE(10) command is implemented. The third-party reservation for the RESERVE(10) command allows an application client to reserve a logical unit within a logical unit for another SCSI device. This is intended for use in multiple initiator systems that use the COPY or EXTENDED COPY command.

3RDPARTY bit

- 0** If the third-party (3RDPTY) bit is zero, then a third-party reservation is not requested. If the 3RDPTY bit is zero then the LONGID bit shall be ignored.
- 1** If the 3RDPTY bit is one then the device server shall reserve the specified logical unit for the SCSI device specified in the THIRD-PARTY DEVICE ID field. Device ID formats are protocol specific. The device server shall preserve the reservation until it is superseded by another valid RESERVE command from the initiator that made the reservation or until it is released by the same initiator, by a TARGET RESET task management function performed by any initiator, a hard reset condition, or by a power on cycle. The device server shall ignore any attempt to release the reservation made by any other initiator.

After a third-party reservation has been granted, the initiator that sent the RESERVE command shall be treated like any other initiator. Reservation conflicts shall occur in all cases where another initiator is not allowed access due to the reservation.

If independent sets of mode parameters are implemented, a third-party reservation shall cause the device server to transfer the set of mode parameters in effect for the application client that sent the RESERVE command to the mode parameters used for commands from the third-party device. Any subsequent command issued by the third-party device shall be executed according to the mode parameters in effect for the application client that sent the RESERVE command.

THIRD-PARTY DEVICE ID field

If the THIRD-PARTY DEVICE ID value associated with the reservation release is smaller than 255, the LONGID bit may be zero and the ID value sent in the CDB. Device ID formats are protocol specific. If the THIRD-PARTY DEVICE ID is greater than 255, the LONGID bit shall be one. If the LONGID bit is one, the THIRD-PARTY DEVICE ID field in the CDB shall be ignored. If the LONGID bit is one, the parameter list length shall be at least eight. If the LONGID bit is one and the parameter list length is less than eight, the device server shall return a CHECK CONDITION status with a sense key of ILLEGAL REQUEST.

Device servers that support device IDs greater than 255 shall accept commands with LONGID equal to one. Device servers whose devices IDs are limited to 255 or smaller may reject commands with LONGID equal to one with CHECK CONDITION status and a sense key of ILLEGAL REQUEST.

If the LONGID bit is one, the parameter list length shall be eight, and the parameter list shall have the format shown in table 181. If the LONGID bit is one and the parameter list length is not eight, the device server shall return a CHECK CONDITION status with a sense key of ILLEGAL REQUEST.

Table 181 RESERVE (10) ID only parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	THIRD-PARTY DEVICE ID							
...								
7								

3.42.4 Superseding reservations

Superseding reservations is mandatory if the RELEASE(10) command is implemented. An application client that holds a current logical unit reservation may modify that reservation by issuing another RESERVE command to the same logical unit. The superseding RESERVE command shall release the previous reservation state when the new reservation request is granted. The current reservation shall not be modified if the superseding reservation request is not granted. If the superseding reservation cannot be granted because of conflicts with a previous reservation, other than the reservation being superseded, then the device server shall return RESERVATION CONFLICT status.

3.43 RESTORE ELEMENTS AND REBUILD command

The RESTORE ELEMENTS AND REBUILD command (see table 182) requests that the device server perform a storage element restoration (see SBC-5).

If deferred microcode has been saved and not activated (see SPC-6), then the device server shall terminate this command with CHECK CONDITION status with the sense key set to NOT READY and the additional sense code set to LOGICAL UNIT NOT READY, MICROCODE ACTIVATION REQUIRED.

Table 182 RESTORE ELEMENTS AND REBUILD command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved			SERVICE ACTION (19h)				
2	Reserved							
...								
14								
15	CONTROL							

OPERATION CODE field and the SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in SPC-6 and shall be set to the values shown in table 182 for the RESTORE ELEMENTS AND REBUILD command.

For a RESTORE ELEMENTS AND REBUILD command, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to COMMAND SEQUENCE ERROR if:

- there is at least one depopulated storage element (e.g., the PHYSICAL ELEMENT HEALTH field is set to FFh); and
- all depopulated storage elements have the RALWD bit (see 3.6.2) set to zero.

For a RESTORE ELEMENTS AND REBUILD command, the following shall not be considered an error:

- the device has no depopulated storage elements; or
- at least one depopulated storage element has the RALWD bit (see 3.6.2) set to one.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

After command completion without error, further processing may occur as described in SBC-5.

3.44 REZERO UNIT command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

Table 183 REZERO UNIT command (01h)

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (01h)							
1	LUN							
2	LOGICAL BLOCK ADDRESS MUST BE 0'S							
3								
4	Reserved							
5	CONTROL							

The Rezero Unit command (see table 183) requests that the disk drive set its logical block address to zero and return the disk drive read/write heads to the track (or cylinder) containing Logical Block Zero. This command is intended for systems which disable retries and the initiator performs error recovery. It is longer than a seek to Logical Block Address zero and should be utilized if seek errors are encountered.

For systems that support disconnection, the disk drive disconnects when this command is received.

A Rezero Command also causes a thermal compensation to occur and resets the thermal compensation cycle timer back to its start, thus allowing the host to know when to expect the next thermal compensation to occur. The host can thus prevent critical data transfer operations from being interrupted at an undesirable time.

For drives that support saved log parameters, the Rezero Unit command will also save log counters to the media and reset the log save timer back to its start.

LUN (Logical Unit Number) field

Seagate drives only support Logical Unit Number 0.

CONTROL byte

The CONTROL byte is described in 2.2.7.

3.45 SANITIZE command

3.45.1 SANITIZE command introduction

The SANITIZE command (see table 184) requests that the device server perform a sanitize operation. This command shall be processed as if it has a HEAD OF QUEUE task attribute.

Table 184 SANITIZE command (48h)

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (48h)							
1	IMMED	ZNR	AUSE	SERVICE ACTION				
2	Reserved							
...								
6								
7	(MSB)	PARAMETER LIST LENGTH						(LSB)
8								
9	CONTROL							

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in Table 184.

IMMED bit

- 0** If the IMMED (immediate) bit is set to zero, then the device server shall return status after the sanitize operation is completed.
- 1** If the IMMED bit set to one, then the device server shall return status as soon as the CDB and parameter data, if any, have been validated. The REQUEST SENSE command may be used to poll for progress of the sanitize operation regardless of the value of the IMMED bit.

ZNR bit

- 0** For a zoned block device, a zoned no reset (ZNR) bit set to zero specifies that as part of completing a sanitize operation, the device server shall perform the equivalent of a RESET WRITE POINTER command (see 4.8) with the ALL bit set to one.
- 1** For a zoned block device, a ZNR bit set to one specifies that as part of completing a sanitize operation, the device server:
 - a) unless otherwise specified (e.g., a write pointer zone is set to offline), shall not modify the write pointer

AUSE bit

If the allow unrestricted sanitize exit (AUSE) bit is set to one, and the specified sanitize operation fails, then the device server shall process a subsequent EXIT FAILURE MODE service action as if the previous sanitize operation had completed without error (see Completing a sanitize operation in SBC-5).

If:

- a) the AUSE bit is set to zero in the SANITIZE command that requested a sanitize operation;
- b) the specified sanitize operation completes with an error; and
- c) a subsequent SANITIZE command with the EXIT FAILURE MODE service action is received,

then the device sever shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

SERVICE ACTION field

The SERVICE ACTION field is defined in 2.2.2 and set to a value defined in table 185.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the parameter data that shall be sent from the application client to the device server. A PARAMETER LIST LENGTH field set to zero specifies that no data shall be transferred.

CONTROL byte

The CONTROL byte is described in 2.2.7.

3.45.2 SANITIZE service actions

The SANITIZE command service actions are defined in (see table 185). At least one service action shall be supported if the SANITIZE command is supported. If the specified service action is not supported, then the command shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and additional sense code set to INVALID FIELD IN CDB.

Table 185 SANITIZE service action codes

Code	Name	Description	PARAMETER LIST LENGTH field requirement [1][1]	Reference
01h	OVERWRITE	Perform the overwrite sanitize method.	Greater than 0004h and less than logical block length + 5	3.45.3
02h	BLOCK ERASE	Perform the block erase sanitize method.	Set to 0000h	3.45.4
03h	CRYPTOGRAPHIC ERASE	Perform the cryptographic erase sanitize method.	Set to 0000h	3.45.5
1Fh	EXIT FAILURE MODE	Exit the Sanitize failure mode	Set to 0000h	3.45.6
all others	Reserved			
[1] If the requirement is not met, then the SANITIZE command is terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.				

3.45.3 SANITIZE command with OVERWRITE service action

3.45.3.1 OVERWRITE service action introduction

The OVERWRITE service action (see table 185) performs a sanitize operation using the overwrite method (see SBC-5).

3.45.3.2 OVERWRITE service action parameter list

The parameter list format for the OVERWRITE service action is shown in Table 186.

Table 186 OVERWRITE service action parameter list

Bit Byte	7	6	5	4	3	2	1	0	
0	INVERT	TEST		OVERWRITE COUNT					
1	Reserved								
2	(MSB)	INITIALIZATION PATTERN LENGTH (n - 3)						(LSB)	
3									
4									
....	INITIALIZATION PATTERN								
n									

INVERT bit

- 1** The INVERT MULT PASSES bit set to one specifies that the initialization pattern and protection information bytes, if any, shall be inverted (i.e., each bit XORed with one) between consecutive overwrite passes.
- 0** The INVERT MULT PASSES bit set to zero specifies that the initialization pattern and protection information bytes, if any, are written as specified in the INITIALIZATION PATTERN field on each overwrite pass.

TEST field

The TEST field is described in Table 187.

Table 187 TEST field

Code	Description
00b	Shall not cause any changes in the defined behavior of the SANITIZE command
01b to 11b	Vendor specific

OVERWRITE COUNT field

The OVERWRITE COUNT field specifies the number of overwrite passes to be performed. A value of 00h is reserved.

INITIALIZATION PATTERN LENGTH field

The INITIALIZATION PATTERN LENGTH field specifies the length in bytes of the INITIALIZATION PATTERN field. The INITIALIZATION PATTERN LENGTH field shall be greater than zero and shall not exceed the logical block length. If the INITIALIZATION PATTERN LENGTH field is set to zero or is greater than the logical block length, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

The INITIALIZATION PATTERN field specifies the data pattern used to write the user data. This data pattern is repeated as necessary to fill each logical block. For each logical block, the first byte of the user data shall begin with the first byte of the initialization pattern. Protection information bytes, if any, shall be set to FFFF_FFFF_FFFF_FFFFh.

If the INVERT bit is set to one and:

- a) the OVERWRITE COUNT field is an even number, then the pattern used for the first write pass shall consist of:
 - A) the user data shall be set to the inversion of the INITIALIZATION PATTERN data; and
 - B) protection information bytes, if any, shall be set to 0000_0000_0000_0000h; or
- b) the OVERWRITE COUNT field is an odd number, then the pattern used for the first write pass shall consist of:
 - A) the user data is set to the INITIALIZATION PATTERN data; and
 - B) protection information bytes, if any, shall be set to FFFF_FFFF_FFFF_FFFFh.

Following a successful sanitize overwrite service action operation:

- a) the medium shall not be format corrupt;
- b) protection information, if any, set to FFFF_FFFF_FFFF_FFFFh; and
- c) read operations should complete without error.

3.45.4 SANITIZE command with BLOCK ERASE service action

The BLOCK ERASE service action (see table 185) performs a sanitize operation using the block erase method (see SBC-5).

After successful completion of a sanitize block erase, the device server:

- a) may terminate commands that perform read operations to mapped LBAs with:
 - A) CHECK CONDITION status with sense key set to MEDIUM ERROR and the appropriate additional sense code for the condition; or
 - B) if the logical unit is formatted with protection information, CHECK CONDITION status with sense key set to ABORTED COMMAND and additional sense code set to one of the protection information check codes shown in Table 110;
 and
- b) should complete read operations to unmapped LBAs without error. (see SBC-5)

3.45.5 SANITIZE command with CRYPTOGRAPHIC ERASE service action

The CRYPTOGRAPHIC ERASE service action (see table 185) performs a sanitize operation using the cryptographic erase method (see SBC-5).

After successful completion of the cryptographic erase operation:

- a) if any LBA is mapped and if the logical unit is formatted with protection information, then the device server may terminate read operations with CHECK CONDITION status with sense key set to ABORTED COMMAND and additional sense code set to one of the protection information check codes shown in Table 110; and
- b) the device server shall process unmapped LBAs as required by logical block provisioning management.

3.45.6 SANITIZE command with EXIT FAILURE MODE service action

The EXIT FAILURE MODE service action (see table 110) requests that the device server complete a sanitize operation which completed with an error as if the sanitize operation completed without an error (see SBC-5).

After successful completion of a SANITIZE command with the EXIT FAILURE MODE service action:

- a) if any LBA is mapped (see SBC-5), and the logical unit is formatted with protection information, then the device server may terminate commands that perform read operations to mapped LBAs with CHECK CONDITION status with the sense key set to ABORTED COMMAND and the additional sense code set to one of the codes defined in Table 110; and
- b) the device server should complete read operations to unmapped LBAs without error (see SBC-5).

3.46 SECURITY PROTOCOL IN command

3.46.1 Command description

The SECURITY PROTOCOL IN command (see table 188) is used to retrieve security protocol information or the results of one or more SECURITY PROTOCOL OUT commands.

Table 188 SECURITY PROTOCOL IN command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A2h)							
1	SECURITY PROTOCOL							
2	SECURITY PROTOCOL SPECIFIC							
3	SECURITY PROTOCOL SPECIFIC							
4	INC_512	Reserved						
5	Reserved							
6	(MSB)	ALLOCATION LENGTH						
...	ALLOCATION LENGTH							(LSB)
9	ALLOCATION LENGTH							
10	Reserved							
11	CONTROL							

SECURITY PROTOCOL field

The SECURITY PROTOCOL field (see table 189) specifies which security protocol is being used.

Table 189 SECURITY PROTOCOL field within SECURITY PROTOCOL IN command

Code	Description	Reference
00h	Security protocol information	3.46.2
01h - 06h	Defined by the TCG	https://www.trustedcomputinggroup.org
07h	CbCS	SPC-6
08h - 1Fh	Reserved	
20h	Tape Data Encryption	SSC-3
21h	Data Encryption Configuration	ADC-3
22h - 3Fh	Reserved	
40h	SA Creation Capabilities	SPC-6
41h	IKEv2-SCSI	SPC-6
42h to E6h	Reserved	
E7h	SD Association	"SD Association" on page 30
E8h	DMTF Security Protocol and Data Model	SPDM
E9 to EAh	Defined by NVM Express	NVMe
EBh	Defined by SCSA	"SCSA" on page 31
ECh	JEDEC Universal Flash Storage	UFS
EDh	Obsolete	
EEh	Authentication in Host Attachments of Transient Storage Devices	IEEE 1667
EFh	ATA Device Server Password Security	SAT-4
F0h - FFh	Vendor specific	

The contents of the SECURITY PROTOCOL SPECIFIC field depend on the protocol specified by the SECURITY PROTOCOL field (see table 189).

INC_512 (512 Increment)

- 0** 0An INC_512 bit set to zero specifies that the ALLOCATION LENGTH field (see 2.2.6) expresses the number of bytes to be transferred.
- 1** 1A 512 increment (INC_512) bit set to one specifies that the ALLOCATION LENGTH field (see 2.2.6) expresses the maximum number of bytes available to receive data in increments of 512 bytes (e.g., a value of one means 512 bytes, two means 1,024 bytes, etc.). Pad bytes may or may not be appended to meet this length. Pad bytes shall have a value of 00h.

Indications of data overrun or underrun and the mechanism, if any, for processing retries depend on the protocol specified by the SECURITY PROTOCOL field (see table 189).

Any association between a previous SECURITY PROTOCOL OUT command and the data transferred by a SECURITY PROTOCOL IN command depends on the protocol specified by the SECURITY PROTOCOL field (see table 190). If the device server has no data to transfer (e.g., the results for any previous SECURITY PROTOCOL OUT commands are not yet available), the device server may transfer data indicating it has no other data to transfer.

The format of the data transferred depends on the protocol specified by the SECURITY PROTOCOL field (see table 189).

The device server shall retain data resulting from a SECURITY PROTOCOL OUT command, if any, until one of the following events is processed:

- a) Transfer of the data via a SECURITY PROTOCOL IN command from the same I_T_L nexus as defined by the protocol specified by the SECURITY PROTOCOL field;
- b) Logical unit reset (See SAM-6); or
- c) I_T nexus loss (See SAM-6) associated with the I_T nexus that sent the SECURITY PROTOCOL OUT command.

If the data is lost due to one of these events the application client may send a new SECURITY PROTOCOL OUT command to retry the operation.

3.46.2 Security protocol information description

3.46.2.1 Overview

The purpose of security protocol information security protocol (i.e., the SECURITY PROTOCOL field set to 00h in a SECURITY PROTOCOL IN command) is to transfer security protocol related information from the logical unit. A SECURITY PROTOCOL IN command in which the SECURITY PROTOCOL field is set to 00h is not associated with a previous SECURITY PROTOCOL OUT command and shall be processed without regard for whether a SECURITY PROTOCOL OUT command has been processed.

If the SECURITY PROTOCOL IN command is supported, the SECURITY PROTOCOL value of 00h shall be supported as defined in this standard.

3.46.2.2 SECURITY PROTOCOL SPECIFIC field

When the SECURITY PROTOCOL field is set to 00h in a SECURITY PROTOCOL IN command, the SECURITY PROTOCOL SPECIFIC field contains a single numeric value as defined in 190.

Table 190 SECURITY PROTOCOL SPECIFIC field for SECURITY PROTOCOL IN protocol 00h

Code	Description	Support	Reference
0000h	Supported security protocol list	Mandatory	3.46.2.3
0001h	Certificate data	Mandatory	3.46.2.4
0002h	Security compliance information	Optional	3.46.2.4.1
0003h - FFFFh	Reserved		

All other CDB fields for SECURITY PROTOCOL IN command shall meet the requirements stated in 3.46.1.

Each time a SECURITY PROTOCOL IN command with the SECURITY PROTOCOL field set to 00h is received, the device server shall transfer the data defined in 3.46.2 starting with byte 0.

3.46.2.3 Supported security protocols list description

If the SECURITY PROTOCOL field is set to 00h and the SECURITY PROTOCOL SPECIFIC field is set to 0000h in a SECURITY PROTOCOL IN command, the parameter data shall have the format shown in table 191.

Table 191 Supported security protocols SECURITY PROTOCOL IN parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
...								
5								
6	(MSB)	SUPPORTED SECURITY PROTOCOL LIST LENGTH (m - 7)						(LSB)
7								
Supported security protocol list								
8	SUPPORTED SECURITY PROTOCOL (first) (00h)							
...	...							
m	SUPPORTED SECURITY PROTOCOL (last)							
m + 1	Pad bytes (optional)							
...								
n								

SUPPORTED SECURITY PROTOCOL LIST LENGTH field

The SUPPORTED SECURITY PROTOCOL LIST LENGTH field indicates the total length, in bytes, of the supported security protocol list that follows.

SUPPORTED SECURITY PROTOCOL field

Each SUPPORTED SECURITY PROTOCOL field in the supported security protocols list shall contain one of the security protocol values supported by the logical unit. The values shall be listed in ascending order starting with 00h.

3.46.2.4 Certificate data description

3.46.2.4.1 Certificate overview

A certificate is either an X.509 Public Key Certificate or an X.509 Attribute Certificate depending on the capabilities of the logical unit.

If the SECURITY PROTOCOL field is set to 00h and the SECURITY PROTOCOL SPECIFIC field is set to 0001h in a SECURITY PROTOCOL IN command, the parameter data shall have the format shown in table 192.

Table 192 Certificate data SECURITY PROTOCOL IN parameter data

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1									
2	(MSB)	CERTIFICATE LENGTH (m - 3)							
3								(LSB)	
4									
...	CERTIFICATE								
m									
m + 1									
...	Pad bytes (optional)								
n									

CERTIFICATE LENGTH field

The CERTIFICATE LENGTH field indicates the total length, in bytes, of the certificate or certificates that follow. The length may include more than one certificates. If the device server doesn't have a certificate to transfer, the CERTIFICATE LENGTH field shall be set to 0000h.

CERTIFICATE field

The contents of the CERTIFICATE field are defined in 3.46.2.4.2 and 3.46.2.4.3.

3.46.2.4.2 Public Key certificate description

RFC 3280 defines the certificate syntax for certificates consistent with X.509v3 Public Key Certificate Specification. Any further restrictions beyond the requirements of RFC 3280 are yet to be defined by T10.

3.46.2.4.3 Attribute certificate description

RFC 3281 defines the certificate syntax for certificates consistent with X.509v2 Attribute certificate Specification. Any further restrictions beyond the requirements of RFC 3281 are yet to be defined by T10.

3.46.2.5 Security compliance information description

3.46.2.5.1 Security compliance information overview

The security compliance information parameter data contains information about security standards that apply to this SCSI target device.

If the SECURITY PROTOCOL field is set to 00h and the SECURITY PROTOCOL SPECIFIC field is set to 0002h in a SECURITY PROTOCOL IN command, then the parameter data shall have the format shown in

Table 193 Certificate data SECURITY PROTOCOL IN parameter data

Bit Byte	7	6	5	4	3	2	1	0								
0	(MSB)															
...	SECURITY COMPLIANCE INFORMATION LENGTH (m-3)															
3									(LSB)							
4	Compliance descriptor [first]															
...																
	...															
...	Compliance descriptor [last]															
m																
m + 1	Pad bytes (optional)															
...																
n																

SECURITY COMPLIANCE INFORMATION LENGTH field

The SECURITY COMPLIANCE INFORMATION LENGTH field indicates the total length, in bytes, of the compliance descriptors that follow.

Each compliance descriptor (see 3.46.2.5.2) contains information about a security standard that applies to this SCSI target device. Compliance descriptors may be returned in any order.

The total data length shall conform to the ALLOCATION LENGTH field requirements (see 2.2.6). Pad bytes may be appended to meet this length. Pad bytes shall have a value of 00h.

3.46.2.5.2 Compliance descriptor overview

The format of a compliance descriptor in the security compliance information SECURITY PROTOCOL IN parameter data is shown in table 192.

Table 194 Compliance descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	Compliance Descriptor Type							
2	(LSB)							
3	Reserved							
4	(MSB)							
...	COMPLIANCE DESCRIPTOR LENGTH (n-3)							
7	(LSB)							
8								
...	Descriptor specific information							
n								

COMPLIANCE DESCRIPTOR TYPE field

The COMPLIANCE DESCRIPTOR TYPE field (see table 195) indicates the format of the descriptor specific information. The security compliance information SECURITY PROTOCOL IN parameter data may contain more than one compliance descriptor with the same value in the COMPLIANCE DESCRIPTOR TYPE field.

Table 195 INFORMATION TYPE

Code	Description	Content	Reference
0001h	Peripheral device identifying information	FIPS 140-2 FIPS 140-3	3.46.2.5.3
All other	Reserved.		

3.46.2.5.3 FIPS 140 compliance descriptor

The FIPS 140 compliance descriptor (see table 196) contains information that may be used to locate information about a FIPS 140 certificate associated with the SCSI target device. The SCSI target device may or may not be operating in the mode specified by that certificate.

Table 196 FIPS 140 Compliance descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	Compliance Descriptor Type (0001h)						(LSB)
1								
2		Reserved						
3								
4	(MSB)	COMPLIANCE DESCRIPTOR LENGTH (0000 0208h)						(LSB)
...								
7								
8		REVISION						
9		OVERALL SECURITY LEVEL						
10								
...		Reserved						
15								
16	(MSB)	Hardware Version						(LSB)
...								
143								
144	(MSB)	Version						(LSB)
...								
271								
272	(MSB)	Module Name						(LSB)
...								
527								

COMPLIANCE DESCRIPTOR TYPE and COMPLIANCE DESCRIPTOR LENGTH fields

The COMPLIANCE DESCRIPTOR TYPE field and COMPLIANCE DESCRIPTOR LENGTH field are defined in 3.46.2.5.2 and shall be set as shown in table 196 for the FIPS 140 compliance descriptor.

REVISION field

The REVISION field (see table 197) is an ASCII data field (see SPC-6) that indicates the FIPS 140 revision that applies to the SCSI target device.

Table 197 REVISION field

Code	Related standard
32h	FIPS 140-2
33h	FIPS 140-3
all others	

OVERALL SECURITY LEVEL field

The OVERALL SECURITY LEVEL field is an ASCII data field (see SPC-6) that indicates the FIPS 140 overall security level that is reported by NIST.

HARDWARE VERSION field

The HARDWARE VERSION field is null terminated, null padded data (see SPC-6) that indicates the version number of the hardware in the module, as reported by NIST.

VERSION field

The VERSION field is null terminated, null padded data (see SPC-6) that indicates the version number of the firmware or software in the module, as reported by NIST. The value in the VERSION field is not related to the PRODUCT REVISION LEVEL field of standard INQUIRY data (see 3.8.2).

MODULE NAME field

The MODULE NAME field is null terminated, null padded data (see SPC-6) that indicates the name or identifier of the cryptographic module, as reported by NIST.

3.47 SECURITY PROTOCOL OUT command

The SECURITY PROTOCOL OUT command (see table 198) is used to send data to the logical unit. The data sent specifies one or more operations to be performed by the logical unit. The format and function of the operations depends on the contents of the SECURITY PROTOCOL field (see table 199). Depending on the protocol specified by the SECURITY PROTOCOL field, the application client may use the SECURITY PROTOCOL IN command (see 3.46) to retrieve data derived from these operations.

Table 198 SECURITY PROTOCOL OUT command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (B5h)							
1	SECURITY PROTOCOL							
2	SECURITY PROTOCOL SPECIFIC							
3								
4	INC_512	Reserved						
5	Reserved							
6	(MSB)							
...	TRANSFER LENGTH							
9								(LSB)
10	Reserved							
11	CONTROL							

SECURITY PROTOCOL field

The SECURITY PROTOCOL field (see table 199) specifies which security protocol is being used.

Table 199 SECURITY PROTOCOL field within SECURITY PROTOCOL OUT command

Code	Description	Reference
00h	Reserved	
01h - 06h	Defined by the TCG	https://www.trustedcomputinggroup.org
07h	CbCS	SPC-6
08h - 1Fh	Reserved	
20h	Tape Data Encryption	SSC-3
21h	Data Encryption Configuration	ADC-3
22h - 40h	Reserved	
41h	IKEv2-SCSI	SPC-6
42h - E6h	Reserved	
42h to E6h	Reserved	
E7h	SD Association	"SD Association" on page 30
E8h	DMTF Security Protocol and Data Model	SPDM
E9 to EAh	Defined by NVM Express	NVMe
EBh	Defined by SCSA	"SCSA" on page 31
ECh	JEDEC Universal Flash Storage	UFS
EDh	Obsolete	
EEh	Authentication in Host Attachments of Transient Storage Devices	IEEE 1667
EFh	ATA Device Server Password Security	SAT-4
F0h - FFh	Vendor specific	

SECURITY PROTOCOL SPECIFIC field

The contents of the SECURITY PROTOCOL SPECIFIC field depend on the protocol specified by the SECURITY PROTOCOL field (see table 199).

INC_512 (512 Increment)

- 0** A INC_512 bit set to zero specifies that the TRANSFER LENGTH field indicates the number of bytes to be transferred.
- 1** INC_512 bit set to one specifies that the TRANSFER LENGTH field (see 2.2.4) expresses the number of bytes to be transferred in increments of 512 bytes (e.g., a value of one means 512 bytes, two means 1,024 bytes, etc.). Pad bytes shall be appended as needed to meet this requirement. Pad bytes shall have a value of 00h.

Any association between a SECURITY PROTOCOL OUT command and a subsequent SECURITY PROTOCOL IN command depends on the protocol specified by the SECURITY PROTOCOL field (see table 199). Each protocol shall define whether:

- a) The device server shall complete the command with GOOD status as soon as it determines the data has been correctly received. An indication that the data has been processed is obtained by sending a SECURITY PROTOCOL IN command and receiving the results in the associated data transfer; or
- b) The device server shall complete the command with GOOD status only after the data has been successfully processed and an associated SECURITY PROTOCOL IN command is not required.

The format of the data transferred depends on the protocol specified by the SECURITY PROTOCOL field (see table 199).

3.48 SEEK command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

Table 200 SEEK command (0Bh)

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (0Bh)							
1	LUN			MSB				
2	LOGICAL BLOCK ADDRESS							LSB
3								
4								Reserved
5	CONTROL							

The Seek command (see table 200) requests that the disk drive seek to the specified logical block address.

For systems which support disconnection, the disk drive disconnects when a valid Seek command is received. The use of this command is infrequent since all commands involving data transfer to/from the disk drive media contain implied seek addresses.

LUN (Logical Unit Number) field

Seagate drives only support Logical Unit Number 0.

LOGICAL BLOCK ADDRESS field

The maximum Logical Block Address that may be specified for a Seek command is defined in Read Capacity Data (see 3.24.1 and 3.25.1). See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

CONTROL byte

The CONTROL byte is described in 2.2.7.

3.49 SEEK EXTENDED command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

Table 201 SEEK command (2Bh)

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Bh)							
1	LUN			Reserved				
2	LOGICAL BLOCK ADDRESS (MSB)							
...								
...	LOGICAL BLOCK ADDRESS (LSB)							
5								
6	Reserved							
7	Reserved							
8	Reserved							
9	CONTROL							

The Seek Extended command (see table 201) requests that the disk drive seek to the specified logical block address.

This command is implemented with the disk drive specific parameters listed in Table 201.

LUN (Logical Unit Number) field

Seagate drives only support Logical Unit Number 0.

LOGICAL BLOCK ADDRESS field

Four byte Logical Address may be specified. The drive will seek to this address when the command is received. The maximum Logical Block Address that may be specified for a Seek command is defined in Read Capacity Data (see 3.24.1 and 3.25.1). See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

CONTROL byte

The CONTROL field is described in 2.2.7.

3.50 SEND DIAGNOSTIC command

The SEND DIAGNOSTIC command (see table 202) requests the device server to perform diagnostic operations on the SCSI target device, on the logical unit, or on both. Logical units that support this command shall implement, at a minimum, the default self-test feature (i.e., the SELFTEST bit equal to one and a parameter list length of zero).

Table 202 SEND DIAGNOSTIC command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (1Dh)							
1	SELF-TEST CODE			PF	Reserved	SELFTEST	DEVOFFL	UNITOFFL
2	Reserved							
3	(MSB)	PARAMETER LIST LENGTH						(LSB)
4								
5	CONTROL							

SELFTEST bit

- 1 If the SELFTEST bit is set to one, the SELF-TEST CODE field shall contain 000b.
- 0 If the SELFTEST bit is set to zero, the contents of SELF-TEST CODE field are specified in table 203.

SELF-TEST CODE field

Table 203 SELF-TEST CODE field

Code	Name	Description
000b		This value shall be used when the SELFTEST bit is set to one, or when the SELFTEST bit is set to zero and the PF bit is set to one. If the PF bit, SELFTEST bit, and PARAMETER LIST LENGTH are all zero then no testing is performed and the command completes without error.
001b	Background short self-test	The device server shall start its short self-test (see SPC-6) in the background mode (see SPC-6). The PARAMETER LIST LENGTH field shall contain zero.
010b	Background extended self-test	The device server shall start its extended self-test (see SPC-6) in the background mode (see SPC-6). The PARAMETER LIST LENGTH field shall contain zero.
011b	Reserved	
100b	Abort background self-test	The device server shall abort the current self-test running in background mode. The PARAMETER LIST LENGTH field shall contain zero. This value is only valid if a previous SEND DIAGNOSTIC command specified a background self-test function and that self-test has not completed. If either of these conditions is not met, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.
101b	Foreground short self-test	The device server shall start its short self-test (see SPC-6) in the foreground mode (see SPC-6). The PARAMETER LIST LENGTH field shall contain zero.
110b	Foreground extended self-test	The device server shall start its extended self-test (see SPC-6) in the foreground mode (see SPC-6). The PARAMETER LIST LENGTH field shall contain zero.
111b	Reserved	

PF (page format) bit

- 1** A page format (PF) bit set to one specifies that the SEND DIAGNOSTIC parameters and any parameters returned by a following RECEIVE DIAGNOSTIC RESULTS command with the PCV bit set to zero shall contain a single diagnostic page as defined in 5.1.1.
- 0** A PF bit set to zero specifies that all SEND DIAGNOSTIC parameters are vendor specific. If the PARAMETER LIST LENGTH field is set to zero and the SEND DIAGNOSTIC command is not going to be followed by a corresponding RECEIVE DIAGNOSTIC RESULTS command with the PCV bit set to zero, then the application client shall set the PF bit to zero. The implementation of the PF bit is optional.

SELFTEST (Self-test) bit

- 1** A self-test (SELFTEST) bit set to one specifies that the device server shall perform the logical unit default self-test. If the self-test successfully passes, the command shall be terminated with GOOD status. If the self-test fails, the command shall be terminated with CHECK CONDITION status, with the sense key set to HARDWARE ERROR.
- 0** A SELFTEST bit set to zero specifies that the device server shall perform the diagnostic operation specified by the SELF-TEST CODE field or in the parameter list. The diagnostic operation may require the device server to return parameter data that contains diagnostic results. If the return of parameter data is not required, the return of GOOD status indicates successful completion of the diagnostic operation. If the return of parameter data is required, the device server shall either:
 - a) Perform the requested diagnostic operation, prepare the parameter data to be returned and indicate completion by returning GOOD status. The application client issues a RECEIVE DIAGNOSTIC RESULTS command to recover the parameter data; or
 - b) Accept the parameter list, and if no errors are detected in the parameter list, return GOOD status. The requested diagnostic operation and the preparation of the parameter data to be returned are performed upon receipt of a RECEIVE DIAGNOSTIC RESULTS command.

UNITOFFL (unit offline) bit

- 1** A unit offline (UNITOFFL) bit set to one specifies that the device server may perform diagnostic operations that may affect the user accessible medium on the logical unit (e.g., write operations to the user accessible medium, or repositioning of the medium on sequential access devices). The device server may ignore the UNITOFFL bit.
- 0** A UNITOFFL bit set to zero specifies that, after the device server has completed any diagnostic operations specified by the SEND DIAGNOSTIC command, the user accessible medium shall exhibit no effects resulting from the device server's processing the SEND DIAGNOSTIC command that are detectable by any application client. When the SELFTEST bit is set to zero, the UNITOFFL bit shall be ignored.

DEVOFFL (SCSI target device offline) bit

- 1** A SCSI target device offline (DEVOFFL) bit set to one grants permission to the device server to perform diagnostic operations that may affect all the logical units in the SCSI target device (e.g., alteration of reservations, log parameters, or sense data). The device server may ignore the DEVOFFL bit.
- 0** A DEVOFFL bit set to zero specifies that, after the device server has completed any diagnostic operations specified by the SEND DIAGNOSTIC command, no logical unit shall exhibit any effects resulting from the device server's processing the SEND DIAGNOSTIC command that are detectable by any application client. If the SELFTEST bit is set to zero, the DEVOFFL bit shall be ignored.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the parameter list that shall be transferred from the application client Data-Out Buffer to the device server. A parameter list length of zero specifies that no data shall be transferred. This condition shall not be considered an error. If PF bit is set to one and the specified parameter list length results in the truncation of the diagnostic page (e.g., the parameter list length does not match the page length specified in the diagnostic page), then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

To ensure that the diagnostic command information is not destroyed by a command sent from another I_T nexus, the logical unit should be reserved.

3.51 SET IDENTIFYING INFORMATION command

The SET IDENTIFYING INFORMATION command (see table 204) requests that the device server set identifying information in the logical unit to the value received in the SET IDENTIFYING INFORMATION parameter list. The SET IDENTIFYING INFORMATION command is an extension to the SET PERIPHERAL DEVICE/COMPONENT DEVICE IDENTIFIER service action of the MAINTENANCE OUT command defined in SCC-2.

On successful completion of a SET IDENTIFYING INFORMATION command that changes identifying information saved by the logical unit, the device server shall establish a unit attention condition (see SAM-6) for the initiator port associated with every I_T nexus except the I_T nexus on which the SET IDENTIFIER command was received, with the additional sense code set to DEVICE IDENTIFIER CHANGED.

Table 204 SET IDENTIFYING INFORMATION command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A4h)							
1	Reserved			SERVICE ACTION (06h)				
2	Reserved							
3	Reserved							
4	RESTRICTED (see SSC-2)							
5	Reserved							
6	(MSB)							
...	PARAMETER LIST LENGTH							
9	(LSB)							
10	INFORMATION TYPE							Reserved
11	CONTROL							

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the identifying information that shall be transferred from the application client to the device server. A parameter list length of zero specifies that no data shall be transferred, and that subsequent REPORT IDENTIFYING INFORMATION commands shall return the INFORMATION LENGTH field set to zero for the specified information type.

INFORMATION TYPE field

The INFORMATION TYPE specifies the identifying information type to be set.

Table 205 INFORMATION TYPE code list

Code	Description
0000000b	Peripheral device identifying information. If the PARAMETER LIST LENGTH field is set to greater than the maximum length of the peripheral device identifying information, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.
0000010b	Peripheral device text identifying information (see 3.34). If the PARAMETER LIST LENGTH field is set to a value greater than the maximum length of the peripheral device text identifying information (see 3.34), the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB. If the format of the INFORMATION field is incorrect, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.
xxxxxx1b	Restricted (see SCC-2)
All other	Reserved.

The SET IDENTIFYING INFORMATION parameter list (see table 206) contains the identifying information to be set by the device server.

Table 206 SET IDENTIFYING INFORMATION parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	INFORMATION							
...								
n								

INFORMATION

The INFORMATION field specifies the identifying information to be set for the specified information type (see 3.34).

Upon successful completion of a SET IDENTIFYING INFORMATION command, the identifying information that is saved by the logical unit shall persist through logical unit resets, hard resets, power loss, I_T nexus losses, media format operations, and media replacement.

3.52 SET TIMESTAMP command

The SET TIMESTAMP command (see table 207) requests the device server to initialize a device clock (see SPC-6) if the SCSIP bit is set to one in the Control Extension mode page (see 5.3.15). If the SCSIP bit is set to zero, the device server shall terminate the SET TIMESTAMP command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB. This command uses the MAINTENANCE OUT CDB format (see SPC-6).

Table 207 SET TIMESTAMP command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (A4h)							
1	Reserved			SERVICE ACTION (0Fh)				
2	Reserved							
...								
5								
6	(MSB)	PARAMETER LIST LENGTH						
...								
9	(LSB)							
10	Reserved							
11	CONTROL							

OPERATION CODE field

The OPERATION CODE field is defined in SPC-6 and shall be set as shown in table 276 for the SET TIMESTAMP command.

SERVICE ACTION field

The SERVICE ACTION field is defined in 2.2.2 and shall be set as shown in table 276 for the SET TIMESTAMP command.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the SET TIMESTAMP parameters that shall be transferred from the application client to the device server. A parameter list length of zero indicates that no data shall be transferred, and that no change shall be made to the timestamp.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The format for the parameter data returned by the SET TIMESTAMP command is shown in table 208.

Table 208 SET TIMESTAMP parameter data format

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
...								
3								
4	TIMESTAMP							
...								
9								
10	Reserved							
11	Reserved							

TIMESTAMP field

The TIMESTAMP field specifies the value to which a device clock shall be initialized (see SPC-6). The timestamp should be the number of milliseconds that have elapsed since midnight, 1 January 1970 UT. If the most significant byte in the TIMESTAMP field is greater than F0h, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

On successful completion of a SET TIMESTAMP command the device server shall establish a unit attention condition for the initiator port associated with every I_T nexus except the I_T nexus on which the SETTIMESTAMP command was received (see SAM-6), with the additional sense code set to TIMESTAMP CHANGED.

3.53 START STOP UNIT command

The START STOP UNIT command (see table 209) requests that the device server change the power condition of the logical unit (see SBC-5) or load or eject the medium. This includes specifying that the device server enable or disable the direct-access block device for medium access operations by controlling power conditions and timers.

If a START STOP UNIT command is being processed by the device server, and a subsequent START STOP UNIT command for which the CDB is validated requests that the logical unit change to a different power condition than was specified by the START STOP UNIT command being processed, then the device server shall terminate the subsequent START STOP UNIT command with CHECK CONDITION status with the sense key set to NOT READY and the additional sense code set to LOGICAL UNIT NOT READY, START STOP UNIT COMMAND IN PROGRESS.

Table 209 START STOP UNIT command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (1Bh)							
1	Reserved							IMMED
2	Reserved							
3	Reserved				POWER CONDITION MODIFIER			
4	POWER CONDITION				Reserved	NO_FLUSH	LOEJ	START
5	CONTROL							

IMMED (Immediate) bit

- 0** If the immediate (IMMED) bit is set to zero, then the device server shall return status after the operation is completed.
- 1** If the IMMED bit set to one, then the device server shall return status as soon as the CDB has been validated.

POWER CONDITION field and POWER CONDITION MODIFIER field

The combinations of values in the POWER CONDITION field and POWER CONDITION MODIFIER field are defined in table 210. If the POWER CONDITION field is supported and is set to a value other than 0h, then the START and LOEJ bits shall be ignored.

Table 210 POWER CONDITION field and POWER CONDITION MODIFIER field

POWER CONDITION	POWER CONDITION Name	POWER CONDITION MODIFIER value	Description
0h	START_VALID	0h	Process the START and LOEJ bits.
1h	ACTIVE	0h	Cause the logical unit to transition to the active power condition (see SPC-6).
2h	IDLE	0h	Cause the logical unit to transition to the idle_a power condition (see SPC-6).
		1h	Cause the logical unit to transition to the idle_b power condition (see SPC-6).
			Cause the logical unit to transition to the idle_c power condition (see SPC-6).
3h	STANDBY	0h	Cause the logical unit to transition to the standby_z power condition (see SPC-6).
		1h	Cause the logical unit to transition to the standby_y power condition (see SPC-6).
5h	Obsolete	0h to Fh	Obsolete
7h	LU_CONTROL	0h	Initialize and start all of the idle condition timers that are enabled (see SPC-6), and initialize and start all of the standby condition timers that are enabled (see SPC-6).

Table 210 POWER CONDITION field and POWER CONDITION MODIFIER field

POWER CONDITION	POWER CONDITION Name	POWER CONDITION MODIFIER value	Description
Ah	FORCE_IDLE_0	0h	Force the idle_a condition timer to be set to zero (see SPC-6).
		1h	Force the idle_b condition timer to be set to zero (see SPC-6).
		2h	Force the idle_c condition timer to be set to zero (see SPC-6).
Bh	FORCE_STANDBY_0	0h	Force the standby_z condition timer to be set to zero (see SPC-6).
		1h	Force the standby_y condition timer to be set to zero (see SPC-6).
All other combinations			Reserved

If the START STOP UNIT command specifies a power condition that conflicts with an operation in progress (e.g., a background self test), then, after the START STOP UNIT command completes with GOOD status, the logical unit may not be in the power condition that was requested by the command.

It is not an error to specify that the logical unit transition to its current power condition.

NO_FLUSH bit

- 0** If the NO_FLUSH bit is set to zero, then logical units that contain cache shall write all cached logical blocks to the medium (e.g., as they would do in response to a SYNCHRONIZE CACHE command (see 3.55 and 3.56) with the SYNC_NV bit set to zero, the LOGICAL BLOCK ADDRESS field set to zero, and the NUMBER OF LOGICAL BLOCKS field set to zero) prior to entering into any power condition that prevents accessing the medium (e.g., before the rotating media spindle motor is stopped during transition to the stopped power condition).
- 1** If the NO_FLUSH bit is set to one, then cached logical blocks should not be written to the medium by the logical unit prior to entering into any power condition that prevents accessing the medium.

LOEJ (load eject) bit

- 0** If the load eject (LOEJ) bit is set to zero, then the logical unit shall take no action regarding loading or ejecting the medium.
- 1** If the LOEJ bit is set to one, then the logical unit shall unload the medium if the START bit is set to zero. If the LOEJ bit is set to one, then the logical unit shall load the medium if the START bit is set to one. If the POWER CONDITION field is supported and is set to a value other than 0h, then the device server shall ignore the LOEJ bit.

START bit

- 0** If the START bit is set to zero, then the device server shall:
 - a) cause the logical unit to transition to the stopped power condition;
 - b) stop any idle condition timer that is enabled (see SPC-6); and
 - c) stop any standby condition timer that is enabled (see SPC-6).
- 1** If the START bit set to one, then the device server shall:
 1. comply with requirements defined in SCSI transport protocol standards (e.g., the NOTIFY (ENABLE SPINUP) requirement (see SPL-5);
 2. cause the logical unit to transition to the active power condition;
 3. initialize and start any idle condition timer that is enabled; and
 4. initialize and start any standby condition timer that is enabled.

If the POWER CONDITION field is supported and is set to a value other than 0h, then the device server shall ignore the START bit.

3.54 STREAM CONTROL command

3.54.1 STREAM CONTROL command overview

The STREAM CONTROL command (see table 211) requests the device server to open a stream and return the stream identifier in the return parameter data or close the stream specified in the STR_ID field in the CDB.

This command uses the SERVICE ACTION IN (16) CDB format (see SBC-5 - Annex A.2).

Table 211 STREAM CONTROL command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Eh)							
1	Reserved	STR_CTL		SERVICE ACTION (14h)				
2	Reserved							
3	Reserved							
4	(MSB)	STR_ID						(LSB)
5	Reserved							
6	Reserved							
...	Reserved							
14	Reserved							
15	CONTROL							

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in Table 211.

SERVICE ACTION field

The SERVICE ACTION field is defined in 2.2.2 and shall be set to the value in table 211.

STR_CTL and STR_ID fields

The stream control (STR_CTL) field specifies the operation to be performed as described in table 212.

Table 212 STR_CTL field

Code	Description
01b	Open a stream and return the stream identifier in the ASSIGNED_STR_ID field in the returned parameter data.
10b	Close the stream associated with the STR_ID field.
All others	Reserved

If the STR_CTL field is set to 10b, then the stream identifier (STR_ID) field specifies the stream identifier associated with the requested operation. If the STR_CTL field is not set to 10b, then the device server shall ignore the STR_ID field.

3.54.2 STREAM CONTROL parameter data

The STREAM CONTROL parameter data is defined in table 213.

Table 213 STREAM CONTROL parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	PARAMETER LENGTH (07h)							
1	Reserved							
...								
3								
4	ASSIGNED_STR_ID							
5	Reserved							
6								
7								

PARAMETER LENGTH field

The PARAMETER LENGTH field indicates the length of the parameter data and shall be set as shown in table104 for the STREAM CONTROL parameter data.

ASSIGNED_STR_ID field

If the STR_CTL field was set to 01b (i.e., close) in the STREAM CONTROL command, then the device server shall set the ASSIGNED_STR_ID field to a value that is not currently assigned to an open stream by the device server and open that stream. If the STR_CTL field was not set to 01b in the STREAM CONTROL command, then the ASSIGNED_STR_ID field is reserved.

3.55 SYNCHRONIZE CACHE (10) command

The SYNCHRONIZE CACHE (10) command (see table 214) requests that the device server ensure that the specified logical blocks have their most recent data values recorded in non-volatile cache and/or on the medium. Logical blocks include user data and, if the medium is formatted with protection information enabled, protection information. Logical blocks may or may not be removed from volatile cache and non-volatile cache as a result of the synchronize cache operation.

Table 214 SYNCHRONIZE CACHE (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (35h)							
1	Reserved				Obsolete		IMMED	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	(MSB)							
8	NUMBER OF BLOCKS							
9	(LSB)							
9	CONTROL							

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 214.

IMMED (Immediate) bit

- 0** An immediate (IMMED) bit set to zero specifies that the device server shall not return status until the synchronize cache operation has been completed.
- 1** An IMMED bit set to one specifies that the device server shall return status as soon as the CDB has been validated. If the IMMED bit is set to one and the device server does not support the IMMED bit, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

If the IMMED bit is set to one and the synchronize cache operation has not completed, then the SYNC_PROG field in the Caching mode page (see 5.3.9) defines device server behavior (see table 215).

Table 215 SYNC_PROG field description

Code	Description
00b	The device server shall not terminate commands due to the synchronize cache operation and shall not provide pollable sense data.
01b	The device server: a) shall not terminate commands due to the synchronize cache operation; and b) shall provide pollable sense data with the sense key set to NO SENSE, the additional sense code set to SYNCHRONIZE CACHE OPERATION IN PROGRESS, and the PROGRESS INDICATION field set to indicate the progress of the synchronize cache operation.
10b	The device server: a) shall process INQUIRY commands, REPORT LUNS commands, REPORT TARGET PORT GROUPS commands, and REQUEST SENSE commands; b) may process commands that do not require resources used for the synchronize cache operation; c) shall terminate commands that require resources used for the synchronize cache operation with CHECK CONDITION status with the sense key set to NOT READY, the additional sense code set to LOGICAL UNIT NOT READY, SYNCHRONIZE CACHE OPERATION IN PROGRESS, and the PROGRESS INDICATION field set to indicate the progress of the synchronize cache operation; and d) shall provide pollable sense data with the sense key set to NOT READY, the additional sense code set to LOGICAL UNIT NOT READY, SYNCHRONIZE CACHE OPERATION IN PROGRESS, and the PROGRESS INDICATION field set to indicate the progress of the synchronize cache operation.
11b	Reserved

LOGICAL BLOCK ADDRESS field

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

GROUP NUMBER field

The GROUP NUMBER field specifies the group into which attributes associated with the command should be collected. A GROUP NUMBER field set to zero specifies that any attributes associated with the command shall not be collected into any group.

NUMBER OF BLOCKS field

The NUMBER OF BLOCKS field specifies the number of logical blocks that shall be synchronized, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A NUMBER OF BLOCKS field set to zero specifies that all logical blocks starting with the one specified in the LOGICAL BLOCK ADDRESS field to the last logical block on the medium shall be synchronized. If the logical block address plus the number of blocks exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

A logical block within the range that is not in cache is not considered an error.

3.56 SYNCHRONIZE CACHE (16) command

The SYNCHRONIZE CACHE (16) command (see table 216) requests that the device server ensure that the specified logical blocks have their most recent data values recorded in non-volatile cache and/or on the medium. Logical blocks include user data and, if the medium is formatted with protection information enabled, protection information. Logical blocks may or may not be removed from volatile cache and non-volatile cache as a result of the synchronize cache operation.

Table 216 SYNCHRONIZE CACHE (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (91h)							
1	Reserved				Obsolete		IMMED	Reserved
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	NUMBER OF BLOCKS							
13	(LSB)							
14	Reserved			GROUP NUMBER				
15	CONTROL							

See the SYNCHRONIZE CACHE (10) command (see 3.55) for the definitions of the fields in this command.

3.57 TEST UNIT READY command

The TEST UNIT READY command (see table 217) provides a means to check if the logical unit is ready. This is not a request for a self-test. If the logical unit is able to accept an appropriate medium-access command without returning CHECK CONDITION status, this command shall return a GOOD status. If the logical unit is unable to become operational or is in a state such that an application client action (e.g., START UNIT command) is required to make the logical unit ready, the command shall be terminated with CHECK CONDITION status, with the sense key set to NOT READY.

Table 217 TEST UNIT READY command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (00h)							
1	Reserved							
...								
4								
5	CONTROL							

Table 218 defines the suggested GOOD and CHECK CONDITION status responses to the TEST UNIT READY command. Other conditions, including deferred errors, may result in other responses (e.g., BUSY or RESERVATION CONFLICT status).

Table 218 Preferred TEST UNIT READY responses

Status	Sense Key	Additional Sense Code
GOOD	not applicable	not applicable
CHECK CONDITION	ILLEGAL REQUEST	LOGICAL UNIT NOT SUPPORTED
CHECK CONDITION	NOT READY	LOGICAL UNIT DOES NOT RESPOND TO SELECTION
CHECK CONDITION	NOT READY	MEDIUM NOT PRESENT
CHECK CONDITION	NOT READY	LOGICAL UNIT NOT READY, CAUSE NOT REPORTABLE
CHECK CONDITION	NOT READY	LOGICAL UNIT IS IN PROCESS OF BECOMING READY
CHECK CONDITION	NOT READY	LOGICAL UNIT NOT READY, INITIALIZING COMMAND REQUIRED
CHECK CONDITION	NOT READY	LOGICAL UNIT NOT READY, MANUAL INTERVENTION REQUIRED
CHECK CONDITION	NOT READY	LOGICAL UNIT NOT READY, FORMAT IN PROGRESS

3.58 UNMAP command

3.58.1 UNMAP command overview

The UNMAP command (see table 219) requests that the device server cause one or more LBAs to be unmapped. The UNMAP command is one of the possible commands that shall be implemented by device servers supporting thin provisioning (see SBC-5).

Table 219 UNMAP command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (42h)							
1	Reserved							ANCHOR
2	Reserved							
...								
5								
6	Reserved	GROUP NUMBER						
7	(MSB)	PARAMETER LIST LENGTH						(LSB)
8	PARAMETER LIST LENGTH							
9								

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 219.

ANCHOR bit

For a thin provisioned logical unit (see SBC-5):

- 0** an ANCHOR bit set to zero specifies that any LBA on which an unmap operation is performed shall become deallocated.
- 1** an ANCHOR bit set to one specifies that any LBA on which an unmap operation is performed shall become anchored.

For a resource provisioned logical unit (see SBC-5), any LBA on which an unmap operation is performed shall become anchored (i.e., the command is processed as if the ANCHOR bit is set to one). If the ANCHOR bit is set to one, and the ANC_SUP bit in the Logical Block Provisioning VPD page (see 5.4.13) is set to zero, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

GROUP NUMBER field

The GROUP NUMBER field specifies the group into which attributes associated with the command should be collected. A GROUP NUMBER field set to zero specifies that any attributes associated with the command shall not be collected into any group.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field specifies the length in bytes of the UNMAP parameter data that shall be sent from the application client to the device server. A PARAMETER LIST LENGTH set to zero specifies that no data shall be sent.

CONTROL byte

The CONTROL byte is described in 2.2.7.

3.58.2 UNMAP parameter list

The UNMAP parameter list (see table 220) contains the data sent by an application client along with an UNMAP command. Included in the data are an UNMAP parameter list header and block descriptors for LBA extents to be processed by the device server for the UNMAP command. The LBAs specified in the block descriptors may contain overlapping extents, and may be in any order.

For each specified LBA:

- a) a mapped LBA should be unmapped (see SBC-5), or may remain mapped; and
- b) an unmapped LBA shall remain unmapped.

Table 220 UNMAP parameter list

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	UNMAP DATA LENGTH (n-1)						(LSB)
1								
2	(MSB)	UNMAP BLOCK DESCRIPTOR DATA LENGTH (n-7)						(LSB)
3								
4								
...		Reserved						
7								
UNMAP block descriptors								
8		UNMAP block descriptor [first] (see table 221)						
...								
23								
...								
n-15		UNMAP block descriptor [last] (see table 221)						
...								
n								

UNMAP DATA LENGTH field

The UNMAP DATA LENGTH field specifies the length in bytes of the following data that is available to be transferred from the data-out buffer. The UNMAP DATA LENGTH does not include the number of bytes in the UNMAP DATA LENGTH field.

UNMAP BLOCK DESCRIPTOR DATA LENGTH field

The UNMAP BLOCK DESCRIPTOR DATA LENGTH field specifies the length in bytes of the UNMAP block descriptor data that is available to be transferred from the data-out buffer. The UNMAP BLOCK DESCRIPTOR DATA LENGTH should be a multiple of 16. If the UNMAP BLOCK DESCRIPTOR DATA LENGTH is not a multiple of 16, then the last UNMAP block descriptor is incomplete and shall be ignored. If the UNMAP BLOCK DESCRIPTOR DATA LENGTH is set to zero, then no UNMAP block descriptors are included in the UNMAP parameter data. This condition shall not be considered an error.

Table 221 defines an UNMAP block descriptor.

Table 221 UNMAP block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
.....	UNMAP LOGICAL BLOCK ADDRESS							
7	(LSB)							
8	(MSB)							
....	NUMBER OF LOGICAL BLOCKS							
11	(LSB)							
12	Reserved							
.....								
15								

UNMAP LOGICAL BLOCK ADDRESS

The UNMAP LOGICAL BLOCK ADDRESS field contains the first LBA of the UNMAP block descriptor to be unmapped.

NUMBER OF LOGICAL BLOCKS field

The NUMBER OF LOGICAL BLOCKS field contains the number of LBAs to be unmapped beginning with the LBA specified by the UNMAP LOGICAL BLOCK ADDRESS field.

If the NUMBER OF LOGICAL BLOCKS is set to zero, then no LBAs shall be unmapped for this UNMAP block descriptor. This condition shall not be considered an error.

If the LBA specified by the UNMAP LOGICAL BLOCK ADDRESS field plus the number of logical blocks exceeds the capacity of the medium, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

If the total number of logical blocks specified in the UNMAP block descriptor data exceeds the value indicated in the MAXIMUM UNMAP LBA COUNT field in the Block Limits VPD page (see 5.4.5), or if the number of UNMAP block descriptors exceeds the value of the MAXIMUM UNMAP PARAMETER COUNT field in the Block Limits VPD page, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

3.59 VERIFY (10) command

The VERIFY (10) command (see table 222) requests that the device server verify the specified logical block(s) on the medium. Each logical block includes user data and may include protection information, based on the VRPROTECT field and the medium format.

Table 222 VERIFY (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Fh)							
1	VRPROTECT			DPO	Reserved	BYTCHK		Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	RESTRICTED FOR MMC-5	Reserved		GROUP NUMBER				
7	(MSB)							
8	VERIFICATION LENGTH							
8	(LSB)							
9	CONTROL							

Logical units that contain cache shall write referenced cached logical blocks to the medium for the logical unit (e.g., as they would do in response to a SYNCHRONIZE CACHE command (see 3.55 and 3.56) with the SYNC_NV bit set to zero, the LOGICAL BLOCK ADDRESS field set to the value of the VERIFY command's LOGICAL BLOCK ADDRESS field, and the NUMBER OF BLOCKS field set to the value of the VERIFY command's VERIFICATION LENGTH field).

See the READ (10) command (see 3.18) for the definition of the DPO bit. See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

GROUP NUMBER field

The GROUP NUMBER field specifies the group into which attributes associated with the command should be collected. A GROUP NUMBER field set to zero specifies that any attributes associated with the command shall not be collected into any group.

If the Verify Error Recovery mode page (see 5.3.34) is implemented, then the current settings in that page specify the verification criteria. If the Verify Error Recovery mode page is not implemented, then the verification criteria is vendor-specific.

BYTCHK field

If the byte check (BYTCHK) field is set to 00b, then:

- a) no Data-Out Buffer transfer shall occur;
- b) for any mapped LBA specified by the command, the device server shall check the protection information from the verify operation based on the VRPROTECT field as defined in table 223; and
- c) for any unmapped LBA specified by the command, the verify operation shall complete without error.

If:

- a) the BYTCHK field is set to 01b or 11b;
- b) the VBULS bit is set to zero in the Block Device Characteristics VPD page (see 5.4.3); and
- c) any LBA specified by the command is unmapped (i.e., deallocated or anchored),

then the device server shall terminate the command with CHECK CONDITION status with the sense key set to MISCOMPARE and the additional sense code set to MISCOMPARE VERIFY OF UNMAPPED LBA.

If:

- a) the BYTCHK field is set to 01b or 11b; and
- b) either:
 - A) the VBULS bit is set to one in the Block Device Characteristics VPD page; or
 - B) all LBAs specified by the command are mapped,

then:

- a) if the BYTCHK field is set to 01b, then the Data-Out Buffer transfer shall include the number of logical blocks specified by the VERIFICATION LENGTH field;
- b) if the BYTCHK field is set to 11b, then:
 - A) the Data-Out Buffer transfer shall include one logical block; and
 - B) the device server shall:
 - 1) duplicate the single logical block, as described in the WRITE SAME command (see 3.77), the number of times required to satisfy the VERIFICATION LENGTH field; and
 - 2) place the duplicated data in the Data-Out Buffer;
- c) the device server shall check the protection information transferred from the Data-Out Buffer based on the VRPROTECT field as defined in table 225;
- d) for any mapped LBA specified by the command, the device server shall perform the verify operation and check the protection information from the verify operation based on the VRPROTECT field as defined in table 224;

and

- e) the device server shall perform:
 - A) a compare operation of:
 - a) user data from the verify operations; and
 - b) user data from the Data-Out Buffer;

and

- B) a compare operation based on the VRPROTECT field as defined in table 226 of:
 - a) protection information from the verify operations; and
 - b) protection information from the Data-Out Buffer.

The order of the user data and protection information checks and comparisons is vendor-specific.

If a byte-by-byte comparison is unsuccessful for any reason, the device server shall terminate the command with CHECK CONDITION status with the sense key set to MISCOMPARE and the additional sense code set to the appropriate value for the condition.

VERIFICATION LENGTH field

The VERIFICATION LENGTH field specifies the number of contiguous logical blocks that shall be verified, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. If the BYTCHK field is set to one, the VERIFICATION LENGTH field also specifies the number of logical blocks that the device server shall transfer from the data-out buffer. A VERIFICATION LENGTH field set to zero specifies that no logical blocks shall be verified. This condition shall not be considered as an error. Any other value specifies the number of logical blocks that shall be verified. If the logical block address plus the verification length exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE. The VERIFICATION LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page.

If the BYTCHK field is set to 00b, then the device server shall check the protection information read from the medium based on the VRPROTECT field as described in table 223.

Table 223 VRPROTECT field with BYTCHK field set to 00b - medium (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Field in protection information [g]	Extended INQUIRY Data VPD page bit value [f]	If check fails [d] [e], additional sense code
000b	Yes [i]	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [h]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
No	No protection information on the medium to check. Only user data is checked.			
001b 101b [b]	Yes	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [h]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
No	Error condition [a]			
010b [b]	Yes	LOGICAL BLOCK GUARD	No check performed	
		LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [h]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
		No	Error condition [a]	
011b [b]	Yes	LOGICAL BLOCK GUARD	No check performed	
		LOGICAL BLOCK APPLICATION TAG	No check performed	
		LOGICAL BLOCK REFERENCE TAG	No check performed	
	No	Error condition [a]		

Table 223 VRPROTECT field with BYTCHK field set to 00b - medium (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Field in protection information [g]	Extended INQUIRY Data VPD page bit value [f]	If check fails [d] [e], additional sense code
100b [b]	Yes	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		LOGICAL BLOCK APPLICATION TAG		No check performed
		LOGICAL BLOCK REFERENCE TAG		No check performed
	No	Error condition [a]		
101b - 111b	Reserved			

[a] A verify operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[b] If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[c] If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field, then the device server shall check each logical block application tag. If the ATO bit in the Control mode page (see 5.3.14) is set to one, then this knowledge is acquired from:

- the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a VERIFY (32) command (see 3.62) is received by the device server;
- the Application Tag mode page (see 5.3.6), if a command other than VERIFY (32) is received by the device server, and the ATMPE bit in the Control mode page (see 5.3.14) is set to one; or
- a method not defined by this standard, if a command other than VERIFY (32) is received by the device server, and the ATMPE bit is set to zero.

[d] If an error is reported, the sense key shall be set to ABORTED COMMAND.

[e] If multiple errors occur, the selection of which error to report is not defined by this manual.

[f] See the Extended INQUIRY Data VPD page (see 5.4.10) for the definitions of the GRD_CHK bit, the APP_CHK bit, and the REF_CHK bits.

[g] If the application client or device server detects a:

- LOGICAL BLOCK APPLICATION TAG field set to FFFFh and type 1 protection (see SBC-5) or type 2 protection (see SBC-5) is enabled; or
- LOGICAL BLOCK APPLICATION TAG field set to FFFFh, LOGICAL BLOCK REFERENCE TAG field set to FFFF FFFFh, and type 3 protection (see SBC-5) is enabled, then the device server shall not check any protection information in the associated logical block.

[h] If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block. If type 2 protection or type 3 protection is enabled, the device server checks the logical block reference tag if it has knowledge of the contents of the LOGICAL BLOCK REFERENCE TAG field. If type 2 protection is enabled, then this knowledge may be acquired through the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field in a VERIFY (32) command (see 3.62). If type 3 protection is enabled, then the method for acquiring this knowledge is not defined by this manual.

[i] If the DPICZ bit in the Control mode page (see 5.3.14) is set to one, then protection information shall not be checked.

If the BYTCHK field is set to 01b or 11b, then the device server shall check the protection information read from the medium based on the VRPROTECT field as described in table 224.

Table 224 VRPROTECT field with BYTCHK field set to 01b or 11b - medium (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Field in protection information [g]	Extended INQUIRY Data VPD page bit value [f]	If check fails [d] [e], additional sense code
000b	Yes [i]	LOGICAL BLOCK GUARD	GRD_CHK = 1	LOGICAL BLOCK GUARD CHECK FAILED
			GRD_CHK = 0	No check performed
		LOGICAL BLOCK APPLICATION TAG	APP_CHK = 1 [c] [g]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
			APP_CHK = 0	No check performed
		LOGICAL BLOCK REFERENCE TAG	REF_CHK = 1 [h]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
			REF_CHK = 0	No check performed
No	No protection information on the medium available to check			
001b 010b 011b 100b 101b [b]	Yes	LOGICAL BLOCK GUARD	No check performed	
		LOGICAL BLOCK APPLICATION TAG	No check performed	
		LOGICAL BLOCK REFERENCE TAG	No check performed	
	No	Error condition [a]		

Table 224 VRPROTECT field with BYTCHK field set to 01b or 11b - medium (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Field in protection information [g]	Extended INQUIRY Data VPD page bit value [f]	If check fails [d] [e], additional sense code
110b - 111b	Reserved			
<p>[a] A verify operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.</p> <p>[b] If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.</p> <p>[c] If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field, then the device server shall check each logical block application tag. If the ATO bit in the Control mode page (see 5.3.14) is set to one, then this knowledge is acquired from:</p> <ul style="list-style-type: none"> a) the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a VERIFY (32) command (see 3.62) is received by the device server; b) the Application Tag mode page (see 5.3.6) if a command other than VERIFY (32) is received by the device server, and the ATMPE bit in the Control mode page (see 5.3.14) is set to one; or c) a method not defined by this standard, if a command other than VERIFY (32) is received by the device server, and the ATMPE bit is set to zero. <p>[d] If an error is reported, the sense key shall be set to ABORTED COMMAND.</p> <p>[e] If multiple errors occur, the selection of which error to report is not defined by this manual.</p> <p>[f] See the Extended INQUIRY Data VPD page (see 5.4.10) for the definitions of the GRD_CHK bit, the APP_CHK bit, and the REF_CHK bit.</p> <p>[g] If the application client or device server detects a:</p> <ul style="list-style-type: none"> a) logical block application tag field set to FFFFh and type 1 protection or type 2 protection is enabled; or b) logical block application tag field set to FFFFh, logical block reference tag field set to FFFF FFFFh, and type 3 protection is enabled, then the device server shall not check any protection information in the associated logical block. <p>[h] If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block. If type 2 protection or type 3 protection is enabled, the device server checks the logical block reference tag if it has knowledge of the contents of the logical block reference tag field. If type 2 protection is enabled, then this knowledge may be acquired through the expected initial logical block reference tag field in a VERIFY (32) command (see 3.62). If type 3 protection is enabled, then the method for acquiring this knowledge is not defined by this manual.</p> <p>[i] If the DPICZ bit in the Control mode page (see 5.3.14) is set to one, then protection information shall not be checked.</p>				

If the BYTCHK field is set to 01b or 11b, then the device server shall check the protection information transferred from the data-out buffer based on the VRPROTECT field as described in table 225.

Table 225 VRPROTECT field with BYTCHK field set to one 01b or 11b - data-out buffer (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Field in protection information	Device server check	If check fails ^[d] ^[e] , additional sense code
000b	Yes	No protection information received from application client to check		
	No	No protection information received from application client to check		
001b [b]	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	May [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	Shall [f]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No	Error condition [a]		
010b [b]	Yes	LOGICAL BLOCK GUARD	Shall not	No check performed
		LOGICAL BLOCK APPLICATION TAG	May [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	May [f]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No	Error condition [a]		
011b [b]	Yes	LOGICAL BLOCK GUARD	Shall not	No check performed
		LOGICAL BLOCK APPLICATION TAG	Shall not	No check performed
		LOGICAL BLOCK REFERENCE TAG	Shall not	No check performed
	No	Error condition [a]		
100b [b]	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	Shall not	No check performed
		LOGICAL BLOCK REFERENCE TAG	Shall not	No check performed
	No	Error condition [a]		

Table 225 VRPROTECT field with BYTCHK field set to one 01b or 11b - data-out buffer (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Field in protection information	Device server check	If check fails ^[d] ^[e] , additional sense code
101b ^[b]	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	May ^[c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	May ^[f]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No	Error condition ^[a]		
110b - 111b	Reserved			

[a] A verify operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[b] If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[c] If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field, then the device server shall check each logical block application tag. If the ATO bit in the Control mode page (see 5.3.14) is set to one, then this knowledge is acquired from:

- the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a VERIFY (32) command (see 3.62) is received by the device server;
- the Application Tag mode page (see 5.3.6), if a command other than VERIFY (32) is received by the device server, and the ATMPE bit in the Control mode page (see 5.3.14) is set to one; or
- a method not defined by this standard, if a command other than VERIFY (32) is received by the device server, and the ATMPE bit is set to zero.

[d] If an error is reported, the sense key shall be set to ABORTED COMMAND.

[e] If multiple errors occur, the selection of which error to report is not defined by this manual.

[f] If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block. If type 2 protection or type 3 protection is enabled, the device server checks the logical block reference tag if it has knowledge of the contents of the logical block reference tag field. If type 2 protection is enabled, then this knowledge may be acquired through the expected initial logical block reference tag field in a VERIFY (32) command (see 3.62). If type 3 protection is enabled, then the method for acquiring this knowledge is not defined by this manual.

If the BYTCHK field is set to 01b or 11b, then the device server shall perform a byte-by-byte comparison of protection information transferred from the data-out buffer with protection information read from the medium based on the VRPROTECT field as described in table 226.

Table 226 VRPROTECT field with BYTCHK field set to 01b or 11b - byte-by-byte comparison requirements (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Field	Byte-by-byte Comparison	If compare fails [c] [d], additional sense code
000b	Yes	No protection information received from application client to compare. Only user data is compared within each logical block.		
	No	No protection information or the medium or received from application client to compare. Only user data is compared within each logical block.		
001b [b]	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 1) [e]	Shall	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 0) [f]	Shall not	No compare performed
		LOGICAL BLOCK REFERENCE TAG	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 0)	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 1)	Shall not	No compare performed
	No	Error condition [a]		
010b [b]	Yes	LOGICAL BLOCK GUARD	Shall not	No compare performed
		LOGICAL BLOCK APPLICATION TAG (ATO = 1) [e]	Shall	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 0) [f]	Shall not	No compare performed
		LOGICAL BLOCK REFERENCE TAG (not type 3)	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 0)	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 1)	Shall not	No compare performed
	No	Error condition [a]		

Table 226 VRPROTECT field with BYTCHK field set to 01b or 11b - byte-by-byte comparison requirements (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Field	Byte-by-byte Comparison	If compare fails [c] [d], additional sense code
010b [b] 100b	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 1) [e]	Shall	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 0) [f]	Shall not	No compare performed
		LOGICAL BLOCK REFERENCE TAG (not type 3)	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 0)	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG (type 3 and ATO = 1)	Shall not	No compare performed
	No	Error condition [a]		
101b [b]	Yes	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 1) [e]	Shall	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG (ATO = 0) [f]	Shall not	No compare performed
		LOGICAL BLOCK REFERENCE TAG	Shall	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No	Error condition [a]		
110b - 111b	Reserved			
<p>[a] A verify operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.</p> <p>[b] If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.</p> <p>[c] If an error is reported, the sense key shall be set to MISCOMPARE.</p> <p>[d] If multiple errors occur, the selection of which error to report is not defined by this manual.</p> <p>[e] If the ATO bit is set to one in the Control mode page (see 5.3.14), the logical block application tag shall not be modified by a device server.</p> <p>[f] If the ATO bit is set to zero in the Control mode page (see 5.3.14), the logical block application tag may be modified by a device server.</p>				

3.60 VERIFY (12) command

The VERIFY (12) command (see table 227) requests that the device server verify the specified logical block(s) on the medium. Each logical block includes user data and may include protection information, based on the VRPROTECT field and the medium format.

Table 227 VERIFY (12) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (AFh)							
1	VRPROTECT			DPO	Reserved	BYCHK		Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	(MSB)							
...	VERIFICATION LENGTH							
9	(LSB)							
10	Restricted For MMC-5	Reserved		GROUP NUMBER				
11	CONTROL							

See the VERIFY (10) command (see 3.59) for the definitions of the fields in this command.

3.61 VERIFY (16) command

The VERIFY (16) command (see table 228) requests that the device server verify the specified logical block(s) on the medium. Each logical block includes user data and may include protection information, based on the VRPROTECT field and the medium format.

Table 228 VERIFY (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Fh)							
1	VRPROTECT			DPO	Reserved	BYTCHK		Reserved
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	VERIFICATION LENGTH							
13	(LSB)							
14	Restricted for MMC-5	Reserved		GROUP NUMBER				
15	CONTROL							

See the VERIFY (10) command (see 3.59) for the definitions of the fields in this command.

3.62 VERIFY (32) command

The VERIFY (32) command (see table 229) requests that the device server verify the specified logical block(s) on the medium. Each logical block includes user data and may include protection information, based on the VRPROTECT field and the medium format.

The VERIFY (32) command shall only be processed if type 2 protection is enabled (see SPC-6).

Table 229 VERIFY (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
...								
5								
6	Reserved			GROUP NUMBER				
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (000Ah)						
9	(LSB)							
10	VRPROTECT			DPO	Reserved	BYTCHK		Reserved
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						
...								
19	(LSB)							
20	(MSB)	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG						
...								
23	(LSB)							
24	(MSB)	EXPECTED LOGICAL BLOCK APPLICATION TAG						
25	(LSB)							
26	(MSB)	LOGICAL BLOCK APPLICATION TAG MASK						
27	(LSB)							
28	(MSB)	VERIFICATION LENGTH						
...								
31	(LSB)							

See the VERIFY (10) command (see 3.59) for the definitions of the GROUP NUMBER field, VRPROTECT field, DPO bit, BYTCHK field, LOGICAL BLOCK ADDRESS field, and VERIFICATION LENGTH field.

When checking of the LOGICAL BLOCK REFERENCE TAG field is enabled (see table 223, table 224, table 225, and table 226 in 3.59), the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field contains the value of the LOGICAL BLOCK REFERENCE TAG field expected in the protection information of the first logical block accessed by the command instead of a value based on the LBA.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is enabled (see table 223, table 224, table 225, and table 226 in 3.59), the LOGICAL BLOCK APPLICATION TAG MASK field contains a value that is a bit mask for enabling the checking of the LOGICAL BLOCK APPLICATION TAG field in the protection information for each logical block accessed by the command. A LOGICAL BLOCK APPLICATION TAG MASK bit set to one enables the checking of the corresponding bit of the EXPECTED LOGICAL BLOCK APPLICATION TAG field with the corresponding bit of the LOGICAL BLOCK APPLICATION TAG field in the protection information.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see table 223, table 224, table 225, and table 226 in 3.59), or if the ATO bit is set to zero, the LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored.

The LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored if:

- a) the ATO bit is set to zero; or
- b) the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see table 223, table 224, table 225, and table 226 in 3.59).

3.63 WRITE (6) command

This command has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The WRITE (6) command (see table 230) requests that the device server transfer the specified logical block(s) from the data-out buffer and write them. Each logical block transferred includes user data but does not include protection information. Each logical block written includes user data and, if the medium is formatted with protection information enabled, protection information.

Table 230 WRITE (6) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (0Ah)							
1	Reserved			(MSB)				
2	LOGICAL BLOCK ADDRESS							
3								
4	TRANSFER LENGTH							
5	CONTROL							

The cache control bits are not provided for this command. Direct-access block devices with cache may have values for the cache control bits that may affect the WRITE (6) command, however no default value is defined by this manual. If explicit control is required, the WRITE (10) command should be used.

LOGICAL BLOCK ADDRESS field

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

TRANSFER LENGTH field

The TRANSFER LENGTH field specifies the number of contiguous logical blocks of data that shall be transferred from the data-out buffer and written, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A TRANSFER LENGTH field set to zero specifies that 256 logical blocks shall be written. Any other value specifies the number of logical blocks that shall be written. If the logical block address plus the transfer length exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page.

If a WRITE (6) command is received after protection information is enabled the device server shall set the protection information as follows as it writes each logical block to the medium:

- a) the LOGICAL BLOCK GUARD field set to a properly generated CRC (see SPC-6);
- b) the LOGICAL BLOCK REFERENCE TAG field set to:
 - A) the least significant four bytes of the LBA, if type 1 protection (see SPC-6) is enabled; or
 - B) FFFFFFFFh, if type 2 protection or type 3 protection is enabled

and

- a) the LOGICAL BLOCK APPLICATION TAG field set to:
 - C) FFFFh, if the ATO bit is set to one in the Control mode page (see 5.3.14); or
 - D) any value, if the ATO bit is set to zero in the Control mode page (see 5.3.14).

3.64 WRITE (10) command

The WRITE (10) command (see table 231) requests that the device server transfer the specified logical block(s) from the data-out buffer and write them. Each logical block transferred includes user data and may include protection information, based on the WRPROTECT field and the medium format. Each logical block written includes user data and, if the medium is formatted with protection information enabled, protection information.

Table 231 WRITE (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Ah)							
1	WRPROTECT			DPO	FUA	Reserved	Obsolete	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	(MSB)							
8	TRANSFER LENGTH							
8	(LSB)							
9	CONTROL							

See the READ (10) command (see 3.18) for the definition of the DPO bit. See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field. See 2.2.8 and SPC-6 for the definition of the GROUP NUMBER field.

The device server shall check the protection information transferred from the data-out buffer based on the WRPROTECT field as described in table 232.

Table 232 WRPROTECT field (Sheet 1 of 2)

Code	Logical unit formatted with protection information	Field in protection information [k]	Device server check	If check fails [d] [i], additional sense code
000b	Yes [f] [g] [h]	No protection information received from application client to check		
	No	No protection information received from application client to check		
001b [b]	Yes [e]	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	Dependent on RWWP [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	Shall (except for type 3j)	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No [a]	No protection information available to check		
010b [b]	Yes [e]	LOGICAL BLOCK GUARD	Shall not	No check performed
		LOGICAL BLOCK APPLICATION TAG	Dependent on RWWP [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	May [j]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No [a]	No protection information available to check		
011b [b]	Yes [e]	LOGICAL BLOCK GUARD	Shall not	No check performed
		LOGICAL BLOCK APPLICATION TAG	Shall not	No check performed
		LOGICAL BLOCK REFERENCE TAG	Shall not	No check performed
	No [a]	No protection information available to check		
100b [b]	Yes [e]	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	Shall not	No check performed
		LOGICAL BLOCK REFERENCE TAG	Shall not	No check performed
	No [a]	No protection information available to check		
101b [b]	Yes [e]	LOGICAL BLOCK GUARD	Shall	LOGICAL BLOCK GUARD CHECK FAILED
		LOGICAL BLOCK APPLICATION TAG	Dependent on RWWP [c]	LOGICAL BLOCK APPLICATION TAG CHECK FAILED
		LOGICAL BLOCK REFERENCE TAG	May [j]	LOGICAL BLOCK REFERENCE TAG CHECK FAILED
	No [a]	No protection information available to check		
110b - 111b	Reserved			

Table 232 WRPROTECT field (Sheet 2 of 2)

Code	Logical unit formatted with protection information	Field in protection information [k]	Device server check	If check fails [d] [i], additional sense code
[a]				A write operation to a logical unit that supports protection information and has not been formatted with protection information shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.
[b]				If the logical unit does not support protection information the requested command should be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.
[c]				If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field, and the ATO bit is set to one in the Control mode page (see 5.3.14), then the device server:
a)				may check each logical block application tag if the RWWP bit is set to zero in the Control mode page (see 5.3.14); and
b)				shall check each logical block application tag if the RWWP bit is set to one in the Control mode page.
				If the ATO bit in the Control mode page (see 5.3.14) is set to one, then this knowledge is acquired from:
a)				the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a WRITE (32), WRITE ATOMIC (32), WRITE SAME (32), or a WRITE STREAM (32) command is received by the device server;
b)				the Application Tag mode page (see 5.3.6), if a command other than WRITE (32), WRITE ATOMIC (32), WRITE SAME (32), or a WRITE STREAM (32) command is received by the device server and the ATMPE bit in the Control mode page (see 5.3.14) is set to one or
c)				a method not defined by this standard, if a command other than WRITE (32), WRITE ATOMIC (32), WRITE SAME (32), or a WRITE STREAM (32) command is received by the device server, and the ATMPE bit is set to zero.
[d]				If an error is reported, the sense key shall be set to ABORTED COMMAND.
[e]				Device server shall preserve the contents of protection information (e.g., write to medium, store in non-volatile memory).
[f]				The device server shall write a properly generated CRC into each LOGICAL BLOCK GUARD field.
[g]				If the RWWP bit in the Control mode page (see 5.3.14) is set to one, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB. If the RWWP bit is set to zero, and:
a)				type 1 protection is enabled, then the device server shall write the least significant four bytes of each LBA into the LOGICAL BLOCK REFERENCE TAG field of each of the written logical blocks; or
b)				type 2 protection or type 3 protection is enabled, then the device server shall write a value of FFFF_FFFFh into the LOGICAL BLOCK REFERENCE TAG field of each of the written logical blocks.
[h]				If the ATO bit is set to one in the Control mode page (see 5.3.14), the device server shall write FFFFh into each LOGICAL BLOCK APPLICATION TAG field. If the ATO bit is set to zero, the device server may write any value into each LOGICAL BLOCK APPLICATION TAG field.
[i]				If multiple errors occur, the selection of which error to report is not defined by this manual.
[j]				If type 1 protection is enabled, the device server checks the logical block reference tag by comparing it to the lower 4 bytes of the LBA associated with the logical block. If type 2 protection or type 3 protection is enabled, the device server checks the logical block reference tag if it has knowledge of the contents of the logical block reference tag field. If type 2 protection is enabled, then this knowledge may be acquired through the expected initial logical block reference tag field in a WRITE (32), WRITE ATOMIC (32), WRITE SAME (32), or a WRITE STREAM (32) command. If type 3 protection is enabled, then the method for acquiring this knowledge is not defined by this manual.
[k]				If the NO_PI_CHK bit is set to one in the Extended INQUIRY Data VPD page (see 5.4.10) and the device server detects:
a)				a LOGICAL BLOCK APPLICATION TAG field set to FFFFh and type 1 protection or type 2 protection is enabled; or
b)				a LOGICAL BLOCK APPLICATION TAG field set to FFFFh, LOGICAL BLOCK REFERENCE TAG field set to FFFF_FFFFh, and type 3 protection is enabled,
				then the device server shall not check any protection information in the associated protection information interval.

FUA bit

- 0** A Force unit Access (FUA) bit set to zero specifies that the device server shall write the logical blocks to volatile cache (if any), non-volatile cache (if any), or the medium.
- 1** An FUA bit set to one specifies that the device server shall write the logical blocks to non-volatile cache (if any) or the medium.

If logical blocks are transferred directly to a cache, the device server may return GOOD status prior to writing the logical blocks to the medium. Any error that occurs after the GOOD status is returned is a deferred error, and information regarding the error is not reported until a subsequent command.

TRANSFER LENGTH field

The TRANSFER LENGTH field specifies the number of contiguous logical blocks of data that shall be transferred from the data-out buffer and written, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A TRANSFER LENGTH field set to zero specifies that no logical blocks shall be written. This condition shall not be considered an error. Any other value specifies the number of logical blocks that shall be written. If the logical block address plus the transfer length exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE. The TRANSFER LENGTH field is constrained by the MAXIMUM TRANSFER LENGTH field in the Block Limits VPD page.

RWWP interaction

If the device server has knowledge of the contents of the LOGICAL BLOCK APPLICATION TAG field and the ATO bit is set to one in the Control mode page (see SPC-6), then the device server:

- a) may check each logical block application tag if the RWWP bit is set to zero in the Control mode page (see SPC-6); and
- b) shall check each logical block application tag if the RWWP bit is set to one in the Control mode page.

If the ATO bit in the Control mode page (see SPC-6) is set to one, then this knowledge is acquired from:

- a) the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in the CDB, if a WRITE(32) command (see 3.67), a WRITE ATOMIC (32) command (see 3.73), a WRITE SAME (32) command (see 3.79), or a WRITE STREAM (32) command (see 3.81) is received by the device server;
- b) the EXPECTED LOGICAL BLOCK APPLICATION TAG field and the LOGICAL BLOCK APPLICATION TAG MASK field in each LBA range descriptor, if a WRITE SCATTERED (32) command (see SBC-5), is received by the device server;
- c) the Application Tag mode page (see 5.3.6), if a command other than WRITE(32), WRITE ATOMIC (32), WRITE SAME (32), WRITE SCATTERED(32), or WRITE STREAM (32) is received by the device server and the ATMPE bit in the Control mode page (see SPC-6) is set to one; or
- d) a method not defined by this standard, if a command other than WRITE(32), WRITE ATOMIC (32), WRITE SAME (32), WRITE SCATTERED(32), or WRITE STREAM (32) is received by the device server, and the ATMPE bit is set to zero.

3.65 WRITE (12) command

The WRITE (12) command (see table 233) requests that the device server transfer the specified logical block(s) from the data-out buffer and write them. Each logical block transferred includes user data and may include protection information, based on the WRPROTECT field and the medium format. Each logical block written includes user data and, if the medium is formatted with protection information enabled, protection information.

Table 233 WRITE (12) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (AAh)							
1	WRPROTECT			DPO	FUA	Reserved	Obsolete	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	(MSB)							
...	TRANSFER LENGTH							
9	(LSB)							
10	Restricted for MMC-5	Reserved		GROUP NUMBER				
11	CONTROL							

See the WRITE (10) command (see 3.64) for the definitions of the fields in this command.

3.66 WRITE (16) command

The WRITE (16) command (see table 234) requests that the device server transfer the specified logical block(s) from the data-out buffer and write them. Each logical block transferred includes user data and may include protection information, based on the WRPROTECT field and the medium format. Each logical block written includes user data and, if the medium is formatted with protection information enabled, protection information.

Table 234 WRITE (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Ah)							
1	WRPROTECT			DPO	FUA	Reserved	Obsolete	DLD2
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	TRANSFER LENGTH							
13	(LSB)							
14	DLD1	DLD0	GROUP NUMBER					
15	CONTROL							

See the READ (16) command (see 3.20) for the definitions of the DLD2 bit, the DLD1 bit, and the DLD0 bit.

See the WRITE (10) command (see 3.64) for the definitions of the other fields in this command.

3.67 WRITE (32) command

The WRITE (32) command (see table 235) requests that the device server transfer the specified logical block(s) from the data-out buffer and write them. Each logical block transferred includes user data and may include protection information, based on the WRPROTECT field and the medium format. Each logical block written includes user data and, if the medium is formatted with protection information enabled, protection information.

The WRITE (32) command shall only be processed if type 2 protection is enabled (see SBC-5).

Table 235 WRITE (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
...								
5								
6	Reserved			GROUP NUMBER				
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (000Bh)						(LSB)
9								
10	WRPROTECT			DPO	FUA	Reserved	Obsolete	Reserved
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
...								
19								
20	(MSB)	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG						(LSB)
...								
23								
24	(MSB)	EXPECTED LOGICAL BLOCK APPLICATION TAG						(LSB)
25								
26	(MSB)	LOGICAL BLOCK APPLICATION TAG MASK						(LSB)
27								
28	(MSB)	TRANSFER LENGTH						(LSB)
...								
31								

See the WRITE (10) command (see 3.64) for the definitions of the GROUP NUMBER field, the WRPROTECT field, the DPO bit, the FUA bit, the LOGICAL BLOCK ADDRESS field, and the TRANSFER LENGTH field.

When checking of the LOGICAL BLOCK REFERENCE TAG field is enabled (see table 232 in 3.64), the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field contains the value of the LOGICAL BLOCK REFERENCE TAG field expected in the protection information of the first logical block accessed by the command instead of a value based on the LBA.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is enabled (see table 232 in 3.64), the LOGICAL BLOCK APPLICATION TAG MASK field contains a value that is a bit mask for enabling the checking of the LOGICAL BLOCK APPLICATION TAG field in the protection information for each logical block accessed by the command. A LOGICAL BLOCK APPLICATION TAG MASK bit set to one enables the checking of the corresponding bit of the EXPECTED LOGICAL BLOCK APPLICATION TAG field with the corresponding bit of the LOGICAL BLOCK APPLICATION TAG field in the protection information.

LOGICAL BLOCK APPLICATION TAG MASK and EXPECTED LOGICAL BLOCK APPLICATION TAG fields

The LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored if:

- a) the ATO bit is set to zero; or
- b) the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see SBC-5).

3.68 WRITE AND VERIFY (10) command

The WRITE AND VERIFY (10) command (see table 236) requests that the device server transfer the specified logical block(s) from the data-out buffer, write them to the medium, and then verify that they are correctly written. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format. The logical blocks are only transferred once from the data-out buffer to the device server.

Table 236 WRITE AND VERIFY (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (2Eh)							
1	WRPROTECT			DPO	Reserved	BYTCHK		Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	(MSB)							
8	TRANSFER LENGTH							
9	(LSB)							
9	CONTROL							

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field. See 2.2.8 for the definition of the GROUP NUMBER field. See the WRITE (10) command (see 3.64) for the definitions of the TRANSFER LENGTH field and the WRPROTECT field. See the READ (10) command (see 3.18) for the definition of the DPO bit.

If the Verify Error Recovery mode page is also implemented, then the current settings in that mode page along with the AWRE bit in the Read-Write Error Recovery mode page specify the verification error criteria. If these mode pages are not implemented, then the verification criteria is vendor-specific.

See the VERIFY (10) command for the definition of the byte check (BYTCHK) field when set to 00b, 01b, or 10b. For WRITE AND VERIFY commands a BYTCHK field set to 11b is reserved.

3.69 WRITE AND VERIFY (12) command

The WRITE AND VERIFY (12) command (see table 237) requests that the device server transfer the specified logical block(s) from the data-out buffer, write them to the medium, and then verify that they are correctly written. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format. The logical blocks are only transferred once from the data-out buffer to the device server.

Table 237 WRITE AND VERIFY (12) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (AEh)							
1	WRPROTECT			DPO	Reserved	BYTCHK		Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	(MSB)							
...	TRANSFER LENGTH							
9	(LSB)							
10	Restricted for MMC-5	Reserved		GROUP NUMBER				
11	CONTROL							

See the WRITE AND VERIFY (10) command (see 3.68) for the definitions of the fields in this command.

3.70 WRITE AND VERIFY (16) command

The WRITE AND VERIFY (16) command (see table 238) requests that the device server transfer the specified logical block(s) from the data-out buffer, write them to the medium, and then verify that they are correctly written. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format. The logical blocks are only transferred once from the data-out buffer to the device server.

Table 238 WRITE AND VERIFY (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (8Eh)							
1	WRPROTECT			DPO	Reserved	BYTCHK		Reserved
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	(MSB)							
...	TRANSFER LENGTH							
13	(LSB)							
14	Restricted for MMC-5	Reserved		GROUP NUMBER				
15	CONTROL							

See the WRITE AND VERIFY (10) command (see 3.68) for the definitions of the fields in this command.

3.71 WRITE AND VERIFY (32) command

The WRITE AND VERIFY (32) command (see table 239) requests that the device server transfer the specified logical block(s) from the data-out buffer, write them to the medium, and then verify that they are correctly written. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format. The logical blocks are only transferred once from the data-out buffer to the device server.

Table 239 WRITE AND VERIFY (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
...								
5								
6	Reserved		GROUP NUMBER					
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)							
9	SERVICE ACTION (000Ch)							
	(LSB)							
10	WRPROTECT		DPO	Reserved	BYTCHK		Reserved	
11	Reserved							
12	(MSB)							
...	LOGICAL BLOCK ADDRESS							
19								
20	(MSB)							
...	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG							
23								
24	(MSB)							
25	EXPECTED LOGICAL BLOCK APPLICATION TAG							
	(LSB)							
26	(MSB)							
27	LOGICAL BLOCK APPLICATION TAG MASK							
	(LSB)							
28	(MSB)							
...	TRANSFER LENGTH							
31								

See the WRITE AND VERIFY (10) command (see 3.68) for the definitions of the GROUP NUMBER field, the WRPROTECT field, the DPO bit, the BYTCHK field, the LOGICAL BLOCK ADDRESS field, and the TRANSFER LENGTH field.

When checking of the LOGICAL BLOCK REFERENCE TAG field is enabled (see table 232), the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field contains the value of the LOGICAL BLOCK REFERENCE TAG field expected in the protection information of the first logical block accessed by the command instead of a value based on the LBA.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is enabled (see table 232), the LOGICAL BLOCK APPLICATION TAG MASK field contains a value that is a bit mask for enabling the checking of the LOGICAL BLOCK APPLICATION TAG field in the protection information for each logical block accessed by the command. A LOGICAL BLOCK APPLICATION TAG MASK bit set to one enables the checking of the corresponding bit of the EXPECTED LOGICAL BLOCK APPLICATION TAG field with the corresponding bit of the LOGICAL BLOCK APPLICATION TAG field in the protection information.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see table 232), or if the ATO bit is set to zero, the LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored.

3.72 WRITE ATOMIC (16) command

The WRITE ATOMIC (16) command (see table 240) requests that the device server.

- a) transfer logical block data from the Data-Out Buffer; and
- b) perform one or more atomic write operations (see SBC-5) of the LBAs specified by this command.

Table 240 WRITE ATOMIC (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Ch)							
1	WRPROTECT			DPO	FUA	Reserved		
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	ATOMIC BOUNDARY							
11	ATOMIC BOUNDARY							
12	(MSB)							
13	TRANSFER LENGTH							
13	(LSB)							
14	Reserved	GROUP NUMBER						
15	CONTROL							

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 240 for the WRITE ATOMIC (16) command.

ATOMIC BOUNDARY field

The ATOMIC BOUNDARY field specifies whether multiple atomic write operations may be performed. If the ATOMIC BOUNDARY field is set to zero, then a single atomic write operation of the length specified in the TRANSFER LENGTH field shall be performed. If the ATOMIC BOUNDARY field is set to a non-zero value then multiple atomic write operations may be performed as described in SBC-5.

See the WRITE (10) command (see 3.64) for the definitions of the other fields in this command.

3.73 WRITE ATOMIC (32) command

The WRITE ATOMIC (32) command (see table 241) requests that the device server perform the actions defined for the WRITE ATOMIC (16) command (see 3.72).

The device server shall process a WRITE ATOMIC (32) command only if type 2 protection is enabled.

Table 241 WRITE ATOMIC (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
3	Reserved							
4	(MSB)	ATOMIC BOUNDARY						(LSB)
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (000Fh)						(LSB)
9	(LSB)							
10	WRPROTECT			DPO	FUA	Reserved	Obsolete	Reserved
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
...								
19	(LSB)							
20	(MSB)	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG						(LSB)
...								
23	(LSB)							
24	(MSB)	EXPECTED LOGICAL BLOCK APPLICATION TAG						(LSB)
25	(LSB)							
26	(MSB)	LOGICAL BLOCK APPLICATION TAG MASK						(LSB)
27	(LSB)							
28	(MSB)	TRANSFER LENGTH						(LSB)
...								
31	(LSB)							

OPERATION CODE, ADDITIONAL CDB LENGTH, and SERVICE ACTION fields

The Operation Code field, the Additional CDB Length field, and the Service Action field are defined in Clause 2.2 and shall be set to the values shown in table 241 for the WRITE ATOMIC (32) command.

See the WRITE ATOMIC (16) command (see 3.72) for the definition of the ATOMIC BOUNDARY field.

See the WRITE (32) command (see 3.67) for the definitions of the other fields in this command.

3.74 WRITE BUFFER command

3.74.1 WRITE BUFFER command introduction

The WRITE BUFFER command (see table 242) is used in conjunction with the READ BUFFER command for:

- a) testing logical unit buffer memory;
- b) testing the integrity of the service delivery subsystem;
- c) downloading microcode; and
- d) downloading application client error history (see SPC-6).

Table 242 WRITE BUFFER command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (3Bh)								
1	MODE SPECIFIC			MODE					
2	BUFFER ID								
3	(MSB)								
...	BUFFER OFFSET								
5								(LSB)	
6	(MSB)								
...	PARAMETER LIST LENGTH								
8								(LSB)	
9	CONTROL								

This command shall not alter any medium of the logical unit when the data mode or the combined header and data mode is specified.

The function of this command and the meaning of fields within the CDB depend on the contents of the MODE field. The MODE field is defined in table 243.

Table 243 WRITE BUFFER MODE field

Mode	Description
00h	Combined header and data [a]
01h	Not supported
02h	Data
04h	Download microcode and activate
05h	Download microcode, save and activate
06h	Download microcode with offsets [b] and activate
07h	Download microcode with offsets [b], save, and activate
08h - 09h	Reserved
0Ah	Echo buffer
0Bh - 0Ch	Reserved
0Dh	Download microcode with offsets, select activation events, save, and defer activate
0Eh	Download microcode with offsets, save, and defer active
0Fh	Activate deferred microcode
10h - 19h	Reserved
1Ah	Enable expander communications protocol and Echo buffer
1Bh	Disable expander communications protocol
1Ch	Download application log
1Dh - 1Fh	Reserved
[a] Mode 00h is not recommended.	
[b] When downloading microcode with buffer offsets, the WRITE BUFFER command mode should be 06h or 07h.	

3.74.2 Combined header and data mode (00h)

NOTE This mode is not recommended.

In this mode, data to be transferred is preceded by a four-byte header. The four-byte header consists of all reserved bytes. The BUFFER ID and the BUFFER OFFSET fields shall be zero.

The MODE SPECIFIC field is reserved.

The PARAMETER LIST LENGTH field specifies the maximum number of bytes that shall be transferred from the Data-Out Buffer. This number includes four bytes of header, so the data length to be stored in the device server's buffer is parameter list length minus four. The application client should attempt to ensure that the parameter list length is not greater than four plus the BUFFER CAPACITY field value (see table 118) that is returned in the header of the READ BUFFER command (mode 0h). If the parameter list length exceeds the buffer capacity, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.74.3 Vendor specific mode (01h)

This mode is not supported by Seagate products. If used, the drive will return CHECK CONDITION and report an ILLEGAL REQUEST/INVALID FIELD IN CDB error.

3.74.4 Data mode (02h)

In this mode, the Data-Out Buffer contains buffer data destined for the logical unit. The BUFFER ID field identifies a specific buffer within the logical unit. Seagate assigns buffer ID codes to buffers within the logical unit. Buffer ID zero shall be supported. If more than one buffer is supported, then additional buffer ID codes shall be assigned contiguously, beginning with one. If an unsupported buffer ID code is selected, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The MODE SPECIFIC field is reserved.

Data are written to the logical unit buffer starting at the location specified by the BUFFER OFFSET field. The application client should conform to the offset boundary requirements returned in the READ BUFFER descriptor. If the device server is unable to accept the specified buffer offset, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The PARAMETER LIST LENGTH field specifies the maximum number of bytes that shall be transferred from the Data-Out Buffer to be stored in the specified buffer beginning at the buffer offset. The application client should attempt to ensure that the parameter list length plus the buffer offset does not exceed the capacity of the specified buffer. The capacity of the buffer is indicated by the BUFFER CAPACITY field in the READ BUFFER descriptor (see table 118). If the BUFFER OFFSET and PARAMETER LIST LENGTH fields specify a transfer in excess of the buffer capacity, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.74.5 Download microcode and activate mode (04h)

In this mode, microcode shall be transferred to the device server and activated (see SPC-6).

The MODE SPECIFIC field is reserved.

The BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field are vendor specific.

3.74.6 Download microcode, save, and activate mode (05h)

In this mode, microcode shall be transferred to the device server, saved to nonvolatile storage, and activated (see 5.4) based on the setting of the ACTIVATE MICROCODE field in the Extended INQUIRY VPD page (see 5.4.10).

The MODE SPECIFIC field is reserved.

The BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field are vendor specific.

3.74.7 Download microcode with offsets and activate mode (06h)

In this mode, microcode shall be transferred to the device server using one or more WRITE BUFFER commands and activated (see SPC-6).

The MODE SPECIFIC field is reserved.

The BUFFER ID field specifies a buffer within the logical unit. The vendor assigns buffer ID codes to buffers within the logical unit. A buffer ID value of zero shall be supported. If more than one buffer is supported, then additional buffer ID codes shall be assigned contiguously, beginning with one. If an unsupported buffer ID code is specified, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The BUFFER OFFSET field specifies the location in the buffer to which the microcode is written. The application client shall send commands that conform to the offset boundary requirements returned in the READ BUFFER descriptor (see table 118). If the device server is unable to process the specified buffer offset, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The PARAMETER LIST LENGTH field specifies the maximum number of bytes that shall be present in the Data-Out Buffer to be stored in the specified buffer beginning at the buffer offset. The application client should ensure that the parameter list length plus the buffer offset does not exceed the capacity of the specified buffer. If the BUFFER OFFSET and PARAMETER LIST LENGTH fields specify a transfer in excess of the buffer capacity, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.74.8 Download microcode with offsets and save mode (07h)

In this mode, microcode shall be transferred to the device server using one or more WRITE BUFFER commands, saved to nonvolatile storage, and activated (see 5.4) based on the setting of the ACTIVATE MICROCODE field in the Extended INQUIRY VPD page (see 5.4.10).

The BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field are defined in the download microcode with offsets mode (see 3.74.7).

3.74.9 Write data to echo buffer mode (0Ah)

In this mode the device server transfers data from the application client and stores it in an echo buffer. An echo buffer is assigned in the same manner by the device server as it would for a write operation. Data shall be sent aligned on four-byte boundaries. The BUFFER ID and BUFFER OFFSET fields are ignored in this mode.

Upon successful completion of a WRITE BUFFER command the data shall be preserved in the echo buffer unless there is an intervening command to any logical unit in which case the data may be changed.

The PARAMETER LIST LENGTH field specifies the maximum number of bytes that shall be transferred from the Data-Out Buffer to be stored in the echo buffer. The application client should ensure that the parameter list length does not exceed the capacity of the echo buffer. The capacity of the echo buffer is indicated by the BUFFER CAPACITY field in the READ BUFFER echo buffer descriptor (see Table 120). If the PARAMETER LIST LENGTH field specifies a transfer in excess of the buffer capacity, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

3.74.10 Download microcode with offsets, select activation events, save, and defer activate mode (0Dh)

In this mode, microcode shall be transferred to the device server using one or more WRITE BUFFER commands, saved to nonvolatile storage, and considered deferred (see SPC-6). The deferred microcode shall be activated and no longer considered deferred if a WRITE BUFFER command with the activate deferred microcode mode (0Fh) is processed (see 3.74.12).

The MODE SPECIFIC field (see table 244) specifies additional events that shall be used to activate the deferred microcode.

Table 244 MODE SPECIFIC field

Bit	7	6	5	...
	PO_ACT	HR_ACT	VSE_ACT	...

If the power on activate (PO_ACT) bit is set to one, then deferred microcode shall be activated and no longer considered deferred if a power on occurs. If the PO_ACT bit is set to zero, then deferred microcode shall not be activated if a power on occurs.

If the hard reset activate (HR_ACT) bit is set to one, then deferred microcode shall be activated and no longer considered deferred if a hard reset occurs. If the HR_ACT bit is set to zero, then deferred microcode shall not be activated if a hard reset occurs.

If the vendor specific event activate (VSE_ACT) bit is set to one, then deferred microcode shall be activated and no longer considered deferred if a vendor specific event occurs. If the VSE_ACT bit is set to zero, then deferred microcode shall not be activated if a vendor specific event occurs.

The supported activation events shall be reported in the POA_SUP bit, HRA_SUP bit, and VSA_SUP bit in the Extended INQUIRY VPD page (see 5.4.10). If the MODE SPECIFIC field specifies an activation event that is not supported (e.g., if the PO_ACT bit is set to one and the POA_SUP bit is set to zero), then the command shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

The BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field are defined in the download microcode with offsets mode (see 3.74.7).

3.74.11 Download microcode with offsets, save, and defer activate mode (0Eh)

In this mode, microcode shall be transferred to the device server using one or more WRITE BUFFER commands, saved to nonvolatile storage, and considered deferred (see SPC-6).

The deferred microcode should be activated and no longer considered deferred if any one of the following occurs:

- a) a power on, if the PWROMACT bit (see 5.3.15) is set to zero;
- b) a hard reset, if the HRDRMACT bit (see 5.3.15) is set to zero;
- c) a START STOP UNIT command is processed (see 3.53), if the SSUMACT bit (see 5.3.15) is set to zero;
- d) a FORMAT UNIT command is processed (see 3.3), if the FMTMACT bit (see 5.3.15) is set to zero;
- or
- e) a WRITE BUFFER command with the activate deferred microcode mode (0Fh) is processed (see 3.74.12).

NOTE Seagate products only support deferred microcode activation on event e (i.e., a WRITE BUFFER command with MODE field set to 0Fh).

The MODE SPECIFIC field, BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field are defined in the download microcode with offsets mode (see 3.74.7).

3.74.12 Activate deferred microcode mode (0Fh)

In this mode, deferred microcode that has been saved using the download microcode with offsets, select activation events, save, and defer activate (see 3.74.10) or download microcode with offsets, save, and defer activate mode (see 3.74.11), if any, shall be activated and no longer considered deferred (see SPC-6).

The MODE SPECIFIC field is reserved.

The the BUFFER ID field, BUFFER OFFSET field, and PARAMETER LIST LENGTH field shall be ignored in this mode.

If there is no deferred microcode that has been saved using the download microcode with offsets, save, and defer activate mode, then the WRITE BUFFER command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to COMMAND SEQUENCE ERROR.

3.74.13 Enable expander communications protocol and Echo buffer mode (1Ah)

Receipt of a WRITE BUFFER command with this mode (1Ah) causes a communicative expander to enter the expanded communications protocol mode. Device servers in SCSI target devices that receive a WRITE BUFFER command with this mode shall process it as if it were a WRITE BUFFER command with mode 0Ah (see 3.74.9).

The MODE SPECIFIC field is reserved.

3.74.14 Disable expander communications protocol mode (1Bh)

Receipt of a WRITE BUFFER command with this mode (1Bh) causes a communicative expander to exit the expanded communications protocol mode and return to simple expander operation. Device servers in SCSI target devices that receive a WRITE BUFFER command with this mode shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

The MODE SPECIFIC field is reserved.

3.74.15 Download application log mode (1Ch)

In this mode the device server transfers data from the application client and stores it in an application log. The format of the application log data is as specified in table 245.

The MODE SPECIFIC field is reserved.

The BUFFER ID field and BUFFER OFFSET field are ignored in this mode.

Upon successful completion of a WRITE BUFFER command, the information contained in the application client error history parameter list shall be appended to the application client error history in a format determined by the logical unit.

The PARAMETER LIST LENGTH field specifies the maximum number of bytes that shall be transferred from the Data-Out Buffer to be stored in the application log. If the PARAMETER LIST LENGTH field specifies a transfer that exceeds the application log's capacity, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB

The device server shall not return an error based on the contents of any of the field values defined in table 245 except:

- a) the CLR bit;
- b) the ERROR LOCATION LENGTH field; and
- c) the APPLICATION CLIENT ERROR HISTORY LENGTH field.

Table 245 Application log data WRITE BUFFER format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)	T10 VENDOR IDENTIFICATION							(LSB)
...									
7									
8	(MSB)	ERROR TYPE							(LSB)
9		Reserved							CLR
10		Reserved							
11		TIME STAMP							(LSB)
12	(MSB)								
...									
17		Reserved							
18		Reserved				CODE SET			
19		ERROR LOCATION FORMAT							
20		ERROR LOCATION LENGTH (m-25)							(LSB)
21	(MSB)	APPLICATION CLIENT ERROR HISTORY LENGTH (n-m)							(LSB)
22	(MSB)	ERROR LOCATION							(LSB)
23									
24									
25	(MSB)	APPLICATION CLIENT ERROR HISTORY							(LSB)
26	(MSB)	APPLICATION CLIENT ERROR HISTORY							(LSB)
...									
m									
m+1		APPLICATION CLIENT ERROR HISTORY							(LSB)
...									
n									

T10 VENDOR IDENTIFICATION field

The T10 VENDOR IDENTIFICATION field contains eight bytes of left-aligned ASCII data identifying the vendor of the product. The T10 vendor identification shall be one assigned by INCITS. A list of assigned T10 vendor identifications is in SPC-6 and on the T10 web site (<http://www.T10.org>).

ERROR TYPE field

The ERROR TYPE field (see table 246) specifies the error detected by the application client.

Table 246 ERROR TYPE field

Code	Description
0000h	No error specified by the application client
0001h	An unknown error was detected by the application client
0002h	The application client detected corrupted data
0003h	The application client detected a permanent error
0004h	The application client detected a service response of SERVICE DELIVERY OR TARGET FAILURE (SAM-6).
0005h - 7FFFh	Reserved
8000h - FFFFh	Vendor specific

CLR bit

If the CLR_SUP bit is set to one in the error history directory parameter data (see 3.74.15), a CLR bit set to one specifies that the device server shall:

- a) clear the portions of the error history that the device server allows to be cleared; and
- b) ignore any application client error history specified in the parameter list.

If the CLR_SUP bit is set to one in the error history directory parameter data, a CLR bit set to zero specifies that the device server shall not ignore the CLR bit.

If the CLR_SUP bit is set to one in the error history directory parameter data, a CLR bit set to zero specifies that the device server shall:

- a) not clear the error history; and
- b) process all application client error history specified in the parameter list.

If the CLR_SUP bit is set to zero in the error history directory parameter data, the device server shall ignore the CLR bit.

TIME STAMP field

The TIME STAMP field shall contain:

- a) a time based on the timestamp reported by the REPORT TIMESTAMP command, if the device server supports a device clock (see SPC-6)
- b) The number of milliseconds that have elapsed since midnight, 1 January 1970 UT; or
- c) Zero, if the application client is not able to determine the UT of the log entry.

CODE SET field

The CODE SET field specifies the code set used for the application log information (see table 247) and shall only apply to information contained in the VENDOR SPECIFIC field.

Table 247 CODE SET field

Code	Description
0h	Reserved
1h	The application log information is binary
2h	The application log information is ASCII printable characters (i.e., code values 20h through 7Eh)
3h	The application log information is ISO/IEC 10646-1 (UTF-8) codes
4h - Fh	Reserved

ERROR LOCATION FORMAT field

The ERROR LOCATION FORMAT field specifies the format (see table 248) of the ERROR LOCATION field.

Table 248 ERROR LOCATION FORMAT field

Code	Description
00h	No error specified by the application client
01h	The ERROR LOCATION field specifies the logical block (e.g., LBA) associated with the error information contained within the application log.
02h - 7Fh	Reserved
80h - FFh	Vendor specific

ERROR LOCATION LENGTH field

The ERROR LOCATION LENGTH field specifies the length of the ERROR LOCATION field. The ERROR LOCATION LENGTH field value shall be a multiple of four. An error location length value of zero specifies there is no error location information.

APPLICATION CLIENT ERROR HISTORY LENGTH field

The APPLICATION CLIENT ERROR HISTORY LENGTH field specifies the length of the APPLICATION CLIENT ERROR HISTORY field. The APPLICATION CLIENT ERROR HISTORY LENGTH field value shall be a multiple of four. A vendor specific length value of zero specifies there is no vendor specific information.

ERROR LOCATION field

The ERROR LOCATION field specifies the location at which the application client detected the error.

APPLICATION CLIENT ERROR HISTORY field

The APPLICATION CLIENT ERROR HISTORY field provides vendor specific information on the error.

3.75 WRITE LONG (10) command

The WRITE LONG (10) command (see table 249) requests that the device server mark a logical block or physical block as containing an error, or transfer data for a single logical block from the data-out buffer and write it to the medium. The data written shall be the same length and shall be in the same order as the data returned by the READ LONG (10) command (see 3.28). The device server shall write the logical block to the medium, and shall not return GOOD status until the logical block has actually been written on the medium without error.

Table 249 WRITE LONG (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (3Fh)							
1	Obsolete	WR_UNCOR	Obsolete	Reserved			Obsolete	
2	(MSB)	LOGICAL BLOCK ADDRESS						
...								
5	(LSB)							
6	Reserved							
7	(MSB)	BYTE TRANSFER LENGTH						
8	(LSB)							
9	CONTROL							

OPERATION CODE field

The OPERATION CODE field contains the operation code for this command and shall be set to the value defined in table 249.

WR_UNCOR bit

- 0** Obsolete
- 1** Mark the specified logical block as containing a pseudo unrecovered error with correction disabled (see SBC-5). No data is transferred.

In the Extended INQUIRY Data VPD page (see 5.4.10), the WU_SUP bit shall be set to one if the WRITE LONG command is supported.

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field (see 2.2.3) specifies an LBA. If the specified LBA exceeds the capacity of the medium, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE

BYTE TRANSFER LENGTH field

If table 249 defines that the value in the BYTE TRANSFER LENGTH field is used, then the BYTE TRANSFER LENGTH field specifies the number of bytes of data that the device server shall transfer from the data-out buffer and write to the specified logical block or physical block. If the BYTE TRANSFER LENGTH field is not set to zero and does not match the data length that the device server returns for a READ LONG command, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB. In the sense data (see 2.4), the ILI and VALID bits shall be set to one and the INFORMATION field shall be set to the difference (i.e., residue) of the requested length minus the actual length in bytes. Negative values shall be indicated by two's complement notation. If the BYTE TRANSFER LENGTH field is set to zero, then no bytes shall be written. This condition shall not be considered an error.

3.76 WRITE LONG (16) command

The WRITE LONG (16) command (see table 250) requests that the device server mark a logical block or physical block as containing an error, or transfer data for a single logical block from the data-out buffer and write it to the medium. The data written shall be the same length and shall be in the same order as the data returned by the READ LONG (16) command (see 3.29). The device server shall write the logical block to the medium, and shall not return GOOD status until the logical block has been written on the medium without error. This command is implemented as a service action of the SERVICE ACTION OUT operation code.

Table 250 WRITE LONG (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Fh)							
1	Obsolete	WR_UNCOR	Obsolete	SERVICE ACTION (11h)				
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	Reserved							
11	Reserved							
12	(MSB)							
13	BYTE TRANSFER LENGTH							
14	(LSB)							
15	Reserved							
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field (see 2.2.1) and SERVICE ACTION field (see 2.2.2) shall be set to the values defined in table 250.

OPERATION CODE field

The OPERATION CODE field contains the operation code of a command supported by the logical unit and shall be set to the value defined in table 250.

See the WRITE LONG (10) command (see 3.75) for the definitions of the fields in this command.

3.77 WRITE SAME (10) command

The WRITE SAME(10) command (see table 251) requests that the device server transfer a single logical block from the Data-Out Buffer and for each LBA in the specified range of LBAs:

- a) perform a write operation using the contents of that logical block; or
- b) perform an unmap operation.

The device server writes (i.e., subsequent read operations behave as if the device server wrote the single block of user data received from the Data-Out Buffer to each logical block without modification (see SBC-5).

If the medium is formatted with protection information and the WRPROTECT field is set to 000b, then the device server shall write the LOGICAL BLOCK GUARD field, APPLICATION TAG field, and LOGICAL BLOCK REFERENCE TAG field (see4.22) for each logical block as described in table119 (i.e., code equal to 000b row of table119).

If:

- a) the medium is formatted with protection information;
- b) the WRPROTECT field is not set to 000b or a reserved value (seetable119); and
- c) the protection information from the Data-Out Buffer is set to FFFF_FFFF_FFFF_FFFFh,

then the device server shall write FFFF_FFFF_FFFF_FFFFh to the protection information for each logical block.

If:

- a) the medium is formatted with type 1 or type 2 protection information;
- b) the WRPROTECT field is not set to 000b or a reserved value (seetable119); and
- c) the protection information from the Data-Out Buffer is not set to FFFF_FFFF_FFFF_FFFFh,

then:

- a) the device server shall write the value from the LOGICAL BLOCK REFERENCE TAG field (see4.22) received in the logical block from the Data-Out Buffer into the corresponding LOGICAL BLOCK REFERENCE TAG field of the first logical block written. The device sever shall write the value of the previous LOGICAL BLOCK REFERENCE TAG field plus one into each of the subsequent LOGICAL BLOCK REFERENCE TAG fields;
- b) if the ATO bit is set to one in the Control mode page (see SPC-6) and the and the ATMPE bit is set to zero in the Control mode page, then the device server shall write the logical block application tag received in the logical block from the Data-Out Buffer into the corresponding LOGICAL BLOCK APPLICATION TAG field (see4.22) of each logical block;
- c) if the ATO bit is set to one in the Control mode page and the and the ATMPE bit is set to zero in the Control mode page, then the device server shall write the value defined in the Application Tag mode page (see6.5.3) into the corresponding LOGICAL BLOCK APPLICATION TAG field of each logical block;
- d) if the ATO bit is set to zero in the Control mode page, then the device server may write any value into the LOGICAL BLOCK APPLICATION TAG field of each logical block; and
- e) the device server shall write the value from the LOGICAL BLOCK GUARD field (see4.22) received in the logical block from the Data-Out Buffer into the corresponding LOGICAL BLOCK GUARD field of each logical block.

If:

- a) the medium is formatted with type 3 protection information;
- b) the WRPROTECT field is not set to 000b or a reserved value (seetable119); and
- c) the protection information from the Data-Out Buffer is not set to FFFF_FFFF_FFFF_FFFFh,

then:

- a) if the ATO bit is set to one in the Control mode page (see SPC-6), then the device server shall write the value from the LOGICAL BLOCK REFERENCE TAG field and the LOGICAL BLOCK APPLICATION TAG field received in the logical block from the Data-Out Buffer into the corresponding LOGICAL BLOCK REFERENCE TAG field of each logical block;
- b) if the ATO bit is set to zero in the Control mode page, then the device server may write any value into the LOGICAL BLOCK REFERENCE TAG field of each logical block; and
- c) the device server shall write the value from the LOGICAL BLOCK GUARD field and the LOGICAL BLOCK APPLICATION TAG field received in the logical block from the Data-Out Buffer into the corresponding LOGICAL BLOCK GUARD field of each logical block.

Table 251 WRITE SAME (10) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (41h)							
1	WRPROTECT			ANCHOR	UNMAP	Obsolete	Obsolete	Obsolete
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
5	(LSB)							
6	Reserved			GROUP NUMBER				
7	(MSB)							
8	NUMBER OF BLOCKS							
9	(LSB)							
	CONTROL							

WRPROTECT field

See the WRITE (10) command (see 3.64) for the definitions of the WRPROTECT field.

LOGICAL BLOCK ADDRESS field

See 2.2.3 for the definition of the LOGICAL BLOCK ADDRESS field.

GROUP NUMBER field

See clause 2.2.8 for the definition of the GROUP NUMBER field.

ANCHOR and UNMAP bits

If the logical unit supports logical block provisioning management (see SBC-5), then the ANCHOR bit, the UNMAP bit, and the ANC_SUP bit in the Logical Block Provisioning VPD page (see 5.4.13) determine how the device server processes the command as described in Table 252.

Table 252 ANCHOR bit, UNMAP bit, and ANC_SUP bit relationships

UNMAP bit ^[a]	ANCHOR bit	ANC_SUP bit ^[b]	Action
0b	0b	n/a	Write ^[c]
	1b	n/a	Error ^[d]
1b	0b	n/a	Unmap ^[e]
	1b	0	Error ^[d]
		1	Anchor ^[f]

[a] The device server in a logical unit that supports logical block provisioning management (see SBC-5) may implement the UNMAP bit.

[b] See the Logical Block Provisioning VPD page (see 5.4.13).

[c] The device server shall perform the specified write operation on each LBA specified by the command.

[d] The device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

[e] The device server in a thin provisioned logical unit should deallocate each LBA specified by the command (see SBC-5) but may anchor each LBA specified by the command (see SBC-5). The device server in a resource provisioned logical unit should anchor each LBA specified by the command. If the device server does not deallocate or anchor the LBA, then the device server shall perform the specified write operation (see SBC-5).

[f] The device server should anchor each LBA specified by the command (see SBC-5). If the device server does not anchor the LBA, then the device server shall perform the specified write operation (see SBC-5).

NUMBER OF BLOCKS field

The NUMBER OF BLOCKS field specifies the number of contiguous logical blocks to be written, starting with the logical block specified by the LOGICAL BLOCK ADDRESS field. A NUMBER OF BLOCKS field set to zero specifies that the device server write all the logical blocks starting with the one specified in the LOGICAL BLOCK ADDRESS field to the last logical block on the medium. If the logical block address plus the number of blocks exceeds the capacity of the medium, the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

3.78 WRITE SAME (16) command

The WRITE SAME (16) command (see table 253) requests that the device server transfer a single logical block from the data-out buffer and write the contents of that logical block to the specified range of logical block addresses. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format. The WRITE SAME (16) command with the UNMAP bit supported is one of the possible commands that shall be implemented by device servers supporting thin provisioning (see SBC-5).

Table 253 WRITE SAME (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (93h)							
1	WRPROTECT			ANCHOR	UNMAP	Obsolete	Obsolete	NDOB
2	(MSB)	LOGICAL BLOCK ADDRESS						
9	(LSB)							
10	(MSB)	NUMBER OF BLOCKS						
13	(LSB)							
14	Reserved			GROUP NUMBER				
15	CONTROL							

NDOB bit

A NDOB bit set to zero specifies that the device server shall process the command using logical block data from the Data-Out Buffer. A NDOB bit set to one specifies that:

- a) the device server shall not transfer data from the Data-Out Buffer;
- b) if the Logical Block Provisioning VPD page (see 5.2.15) is not supported or the LBPRZ field (see 5.2.15) is set to 000b or xx1b, then the device server shall process the command as if the Data-Out Buffer contained user data set to all zeroes and protection information, if any, containing:
 - A. the logical block guard field set to FFFFh;
 - B). the logical block reference tag field set to FFFF_FFFFh; and
 - C). the logical block application tag field set to FFFFh;

and

- c) if the LBPRZ field is set to 010b, then the device server shall process the command as if the Data-Out Buffer contained user data set to the provisioning initialization pattern and protection information, if any, containing:
 - A. the logical block guard field set to FFFFh;
 - B). the logical block reference tag field set to FFFF_FFFFh; and
 - C). the logical block application tag field set to FFFFh.

See the WRITE SAME (10) command (see 3.77) for the definitions of the other fields in this command.

3.79 WRITE SAME (32) command

The WRITE SAME (32) command (see table 254) requests that the device server transfer a single logical block from the data-out buffer and write the contents of that logical block. Each logical block includes user data and may include protection information, based on the WRPROTECT field and the medium format.

Table 254 WRITE SAME (32) command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (7Fh)								
1	CONTROL								
2	Reserved								
...									
5									
6	Reserved			GROUP NUMBER					
7	ADDITIONAL CDB LENGTH (18h)								
8	(MSB)								
9	SERVICE ACTION (000Dh)								
10	WRPROTECT			ANCHOR	UNMAP	Obsolete	Obsolete	NDOB	
11	Reserved								
12	(MSB)								
...	LOGICAL BLOCK ADDRESS								
19									(LSB)
20	(MSB)								
...	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG								
23									(LSB)
24	(MSB)								
25	EXPECTED LOGICAL BLOCK APPLICATION TAG								
26	(MSB)								
27	LOGICAL BLOCK APPLICATION TAG MASK								
28	(MSB)								
...	NUMBER OF BLOCKS								
31									(LSB)

See the WRITE SAME (10) command (see 3.77) for the definition of the function of this command.

OPERATION CODE, ADDITIONAL CDB LENGTH, and SERVICE ACTION fields

The OPERATION CODE field, the ADDITIONAL CDB LENGTH field, and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 254 for the WRITE SAME (32) command.

See the WRITE SAME (10) command (see 3.77) for the definitions of the GROUP NUMBER field, the WRPROTECT field, the ANCHOR bit, the UNMAP bit, the NDOB bit, the LOGICAL BLOCK ADDRESS field, and the NUMBER OF BLOCKS field.

LOGICAL BLOCK REFERENCE TAG field

When checking of the LOGICAL BLOCK REFERENCE TAG field is enabled (see 3.77), the EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG field contains the value of the LOGICAL BLOCK REFERENCE TAG field expected in the protection information of the first logical block accessed by the command instead of a value based on the LBA (see SBC-5).

ATO bit, LOGICAL BLOCK APPLICATION TAG field and EXPECTED LOGICAL BLOCK APPLICATION TAG field

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is enabled (see table 232), then the LOGICAL BLOCK APPLICATION TAG MASK field contains a value that is a bit mask for enabling the checking of the LOGICAL BLOCK APPLICATION TAG field in every instance of protection information for each logical block accessed by the command. A LOGICAL BLOCK APPLICATION TAG MASK bit set to one enables the checking of the corresponding bit of the EXPECTED LOGICAL BLOCK APPLICATION TAG field with the corresponding bit of the LOGICAL BLOCK APPLICATION TAG field in every instance of protection information.

If the ATO bit is set to one in the Control mode page (see 5.3.14) and checking of the LOGICAL BLOCK APPLICATION TAG field is disabled (see table 232), or if the ATO bit is set to zero, then the LOGICAL BLOCK APPLICATION TAG MASK field and the EXPECTED LOGICAL BLOCK APPLICATION TAG field shall be ignored.

3.80 WRITE STREAM (16) command

The WRITE STREAM (16) command (see table 255) requests that the device server perform the actions defined for the WRITE (10) command (see 3.64).

Table 255 WRITE STREAM (16) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (9Ah)							
1	WRPROTECT			DPO	FUA	Reserved		
2	(MSB)							
...	LOGICAL BLOCK ADDRESS							
9	(LSB)							
10	STR_ID							
11	STR_ID							
12	(MSB)							
13	TRANSFER LENGTH							
14	Reserved		GROUP NUMBER					
15	CONTROL							

OPERATION CODE field

The OPERATION CODE field is defined in 2.2 and shall be set to the value shown in table 255 for the WRITE STREAM (16) command.

STR_ID field

The stream identifier (STR_ID) field specifies the stream identifier associated with this command as described in SBC-5.

See the WRITE (10) command (see 3.64) for the definitions of the other fields in this command.

3.81 WRITE STREAM (32) command

The WRITE STREAM (32) command (see table 255) requests that the device server perform the actions defined for the WRITE (32) command (see 3.67).

Table 256 WRITE STREAM (32) command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (7Fh)							
1	CONTROL							
2	Reserved							
3	Reserved							
4	(MSB)	STR_ID						(LSB)
5	(LSB)							
6	Reserved	GROUP NUMBER						
7	ADDITIONAL CDB LENGTH (18h)							
8	(MSB)	SERVICE ACTION (0010h)						(LSB)
9	(LSB)							
10	WRPROTECT		DPO		FUA		Reserved	
11	Reserved							
12	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)
...								
19	(LSB)							
20	(MSB)	EXPECTED INITIAL LOGICAL BLOCK REFERENCE TAG						(LSB)
...								
23	(LSB)							
24	(MSB)	EXPECTED LOGICAL BLOCK APPLICATION TAG						(LSB)
25	(LSB)							
26	(MSB)	LOGICAL BLOCK APPLICATION TAG MASK						(LSB)
27	(LSB)							
28	(MSB)	TRANSFER LENGTH						(LSB)
...								
31	(LSB)							

OPERATION CODE, ADDITIONAL CDB LENGTH, and SERVICE ACTION fields

The OPERATION CODE field, the ADDITIONAL CDB LENGTH field, and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 256 for the WRITE STREAM (32) command.

See the WRITE STREAM (16) command (see 3.80) for the definition of the STR_ID field.

See the WRITE (32) command (see 3.67) for the definitions of the other fields in this command.

4. Zone Block Commands (ZBC)

4.1 Commands for zoned block devices overview

4.1.1 Summary of commands for zoned block devices

For zoned block devices, the contents of the PERIPHERAL DEVICE TYPE field in the Standard INQUIRY data (see SPC-6) indicate the command support requirements as described in ZBC-2.

Table 257 summarizes the commands that are unique to zoned block devices..

Table 257 Commands for host managed zoned block devices

Command	Operation Code ^[a]	Reference
CLOSE ZONE	94h/01h	4.2
FINISH ZONE	94h/02h	4.3
OPEN ZONE	94h/03h	4.4
REPORT REALMS	95h/06h	4.5
REPORT ZONE DOMAINS	95h/07h	4.6
REPORT ZONES	95h/00h	4.7
RESET WRITER POINTER	94h/04h	4.8
SEQUENTIALIZE ZONE	94h/10h	4.9
ZONE ACTIVATE	95h/08h	4.10
ZONE QUERY	95h/09h	4.11
<p>a For operation codes 94h and 95h, combinations of operation code and service action not shown in this table are reserved.</p>		

4.1.2 Zoned block device 16-byte CDB format with no data transfer

Table 20 shows the typical format of a 16-byte CDB for zoned block device command that does not result in data transfers (i.e., the CLOSE ZONE command (see 4.2), the FINISH ZONE command (see 4.3), the OPEN ZONE command (see 4.4) the RESET WRITE POINTER command (see 4.8), and the SEQUENTIALIZE ZONE command (see 4.9)), including the location of:

- the ZONE ID field;
- the ZONE COUNT field; and
- the ALL bit.

Table 258 Typical 16-byte zoned block device CDB format with no data transfer

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Command specific fields, if any			SERVICE ACTION				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Command specific fields, if any							
11								
12	(MSB)							
13	ZONE COUNT							
13	(LSB)							
14	Command specific fields, if any							ALL
15	CONTROL							

OPERATION CODE field, SERVICE ACTION field, CONTROL byte, and command specific fields

The OPERATION CODE field, SERVICE ACTION field, CONTROL byte, and command specific fields are defined by each zoned block device command.

The usage of the ZONE ID field and the ZONE COUNT field depends on the value of the ALL bit.

If the ALL bit is set to zero, then:

- a) the ZONE ID field specifies the lowest LBA of a write pointer zone;
- b) if the ZONE COUNT field is set to:
 - A) zero or one, then the command requests the device server to perform the requested operation on the zone specified by the ZONE ID field; and
 - B) a value greater than one, then the command requests the device server to perform the requested operation on the zone range specified by the ZONE ID field and the ZONE COUNT field; and
- c) the device server shall terminate the command with CHECK CONDITION status:
 - A) with the sense key set to ILLEGAL REQUEST and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE, if:
 - a) the ZONE ID field specifies an LBA that is greater than the zoned maximum address; or
 - b) the specified zone range, if any, includes an LBA that is greater than the zoned maximum address;
 - B) with the sense key set to DATA PROTECT and the additional sense code set to ZONE IS READ ONLY, if the ZONE COUNT field is set to zero and the ZONE ID field specifies zone with a Zone Condition of READ ONLY;
 - C) with the sense key set to DATA PROTECT and the additional sense code set to ZONE IS OFFLINE, if the ZONE COUNT field is set to zero and the ZONE ID field specifies zone with a Zone Condition OFFLINE;
 - D) with the sense key set to DATA PROTECT and the additional sense code set to ZONE IS INACTIVE, if the ZONE COUNT field is set to zero and the ZONE ID field specifies zone with a Zone Condition INACTIVE;
 - E) with the sense key set to ILLEGAL REQUEST and the additional sense code set to ATTEMPT TO ACCESS GAP ZONE, if:
 - a) the ZONE ID field specifies an LBA that is in a gap zone (see ZBC-2); or
 - b) the specified zone range, if any, includes a gap zone;
 - F) with the sense key and additional sense code set to the values specified for any command specific errors, see:
 - a) 4.2 for the CLOSE ZONE command;
 - b) 4.3 for the FINISH ZONE command;
 - c) 4.4 for the OPEN ZONE command;
 - d) 4.8 for the RESET WRITE POINTER command; and
 - e) 4.9 for the SEQUENTIALIZE ZONE command;
 and
 - G) with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB, if:
 - a) the ZONE ID field:
 - A) does not specify the lowest LBA of a zone; or
 - B) specifies a conventional zone;
 or
 - b) the specified zone range, if any, includes:
 - A) a zone that is a conventional zone; or
 - B) more than one zone domain (see ZBC-2).

If the ALL bit set to one, then:

- a) the command requests the device server to:
 - A) ignore the contents of the ZONE ID field; and
 - B) perform the requested operation as defined for the command, if the ZONE COUNT field is set to zero;
 and
- b) if the ZONE COUNT field is not set to zero, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB.

4.2 CLOSE ZONE command (94h/01h)

The CLOSE ZONE command (see table 259) requests the device server to perform close zone operations (see ZBC-2).

Table 259 CLOSE ZONE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Reserved			SERVICE ACTION (01h)				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Reserved							
11	Reserved							
12	(MSB)							
13	ZONE COUNT							
14	Reserved							ALL
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 259 for the CLOSE ZONE command.

ZONE ID field, ZONE COUNT field and ALL bit

The ZONE ID field, ZONE COUNT field, and ALL bit are defined in 4.1.2.

For a domains and realms zoned block device (see ZBC-2), the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB, if the ALL bit is set to zero, and:

- the ZONE ID field specifies an LBA that is in a sequential or before required zone (see ZBC-2); or
- the specified zone range (see 4.1.2), if any, includes a sequential or before required zone.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

CLOSE ZONE command

If the CLOSE ZONE command is not terminated with CHECK CONDITION status (see 4.1.2), then the device server processes the command as described in table 260.

Table 260 CLOSE ZONE command processing

ZONE COUNT field	ALL bit	Description
zero or one	zero	If the specified zone has a Zone Condition of: a) EMPTY, CLOSED, or FULL, then the device server shall make no changes in the Zone Condition and not return an error; and b) IMPLICITLY OPENED or EXPLICITLY OPENED, then the device server shall perform a close zone operation (see ZBC-2) on the specified zone.
two or more	zero	For each zone in the specified zone range that has a Zone Condition of IMPLICITLY OPENED or EXPLICITLY OPENED, the device server shall perform a close zone operation.
zero	one	For each zone that has a Zone Condition of IMPLICITLY OPENED or EXPLICITLY OPENED, the device server shall perform a close zone operation.
non-zero	one	See 4.1.2.

4.3 FINISH ZONE command (94h/02h)

The FINISH ZONE command (see table 261) requests the device server to perform finish zone operations (see ZBC-2).

The device server returns the initialization pattern for all unwritten LBAs in this zone (see ZBC-2) in response to a read operation. The device server may write the initialization pattern to the media for unwritten LBAs.

Table 261 FINISH ZONE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Reserved			SERVICE ACTION (02h)				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Reserved							
11								
12	(MSB)							
13	ZONE COUNT							
14	Reserved							ALL
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 261 for the FINISH ZONE command.

ZONE ID field, ZONE COUNT field and ALL bit

The ZONE ID field, ZONE COUNT field, and ALL bit are defined in 4.1.2.

For a domains and realms zoned block device (see ZBC-2), the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB, if the ALL bit is set to:

- a) zero and:
 - A) the ZONE ID field specifies an LBA that is in a sequential or before required zone (see ZBC-2); or
 - B) the specified zone range (see 4.1.2), if any, includes a sequential or before required zone;
 and
- b) one and at least one sequential or before required zone has a Zone Condition of IMPLICITLY OPENED.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

If the FINISH ZONE command is not terminated with CHECK CONDITION status (see 4.1.2), then the device server processes the command as described in table 262.

Table 262 FINISH ZONE command processing

ZONE COUNT field	ALL bit	Description
zero or one	zero	If the specified zone has a Zone Condition of: a) FULL, then the device server shall make no changes in the Zone Condition and not return an error; and b) IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or EMPTY, then the device server shall perform a finish zone operation (see ZBC-2) on the specified zone.
two or more	zero	For each zone in the specified zone range that has a Zone Condition of IMPLICITLY OPENED, EXPLICITLY OPENED, or CLOSED, the device server shall perform a finish zone operation.
zero	one	For each zone that has a Zone Condition of IMPLICITLY OPENED, EXPLICITLY OPENED, or CLOSED, the device server shall perform a finish zone operation.
non-zero	one	See 4.1.2.

4.4 OPEN ZONE command (94h/03h)

The OPEN ZONE command (see table 263) requests the device server to perform open zone operations (see ZBC-2).

Table 263 OPEN ZONE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Reserved			SERVICE ACTION (03h)				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Reserved							
11	Reserved							
12	(MSB)							
13	ZONE COUNT							
13	(LSB)							
14	Reserved							ALL
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 263 for the CLOSE ZONE command.

ZONE ID field, ZONE COUNT field and ALL bit

The ZONE ID field, ZONE COUNT field, and ALL bit are defined in 4.1.2.

The device server shall terminate the command with CHECK CONDITION status, with the sense key set to DATA PROTECT and the additional sense code set to INSUFFICIENT ZONE RESOURCES, if the value in the MAXIMUM NUMBER OF OPEN SEQUENTIAL WRITE REQUIRED ZONES field (see 6.5.2) is less than or equal to the sum of:

- a) the number of sequential write required zones (see ZBC-2) in the logical unit with a Zone Condition of EXPLICITLY OPENED; and
- b) the number of sequential write required zones in:
 - A) the specified zone range (see 4.1.2) with a Zone Condition of IMPLICITLY OPENED, CLOSED, or EMPTY, if the ALL bit is set to zero; or
 - B) the logical unit with a Zone Condition of CLOSED, if the ALL bit is set to one.

For a domains and realms zoned block device (see ZBC-2), the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB, if the ALL bit is set to zero, and:

- a) the ZONE ID field specifies an LBA that is in a sequential or before required zone (see ZBC-2); or
- b) the specified zone range (see 4.1.2), if any, includes a sequential or before required zone.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

If the OPEN ZONE command is not terminated with CHECK CONDITION status (see 4.1.2), then the device server processes the command as described in table 264.

Table 264 OPEN ZONE command processing

ZONE COUNT field	ALL bit	Description
zero or one	zero	If the specified zone has a Zone Condition of: <ul style="list-style-type: none"> a) EXPLICITLY OPENED or FULL, then the device server shall make no changes in the Zone Condition and not return an error; and b) IMPLICITLY OPENED, CLOSED, or EMPTY, then the device server shall perform an open zone operation (see 4.5.3.2.2) on the specified zone.
two or more	zero	For each zone in the specified zone range that has a Zone Condition of IMPLICITLY OPENED, CLOSED, or EMPTY, the device server shall perform an open zone operation.
zero	one	For each zone that has a Zone Condition of CLOSED, the device server shall perform an open zone operation.
non-zero	one	See 4.1.2.

4.5 REPORT REALMS command (95h/06h)

The REPORT REALMS command (see table 265) requests that the device server transfer parameter data describing the realms structure (see 4.5.1) of the zoned block device.

Table 265 REPORT REALMS command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (95h)							
1	Reserved			SERVICE ACTION (06h)				
2	(MSB) _____							
...	REALM LOCATOR							
9	_____ (LSB)							
10	_____							
...	ALLOCATION LENGTH							
13	_____							
14	Reserved			REPORTING OPTIONS				
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 265 for the REPORT REALMS command.

REALM LOCATOR field

The REALM LOCATOR field specifies information that locates the first realm to be reported. The first realm descriptor table 4.5.2 shall describe:

- the realm that contains the LBA specified by the REALM LOCATOR field, if that realm meets the criteria specified by the REPORTING OPTIONS field; or
- the first realm, if any, that:
 - meets the criteria specified by the REPORTING OPTIONS field; and
 - contains an LBA that is greater than the value in the REALM LOCATOR field.

If the REALM LOCATOR field specifies an LBA that is greater than the zoned maximum address, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. If the allocation length is less than 64, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

REPORTING OPTIONS field

The REPORTING OPTIONS field (see table 266) specifies the information to be returned in the parameter data.

Table 266 REPORT REALMS REPORTING OPTIONS field

Code	Description
00h	Report all realms
01h	Report all realms that contain Sequential Or Before Required zones that are active zones
02h	Report all realms that contain Sequential Write Required zones that are active zones
03h	Report all realms that contain Sequential Write Preferred zones that are active zones
all others	Reserved

CONTROL byte

The CONTROL byte is defined in 2.2.7.

4.5.1 REPORT REALMS parameter data

The REPORT REALMS parameter data (see table 267) contains information about the specified zone domains starting with the zone domain specified by the ZONE DOMAIN LOCATOR field.

Table 267 REPORT REALMS parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	REALMS DESCRIPTORS LIST LENGTH (n-63)							
3								
4	(MSB)							
...	REALMS COUNT							
7								
8	(MSB)							
...	REALMS DESCRIPTOR LENGTH							
11								
12	(MSB)							
...	NEXT REALM LOCATOR							
19								
20	Reserved							
...								
63								
REALM DESCRIPTOR LIST								
64	Realm descriptor [first] (see 4.5.2)							
...								
63+r ^[a]	...							
...								
n-1-r ^[a]	Realm descriptor [last] (see 4.5.2)							
...								
n								

a Where r equals the contents of the REALMS DESCRIPTOR LENGTH field.

REALMS DESCRIPTORS LIST LENGTH field

The REALMS DESCRIPTORS LIST LENGTH field indicates the number of bytes in the realm descriptors list.

REALMS COUNT field

The REALMS COUNT field indicates the number of realms configured on the device server. The value in the REALMS COUNT field shall not be affected by:

- a) the contents of the REPORTING OPTIONS field (see 4.5);
- b) the contents of the REALM LOCATOR field (see 4.5); or
- c) the contents of or number of realms descriptors returned in the REPORT REALMS parameter data.

REALMS DESCRIPTOR LENGTH field

The REALMS DESCRIPTOR LENGTH field indicates the number of bytes in one realm descriptor (see 4.5.2).

NEXT REALMS LOCATOR field

The NEXT REALMS LOCATOR field indicates a possible contents for a subsequent REPORT REALMS command as follows. If the parameter data transferred to the application client by this REPORT REALMS command:

- a) contains the last realm descriptor requested by the REPORT REALMS command (see 4.5), then the NEXT REALM LOCATOR field shall be set to zero; and
- b) does not contain the last realm descriptor requested by the REPORT REALMS command, then a subsequent REPORT REALMS command should return data that begins reporting realms where this REPORT REALMS command stopped, if that subsequent REPORT REALMS command has:
 - A) the REALM LOCATOR field (see 4.5) set to the value in this NEXT REALM LOCATOR field; and
 - B) the REPORTING OPTIONS field (see 4.5) set to the same value as the REPORTING OPTIONS field of this REPORT REALMS command.

The realm descriptors contain information about the specified realms as defined in 4.5.2.

4.5.2 Realm descriptor

Each realm descriptor (see table 268) contains information about one realm and all the zone domains included in that realm. The contents of the REALM LOCATOR field (see 4.5) shall not affect the zone domains included in any realm descriptor. The realm descriptors shall be sorted in ascending order based on the contents of the REALM ID field.

Table 268 Realm descriptor

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)								
...	REALMS ID								
3								(LSB)	
4	(MSB)	REALMS RESTRICTIONS							
5								(LSB)	
6	Reserved								
7	ACTIVE ZONE DOMAIN ID								
8	Reserved								
...	Reserved								
15									
Realm Start/End descriptors list									
16									
...	Realm Start/End descriptor for zone domain 0								
31									
32									
...	Realm Start/End descriptor for zone domain 1								
47									
48									
...	Realm Start/End descriptor for zone domain 2, if any								
63									
...	...								
n - 15									
...	Realm Start/End descriptor for zone domain $z_d^{[a]}$, if any								
n									

- a** Where z_d is one less than the value in the NUMBER OF SUPPORTED ZONE DOMAINS field in the parameter data returned by the REPORT ZONE DOMAINS command (see 4.6).

REALM ID field

The REALM ID field indicates the identifier number assigned to this realm. Realms are numbered from 0 to n incrementing by one for each realm.

REALM RESTRICTIONS field

The REALM RESTRICTIONS field (see table 269) indicates what restrictions, if any, affect this realm.

Table 269 REALM RESTRICTIONS field

Code	Description
0000h	No restrictions affect this realm.
0001h	The Restrict Zone Activate realm attribute (see ZBC-2) is true.
003h	The Restrict Zone Activate realm attribute (see ZBC-2) is true and the Restrict Write Pointer Reset realm attribute (see ZBC-2) is true.
all others	Reserved

ACTIVE ZONE DOMAIN ID field

The ACTIVE ZONE DOMAIN ID field indicates the zone domain ID (see ZBC-2) of the zone domain that contains active zones in this realm. If no zone domain contains active zones in this realm, the ACTIVE ZONE DOMAIN ID field shall contain FFh.

4.5.3 Realm Start/End descriptor

Each realm start/end descriptor (see table 270) contains information about one zone domain that is in the realm described by this realm descriptor.

Table 270 Realm Start/End descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	REALM STARTING LBA							
.....								
7								
8	REALM ENDING LBA							
....								
15								

REALM STARTING LBA

The REALM STARTING LBA field shall contain the lowest LBA in the realm described by this realm start/end descriptor. The processing of a ZONE ACTIVATE command (see 4.10) may result in the contents of the REALM STARTING LBA field changing (see ZBC-2).

REALM ENDING LBA field

The REALM ENDING LBA field shall contain the highest LBA in the realm described by this realm start/end descriptor. A REALM ENDING LBA field set to zero indicates that the zone domain associated with this realm start/end descriptor is not contained in the realm described by this realm descriptor. The processing of a ZONE ACTIVATE command may result in the contents of the REALM ENDING LBA field changing (see ZBC-2).

4.6 REPORT ZONE DOMAINS command (95h/07h)

The REPORT ZONE DOMAINS command (see table 271) requests that the device server transfer parameter data describing the zone domains structure (see 5.6.2) of the zoned block device.

Table 271 REPORT ZONE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (95h)							
1	Reserved				SERVICE ACTION (07h)			
2	(MSB)							
...	ZONE DOMAIN LOCATOR							
9	(LSB)							
10	ALLOCATION LENGTH							
...								
13								
14	Reserved				REPORTING OPTIONS			
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 265 for the REPORT ZONE DOMAINS command.

ZONE DOMAIN LOCATOR field

The ZONE DOMAIN LOCATOR field specifies information that locates the first zone domain to be reported. The first zone domain descriptor (see 4.5.2) shall describe:

- the zone domain that contains the LBA specified the ZONE DOMAIN LOCATOR field, if that zone domain meets the criteria specified by the REPORTING OPTIONS field; or
- the first zone domain, if any, that:
 - meets the criteria specified by the REPORTING OPTIONS field; and
 - contains an LBA that is greater than the value in the ZONE DOMAIN LOCATOR field.

If the ZONE DOMAIN LOCATOR field specifies an LBA that is greater than the zoned maximum address, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. If the allocation length is less than 160, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

REPORTING OPTIONS field

The REPORTING OPTIONS field (see table 272) specifies the information to be returned in the parameter data.

Table 272 REPORT REALMS REPORTING OPTIONS field

Code	Description
00h	Report all zone domains
01h	Report all zone domains in which all zones are active
02h	Report all zone domains that contain active zones
03h	Report all zone domains that do not contain any active zones
all others	Reserved

CONTROL byte

The CONTROL byte is defined in 2.2.7.

4.6.1 REPORT ZONE DOMAINS parameter data

The REPORT ZONE DOMAINS parameter data (see table 273) contains information about the specified zone domains starting with the zone domain specified by the ZONE DOMAIN LOCATOR field.

Table 273 REPORT REALMS parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	ZONE DOMAINS LIST LENGTH (n-63)							
3	(LSB)							
4	(MSB)							
...	ZONE DOMAINS RETURNED LIST LENGTH							
7	(LSB)							
8	NUMBER OF ZONE DOMAINS SUPPORTED							
9	ZONE DOMAINS REPORTED							
10	REPORTING OPTIONS							
11	Reserved							
...	Reserved							
15	Reserved							
16	(MSB)							
...	ZONE DOMAIN LOCATOR							
23	(LSB)							
24	Reserved							
...	Reserved							
63	Reserved							
Zone domain descriptors list								
64	Zone domain descriptor [first]							
...	Zone domain descriptor [first]							
159	Zone domain descriptor [first]							
...	...							
n - 95	Zone domain descriptor [last]							
...	Zone domain descriptor [last]							
n	Zone domain descriptor [last]							

ZONE DOMAINS LIST LENGTH field

The REALMS DESCRIPTORS LIST LENGTH field indicates the length in bytes of the zone domain descriptors list. The contents of the ZONE DOMAINS LIST LENGTH field shall not be altered based on the allocation length (see 2.2.6).

ZONE DOMAINS RETURNED LIST LENGTH field

The ZONE DOMAINS RETURNED LIST LENGTH field indicates the length in bytes of the part of the zone domain descriptors list that is available for the application client to process. If the allocation length (see 2.2.6) is not sufficient to contain all of the contents of the zone domain descriptors list, then the ZONE DOMAINS RETURNED LIST LENGTH field shall be altered to indicate the truncation of the zone domain descriptors list.

NUMBER OF SUPPORTED DOMAINS field

The NUMBER OF SUPPORTED DOMAINS field indicates the total number of zone domains by the device server, regardless of the value of the REPORTING OPTIONS field.

ZONE DOMAINS REPORTED field

The ZONE DOMAINS REPORTED field indicates the number of zone domain descriptors returned based on the REPORTING OPTIONS field and the ZONE DOMAIN LOCATOR field.

REPORTING OPTIONS field

The REPORTING OPTIONS field in the parameter data is a copy of the REPORTING OPTIONS field in the REPORT ZONE DOMAINS command (see 4.6).

ZONE DOMAIN LOCATORS field

The ZONE DOMAIN LOCATOR field in the parameter data is a copy of the ZONE DOMAIN LOCATOR field in the REPORT ZONE DOMAINS command (see 4.6).

Each zone domain descriptor (see table 274) describes one zone domain (see ZBC-2). Zone domain descriptors shall be sorted in order of increasing value of the ZONE DOMAIN ID field.

Table 274 Zone domain descriptor

Bit Byte	7	6	5	4	3	2	1	0	
0	ZONE DOMAIN ID								
1	Reserved								
...									
15									
16	(MSB)	ZONE COUNT						(LSB)	
...									
23									
24	(MSB)	STARTING LBA						(LSB)	
...									
31									
32	(MSB)	ENDING LBA						(LSB)	
...									
39									
40	ZONE DOMAIN ZONE TYPE								
41	Reserved								
42	Reserved					VZDZT	SRB		
43	Reserved								
...									
95									

ZONE DOMAIN ID field

The ZONE DOMAIN ID field indicates the zone domain ID (see ZBC-2) associated with this zone domain.

ZONE COUNT field

The ZONE COUNT field indicates the number of zones in this zone domain.

START LBA field

The START LBA field indicates the starting LBA for this zone domain.

END LBA field

The END LBA field indicates the ending LBA for this zone domain.

ZONE DOMAIN ZONE TYPE field

The contents of the ZONE DOMAIN ZONE TYPE field depend on the value of the VZDZT bit. If the VZDZT bit is set to:

- 0** then:
 - A) the Zone Type attribute (see ZBC-2) for all zones in this zone domain may not be the same; and
 - B) the contents of the ZONE DOMAIN ZONE TYPE field are invalid;

and

- 1** then:
 - A) the Zone Type attribute for all zones in this zone domain is the same; and
 - B) the ZONE DOMAIN ZONE TYPE field indicates that zone type as described in table 280.

VZDZT bit

If the valid zone domain zone type (VZDZT) bit is set to:

- 0** then the contents of the ZONE DOMAIN ZONE TYPE field are invalid; and
- 1** then the contents of the ZONE DOMAIN ZONE TYPE field are valid.

SRB bit

- 0** indicates that realm boundaries do not shift during the processing of a ZONE ACTIVATE command (see ZBC-2).
- 1** indicates that realm boundaries may shift during the processing of a ZONE ACTIVATE command. Other realm boundary considerations are described in ZBC-2.

4.7 REPORT ZONES command (95h/00h)

The REPORT ZONE command (see table 275) requests the device server to perform open zone operations (see ZBC-2).

Table 275 REPORT ZONE command

Bit Byte	7	6	5	4	3	2	1	0	
0	OPERATION CODE (95h)								
1	Reserved			SERVICE ACTION (00h)					
2	(MSB)								
...	ZONE START LBA								
9	(LSB)								
10	(MSB)								
...	ALLOCATION LENGTH								
13	(LSB)								
14	PARTIAL	Reserved	REPORTING OPTIONS						
15	CONTROL								

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 275 for the REPORT ZONE command.

ZONE START LBA field

The ZONE START LBA field specifies an LBA in the first zone to be reported. If the ZONE START LBA field does not specify the lowest LBA of a zone, then the device server uses the lowest LBA of the zone that contains the specified LBA to specify the first zone to be reported. If the ZONE START LBA field specifies an LBA that is greater than the value in the MAXIMUM LBA field (see table 279), then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to LOGICAL BLOCK ADDRESS OUT OF RANGE.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6.

PARTIAL bit

The PARTIAL bit modifies the definition of the ZONE LIST LENGTH field as described in 4.7.1

REPORTING OPTIONS field

The REPORTING OPTIONS field (see table 276) specifies the information to be returned in the parameter data.

Table 276 REPORT ZONES REPORTING OPTIONS field

Code	Description
00h	List all of the zones in the zoned block device.
01h	List the zones with a Zone Condition of EMPTY.
02h	List the zones with a Zone Condition of IMPLICITLY OPENED.
03h	List the zones with a Zone Condition of EXPLICITLY OPENED.
04h	List the zones with a Zone Condition of CLOSED.
05h	List the zones with a Zone Condition of FULL.
06h	List the zones with a Zone Condition of READ ONLY.
07h	List the zones with a Zone Condition of OFFLINE.
08h	List the zones with a Zone Condition of INACTIVE.
09h to 0Fh	Reserved
10h	List of the zones with RWP Recommended set to true.
11h	List of the zones with Non-Sequential Write Resources Active set to true.
12h to 3Eh	Reserved
3Fh	List of the zones with a Zone Condition of NOT WRITE POINTER.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

4.7.1 REPORT ZONES parameter data

The REPORT ZONES parameter data is defined in table 277.

Table 277 REPORT ZONES parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	ZONE LIST LENGTH (n-63)							
3								
4	Reserved				SAME			
5	Reserved							
...								
7								
8	(MSB)							
...	MAXIMUM LBA							
15								
16	Reserved							
...								
63								
ZONE DESCRIPTOR LIST								
64	Zone descriptor [first]							
...								
127	...							
...								
n - 63	Zone descriptor [last]							
...								
n								

ZONE LIST LENGTH field

The ZONE LIST LENGTH field shall contain the length in bytes of the zone descriptors list. The zone descriptors list is the list of zones that:

- meet the requirements of the REPORTING OPTIONS field; and
- include the LBA specified by the ZONE START LBA field or have a lowest LBA that is greater than the LBA specified by the ZONE START LBA field.

If the PARTIAL bit is set to zero, then the content of the ZONE LIST LENGTH field is not altered based on the allocation length (see 2.2.6). If the PARTIAL bit is set to one then the ZONE LIST LENGTH field shall be set to the lesser of:

- the allocation length minus 64 if the allocation length is greater than 64;
- zero if the allocation length is less than or equal to 64; or
- the length of the zone descriptors list.

SAME field

The SAME field is defined in table 278. If the ZONE LIST LENGTH field is zero then the SAME field is invalid and should be ignored by the application client. If the last zone descriptor is an incomplete zone descriptor (e.g., as a result of the PARTIAL bit being set to one and the allocation length not being a multiple of 64), then that zone descriptor shall be included in the determination of the value of the SAME field.

Table 278 SAME field description

Code	Description
0h	The zone type and zone length in each zone descriptor may be different.
1h	The zone type and zone length in each zone descriptor are equal to the zone type and zone length indicated in the first zone descriptor in the zone descriptor list.
2h	The zone type in each zone descriptor is equal to the zone type indicated in the first zone descriptor in the zone descriptor list. The zone length of each zone except the last zone is equal to the zone length of the first zone descriptor in the zone descriptor list. The zone length of the last zone descriptor is different than the zone length of the first descriptor in the zone descriptor list.
3h	The zone type in each descriptor may be different. The zone length in each zone descriptor is equal to the zone length indicated in the first zone descriptor in the zone descriptor list.
4h to Fh	Reserved

MAXIMUM LBA field

The MAXIMUM LBA field contains the LBA of the last logical block on the logical unit.

Zone Descriptors list

The zone descriptors list contains zone descriptors that shall be sorted in ascending order based on the ZONE START LBA field of each zone descriptor.

Each zone descriptor (see table 279) contains the description of a single zone.

Table 279 Zone descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved				ZONE TYPE			
1	ZONE CONDITION				Reserved		NON_SEQ	RESET
2	Reserved							
...								
7								
8	ZONE LENGTH							
...								
15								
16	ZONE START LBA							
...								
23								
24	WRITE POINTER LBA							
...								
31								
32	Reserved							
...								
63								

ZONE TYPE field

The ZONE TYPE field indicates the Zone Type (see ZBC-2) of zone as described in table 280.

Table 280 Zone descriptor ZONE TYPE field

Code	Description
0h	Reserved
1h	CONVENTIONAL
2h	SEQUENTIAL WRITE REQUIRED
3h	SEQUENTIAL WRITE PREFERRED
4h	SEQUENTIAL OR BEFORE REQUIRED
5h	GAP
6h to Fh	Reserved

The ZONE CONDITION field indicates the Zone Condition (see ZBC-2) of the zone as described in table 281.

Table 281 Zone descriptor ZONE CONDITION field

Code	Description	The content of the WRITE POINTER LBA field is valid
0h	NOT WRITE POINTER	no
1h	EMPTY	yes
2h	IMPLICITLY OPENED	yes
3h	EXPLICITLY OPENED	yes
4h	CLOSED	yes
5h	INACTIVE	no
6h to Ch	Reserved	
Dh	READ ONLY	no
Eh	FULL	no
Fh	OFFLINE	no

NON_SEQ bit

The value of the non-sequential (NON_SEQ) bit is based on the Non-Sequential Write Resources Active zone attribute (see ZBC-2). If Non-Sequential Write Resources Active is:

- a) false, then the NON_SEQ bit shall be set to zero; or
- b) true, then the NON_SEQ bit shall be set to one.

RESET bit

The value of the RESET bit is based on the RWP Recommended zone attribute (see ZBC-2). If RWP Recommended is:

- a) false, then the RESET bit shall be set to zero; or
- b) true, then the RESET bit shall be set to one.

ZONE LENGTH field

The ZONE LENGTH field indicates the number of logical blocks in this zone.

ZONE START LBA field

The ZONE START LBA field indicates the lowest LBA in this zone.

WRITE POINTER LBA field

The WRITE POINTER LBA field indicates the starting LBA that the application client should specify in the next write command associated with this zone (i.e., the write pointer). The content of the WRITE POINTER LBA field is invalid if the content of the ZONE CONDITION field (see table 281) indicates that the WRITE POINTER LBA field is invalid.

4.8 RESET WRITE POINTER command (94h/04h)

The RESET WRITE POINTER command (see table 282) requests the device server to perform reset write pointer operations (see ZBC-2).

Table 282 RESET WRITE POINTER command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Reserved			SERVICE ACTION (04h)				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Reserved							
11	Reserved							
12	ZONE COUNT							
13	ZONE COUNT							
14	Reserved							ALL
15	CONTROL							

OPERATION CODE field and SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 282 for the RESET WRITE POINTER command.

ZONE ID field, ZONE COUNT field and ALL bit

The ZONE ID field, ZONE COUNT field, and ALL bit are defined in 4.1.2.

For a domains and realms zoned block device (see ZBC-2), the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST and the additional sense code set to RESET WRITE POINTER NOT ALLOWED, if:

- the ZONE ID field specifies an LBA that is in a zone that is associated with a Restrict Write Pointer Reset realm attribute (see ZBC-2) that is true; and
- the specified zone range, if any, includes a zone that is associated with a Restrict Write Pointer Reset realm attribute that is true.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

If the RESET WRITE POINTER command is not terminated with CHECK CONDITION status (see ZBC-2), then the device server processes the command as described in table 283.

Table 283 RESET WRITE POINTER command processing

ZONE COUNT field	ALL bit	Description
zero or one	zero	If the specified zone has a Zone Condition of: <ol style="list-style-type: none"> EMPTY, then the device server shall make no changes in the Zone Condition and not return an error; and IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or FULL, then the device server shall perform a reset write pointer zone operation (see ZBC-2) on the specified zone.
two or more	zero	For each zone in the specified zone range that has a Zone Condition of IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or FULL, the device server shall perform a reset write pointer operation.
zero	one	For each zone that has: <ol style="list-style-type: none"> a Restrict Write Pointer Reset realm attribute (see 4.4.2) that is false and a Zone Condition of IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or FULL, the device server shall perform a reset write pointer operation.
non-zero	one	See 4.1.2.

4.9 SEQUENTIALIZE ZONE command (94h/10h)

The SEQUENTIALIZE ZONE command (see table 284) requests the device server to perform sequentialize zone operations (see ZBC-2).

Table 284 SEQUENTIALIZE ZONE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (94h)							
1	Reserved			SERVICE ACTION (10h)				
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	Reserved							
11	Reserved							
12	ZONE COUNT							
13	ZONE COUNT							
14	Reserved							ALL
15	CONTROL							

OPERATION CODE and SERVICE ACTION fields

The OPERATION CODE field and the SERVICE ACTION field are defined in 2.2 and shall be set to the values shown in table 284 for the SEQUENTIALIZE ZONE command.

ZONE ID field, ZONE COUNT field and ALL bit

The ZONE ID field, ZONE COUNT field, and ALL bit are defined in 4.1.2.

The device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB, if:

- the ZONE ID field does not specify a sequential write preferred zone (see ZBC-2); and
- the specified zone range, if any, includes a zone that is not a sequential write preferred zone.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

If the SEQUENTIALIZE ZONE command is not terminated with CHECK CONDITION status (see ZBC-2), then the device server processes the command as described in table 285.

Table 285 SEQUENTIALIZE ZONE command processing

ZONE COUNT field	ALL bit	Description
zero or one	zero	If the specified zone has a Zone Condition of: <ol style="list-style-type: none"> EMPTY, then the device server shall make no changes in the Zone Condition and not return an error; and IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or FULL, then the device server shall perform a sequentialize zone operation (see ZBC-2) on the specified zone.
two or more	zero	For each zone in the specified zone range that has a Zone Condition of CLOSED, the device server shall perform a sequentialize zone operation.
zero	one	For each sequential write preferred zone (see ZBC-2) that has a Zone Condition of IMPLICITLY OPENED, EXPLICITLY OPENED, CLOSED, or FULL, the device server shall perform a sequentialize zone operation.
non-zero	one	See 4.1.2.

4.10 ZONE ACTIVATE command (95h/08h)

The ZONE ACTIVATE command (see table 286) requests that the device server perform a zone activation operation (see ZBC-2) that:

- a) changes which zones are active zones and which zones are inactive zones; and
- b) transfers the resulting parameter data.

The device server shall process each ZONE ACTIVATE command as if it has an ORDERED task attribute (see SAM-6).

Table 286 ZONE ACTIVATE command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (95h)							
1	ALL	Reserved	SERVICE ACTION (08h)					
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	(MSB)							
11	NUMBER OF ZONES							
12	(MSB)							
13	ALLOCATION LENGTH							
14	(LSB)							
15	OTHER ZONE DOMAIN ID							
	CONTROL							

OPERATION CODE field and the SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in SPC-6 and shall be set to the values shown in table 286 for the ZONE ACTIVATE command.

ALL bit

An ALL bit set to:

- 0** specifies that the zone activation operation is not requested to process all zones; and
- 1** specifies that the zone activation operation is requested to process all zones.

If the ALL bit is set to zero, the ZONE ID field specifies the lowest LBA of the write pointer zone (see ZBC-2) for which performing a zone activation operation is requested.

If the ALL bit is set to one, the ZONE ID field is ignored.

If the ALL bit is set to zero, the NUMBER OF ZONES field specifies the number of write pointer zones with LBAs greater than the zone id for which performing a zone activation operation is requested.

The device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB, if the ALL bit is set to zero

and:

- a) the NUMBER OF ZONES field is set to zero;
- b) one or more LBAs in the specified zone range is:
 - A) not contained in a write pointer zone;
 - B) associated with a Restrict Zone Activate realm attribute (see ZBC-2) that is true;
 or
- c) the AAORB bit (see 5.4.23) is set to one and the specified zone range does not:
 - A) start on a realm boundary; and
 - B) end on a realm boundary.

If the ALL bit is set to one, the NUMBER OF ZONES field is ignored.

ALLOCATION LENGTH field

The ALLOCATION LENGTH field is defined in 2.2.6. If the allocation length is less than 64, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

OTHER ZONE DOMAIN ID field

The OTHER ZONE DOMAIN ID field specifies a second zone domain, if any, for which performing a zone activation operation is requested (see 4.10.1). In some cases, the device server is able to determine all necessary zone domain information without a specified second domain. If Table 287 does not describe the OTHER ZONE DOMAIN ID field as ignored and the OTHER ZONE DOMAIN ID field contains a zone domain ID (see ZBR) that is not supported by the device server, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The parameter data returned by a ZONE ACTIVATE command is defined in 4.10.2.

The device server shall process the ZONE ACTIVATE command by:

- 1) identifying the candidate zones to activate and the candidate zones to deactivate (see 4.10.1); and
- 2) if no errors are detected in step 1, then performing a zone activation operation (see ZBC-2).

4.10.1 Identifying the candidate zones to activate and the candidate zones to deactivate

This subclause defines how a ZONE ACTIVATE command (see 4.10) or a ZONE QUERY command (see 4.11) identifies:

- a) the candidate zones to activate; and
- b) the candidate zones to deactivate.

The candidate zones to activate and the candidate zones to deactivate that are inputs to the zone activation operation (see ZBC-2).

The command fields (see 4.10) used in this subclause (i.e., 4.10.1) are:

- a) the ALL bit;
- b) the ZONE ID field;
- c) the NUMBER OF ZONES field; and
- d) the OTHER ZONE DOMAIN ID field.

Some of the command fields may be ignored by this subclause (i.e., 4.10.1) if other command fields specify that action (e.g., if the ALL bit is set to one, the NUMBER OF ZONES field is ignored).

ALL bit

An ALL bit set to:

1 then:

- a) the candidate zones to activate are all zones in the zone domain specified by the OTHER ZONE DOMAIN ID field that are associated with a Restrict Zone Activate realm attribute (see ZBC-2) that is false; and
- b) the candidate zones to deactivate are zones that are:
 - A) in any zone domain except the zone domain specified by the OTHER ZONE DOMAIN ID field; and
 - B) associated with a Restrict Zone Activate realm attribute that is false.

0 then:

- a) the specified zone range is the set of zones starting with the value of the ZONE ID field and extending for the number of zones specified by the NUMBER OF ZONES field; and
- b) Table 287 defines how the specified zone range is used to identify the candidate zones to activate and the candidate zones to deactivate.

Table 287 Selecting candidate zones to activate and deactivate with ALL bit set to zero

Zone Conditions in the specified zone range	Activation aligned on realm boundaries ^[a]	Candidate zones to activate	Candidate zones to deactivate
All specified zones are inactive zones	No	The zone domain to activate is the zone domain that contains the specified zone range. The candidate zones to activate are the zones in the specified zone range. The OTHER ZONE DOMAIN ID field is ignored.	The zone domain and the candidate zones to deactivate are determined by the device server using the specified zone range. ^[b] The device server shall select zones to deactivate that have a Zone Condition of EMPTY or INACTIVE.
	Yes		The zone domain and candidate zones with a Zone Condition of EMPTY to deactivate are determined by the device server using the realm and zone domain of the specified zone range.
All specified zones are active zones	No	The zone domain to activate is specified by the OTHER ZONE DOMAIN ID field. The candidate zones to activate in that zone domain are determined by the device server using the zone range that is specified to be deactivated. ^[c] The device server shall not select any zone to activate if that zone has a Zone Condition that is not INACTIVE.	The zone domain to deactivate is the zone domain of the specified zone range. The candidate zones to deactivate are the zones in the specified zone range.
	Yes	The zone domain to activate is specified by the OTHER ZONE DOMAIN ID field. The candidate zones with a Zone Condition of INACTIVE to activate are determined by the device server using the realm and zone domain of the zone range that is specified to be deactivated.	
Some specified zones are active zones and some specified zones are inactive zones	n/a	The candidate zones to activate are the specified zone range so that an error is able to be reported as described in ZBC-2.	
<p>a Is the AAORB bit (see clause 5.4.23) set to one?</p> <p>b The candidate zones to deactivate should include the smallest possible number of zones. There may be zero candidate zones to deactivate.</p> <p>c The candidate zones to activate should include the largest possible number of zones.</p>			

4.10.2 ZONE ACTIVATE parameter data and ZONE QUERY parameter data

The ZONE ACTIVATE parameter data and ZONE QUERY parameter data (see table 288) is returned whenever the command completes with GOOD status.

Table 288 ZONE ACTIVATE parameter data and ZONE QUERY parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	ZONE ACTIVATION RESULTS LENGTH (n-63)							
3	(LSB)							
4	(MSB)							
...	ZONE ACTIVATION RESULTS RETURNED LENGTH							
7	(LSB)							
8	NZ_VALID	ZIWUP_VALID	Reserved					ACTIVATED
9	Reserved	SECURITY	MULT DOMN	RLM RSTCT	MULT ZTYP	RLM ALIGN	NOT EMPTY	NOT INACT
10	OTHER ZONE DOMAIN ID							
11	Reserved							ALL
12	Reserved							
13	Reserved							
...	Reserved							
15	Reserved							
16	Reserved							
...	NUMBER OF ZONES							
19	Reserved							
20	Reserved							
...	Reserved							
23	Reserved							
24	Reserved							
...	ZONE ID WITH UNMET PREREQUISITE							
31	Reserved							
32	Reserved							
...	Reserved							
63	Reserved							
Zone activation descriptors list								
64	Zone activation descriptor [first] (see 4.10.3)							
...	...							
95	Zone activation descriptor [last] (see 4.10.3)							
...	...							
n - 31	Zone activation descriptor [last] (see 4.10.3)							
...	...							
n	Zone activation descriptor [last] (see 4.10.3)							

ZONE ACTIVATION RESULTS LENGTH field

The ZONE ACTIVATION RESULTS LENGTH field indicates the length in bytes of the zone activation descriptors list. The contents of the ZONE ACTIVATION RESULTS LENGTH field shall not be altered based on the allocation length (see 2.2.6).

ZONE ACTIVATION RESULTS RETURNED LENGTH field

The ZONE ACTIVATION RESULTS RETURNED LENGTH field indicates the length in bytes of the part of the zone activation descriptors list that is available for the application client to process. If the allocation length (see 2.2.6) is not sufficient to contain all of the contents of the zone activation descriptors list, then the ZONE ACTIVATION RESULTS RETURNED LENGTH field shall be altered to indicate the truncation of the zone activation descriptors list.

NZ_VALID bit

- 0** Indicates that the NUMBER OF ZONES field does not contain valid information (i.e., the ALL bit is set to one).
- 1** Indicates that the NUMBER OF ZONES field contains valid information (i.e., the ALL bit is set to zero).

ZIWUP_VALID bit

- 0** Indicates that the ZONE ID WITH UNMET PREREQUISITE field does not contain valid information.
- 1** Indicates that the ZONE ID WITH UNMET PREREQUISITE field contains valid information.

ACTIVATED bit

The ACTIVATED bit indicates:

- a) whether any zones have been activated by a change activations operation as described in ZBC-2; and
- b) what is described by each zone activation descriptor (see 4.10.3).

SECURITY, MULT DOMN, RLM RSTCT, MULT ZTYP, RLM ALIGN, NOT EMPTY, and NOT INACT bits

The SECURITY (security prerequisites) bit, MULT DOMN (multiple domains) bit, RLM RSTCT (realm restrictions) bit, MULT ZTYP (multiple zone types) bit, RLM ALIGN (realm alignment) bit, NOT EMPTY bit, and NOT INACT (not inactive) bit indicate unmet prerequisites as described in ZBC-2.

OTHER ZONE DOMAIN ID field

The OTHER ZONE DOMAIN ID field contains a copy of the OTHER ZONE DOMAIN ID field in the ZONE ACTIVATE command (see 4.10) or the ZONE QUERY command (see 4.11).

ALL bit

The ALL bit contains a copy of the ALL bit in the ZONE ACTIVATE command or the ZONE QUERY command.

NUMBER OF ZONES field

The NUMBER OF ZONES field contains a copy of the NUMBER OF ZONES field in the ZONE ACTIVATE command or the ZONE QUERY command. The NZ_VALID bit indicates whether the contents of the NUMBER OF ZONES field are valid.

ZONE ID WITH UNMET PREREQUISITE field

The ZONE ID WITH UNMET PREREQUISITE field indicates the zone ID of the lowest numbered zone associated with an unmet prerequisite. The ZIWUP_VALID bit indicates whether the contents of the ZONE ID WITH UNMET PREREQUISITE field are valid.

Each zone activation descriptor (see 4.10.3) contains information about a zone range associated with an activation or deactivation. Zone activation descriptors are not returned if the verify activations operation (see ZBC-2) detects one or more unmet prerequisites.

4.10.3 Zone activation descriptors**ACTIVATED bit**

If the ACTIVATED bit (see 4.10.2) is set to:

- 1** then each zone activation descriptor (see table 289) indicates one zone range that has been activated or deactivated by the ZONE ACTIVATE command returning that descriptor;
and
- 0** then each zone activation descriptor indicates one zone range that may be activated or deactivated by a subsequent ZONE ACTIVATE command with command inputs that are identical to those for the command that is returning that descriptor.

ALL bit

If the ALL bit (see 4.10.2) is set to zero, then zone activation descriptors are returned by a ZONE ACTIVATE command or a ZONE QUERY command (see 4.11) that:

- a) does not detect unmet prerequisites; or
- b) detects only unmet prerequisites with the result that one or more of the following bits (see 4.10.2) are set to one:

- A) the SECURITY bit;
- B) the NOT EMPTY bit; or
- C) the NOT INACT bit.

Zone activation descriptors are not returned by a ZONE ACTIVATE command or a ZONE QUERY command that:

- a) has the ALL bit set to one; or
- b) detects any unmet prerequisites with the result that one or more of the following bits (see 4.10.2) are set to one:
 - A) the MULT DOMN bit;
 - B) the RLM RSTCT bit;
 - C) the MULT ZTYP bit; or
 - D) the RLM ALIGN bit.

Table 289 shows the format of a zone activation descriptor.

Table 289 Zone activation descriptor

Bit Byte	7	6	5	4	3	2	1	0								
0	Reserved				ZONE TYPE											
1	ZONE CONDITION				Reserved											
2	ZONE DOMAIN ID															
3	Reserved															
...																
7																
8	(MSB)	ZONE RANGE SIZE						(LSB)								
...	STARTING ZONE LOCATOR															
15									(MSB)	STARTING ZONE LOCATOR						(LSB)
23									STARTING ZONE LOCATOR						(LSB)	
24	Reserved															
...																
31																

ZONE TYPE field

The ZONE TYPE field (see ZBC-2) indicates the Zone Type (see ZBC-2) for all zones described by this zone activation descriptor.

ZONE CONDITION field

The ZONE CONDITION field (see ZBC-2) indicates the Zone Type (see ZBC-2) for all zones described by this zone activation descriptor.

ZONE DOMAIN ID field

The ZONE DOMAIN ID field indicates the zone domain ID (see ZBC-2) for all zones described by this zone activation descriptor.

ZONE RANGE SIZE field

The ZONE RANGE SIZE field indicates the number of zones described by this zone activation descriptor.

STARTING ZONE LOCATOR field

The STARTING ZONE LOCATOR field indicates the lowest LBA of the first zone described by this zone activation descriptor.

4.11 ZONE QUERY command (95h/09h)

The ZONE QUERY command (see table 290) requests that the device server perform a zone activation operation (see ZBC-2) that:

- a) does not change which zones are active zones and which zones are inactive zones; and
- b) transfers the resulting parameter data.

Table 290 ZONE QUERY command

Bit Byte	7	6	5	4	3	2	1	0
0	OPERATION CODE (95h)							
1	ALL	Reserved	SERVICE ACTION (09h)					
2	(MSB)							
...	ZONE ID							
9	(LSB)							
10	(MSB)							
11	NUMBER OF ZONES							
12	(MSB)							
13	ALLOCATION LENGTH							
14	OTHER ZONE DOMAIN ID							
15	CONTROL							

OPERATION CODE field and the SERVICE ACTION field

The OPERATION CODE field and the SERVICE ACTION field are defined in SPC-6 and shall be set to the values shown in table 290 for the ZONE QUERY command.

ALL bit, ZONE ID field, NUMBER OF ZONES field, and OTHER ZONE DOMAIN ID field

The ALL bit, ZONE ID field, NUMBER OF ZONES field, and OTHER ZONE DOMAIN ID field are defined in 4.10.

CONTROL byte

The CONTROL byte is defined in 2.2.7.

The parameter data returned by a ZONE QUERY command is defined in 4.10.2.

The device server shall process the ZONE QUERY command by:

- 1) identifying the candidate zones to activate and the candidate zones to deactivate (see 4.10.2); and
- 2) if no errors are detected in step 1), then performing a zone activation operation (see ZBC-2).

If the device server processes zone activation operation for the ZONE QUERY command, then the device server shall not terminate the command with CHECK CONDITION status.

5. Parameters for direct access devices

5.1 Diagnostic parameters

5.1.1 Diagnostic page format and page codes for direct access devices

This subclause describes the diagnostic page structure and the diagnostic pages that are applicable to all SCSI devices. Diagnostic pages specific to each device type are described in the command standard that applies to that device type.

A SEND DIAGNOSTIC command with a PF bit set to one specifies that the SEND DIAGNOSTIC parameter list consists of a single diagnostic page and that the data returned by the subsequent RECEIVE DIAGNOSTIC RESULTS command that has the PCV bit set to zero shall use the diagnostic page format defined in table 291. A RECEIVE DIAGNOSTIC RESULTS command with a PCV bit set to one specifies that the device server return a diagnostic page using the format defined in table 291.

Table 291 Diagnostic page format

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE								
1	PAGE CODE SPECIFIC								
2	(MSB)	PAGE LENGTH (N-3)							
3								(LSB)	
4	DIAGNOSTIC PARAMETERS								
...									
n									

Each diagnostic page defines a function or operation that the device server shall perform as a result of a SEND DIAGNOSTIC command or the information being returned as a result of a RECEIVE DIAGNOSTIC RESULTS command with the PCV bit equal to one. The diagnostic parameters contain data that is formatted according to the page code specified.

PAGE CODE field

The PAGE CODE field identifies the diagnostic page (see table 292).

Table 292 Diagnostic page codes

Page Code	Diagnostic Page Name	Reference
00h	Supported Diagnostic Pages	5.1.2
01h - 2Fh	Defined by SES-3 for: <ul style="list-style-type: none"> a Enclosure services devices (i.e., SCSI devices with the PERIPHERAL DEVICE TYPE field set to 0Dh in standard INQUIRY data); and b SCSI devices with the ENCSERV bit set to one in standard INQUIRY data (see 3.8.2). <p>NOTE These pages are described in SES-3 these pages are passed along to any attached enclosure services device.</p>	5.1.5
30h - 3Eh	Reserved	
3Fh	See specific SCSI transport protocol for definition	SPC-6
40h	Translate Address Input diagnostic page	5.1.3
	Translate Address Output diagnostic page	5.1.4
41h	Obsolete	
42h	Rebuild Assist Input diagnostic page	5.1.6
	Rebuild Assist Output diagnostic page	5.1.7
43h - 7Fh	See specific device type for definition	
80h - FFh	Vendor specific	

PAGE LENGTH field

The PAGE LENGTH field contains the length in bytes of the diagnostic parameters that follow this field. If the application client sends a SEND DIAGNOSTIC command with a parameter list containing a PAGE LENGTH field that results in the truncation of any parameter, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

The diagnostic parameters are defined for each diagnostic page code. The diagnostic parameters within a diagnostic page may be defined differently in a SEND DIAGNOSTIC command than in a RECEIVE DIAGNOSTIC RESULTS command.

5.1.2 Supported diagnostic pages (00h)

The Supported Diagnostic Pages diagnostic page (see table 293) returns the list of diagnostic pages supported by the device server. This diagnostic page shall be implemented if the device server implements the diagnostic page format option of the SEND DIAGNOSTIC and RECEIVE DIAGNOSTIC RESULTS commands.

Table 293 Supported diagnostic pages

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (00h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (N-3)							
3								(LSB)	
4	SUPPORTED PAGE LIST								
...									
n									

The definition of this diagnostic page for the SEND DIAGNOSTIC command includes only the first four bytes. If the PAGE LENGTH field is not zero, the device server shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. This diagnostic page instructs the device server to make available the list of all supported diagnostic pages to be returned by a subsequent RECEIVE DIAGNOSTIC RESULTS command.

The definition of this diagnostic page for the RECEIVE DIAGNOSTIC RESULTS command includes the list of diagnostic pages supported by the device server.

PAGE CODE field

The PAGE CODE field is described in 5.1.1, and shall be set as shown in table 293 for Supported Diagnostics Pages diagnostic page.

PAGE LENGTH field

The PAGE LENGTH field specifies the length in bytes of the following supported page list.

SUPPORTED PAGE LIST field

The SUPPORTED PAGE LIST field shall contain a list of all diagnostic page codes, one per byte, supported by the device server in ascending order beginning with page code 00h. The supported page list may or may not include all the diagnostic pages that are able to be returned by the device server.

5.1.3 Translate Address input page (40h)

Table 294 defines the Translate Address Input diagnostic page retrieved with the RECEIVE DIAGNOSTIC RESULTS command after the Translate Address Output diagnostic page (see 5.1.4) has been sent with the SEND DIAGNOSTIC command. If a Translate Address Output diagnostic page has not yet been processed, the results of a RECEIVE DIAGNOSTIC RESULTS command requesting this diagnostic page are vendor specific.

Table 294 Translate Address page—input diagnostic page (40h)

Bit Byte	7	6	5	4	3	2	1	0								
0	PAGE CODE (40h)															
1	Reserved															
2	PAGE LENGTH (n-3)															
3									(MSB)							(LSB)
4	Reserved				SUPPLIED FORMAT											
5	RAREA	ALTSEC	ALTTK	Reserved	TRANSLATED FORMAT											
TRANSLATED ADDRESS (if available)																
6	TRANSLATED ADDRESS 1															
...									(MSB)							(LSB)
13																
...																
n-7	TRANSLATED ADDRESS x (if required)															
...									(MSB)							(LSB)
n																

PAGE CODE field

The PAGE CODE field is defined in 5.1.1 and shall be set to the value defined in Table 294.

PAGE LENGTH field

The PAGE LENGTH field is defined in 5.1.1.

SUPPLIED FORMAT field

The SUPPLIED FORMAT field contains the value from the SEND DIAGNOSTIC command supplied format field (see table 297).

RAREA (Reserved Area) bit

- 1** A Reserved Area (RAREA) bit of one indicates that all or part of the translated address falls within a reserved area of the medium (e.g., speed tolerance gap, alternate logical block, vendor reserved area, etc.). If the entire translated address falls within a reserved area the target may not return a translated address.
- 0** An RAREA bit of zero indicates that no part of the translated address falls within a reserved area of the medium.

TRANSLATED FORMAT field

The TRANSLATED FORMAT field contains the format description of the translated address(es) (see table 45).

Table 295 Address Field for Short Logical Block Address Format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	LOGICAL BLOCK ADDRESS							
3								
4	0	0	0	0	0	0	0	0
5	0	0	0	0	0	0	0	0
6	0	0	0	0	0	0	0	0
7	0	0	0	0	0	0	0	0

Table 296 Address Field for Physical Sector Address Format

Bit Byte	7	6	5	4	3	2	1	0								
0	(MSB)															
1	CYLINDER NUMBER															
2									(LSB)							
3	HEAD NUMBER															
4	SECTOR NUMBER															
...																
7																

ALTSEC (Alternate Sector) bit

- 1** An Alternate Sector (ALTSEC) bit of one indicates that the translated address is physically located in an alternate sector of the medium. If the drive cannot determine if all or part of the translated address is located in an alternate sector it shall set this bit to zero.
- 0** An ALTSEC bit of zero indicates that no part of the translated address is located in an alternate sector of the medium or that the drive is unable to determine this information.

ALTRK (Alternate Track) bit

- 1** An Alternate Track (ALTRK) bit of one indicates that part or all of the translated address is located on an alternate track of the medium or the drive cannot determine if all or part of the translated address is located on an alternate track.
- 0** An ALTRK bit of zero indicates that no part of the translated address is located on an alternate track of the medium.

TRANSLATED ADDRESS field

The TRANSLATED ADDRESS field contains the address the target translated from the address supplied by the initiator in the SEND DIAGNOSTIC command. This field shall be in the format specified in the translate format field. The supported formats are shown in Tables 295 and 296.

5.1.4 Translate Address Output diagnostic page (40h)

The Translate Address diagnostic pages allow the application client to translate an address in one of the formats supported by the FORMAT UNIT command (see 3.3.5.1) (i.e., a short block format address, a long block format address, a physical sector format address, or a bytes from index format address) into any one of the other formats. The address to be translated is sent to the device server with the SEND DIAGNOSTIC command and the results are returned to the application client by the RECEIVE DIAGNOSTIC RESULTS command.

Table 297 defines the format of the Translate Address Output diagnostic page sent with the SEND DIAGNOSTIC command. The translated address is returned in the Translate Address Input diagnostic page (see 5.1.3).

Table 297 Translate Address Output diagnostic page

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (40h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (000Ah)						(LSB)	
3									
4	Reserved				SUPPLIED FORMAT				
5	Reserved				TRANSLATE FORMAT				
6	(MSB)	ADDRESS TO TRANSLATE						(LSB)	
.....									
13									

PAGE CODE field

The PAGE CODE field is defined in 5.1.1 and shall be set to the value defined in table 297.

PAGE LENGTH field

The PAGE LENGTH field is defined in 5.1.1.

SUPPLIED FORMAT field

The SUPPLIED FORMAT field specifies the requested format of the ADDRESS TO TRANSLATE field. Valid values for this field are defined in table 45. If the device server does not support the requested format it shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

TRANSLATE FORMAT field

The TRANSLATE FORMAT field specifies the format the device server shall use for the result of the address translation. Valid values for this field are defined in the DEFECT LIST FORMAT field of the FORMAT UNIT command. If the device server does not support the specified format it shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

ADDRESS TO TRANSLATE field

The ADDRESS TO TRANSLATE field contains a single address descriptor which the application client is requesting the device server to translate. The format of this field depends on the value in the SUPPLIED FORMAT field. The formats are described in (see 3.3.5.1). If the short block format address descriptor is specified, the first four bytes of the ADDRESS TO TRANSLATE field shall contain the short block format address descriptor and the last four bytes shall contain 0000_0000h.

5.1.5 SCSI Enclosure Services pages (01h - 2Fh)

When the drive supports the SCSI Enclosure Service (SES) pages, it does not process the contents of the pages. The drive attempts to transfer the page contents to the enclosure using the Enclosure Services Interface (ESI) as directed by the command. Errors detected in the transfer are returned to the initiator in response to the command. See SCSI-3 Enclosure Services-3 (SES-3) for descriptions of the data presented in the SES pages. Reference the drive product manual to determine if the SES pages are supported.

Table 298 SCSI Enclosure Services page

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (01h - 2Fh)								
1	Page Specific								
2	(MSB)	PAGE LENGTH (n - 3)							
3								(LSB)	
4	Page Specific								
...									
n									

PAGE CODE

The PAGE CODE (01h - 2Fh) defined in SCSI Enclosure Services - 3 (SES-3) standard.

Page Specific

The Page Specific field is defined in the SCSI-3 Enclosure Services - 3 (SES-3) standard.

PAGE LENGTH

The PAGE LENGTH field is defined in (see 5.1.1).

5.1.6 Rebuild Assist Input diagnostic page (42h)

Application client sends a RECEIVE DIAGNOSTIC RESULTS command to retrieve a Rebuild Assist Input diagnostic page (see table 299), which provides information about whether the rebuild assist mode (see SBC-5) is enabled or not and a device server's rebuild assist mode capabilities.

Table 299 Rebuild Assist Input diagnostic page

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (42h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (4 + (2 x n))						(LSB)	
3									
4	Reserved							ENABLED	
5	Reserved								
6									
7	PHYSICAL ELEMENT LENGTH (n)								
8									
...	DISABLED PHYSICAL ELEMENT MASK								
7 + n									
8 + n									
...	DISABLED PHYSICAL ELEMENT								
7 + (2 x n)									

PAGE CODE field

The PAGE CODE field is defined in 5.1.1 and shall be set to the value defined in table 299.

PAGE LENGTH field

The PAGE LENGTH field is defined in 5.1.1.

ENABLED bit

- 1** An ENABLED bit set to one indicates that the rebuild assist mode is enabled.
- 0** An ENABLED bit set to zero indicates that the rebuild assist mode is disabled.

PHYSICAL ELEMENT LENGTH field

The PHYSICAL ELEMENT LENGTH field indicates the length in bytes of the DISABLED PHYSICAL ELEMENT MASK field and the length in bytes of the DISABLED PHYSICAL ELEMENT field.

DISABLED PHYSICAL ELEMENT MASK field

The bits in the DISABLED PHYSICAL ELEMENT MASK field indicate the bits in the DISABLED PHYSICAL ELEMENT field that are supported. Each bit set to one in the DISABLED PHYSICAL ELEMENT MASK field indicates that the corresponding bit in the DISABLED PHYSICAL ELEMENT field is supported and may be set to one in a Rebuild Assist Output diagnostic page sent with a SEND DIAGNOSTIC command.

DISABLED PHYSICAL ELEMENT field

The bits in the DISABLED PHYSICAL ELEMENT field indicate the physical elements that are disabled in this logical unit. Each bit set to one indicates that a physical element is disabled, and the device server shall report predicted read errors and predicted write errors for the associated group of LBAs.

5.1.7 Rebuild Assist Output diagnostic page (42h)

An application client sends a SEND DIAGNOSTIC command to send a Rebuild Assist Output diagnostic page (see table 300) that:

- a) enables or disables rebuild assist mode (see SBC-5); and/or
- b) puts the logical unit in a simulated failure mode by disabling physical elements in conjunction with rebuild assist mode (see SBC-5).

Table 300 Rebuild Assist Output diagnostic page

Bit Byte	7	6	5	4	3	2	1	0	
0	PAGE CODE (42h)								
1	Reserved								
2	(MSB)	PAGE LENGTH (4 + (2 x n))						(LSB)	
3									
4		Reserved						ENABLED	
5		Reserved							
6									
7		PHYSICAL ELEMENT LENGTH (n)							
8									
...		DISABLED PHYSICAL ELEMENT MASK							
7 + n									
8 + n									
...		DISABLE PHYSICAL ELEMENT							
7 + (2 x n)									

PAGE CODE field

The PAGE CODE field is defined in 5.1.1 and shall be set to the value defined in table 300.

PAGE LENGTH field

The PAGE LENGTH field is defined in (see 5.1.1).

ENABLED bit

- 1** The ENABLED bit set to one indicates that, after all fields in this diagnostic page have been validated:
- a self-test of the physical elements in the logical unit may be performed; and
 - rebuild assist mode is enabled.
- 0** The ENABLE bit set to zero specifies that:
- rebuild assist mode shall be disabled;
 - the other fields in this page shall be ignored; and
 - all physical elements shall be enabled (i.e., shall not simulate a predicted error response).

PHYSICAL ELEMENT LENGTH field

The PHYSICAL ELEMENT LENGTH field shall be set to the same value that is returned in the PHYSICAL ELEMENT LENGTH field in the Rebuild Assist Input diagnostic page.

If the PHYSICAL ELEMENT LENGTH field is not set to the same value that is returned in the PHYSICAL ELEMENT LENGTH field in the Rebuild Assist Input diagnostic page, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

DISABLED PHYSICAL ELEMENT MASK field

The device server shall ignore the DISABLED PHYSICAL ELEMENT MASK field.

DISABLED PHYSICAL ELEMENT field

Each bit in the DISABLE PHYSICAL ELEMENT field specifies a physical element that shall be disabled. A bit set to one in the DISABLE PHYSICAL ELEMENT field specifies that the device server shall respond to read commands and write commands specifying LBAs associated with that physical element as if the associated LBAs have predicted errors. A bit set to zero in the DISABLE PHYSICAL ELEMENT field specifies that the device servers shall not respond to read commands and write commands specifying LBAs associated with that physical element as if the associated LBAs do not have predicted errors. If the ENABLE bit is set to one, and the DISABLE PHYSICAL ELEMENT field specifies:

- any bits set to one that are not supported by the logical unit;
- all bits that are supported by the logical unit are set to one; or
- setting to zero any bits that are set to one,

then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

5.2 Log parameters

5.2.1 Summary of log page codes

The page code assignments for the log pages are listed in table 301.

Table 301 Log page codes

Page Code	Subpage Code	Log Page Name	Reference
0Fh	00h	Application Client	5.2.3
15h	00h	Background Scan	5.2.4
15h	02h	Background Operation	5.2.5
37h	00h	Cache Statistics	5.2.6
19h	20h	Cache Memory Statistics	5.2.7
19h	21h	Command Duration Limits Statistics	5.2.8
0Dh	02h	Environmental Limits	5.2.9
0Dh	01h	Environmental Reporting	5.2.10
03h	00h	Read Error Counter	5.2.11
05h	00h	Verify Error Counter	5.2.11
02h	00h	Write Error Counter	5.2.11
3Eh	00h	Factory Log	5.2.12
08h	00h	Format Status	5.2.13
2Fh	00h	Informational Exceptions	5.2.14
0Ch	00h	Logical Block Provisioning	5.2.15
06h	00h	Non-Medium Error	5.2.16
15h	01h	Pending Defects	5.2.17
1Ah	00h	Power Condition Transitions	5.2.18
18h	00h	Protocol Specific Port	5.2.19
10h	00h	Self-Test Results	5.2.20
11h	00h	Solid State Media	5.2.21
0Eh	00h	Start-Stop Cycle Counter	5.2.22
00h	00h	Supported Log Pages	5.2.23
00h	FFh	Supported Log Pages and Subpages	5.2.24
__h	FFh	Supported Subpages Log Page	5.2.25
0Dh	00h	Temperature	5.2.26
0Eh	01h	Utilization	5.2.27
14h	01h	Zoned Block Device Statistics	5.2.28

5.2.2 Log page structure

This subclause describes the log page structure and the log pages that are applicable to all SCSI devices. Log pages specific to each device type are described in the command standard that applies to that device type. The LOG SELECT command (see 3.9) supports the ability to send zero or more log pages. The LOG SENSE command (see 3.10) returns a single log page specified in the PAGE CODE field of the CDB.

5.2.2.1 Log page format

Each log page begins with a four-byte page header followed by zero or more variable-length log parameters defined for that log page. The log page format is defined in table 302.

Table 302 Log page format

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF	PAGE CODE					
1	SUBPAGE CODE							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Log parameter(s)								
4	Log parameter (First) (Length x)							
...								
x+3	...							
...								
n-y+1	Log parameter (Last) (Length y)							
...								
n								

DS (DISABLE SAVE) bit

- 0** For the LOG SENSE command (see 3.10), if the DS bit is set to zero, the log parameters are saved when the SP bit is set to one.
- 1** For the LOG SENSE command, if the DS bit is set to one, the log parameters are not saved. For the LOG SELECT command (see 3.9), the disable save (DS) bit operates in conjunction with the parameter code reset (PCR) bit, the save parameters (SP) bit, the page control (PC) field, and the PARAMETER LIST LENGTH field in the CDB.

SPF (SUBPAGE FORMAT) bit

- 0** If the SPF bit is set to zero, the SUBPAGE CODE field shall contain 00h.
- 1** If the SPF bit is set to one, the SUBPAGE CODE field shall contain a value between 01h and FFh.

PAGE CODE field

The value in the PAGE CODE field is the number of the log page being transferred.

SUBPAGE CODE field

The value in the SUBPAGE CODE field is the number of the subpage page being transferred.

If an application client specifies values in the PAGE CODE field and SUBPAGE CODE field for a log page that is reserved or not implemented by the logical unit, then the device server shall terminate the LOG SELECT command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

If the PARAMETER LIST LENGTH field in a LOG SELECT CDB contains zero, the meanings for the PCR bit, SP bit, and PC field are defined in table 80.

If the PARAMETER LIST LENGTH field in a LOG SELECT CDB contains a non-zero value (i.e., when parameter data is being sent with the LOG SELECT command), table 303 defines the meaning for the combinations of values for:

- a) the PCR bit, the SP bit, and the PC field in the LOG SELECT CDB; and
- b) the DS bit in the LOG SELECT parameter data.

Table 303 LOG SELECT PCR bit, SP bit, and DS bit meanings when parameter list length is not zero

PCR bit	SP bit	DS bit	Description
0b	0b	xb	The device server shall set the specified values to the values in the parameter list and shall not save any values to non-volatile media.
0b	1b	0b	The device server shall set the specified values to the values in the parameter list and shall process the optional saving of log parameter values as follows: <ol style="list-style-type: none"> a) If default data counter values are specified (see table 86), no values shall be saved; b) If values other than default data counter values are specified and the device server implements saving of the specified values, then the device server shall save the specified values in the parameter list to non-volatile media; or c) If values other than default values are specified and the device server does not implements saving of one or more of the specified values, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.
0b	1b	1b	The device server shall set the specified values to the values in the parameter list and shall not save any values in the specified log page to non-volatile media.
1b	xb	xb	The device server terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN CDB.
The specified parameters are determined by the format and linking field contents (see table 305) in the LOG SELECT parameter data and by the PC field contents (see table 86) in the LOG SELECT CDB.			

PAGE LENGTH field

The value in the PAGE LENGTH field is the length in bytes of the following log parameters. If the application client sends a LOG SELECT command with a log page length that results in the truncation of any parameter, the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

5.2.2.2 Log parameter format

5.2.2.2.1 Introduction

Most log pages contain one or more special data structures called log parameters (see table 304). Log parameters may be data counters of a particular event(s), the conditions under which certain operations were performed, or list parameters that contain a character string description of a particular event.

Table 304 Log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE _____							
1	_____ (LSB)							
2	PARAMETER CONTROL BYTE – (see 5.2.2.2.2)							
3	PARAMETER LENGTH (N-3)							
4	_____							
...	PARAMETER VALUE _____							
n	_____							

Each log parameter begins with a four-byte parameter header followed by one or more bytes of PARAMETER VALUE data.

PARAMETER CODE field

The PARAMETER CODE field identifies the log parameter being transferred for that log page. The device server shall return the log parameters in a log page in ascending order based on the value in their PARAMETER CODE field.

If an application client specifies a value in the PARAMETER CODE field in the LOG SELECT command parameter data that is reserved or not implemented by the logical unit, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

PARAMETER LENGTH field

The PARAMETER LENGTH field specifies the length in bytes of the PARAMETER VALUE field that follows. If the application client specifies a parameter length that results in the truncation of the PARAMETER VALUE field, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

If an application client sends a log parameter that is not supported by the logical unit, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

PARAMETER VALUE field

If the application client sends a log parameter value of the PARAMETER VALUE field that is outside the range supported by the logical unit, and rounding is implemented for that parameter, the device server may either:

- round to an acceptable value and terminate the command as described in 2.3; or
- terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

If the parameter data for one LOG SELECT command contains more than one log page and the log pages are not in ascending order by page code value then subpage code value, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

If the parameter data for one LOG SELECT command contains more than one log parameter in any one log page and the log parameters are not in ascending order by parameter code value, then the device server shall terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Application clients should send LOG SENSE commands prior to sending LOG SELECT commands to determine supported log pages and page lengths.

The SCSI target device may provide independent sets of log parameters for each logical unit or for each combination of logical units and I_T nexuses. If the SCSI target device does not support independent sets of log parameters and any log parameters are changed that affect other I_T nexuses, then the device server shall establish a unit attention condition (see SAM-6) for the initiator port associated with every I_T nexus except the I_T nexus on which the LOG SELECT command was received, with the additional sense code set to LOG PARAMETERS CHANGED.

5.2.2.2.2 Parameter control byte

5.2.2.2.2.1 Introduction

The DU bit, TSD bit, and FORMAT AND LINKING field are collectively referred to as the parameter control byte. These fields are described in this subclause.

DU (Disable Update) bit

For cumulative log parameter values, indicated by the PC field (see table 86) of the LOG SELECT command and LOG SENSE command, the disable update (DU) bit is defined as follows:

- 0** DU set to zero indicates that the device server shall update the log parameter value to reflect all events that should be noted by that parameter; or
- 1** DU set to one indicates that the device server shall not update the log parameter value except in response to a LOG SELECT command that specifies a new value for the parameter.

Note. When updating cumulative log parameter values, a device server may use volatile memory to hold these values until a LOG SELECT or LOG SENSE command is received with an SP bit set to one or a vendor specific event occurs. As a result the updated cumulative log parameter values may be lost if a power cycle occurs.

If the PC field (see table 86) indicates that threshold values or default values are being processed, the device server shall:

- a) set the DU bit to zero, if a LOG SENSE command is being processed; and
- b) ignore the DU bit, if a LOG SELECT command is being processed.

Regardless of the value in the PC field, the device server shall process ASCII format list log parameters (see 5.2.2.2.2.4) and binary format list log parameters (see 5.2.2.2.2.5) by:

- a) setting the DU bit to zero, if a LOG SENSE command is being processed; and
- b) ignoring the DU bit, if a LOG SELECT command is being processed.

TSD (Target Save Disable) bit

- 0** A target save disable (TSD) bit set to zero indicates that the logical unit implicitly saves the log parameter at vendor specific intervals. This implicit saving operation shall be done frequently enough to insure that the cumulative parameter values retain statistical significance (i.e., across power cycles).
- 1** A TSD bit set to one indicates that either the logical unit does not implicitly save the log parameter or implicit saving of the log parameter has been disabled individually by an application client setting the TSD bit to one. An application client may disable the implicit saving for all log parameters without changing any TSD bits using the GLTSD bit in the Control mode page. (see 5.3.14).

FORMAT AND LINKING field

The FORMAT AND LINKING field (see table 305) indicates the type of log parameter.

Table 305 FORMAT AND LINKING field

Code	Log parameter type	Reference
00b	Bounded data counter	5.2.2.2.2.2
01b	ASCII format list	5.2.2.2.2.4
10b	Bounded data counter or unbounded data counter	5.2.2.2.2.2 or 5.2.2.2.2.3
11b	Binary format list	5.2.2.2.2.5

5.2.2.2.2.2 Parameter control byte values for bounded data counter parameters

The device server shall return LOG SENSE parameter control byte values and process LOG SELECT parameter control byte values as shown in table 306 for any log parameter that is defined to be a bounded data counter log parameter.

Table 306 Parameter control byte values for bounded data counter parameters

Field or bit	Value for LOG SENSE	Value for LOG SELECT	Description
DU	0 or 1	0 or 1	When the DU bit is set to zero, the device server shall update the log parameter value to reflect all events that should be noted by that parameter. When the DU bit is set to one, the device server shall not update the log parameter value except in response to a LOG SELECT command that specifies a new value for the parameter.
TSD	0 or 1	0 or 1	When the TSD bit is set to zero, the device server shall save the log parameter to its medium at vendor specific intervals. When the TSD bit is set to one, implicit saving of the log parameter is disabled by an application client.
FORMAT AND LINKING	00b or 10b	00b or 10b	The log parameter is a data counter (see table 305) and the handling of a parameter that reaches its maximum value is described in this subclause.

If a LOG SELECT command contains a bounded data counter log parameter in which the parameter control byte values differ from those shown in table 306, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Each bounded data counter log parameter contains one saturating counter that is:

- a) associated with one or more events; and
- b) incremented whenever one of these events occurs.

If the counter in a bounded data counter log parameter has associated with it a vendor specific maximum value, then upon reaching this maximum value, the data counter shall not be incremented (i.e., its value does not wrap).

If the counter in a bounded data counter log parameter reaches its maximum value (i.e., saturates), the device server shall:

- a) set the DU bit to one;
 - b) handle other bounded data counter log parameters in the log page based on the contents of the FORMAT AND LINKING field in each other log parameter as follows:
 - A. if the FORMAT AND LINKING field is set to 00b, then that other log parameter shall stop incrementing until reinitialized by a LOG SELECT command; or
 - B. if the FORMAT AND LINKING field is set to 10b, then that other log parameter shall not stop incrementing, but may be reinitialized by a LOG SELECT command.
- and
- c) not alter the handling of other log parameters in the log page that are:
 - A. unbounded data counter log parameters (see 5.2.2.2.2.3);
 - B. ASCII format list log parameters (see 5.2.2.2.2.4); and
 - C. binary format list log parameters (see 5.2.2.2.2.5).

The processing of a command shall not be altered because the counter in a bounded data counter log parameter reaches its maximum value (i.e., saturates). If the RLEC bit is set to one in the Control mode page (see 5.3.14) and the processing of a command encounters no exception conditions other than the counter in a bounded data counter log parameter reaching its maximum value, then the command shall be terminated with CHECK CONDITION status, with the sense key set to RECOVERED ERROR, and the additional sense code set to LOG COUNTER AT MAXIMUM.

5.2.2.2.3 Parameter control byte values for unbounded data counter parameters

The device server shall return LOG SENSE parameter control byte values and process LOG SELECT parameter control byte values as shown in table 307 for any log parameter that is defined to be an unbounded data counter log parameter.

Table 307 Parameter control byte values for unbounded data counter parameters

Field or bit	Value for LOG SENSE	Value for LOG SELECT	Description
DU	0 or 1	0 or 1	If the DU bit is set to zero, the device server shall update the log parameter value or values to reflect all events that should be noted by that parameter. If the DU bit is set to one, the device server shall not update the log parameter value or values except in response to a LOG SELECT command that specifies a new value for the parameter.
TSD	0 or 1	0 or 1	If the TSD bit is set to zero, the device server shall save the log parameter to its medium at vendor specific intervals. If the TSD bit is set to one, implicit saving of the log parameter is disabled by an application client.
FORMAT AND LINKING	10b	10b	The log parameter is a data counter for which saturation of another log parameter does not affect the incrementing of this log parameter (see table 305).

If a LOG SELECT command contains an unbounded data counter log parameter in which the parameter control byte values differ from those shown in table 307, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Each unbounded data counter log parameter contains one or more saturating counters or wrapping counters. The description of each counter field in the log parameter defines when the device server modifies the contents of the counter that is transferred in that field.

Changes in an unbounded data counter (e.g., a counter reaching saturation or another maximum value) shall not affect the handling of other log parameters in the log page. The processing of a command and the status returned by that command shall not be altered because a counter in an unbounded data counter log parameter saturates or reaches its maximum value.

The device server shall not change the value in the DU bit in an unbounded data counter log parameter unless requested to do so by a LOG SELECT command.

5.2.2.2.4 Parameter control byte values for ASCII format list log parameters

The device server shall return LOG SENSE parameter control byte values and process LOG SELECT parameter control byte values as shown in table 308 for any log parameter that is defined to be an ASCII format (see SPC-6) list log parameter.

Table 308 Parameter control byte values for ASCII format list log parameters

Field or bit	Value for LOG SENSE	Value for LOG SELECT	Description
DU	0	ignored	The DU bit is not defined for list parameters.
TSD	0 or 1	0 or 1	If the TSD bit is set to zero, the device server shall save the log parameter to its medium at vendor specific intervals. If the TSD bit is set to one, implicit saving of the log parameter is disabled by an application client.
FORMAT AND LINKING	01b	01b	The log parameter is an ASCII format list parameter (see table 305).

If a LOG SELECT command contains an ASCII format list log parameter in which the parameter control byte values differ from those shown in table 308, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

5.2.2.2.5 Parameter control byte values for binary format list log parameters

The device server shall return LOG SENSE parameter control byte values and process LOG SELECT parameter control byte values as shown in table 309 for any log parameter that is defined to be a binary format list log parameter.

Table 309 Parameter control byte values for binary format list log parameters

Field or bit	Value for LOG SENSE	Value for LOG SELECT	Description
DU	0	ignored	The DU bit is not defined for list parameters.
TSD	0 or 1	0 or 1	If the TSD bit is set to zero, the device server shall save the log parameter to its medium at vendor specific intervals. If the TSD bit is set to one, implicit saving of the log parameter is disabled by an application client.
FORMAT AND LINKING	01b	01b	The log parameter is a binary format list parameter (see table 305).

If a LOG SELECT command contains a binary format list log parameter in which the parameter control byte values differ from those shown in table 309, then the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

5.2.2.3 Resetting and setting log parameters

In a LOG SELECT command, an application client may specify that:

- a) all the parameters in a log page or pages are to be reset (i.e., the PCR bit set to one);
or
- b) individual parameters in log page are to be changed to specified new values (i.e., the PCR bit set to zero and the PARAMETER LIST LENGTH field not set to zero).

The device server handling of these requests depends on the log parameter that is being reset or changed, and is defined in the table that defines the log parameter using the keywords defined in table 310.

Table 310 Keywords for resetting or changing log parameters

Keyword	Device server handling when	
	PCR bit is set to one ^[a]	PCR bit is set to zero [b]
Always	Reset the log parameter	Change the log parameter
Reset Only	Reset the log parameter	If any changes are requested in the parameter value field of the log parameter, then a) terminate the command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST; and b) do not make any requested changes in any field in any log parameter in any log page
Never	Do not reset the log parameter.	
<p>[a] If the PCR bit is set to one and the PARAMETER LIST LENGTH field is not set to zero. then the LOG SELECT command shall be terminated (see table 303).</p> <p>[b] If the PCR bit is set to zero and the PARAMETER LIST LENGTH field is set to zero. then no log parameters are changed (see 3.9.1).</p>		

5.2.3 Application Client log page (0Fh/00h)

The parameter codes for the Application Client log page are listed in Table 311.

Table 311 Application Client log page parameter codes

Parameter code	Description	Resettable or Changeable (PCR) [a]	Support requirements
0000h to 003Fh	General Usage Application Client	Always	Mandatory
0040h to 0FFFh			Optional
all others	Reserved		
[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.			

The Application Client log page (see table 312) provides a place for application clients to store information. The page code for the application client page is 0Fh.

Table 312 Application client log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (0Fh)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Application client log parameters								
4	First application client log parameter							
...								
...								
...								
n	Last application client log parameter							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

Parameter codes 0000h through 0FFFh are for general usage application client data. The intended use for this information is to aid in describing the system configuration and system problems, but the specific definition of the data is application client specific. The general usage application client data parameters all have the format shown in table 313.

Table 313 General usage application client parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (FCh)							
4								
...	GENERAL USAGE PARAMETER BYTES							
255								

PARAMETER CODE field

For general usage application client data, the value in the PARAMETER CODE field shall be between 0000h and 0FFFh. The first supported general usage application client parameter code shall be 0000h and additional supported parameters shall be sequentially numbered. If any general usage parameter codes are implemented, the device shall support at least 64 general usage parameter descriptors and they shall be parameter codes 0000h through 003Fh.

PARAMETER LENGTH value

For the general usage application client parameter, the PARAMETER LENGTH value for each parameter shall be FCh.

GENERAL USAGE PARAMETER BYTES

The values stored in the GENERAL USAGE PARAMETER BYTES represent data sent to the device server in a previous LOG SELECT command. If a previous LOG SELECT command has not occurred, the data is vendor specific.

5.2.4 Background Scan log page (15h/00h)

The Background Scan log page (see table 315) returns the background scanning status parameter and zero or more Medium Scan parameters when background scanning is supported. The Background Scan Status parameter provides information about background pre-scan and background medium scan operations. Each Background Scan log entry corresponds to a logical block where an error was detected. If the Background Scan log page is filled up, a new Background Scan parameter overwrites the oldest entry. When a LOG SELECT command with PCR bit set to one is processed all Background Scan parameters are deleted, however, the values in the Background Scan Status parameter shall not be affected.

Table 314 defines the parameter codes for the Background Scan log page.

Table 314 Background Scan log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Background Scan Status parameter	Never		Mandatory
0001h - 0800h	Background Scan parameter	Reset Only		Optional ^[b]
8000h - AFFFh	Vendor specific		n/a	Optional
All others	Reserved			

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.
 [b] If the Background Scan log page is supported, then at least one Background Scan log parameter shall be supported.

The Background Scan log page has the format shown in table 315.

Table 315 Background Scan log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1)	SPF (0)	PAGE CODE (15h)					
1	SUBPAGE CODE(00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Background Scan Status log parameter								
4								
...	Background Scan Status Parameter (see table 316)							
19								
Background Scan parameter list								
20	(MSB)	Background Scan parameter (first) (see table 318)						(LSB)
...								
43								
...								
n-23	(MSB)	Background Scan parameter (last) (see table 318)						(LSB)
...								
n								

The background Scan Status parameter (see table 316) contains status information about the background pre-scan and background medium scan features.

Table 316 Background Scan Status parameter format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)	PARAMETER CODE (0000h)							(LSB)
1									
2	Parameter control byte – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (0Ch)								
4	(MSB)	ACCUMULATED POWER ON MINUTES							(LSB)
...									
7									
8	Reserved								
9	BACKGROUND SCAN STATUS								
10	(MSB)	NUMBER OF BACKGROUND SCANS PERFORMED							(LSB)
11									
12	(MSB)	BACKGROUND MEDIUM SCAN PROGRESS							(LSB)
13									
14	NUMBER OF BACKGROUND MEDIUM SCANS PERFORMED								
15									

PARAMETER CODE field

For general usage application client data, the value in the PARAMETER CODE field shall be between 0000h and 0FFFh. The first supported general usage application client parameter code shall be 0000h and additional supported parameters shall be sequentially numbered. If any general usage parameter codes are implemented, the device shall support at least 64 general usage parameter descriptors and they shall be parameter codes 0000h through 003Fh.

PARAMETER LENGTH field

The PARAMETER LENGTH field indicates that number of bytes remaining in the log parameter.

ACCUMULATED POWER ON MINUTES field

The ACCUMULATED POWER ON MINUTES field indicates the number of minutes the device server has been powered on since manufacturing.

Table 317 defines the BACKGROUND SCAN STATUS field.

Table 317 Background Scan Status field

Code	Description
00h	No background scans active
01h	Background medium scan is active
02h	Background pre-scan is active
03h	Background medium scan halted due to fatal error
04h	Background medium scan halted due to a vendor-specific pattern of errors
05h	Background medium scan halted due to medium formatted without P-list
06h	Background medium scan halted - vendor-specific cause
07h	Background medium scan halted due to temperature out of allowed range
08h	Background medium scan halted, waiting for Background Medium Interval timer expiration.
09h - FFh	Reserved

NUMBER OF SCANS PERFORMED field

The NUMBER OF SCANS PERFORMED field indicates the number of background scans (i.e., the total number of background pre-scan operations plus the number of background medium scan operations) that have been performed since the SCSI target device was shipped by the manufacturer.

BACKGROUND MEDIUM SCAN PROGRESS field

The BACKGROUND MEDIUM SCAN PROGRESS field indicates the percent complete of a background scan operation in progress. The returned value is a numerator that has 65 536 (i.e., 1_0000h) as its denominator. If there is no background scan operation in progress (i.e., no background scan operation has been initiated since power on or the most recent background scan operation has completed), then the device server shall set the BACKGROUND MEDIUM SCAN PROGRESS field to 0000h.

NUMBER OF BACKGROUND MEDIUM SCAN PERFORMED field

The NUMBER OF BACKGROUND MEDIUM SCAN PERFORMED field indicates the number of background medium scan operations that have been performed since the SCSI target device was shipped by the manufacturer. If the NUMBER OF BACKGROUND MEDIUM SCAN PERFORMED field contains 0000h, then the number of background medium scan operations is not reported.

A Background Scan parameter (see table 318) describes a defect location on the medium that was encountered by background scanning.

Table 318 Background Scan parameter format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)	PARAMETER CODE (0001h - 0800h)							
1								(LSB)	
2	Parameter control byte – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (14h)								
4	(MSB)	ACCUMULATED POWER ON MINUTES							
...									
7								(LSB)	
8	REASSIGN STATUS				SENSE KEY				
9	ADDITIONAL SENSE CODE								
10	ADDITIONAL SENSE CODE QUALIFIER								
11		Vendor-specific							
...									
15									
16	Reserved								
17	Reserved								
18	(MSB)	LOGICAL BLOCK ADDRESS							
...									
23								(LSB)	

PARAMETER LENGTH field

The PARAMETER LENGTH field indicates the number of bytes remaining in the log parameter.

ACCUMULATED POWER ON MINUTES field

The ACCUMULATED POWER ON MINUTES field indicates the number of minutes the device server has been powered on since manufacturing at the time the background scan error occurred.

Table 319 defines the REASSIGN STATUS field.

Table 319 REASSIGN STATUS field

Code	LOWIR bit ^[a]		Reason	
	0	1	Original Error ^[b]	Additional conditions
1h	Yes	Yes	Recovered or unrecovered	The LBA has not yet been reassigned. ^[c]
2h	Yes	No	Recovered	The device server performed automatic read reassignment for the LBA (i.e., performed a reassign operation for the LBA and a write operation with recovered logical block data). ^[d]
4h	Yes	Yes	Recovered	The device server's attempt to perform automatic read reassignment failed. The logical block may or may not now have an uncorrectable error. ^[c]
5h	Yes	No	Recovered	The error was corrected by the device server rewriting the logical block without performing a reassign operation.
6h	Yes	Yes	Recovered or unrecovered	Either: a) an application client caused automatic write reassignment for the LBA with a command performing a write operation; or b) the LBPRZ bit is set to one in the Logical Block Provisioning VPD page (see 5.2.21), and an application client caused an unmap operation for the LBA. ^[c]
7h	Yes	Yes	Recovered or unrecovered	Either: a) an application client caused a reassign operation for the LBA with a REASSIGN BLOCKS command; or b) the LBPRZ bit is set to zero in the Logical Block Provisioning VPD page (see 5.2.21), and an application client caused an unmap operation for the LBA. ^[c]
8h	Yes	Yes	Recovered or unrecovered	An application client's request for a reassign operation for the LBA with a REASSIGN BLOCKS command failed. The logical block referenced by the LBA may or may not still have an uncorrectable error.
All others	Reserved.			

[a] Based on the LOWIR bit in the Background Control mode page (see 5.3.7), "No" specifies that a Background Scan log parameter shall not be generated for the error and "Yes" specifies that a Background Scan log parameter shall be generated for the error.

[b] Type of error detected while reading the logical block referenced by the LBA specified by the LOGICAL BLOCK ADDRESS field during a background scan operation.

[c] The REASSIGN STATUS field in a given log parameter changes from 1h or 4h to 6h, 7h, or 8h when a reassign operation, write medium operation based on the rules for caching, or unmap operation for the LBA succeeds or when a reassign operation for the LBA fails. After the LBA is reassigned, any subsequent medium error occurring for the LBA is reported in a new log parameter with the same value in the LOGICAL BLOCK ADDRESS field as the value in the LOGICAL BLOCK ADDRESS field in the log parameter for the previous medium error for the LBA.

[d] The ARRE bit in the Read-Write Error Recovery mode page (see 5.3.23) controls automatic read reassignment based on errors detected during all read operations, including those that are part of background scan operations.

SENSE KEY, ADDITIONAL SENSE CODE, and the ADDITIONAL SENSE CODE QUALIFIER fields

The SENSE KEY field, ADDITIONAL SENSE CODE field, and the ADDITIONAL SENSE CODE QUALIFIER field may contain a hierarchy of additional information relating to error conditions that occurred during background scanning. They are represented in the same format used by the sense data (see SPC-6).

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field indicates the LBA associated with the medium error.

5.2.5 Background Operation log page (15h/02h)

5.2.5.1 Background Operation log page overview

Using the format shown in table 273, the Background Operation log page reports parameters that are specific to background operations.

Table 320 Background Operation log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1)	SPF (1b)	PAGE CODE (15h)					
1	SUBPAGE CODE (02h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Background Operation parameter								
4								
...	Background Operation parameter [first] (if any)							
	...							
...	Background Operation parameter [last] (if any)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The disable save (DS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are described in 5.2.2.1.

SPF bit, PAGE CODE field, and SUBPAGE CODE field

The SPF bit, the PAGE CODE field, and the SUBPAGE CODE field shall be set to the values shown in table 320 for the Background Operation log page.

The parameter codes for the Background Operation log page are listed in table 321.

Table 321 Background Operation log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Background Operation	Never	5.2.5.2	Mandatory
All others	Reserved			

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

5.2.5.2 Background Operation log parameter

The Background Operation log parameter of the Background Operation log page has the format defined in table 322.

Table 322 Background Operation log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0000h) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (4h)							
4	BO_STATUS							
5								
...	Reserved							
n								

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 322 for the Background Operation log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 322 for the Background Operation log parameter.

BO_STATUS field

The background operation status (BO_STATUS) field indicates the type of background operation, if any, that is being performed by the device server as defined in table 323.

Table 323 BO_STATUS Definitions

Code	Description
00h	No indication
01h	No advanced background operation being performed
02h	Host initiated advanced background operation being performed
03h	Device initiated advanced background operation being performed
All others	Reserved

5.2.6 Cache Statistics page (37h/00h)

Log Page code 37h specifies Cache Statistics page. The page format is shown in Table 325.

Table 324 Parameter codes

Parameter code	Description	Resettable or Changeable [a]
0000h	This parameter code represents the number of logical blocks that have been sent to a SCSI initiator port.	Reset Only
0001h	This parameter code represents the number of logical blocks that have been received from a SCSI initiator port.	Reset Only
0002h	This parameter code represents the number of logical blocks read from the cache memory that have been sent to a SCSI initiator port.	Reset Only
0003h	This parameter code represents the number of READ and WRITE commands that had data lengths equal or less than the current segment size.	Reset Only
0004h	This parameter code represents the number of READ and WRITE commands that had data lengths greater than the current segment size.	Reset Only

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.

Table 325 Cache Statistics page (37h)

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (37h) (see 5.1.1)					
1	SUBPAGE CODE(00h) (see 5.2.2.1)							
2	(MSB)	PAGE LENGTH (see 5.1.1)						(LSB)
3								
CACHE STATISTICS LOG PARAMETERS								
4	(MSB)	PARAMETER CODE (see table 324)						(LSB)
...								
...	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
...	PARAMETER LENGTH							
...	PARAMETER VALUE							
...	...							
...	(MSB)	PARAMETER CODE (see table 324)						(LSB)
...								
...	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
...	PARAMETER LENGTH							
...	PARAMETER VALUE							
n								

5.2.7 Cache Memory Statistics log page

Using the format shown in table 328, the Cache Memory Statistics log page contains statistics and performance results identified by the parameter codes listed in table 326.

Table 326 Cache Memory Statistics log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]		Support
0001h	Read Cache Memory Hits	Reset Only	5.2.7.1	At least one ^[b]
0002h	Reads To Cache Memory	Reset Only	5.2.7.2	
0003h	Write Cache Memory Hits	Reset Only	5.2.7.3	
0004h	Writes From Cache Memory	Reset Only	5.2.7.4	
0005h	Time From Last Hard Reset	Never	5.2.7.5	
0006h	Time Interval	Never	5.2.7.6	
all others	Reserved			

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.
 [b] If the Cache Memory Statistics log page is supported, at least one of the parameter codes listed in this table shall be supported.

The Cache Memory Statistics log page provides the following statistics and performance results associated with the addressed logical unit:

- a) Cache Memory Statistics log parameters:
 - A) number of read cache memory hits;
 - B) number of reads to cache memory;
 - C) number of write cache memory hits; and
 - D) number of writes from cache memory;
- b) Hard Reset log parameter:
 - A) time from last hard reset (see SAM-5);
and
- c) Time Interval log parameter:
 - A) time interval.

In the Cache Memory Statistics log page, read commands and write commands are those shown in table 327.

Table 327 Cache Memory Statistics log page commands

Read commands ^[a]	Write commands ^[a]
READ(10) READ(12) READ(16) READ(32) PRE-FETCH(10) PRE-FETCH(16)	SYNCHRONIZE CACHE(10) SYNCHRONIZE CACHE(16) WRITE(10) WRITE(12) WRITE(16) WRITE(32) WRITE AND VERIFY(10) WRITE AND VERIFY(12) WRITE AND VERIFY(16) WRITE AND VERIFY(32)

[a] All commands in this column are defined in SBC-5.

The Cache Memory Statistics log page has the format shown in table 328.

Table 328 Cache Memory Statistics log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (19h)					
1	SUBPAGE CODE (20h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Cache memory statistics log parameter								
4	Cache memory statistics log parameter (see table 326) [first]							
...								
...								
...	Cache memory statistics log parameter (see table 326) [last]							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 328 for the Cache Memory Statistics log page.

The contents of each cache memory statistics log parameter depends on the value in its PARAMETER CODE field (see table 326).

5.2.7.1 Read Cache Memory Hits log parameter

The Read Cache Memory Hits log parameter has the format shown in table 329.

Table 329 Read Cache Memory Hits log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (0001h)						(LSB)
1								
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	(MSB)	NUMBER OF READ CACHE MEMORY HITS						(LSB)
...								
11								

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1, and shall be set as shown in table 329 for the Read Cache Memory Hits log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.1. These fields shall be set as described for a bounded data counter log parameter (see 5.2.2.2.3) for the Read Cache Memory Hits log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 329 for the Read Cache Memory Hits log parameter.

NUMBER OF READ CACHE MEMORY HITS field

The NUMBER OF READ CACHE MEMORY HITS field indicates the number of read commands (see table 327 in 5.2.7) received on an I_T nexus that resulted in:

- a) user data being read from cache memory; and
- b) no user data read from the medium before the read command being processed is completed.

The NUMBER OF READ CACHE MEMORY HITS field shall not be modified as a result of any read command that contains an FUA bit (see SBC-5) set to one or an FUA_NV bit (see SBC-2) set to one.

The contents of the NUMBER OF READ CACHE MEMORY HITS field shall be set to zero as part of processing a hard reset condition (see SAM-5).

5.2.7.2 Reads To Cache Memory log parameter

The Reads To Cache Memory log parameter has the format shown in table 330.

Table 330 Read to Cache Memory log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0002h) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD	Obsolete		FORMAT AND LINKING		
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	NUMBER OF READ TO CACHE MEMORY _____							
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1, and shall be set as shown in table 330 for the Reads To Cache Memory log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.2.1. These fields shall be set as described for a bounded data counter log parameter (see 5.2.2.2.3) for the Reads To Cache Memory log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 330 for the Reads To Cache Memory log parameter.

NUMBER OF READS TO CACHE MEMORY field

The NUMBER OF READS TO CACHE MEMORY field indicates the number of read commands (see table 327 in 5.2.7) that move user data from the medium to cache memory.

The NUMBER OF READS TO CACHE MEMORY field shall not be modified as a result of any read command that contains an FUA bit (see SBC-5) set to one or an FUA_NV bit (see SBC-2) set to one.

The contents of the NUMBER OF READS TO CACHE MEMORY field shall be set to zero as part of processing a hard reset condition (see SAM-5).

5.2.7.3 WRITE Cache Memory Hits log parameter

The Write Cache Memory Hits log parameter has the format shown in table 331.

Table 331 Write Cache Memory Hits log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0003h)							_____ (LSB)
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	NUMBER OF WRITES FROM CACHE MEMORY							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1, and shall be set as shown in table 331 for the Write Cache Memory Hits log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.1. These fields shall be set as described for a bounded data counter log parameter (see 5.2.2.2.3) for the Write From Cache Memory log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 329 for the Write Cache Memory Hits log parameter.

NUMBER OF WRITES FROM CACHE MEMORY field

The NUMBER OF WRITES FROM CACHE MEMORY field indicates the number of write commands (see table 327 in 5.2.7) received on an I_T nexus that resulted in:

- a) user data being written to cache memory; and
- b) no user data written to the medium before the write command being processed is completed.

The NUMBER OF WRITES FROM CACHE MEMORY field shall not be modified as a result of any write command that contains an FUA bit (see SBC-5) set to one or an FUA_NV bit (see SBC-2) set to one.

The contents of the NUMBER OF WRITES FROM CACHE MEMORY field shall be set to zero as part of processing a hard reset condition (see SAM-5).

5.2.7.4 Writes From Cache Memory log parameter

The Writes From Cache Memory log parameter has the format shown in table 332.

Table 332 Writes From Cache Memory log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0004h)						_____ (LSB)	
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD	Obsolete		FORMAT AND LINKING		
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	NUMBER OF WRITES FROM CACHE MEMORY							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1, and shall be set as shown in table 332 for the Writes From Cache Memory log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.1. These fields shall be set as described for a bounded data counter log parameter (see 5.2.2.2.3) for the Writes From Cache Memory log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 332 for the Writes From Cache Memory log parameter.

NUMBER OF WRITES FROM CACHE MEMORY field

The NUMBER OF WRITES FROM CACHE MEMORY field indicates the number of write commands (see table 327 in 5.2.7) that move user data from the medium from cache memory.

The NUMBER OF WRITES FROM CACHE MEMORY field shall not be modified as a result of any write command that contains an FUA bit (see SBC-5) set to one or an FUA_NV bit (see SBC-2) set to one.

The contents of the NUMBER OF WRITES FROM CACHE MEMORY field shall be set to zero as part of processing a hard reset condition (see SAM-5).

5.2.7.5 Time From Last Hard Reset log parameter

The Time From Last Hard Reset log parameter has the format shown in table 333.

Table 333 Time From Last Hard Reset log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0005h)							_____ (LSB)
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	LAST HARD RESET INTERVALS							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1, and shall be set as shown in table 343 for the Time From Last Hard Reset log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.1. These fields shall be set as described for a bounded data counter log parameter (see 5.2.2.2.3) for the Time From Last Hard Reset log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 333 for the Time From Last Hard Reset log parameter.

LAST HARD RESET INTERVALS field

The LAST HARD RESET INTERVALS field indicates the number of time intervals that have occurred since a hard reset was processed by the logical unit.

The time since a hard reset was processed by the logical unit is calculated as follows:

$$\text{time} = (\text{time intervals since last hard reset} \times \text{time interval})$$

where:

time intervals since last hard reset is the contents of the LAST HARD RESET INTERVALS field; and

time interval is the value represented in the time interval descriptor of the Time Interval log parameter (see table 334 in 5.2.7.6).

5.2.7.6 Time Interval log parameter

The Time Interval log parameter has the format shown in table 334.

Table 334 Time Interval log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE							_____ (LSB)
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
	DU	Obsolete	TSD	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Time Interval descriptor (see table 345)							
11	_____							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1.

A PARAMETER CODE field set to:

- 0003h identifies the log parameter being transferred as the Time Interval log parameter in the General Statistics and Performance log page (see SPC-6); or
- 0006h identifies the log parameter being transferred as the Time Interval log parameter in the Cache Memory Statistics log page (see 5.2.7)

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.1. These fields shall be set as described for a binary format list log parameter (see 5.2.2.2.3) for the log parameters described in this subclause.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1, and shall be set as shown in table 334 for the log parameters described in this subclause.

Time Interval descriptor

The time interval descriptor (see table 335) contains the time interval in seconds used in various time interval fields in:

- the Time From Last Hard Reset log parameter table 5.2.7.5;
- the General Access Statistics and Performance log parameter (see SPC-6);
- the Force Unit Access Statistics and Performance log parameter (see SPC-6);
- the Group n Statistics and Performance log parameter (see SPC-6); and
- the Group n Force Unit Access Statistics and Performance log parameter (see SPC-6).

Table 335 Time interval descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	EXPONENT							
3								
4	(MSB)							
...	INTEGER							
7								

EXPONENT field

The EXPONENT field contains the negative power of 10 exponent to multiply with the INTEGER field (e.g., a value of 9 represents 10^{-9}).

INTEGER field

When multiplied by the exponent, the INTEGER field contains the value that represents one time interval (e.g., a value of 5 in the INTEGER field and a value of 9 in the EXPONENT field represents a time interval of 5×10^{-9} seconds or 5 nanoseconds).

5.2.8 Command Duration Limits Statistics log page

5.2.8.1 Overview

Using the format shown in table 336, the Command Duration Limits Statistics log page contains log parameters (see table 336) that indicate the effects of the Command Duration Limit T2A mode page (see 5.3.12) and the Command Duration Limit T2B mode page (see 5.3.13).

Table 336 Command Duration Limits Statistics log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0001h	Achievable Latency Target	Never	5.2.8.2	Mandatory
0011h - 0017h	Restricted			
0021h - 0027h	Restricted			
For the Command Duration Limit T2A mode page (see 5.3.12)				
0031h	First T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0032h	Second T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0033h	Third T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0034h	Fourth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0035h	Fifth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0036h	Sixth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0037h	Seventh T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
For the Command Duration Limit T2B mode page (see 5.3.13)				
0041h	First T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0042h	Second T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0043h	Third T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0044h	Fourth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0045h	Fifth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0046h	Sixth T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
0047h	Seventh T2 command duration limit descriptor	Reset Only	5.3.12.1	See [b]
All others	Reserved			
<p>[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.</p> <p>[b] This log parameter shall be supported, if for this T2 command duration limits descriptor (see 7.5.11.2), any of the following fields have a non-zero default value or are changeable:</p> <ul style="list-style-type: none"> a) the MAX INACTIVE TIME field; or b) the MAX ACTIVE TIME field. 				

The Command Duration Limits Statistics log page has the format shown in table 337.

Table 337 Command Duration Limits Statistics log page

Bit Byte	7	6	5	4	3	2	1	0	
0	DS	SPF (1b)	PAGE CODE (19h)						
1	SUBPAGE CODE (21h)								
2	(MSB)	PAGE LENGTH (n-3)							
3								(LSB)	
Command duration limits statistics log parameter									
4	Command duration limits statistics log parameter [first] (see table 336)								
...									
	...								
...	Command duration limits statistics log parameter [last] (see table 336)								
n									

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 337 for the Command Duration Limits Statistics log page.

Command duration limits statistics log parameter

The contents of each command duration limits statistics log parameter depends on the value in its PARAMETER CODE field (see table 336).

5.2.8.2 Achievable Latency Target log parameter

The Achievable Latency Target log parameter has the format shown in table 338.

Table 338 Achievable Latency Target log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0001h) _____							
1	(LSB)							
2	PARAMETER CONTROL BYTE – unbounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD (1b)	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (04h)							
4	(MSB) _____							
...	NUMBER OF READ COMMANDS _____							
9	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 338 for the Achievable Latency Target log parameters.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.2.1. The DU bit and FORMAT AND LINKING field shall be set as described for an unbounded data counter log parameter (see 5.2.2.2.2.3) for the Achievable Latency Target parameter. The TSD bit shall be set as shown in table 348 for the Achievable Latency Target log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 338 for the Achievable Latency Target log parameter.

ACHIEVABLE LATENCY TARGET field

At the time the LOG SENSE command (see 3.10) is processed, the ACHIEVABLE LATENCY TARGET field indicates the lowest achievable value for any REQUESTED LATENCY TARGET field (see 5.3.12.1) in the Command Duration Limit T2A mode page (see 5.3.12) and the Command Duration Limit T2B mode page (see 5.3.13). The contents of the ACHIEVABLE LATENCY TARGET field are measured in microseconds (i.e., the value contained in the REQUESTED LATENCY TARGET field if the T2CDLUNITS field 5.3.12.1 is set to 100b).

Factors that affect the ACHIEVABLE LATENCY TARGET field include:

- a) the contents of the PERFORMANCE VERSUS LATENCY CONTROLS field 5.3.12;
- b) The contents of all non-zero REQUESTED LATENCY TARGET fields and their associated:
 - A) PREDICTIVE MISS POLICY fields;
 - B) LATENCY MISS POLICY fields;
 - C) NONCONFORMANCE POLICY fields; and
 - D) CONFORMANCE TARGET fields;
- c) the commands being processed by the device server;
- d) data transfer errors, if any, processed by the device server; and
- e) the background activities, if any, being performed by the device server.

The ACHIEVABLE LATENCY TARGET field may be set to zero, if:

- a) all REQUESTED LATENCY TARGET fields are set to zero; or
- b) the number data transfer commands processed by the device server are not sufficient to determine an achievable latency target.

5.2.8.3 Command Duration Limits T2A or T2B log parameter

A Command Duration Limit T2A or T2B log parameter has the format shown in table 349.

Table 339 Command Duration Limits T2A or T2B log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (see table 336) _____ (LSB)							
2	PARAMETER CONTROL BYTE – unbounded data counter log parameter (see 5.2.2.2.3)							
	DU	Obsolete	TSD (1b)	Obsolete			FORMAT AND LINKING	
3	PARAMETER LENGTH (10h) _____							
4	(MSB) _____							
...	NUMBER OF INACTIVE TARGET MISS COMMANDS							
7	_____ (LSB)							
8	(MSB) _____							
...	NUMBER OF ACTIVE TARGET MISS COMMANDS							
11	_____ (LSB)							
12	(MSB) _____							
...	NUMBER OF INACTIVE TARGET AND ACTIVE TARGET MISS COMMANDS							
15	_____ (LSB)							
16	(MSB) _____							
...	NUMBER OF COMMANDS							
19	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 339 for a command duration limit log parameter.

DU bit, TSD bit, and FORMAT AND LINKING field

The DU bit, TSD bit, and FORMAT AND LINKING field are described in 5.2.2.2.2.1. The DU bit and FORMAT AND LINKING field shall be set as described for an unbounded data counter log parameter (see 5.2.2.2.3) for a command duration limit log parameter. The TSD bit shall be set as shown in table 339 for a Command Duration Limits log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 348 for a command duration limit parameter.

NUMBER OF INACTIVE TARGET MISS COMMANDS field

The NUMBER OF INACTIVE TARGET MISS COMMANDS field indicates the number of commands for which the MAX INACTIVE TIME POLICY field (see 5.3.12.1) was processed.

NUMBER OF ACTIVE TARGET MISS COMMANDS field

The NUMBER OF ACTIVE TARGET MISS COMMANDS field indicates the number of commands for which the MAX ACTIVE TIME POLICY field (see 5.3.12.1) was processed.

NUMBER OF INACTIVE TARGET AND ACTIVE TARGET MISS COMMANDS field

The NUMBER OF INACTIVE TARGET AND ACTIVE TARGET MISS COMMANDS field indicates the sum of the number of commands for which the MAX INACTIVE TIME POLICY field was processed and the number of commands for which the MAX ACTIVE TIME POLICY field was processed.

NUMBER OF COMMANDS field

The NUMBER OF COMMANDS field indicates the number of commands processed using the associated command duration limits descriptor.

5.2.9 Environmental Limits log page (0Dh/02h)

5.2.9.1 Overview

Using the format shown in table 341, the Environmental Limits log page provides information about the environmental limits of the logical unit using the parameter codes listed in table 340.

The Environmental Reporting log page (see 5.2.10) shall be supported if the Environmental Limits log page is supported. Each log parameter in the Environmental Limits log page contains limits that are applied to the environmental measurement in the log parameter in the Environmental Reporting log page that has the same parameter code (e.g., parameter 0000h in this log page is associated with log parameter 0000h in the Environmental Reporting log page).

Table 340 Environmental Limits log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h - 00FFh	Temperature Limits ^[c]	Always or Never ^[b]	5.2.9.2	Optional
0100h - 01FFh	Relative Humidity Limits ^[d]	Always or Never ^[b]	5.2.9.3	Optional
All others	Reserved			

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.

[b] The device server may support either Always or Never. If supporting Always, then the device server may round each field up or down as defined in 2.3.

[c] If more than one Temperature Limits parameter is supported, each Temperature Limits parameter is associated with the temperature at a separate location.

[d] If more than one Relative Humidity Report parameter is supported, each Relative Humidity Limits parameter is associated with the relative humidity at a separate location.

The Environmental Limits log page has the format shown in table 341.

Table 341 Environmental Limits log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (0Dh)					
1	SUBPAGE CODE (02h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3	Environmental Limits log parameter							
4	Environmental Limits log parameter [first] (if any)							
...	...							
...	Environmental Limits log parameter [last] (if any)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 341 for the Environmental Limits log page.

The contents of each environmental limits log parameter depends on the value in its PARAMETER CODE field (see table 340).

5.2.9.2 Temperature Limits log parameter

The Temperature Limits log parameter has the format shown in table 342.

Table 342 Temperature Limits log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (see table 340)						(LSB)
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	HIGH CRITICAL TEMPERATURE LIMIT TRIGGER							
5	HIGH CRITICAL TEMPERATURE LIMIT RESET							
6	LOW CRITICAL TEMPERATURE LIMIT RESET							
7	LOW CRITICAL TEMPERATURE LIMIT TRIGGER							
8	HIGH OPERATING TEMPERATURE LIMIT TRIGGER							
9	HIGH OPERATING TEMPERATURE LIMIT RESET							
10	LOW OPERATING TEMPERATURE LIMIT RESET							
11	LOW OPERATING TEMPERATURE LIMIT TRIGGER							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 340 for the Temperature Limits log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 342 for the Temperature Limits log parameters.

The temperature values reported in the Temperature Limits log parameters indicate a temperature in degrees Celsius. Negative values shall be indicated by two's complement notation. A value of -128 (i.e., 80h) specifies that there is no limit.

HIGH CRITICAL TEMPERATURE LIMIT TRIGGER field

The HIGH CRITICAL TEMPERATURE LIMIT TRIGGER field indicates the maximum temperature at this sensor for which the logical unit should be operated. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current temperature (see 5.2.10.2) is greater than the value in the HIGH CRITICAL TEMPERATURE LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - HIGH CRITICAL TEMPERATURE LIMIT EXCEEDED.

HIGH CRITICAL TEMPERATURE LIMIT RESET field

The HIGH CRITICAL TEMPERATURE LIMIT RESET field indicates the temperature at which the informational exception condition for a high critical temperature limit, if any, shall be cleared.

LOW CRITICAL TEMPERATURE LIMIT RESET field

The LOW CRITICAL TEMPERATURE LIMIT RESET field indicates the temperature at which the informational exception condition for a low critical temperature limit, if any, shall be cleared.

LOW CRITICAL TEMPERATURE LIMIT TRIGGER field

The LOW CRITICAL TEMPERATURE LIMIT TRIGGER field indicates the minimum temperature at this sensor for which the logical unit should be operated. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current temperature (see 5.2.10.2) is less than the value in the LOW CRITICAL TEMPERATURE LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - LOW CRITICAL TEMPERATURE LIMIT EXCEEDED.

HIGH OPERATING TEMPERATURE LIMIT TRIGGER field

The HIGH OPERATING TEMPERATURE LIMIT TRIGGER field indicates the maximum temperature at this sensor for which the logical unit is capable of operating continuously without degrading the reliability beyond manufacturer accepted limits. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current temperature (see 5.2.10.2) is greater than the

value of the HIGH OPERATING TEMPERATURE LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - HIGH OPERATING TEMPERATURE LIMIT EXCEEDED.

HIGH OPERATING TEMPERATURE LIMIT RESET field

The HIGH OPERATING TEMPERATURE LIMIT RESET field indicates the temperature at which the informational exception condition for the associated high critical temperature limit, if any, shall be cleared.

LOW OPERATING TEMPERATURE LIMIT RESET field

The LOW OPERATING TEMPERATURE LIMIT RESET field indicates the temperature at which the informational exception condition for the associated low critical temperature limit, if any, shall be cleared.

LOW OPERATING TEMPERATURE LIMIT TRIGGER field

The LOW OPERATING TEMPERATURE LIMIT TRIGGER field indicates the minimum temperature at this sensor for which the logical unit is capable of operating continuously without degrading the logical unit's reliability beyond manufacturer accepted limits. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current temperature (see 5.2.10.2) is less than the value of the LOW OPERATING TEMPERATURE LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - LOW OPERATING TEMPERATURE LIMIT EXCEEDED.

5.2.9.3 Relative Humidity Limits log parameter

The Relative Humidity Limits log parameter has the format shown in table 343.

Table 343 Relative Humidity Limits log parameter

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) _____							PARAMETER CODE (see table 340)	
1								_____ (LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (08h)								
4	HIGH CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER								
5	HIGH CRITICAL RELATIVE HUMIDITY LIMIT RESET								
6	LOW CRITICAL RELATIVE HUMIDITY LIMIT RESET								
7	LOW CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER								
8	HIGH OPERATING RELATIVE HUMIDITY LIMIT TRIGGER								
9	HIGH OPERATING RELATIVE HUMIDITY LIMIT RESET								
10	LOW OPERATING RELATIVE HUMIDITY LIMIT RESET								
11	LOW OPERATING RELATIVE HUMIDITY LIMIT TRIGGER								

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 340 for the Temperature Limits log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 343 for the Temperature Limits log parameters.

The relative humidity limit values used in the Relative Humidity Limits log parameters are shown in table 350.

Table 344 Relative humidity limit values

Value	Description
0 to 100	Relative humidity
101 to 254	Reserved
255	No relative humidity limit

HIGH CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field

The HIGH CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field indicates the maximum relative humidity at this sensor for which the logical unit should be operated. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current relative humidity (see 5.2.9.3) is greater than the value in the HIGH CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - HIGH CRITICAL HUMIDITY LIMIT EXCEEDED.

HIGH CRITICAL RELATIVE HUMIDITY LIMIT RESET field

The HIGH CRITICAL RELATIVE HUMIDITY LIMIT RESET field indicates the relative humidity at which the informational exception condition for a high critical relative humidity limit, if any, shall be cleared.

LOW CRITICAL RELATIVE HUMIDITY LIMIT RESET field

The LOW CRITICAL RELATIVE HUMIDITY LIMIT RESET field indicates the relative humidity at which the informational exception condition for a low critical relative humidity limit, if any, shall be cleared.

LOW CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field

The LOW CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field indicates the minimum relative humidity at this sensor for which the logical unit should be operated. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current relative humidity (see 5.2.9.3) is less than the value in the LOW CRITICAL RELATIVE HUMIDITY LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - LOW CRITICAL HUMIDITY LIMIT EXCEEDED.

HIGH OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field

The HIGH OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field indicates the maximum relative humidity at this sensor for which the logical unit is capable of operating continuously without degrading the reliability beyond manufacturer accepted limits. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current relative humidity (see 5.2.9.3) is greater than the value of the HIGH OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - HIGH OPERATING HUMIDITY LIMIT EXCEEDED.

HIGH OPERATING RELATIVE HUMIDITY LIMIT RESET field

The HIGH OPERATING RELATIVE HUMIDITY LIMIT RESET field indicates the relative humidity at which the informational exception condition for the associated high critical relative humidity limit, if any, shall be cleared.

LOW OPERATING RELATIVE HUMIDITY LIMIT RESET field

The LOW OPERATING RELATIVE HUMIDITY LIMIT RESET field indicates the relative humidity at which the informational exception condition for the associated low critical relative humidity limit, if any, shall be cleared.

LOW OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field

The LOW OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field indicates the minimum relative humidity at this sensor for which the logical unit is capable of operating continuously without degrading the logical unit's reliability beyond manufacturer accepted limits. If the EWASC bit is set to one in the Information Exceptions Control mode page (see SBC-5, SSC-4, or SMC-3) and the associated current relative humidity (see 5.2.9.3) is less than the value of the LOW OPERATING RELATIVE HUMIDITY LIMIT TRIGGER field, then the device server shall report an informational exception condition with the additional sense code set to WARNING - LOW OPERATING HUMIDITY LIMIT EXCEEDED.

5.2.10 Environmental Reporting log page (0Dh/01h)

5.2.10.1 Overview

Using the format shown in table 346, the Environmental Reporting log page provides information about the environmental conditions of the logical unit using the parameter codes listed in table 345.

Table 345 Environmental Reporting log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support
0000h - 00FFh	Temperature Report ^[c]	Never	5.2.10.2	At least one ^[b]
0100h - 01FFh	Relative Humidity Report ^[d]	Never	5.2.9.3	Optional
All others	Reserved			

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.

[b] If the Environmental Reporting log page is supported, at least one of the parameter codes listed in this table shall be supported.

[c] If more than one Temperature Report parameter is supported, then each Temperature Report parameter represents the temperature at a separate location.

[d] If more than one Relative Humidity Report parameter is supported, then each Relative Humidity Report parameter represents the temperature at a separate location.

The Environmental Reporting log page has the format shown in table 346.

Table 346 Environmental Reporting log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (0Dh)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Environmental Reporting log parameter								
4								
...	Environmental Reporting log parameter [first] (if any)							
	...							
...	Environmental Reporting log parameter [last] (if any)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 346 for the Environmental Reporting log page.

The contents of each environmental reporting log parameter depends on the value in its PARAMETER CODE field (see table 345).

5.2.10.2 Temperature Report log parameter

The Temperature Report log parameter has the format shown in table 347.

Table 347 Temperature Report log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (see table 340)						(LSB)
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	Reserved							
5	TEMPERATURE							
6	LIFETIME MAXIMUM TEMPERATURE							
7	LIFETIME MINIMUM TEMPERATURE							
8	MAXIMUM TEMPERATURE SINCE POWER ON							
9	MINIMUM TEMPERATURE SINCE POWER ON							
10	Reserved							
11	Reserved							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 345 for the Temperature Report log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 347 for the Temperature Report log parameters.

The temperature values reported in the Temperature Report log parameters indicate a temperature in degrees Celsius. Negative values shall be indicated by two's complement notation. A value of -128 (i.e., 80h) specifies that temperature is not valid.

TEMPERATURE field

The TEMPERATURE field indicates the most recently detected temperature by the temperature sensor associated with this log parameter.

LIFETIME MAXIMUM TEMPERATURE field

The LIFETIME MAXIMUM TEMPERATURE field indicates the maximum temperature detected by the temperature sensor associated with this log parameter since the time of manufacture.

LIFETIME MINIMUM TEMPERATURE field

The LIFETIME MINIMUM TEMPERATURE field indicates the minimum temperature detected by the temperature sensor associated with this log parameter since the time of manufacture.

MAXIMUM TEMPERATURE SINCE POWER ON field

The MAXIMUM TEMPERATURE SINCE POWER ON field indicates the maximum temperature detected by the temperature sensor associated with this log parameter since the most recent power on.

MINIMUM TEMPERATURE SINCE POWER ON field

The MINIMUM TEMPERATURE SINCE POWER ON field indicates the minimum temperature detected by the temperature sensor associated with this log parameter since the most recent power on.

5.2.10.3 Relative Humidity Report log parameter

The Relative Humidity Report log parameter has the format shown in table 348.

Table 348 Relative Humidity Report log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (see table 340)						(LSB)
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	Reserved							
5	RELATIVE HUMIDITY							
6	LIFETIME MAXIMUM RELATIVE HUMIDITY							
7	LIFETIME MINIMUM RELATIVE HUMIDITY							
8	MAXIMUM RELATIVE HUMIDITY SINCE POWER ON							
9	MINIMUM RELATIVE HUMIDITY SINCE POWER ON							
10	Reserved							
11	Reserved							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 345 for the Relative Humidity Report log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 348 for the Relative Humidity Report log parameters.

The relative humidity limit values used in the Relative Humidity Limits log parameters are shown in table 349.

Table 349 Relative humidity reporting values

Value	Description
0 to 100	Relative humidity
101 to 254	Reserved
255	No valid relative humidity

RELATIVE HUMIDITY field

The RELATIVE HUMIDITY field indicates the most recently detected relative humidity for the humidity sensor associated with this log parameter.

LIFETIME MAXIMUM RELATIVE HUMIDITY field

The LIFETIME MAXIMUM RELATIVE HUMIDITY field indicates the maximum relative humidity detected by the humidity sensor associated with this log parameter since the time of manufacture.

LIFETIME MINIMUM RELATIVE HUMIDITY field

The LIFETIME MINIMUM RELATIVE HUMIDITY field indicates the minimum relative humidity detected by the humidity sensor associated with this log parameter since the time of manufacture.

MAXIMUM RELATIVE HUMIDITY SINCE POWER ON field

The MAXIMUM RELATIVE HUMIDITY SINCE POWER ON field indicates the maximum relative humidity detected by the humidity sensor associated with this log parameter since the most recent power on.

MINIMUM RELATIVE HUMIDITY SINCE POWER ON field

The MINIMUM RELATIVE HUMIDITY SINCE POWER ON field indicates the minimum relative humidity detected by the humidity sensor associated with this log parameter since the most recent power on.

5.2.11 Error counter log pages (WRITE, READ, and VERIFY)

This subclause defines the error counter log pages (see table 350).

Table 350 Error counter log page codes

Page Code	Loge Page Name
03h / 00h	Read Error Counter
05h / 00h	Verify Error Counter
02h / 00h	Write Error Counter

Table 351 defines the parameter codes for the error counter log pages.

Table 351 Parameter codes for error counter log pages

Parameter code	Description	Resettable or Changeable [a]
0000h	Errors corrected without substantial delay. An error correction was applied to get perfect data (a.k.a., ECC on-the-fly). "Without Substantial Delay" means the correction did not postpone reading of later sectors (e.g., a revolution was not lost). The counter is incremented once for each logical block that requires correction. Two different blocks corrected during the same command are counted as two events.	Reset Only
0001h	Errors corrected with possible delays. An error code or algorithm (e.g., ECC, checksum) is applied in order to get perfect data with substantial delay. "With possible delay" means the correction took longer than a sector time so that reading/writing of subsequent sectors was delayed (e.g., a lost revolution). The counter is incremented once for each logical block that requires correction. A block with a double error that is correctable counts as one event and two different blocks corrected during the same command count as two events.	Reset Only
0002h	Total (e.g., rewrites or rereads). This parameter code specifies the counter counting the number of errors that are corrected by applying retries. This counts errors recovered, not the number of retries. If five retries were required to recover one block of data, the counter increments by one, not five. The counter is incremented once for each logical block that is recovered using retries. If an error is not recoverable while applying retries and is recovered by ECC, it isn't counted by this counter; it will be counted by the counter specified by parameter code 01h—Error Corrected With Possible Delay.	Reset Only
0003h	Total errors corrected. This counter counts the total of parameter code errors 00h, 01h, and 02h. There is to be no "double counting" of data errors among these three counters. The sum of all correctable errors can be reached by adding parameter code 01h and 02h errors, not by using this total.	Reset Only
0004h	Total times correction algorithm processed. This parameter code specifies the counter that counts the total number of retries, or "times the retry algorithm is invoked." If after five attempts a counter 02h type error is recovered, then five is added to this counter. If three retries are required to get a stable ECC syndrome before a counter 01h type error is corrected, then those three retries are also counted here. The number of retries applied to unsuccessfully recover an error (counter 06h type error) are also counted by this counter.	Reset Only
0005h	Total bytes processed. This parameter code specifies the counter that counts the total number of bytes either successfully or unsuccessfully read, written, or verified (depending on the log page) from the drive. If a transfer terminates early because of an unrecoverable error, only the logical blocks up to and including the one with the unrecoverable error are counted.	Reset Only
0006h	Total uncorrected errors. This parameter code specifies the counter that contains the total number of blocks for which an uncorrected data error has occurred.	Reset Only
0007h - 7FFFh	Reserved	Reset Only
8000h - FFFFh	Vendor specific	Reset Only

[a] The keywords in this column -- Always, Reset Only, and Never -- are defined in 5.2.2.3.

The exact definition of the error counters is not part of this manual. These counters should not be used to compare products because the products may define errors differently.

Table 352 Error counter log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1)	SPF (0)	PAGE CODE (see table 350)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Error counter log parameter								
4	(MSB)	PARAMETER CODE (see table 351)						(LSB)
...								
...	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.2)							
...	PARAMETER LENGTH							
...	PARAMETER VALUE							
...								
Error counter log parameter								
...	(MSB)	PARAMETER CODE (see table 351)						(LSB)
...								
...	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.2)							
...	PARAMETER LENGTH							
n	PARAMETER VALUE							

The log page format is defined in 5.2.2. A log page may return one or more log parameters that record events defined by the parameter codes.

5.2.12 Factory Log page (3Eh/00h)

Log page code 3Eh specifies factory status parameters (see table 353).

Table 353 Factory Log page (3Eh)

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (3Eh)					
1	SUBPAGE CODE(00h)							
2	(MSB)	PAGE LENGTH						(LSB)
3								
4	(MSB)	PARAMETER CODE ^[1] ^[2]						(LSB)
...								
...	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
...	PARAMETER LENGTH							
...	PARAMETER VALUE							
...	...							
...	(MSB)	PARAMETER CODE						(LSB)
...								
...	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
...	PARAMETER LENGTH							
...	PARAMETER VALUE							
n								

[1] PARAMETER CODE 0000h–Power-on Time. This parameter code represents the number of drive power-on minutes.

[2] PARAMETER CODE 08h. This parameter reports the time, in minutes, to the next scheduled interrupt for a S.M.A.R.T. measurement.

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

5.2.13 Format Status log page (08h/00h)

5.2.13.1 Format Status log page overview

Using the format shown table 175, the Format Status log page reports information about the most recent successful format operation and the state of the direct access block device since that operation was performed. The parameter codes for the Format Status log page are listed in table 354.

Table 354 Format Status log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Format Data Out	Never	5.2.10.2	Mandatory
0001h	Grown Defects During Certification	Never	5.2.9.3	Mandatory
0002h	Total Blocks Reassigned During Format	Never	5.2.10.2	Mandatory
0003h	Total New Blocks Reassigned	Never	5.2.9.3	Mandatory
0004h	Power On Minutes Since Format	Never	5.2.10.2	Mandatory
0005h - 7FFFh	Reserved			
8000h - FFFFh	Vendor Specific			Optional

[a] The keywords in this column-- Always, Reset Only, and Never -- are defined in 5.2.2.3.

The Format Status log page has the format defined in table 355.

Table 355 Format Status log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1b)	SPF (0b)	PAGE CODE (08h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Format Status log parameter								
4	Format Status log parameter [first] (if any)							
...								
...								
...	Format Status log parameter [last] (if any)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The DS bit, the SPF bit, the PAGE CODE field, and the SUBPAGE CODE field shall be set to the values shown in table 355 for the Format Status log page.

If a format operation has never been performed by the logical unit, then the log parameter for each Format Status log parameter listed in table 354 is not defined by this standard. If a device server begins a format operation, then the device server shall set each byte of the log parameter data (i.e., bytes four to n of the log parameter), if any, to FFh for each Format Status log parameter (e.g., if the PARAMETER LENGTH field is set to 02h, then the log parameter data is set to FFFFh).

If the most recent format operation failed or the information for a Format Status log parameter is not available, then the device server shall return FFh in each byte of the log parameter data (i.e., bytes four to n of the log parameter), if any, for the Format Status log parameter (e.g., if the PARAMETER LENGTH field is set to 04h, then the log parameter data shall be set to FFFF_FFFFh). The device server shall set each Format Status log parameter to be a multiple of four bytes.

5.2.13.2 Format Data Out log parameter

The Format Data Out log parameter of the Format Status log page has the format defined in table 356.

Table 356 Format Data Out log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0000h)							_____ (LSB)
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (n-3)							
4	(MSB) _____							
...	FORMAT DATA OUT							
n	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 356 for the Format Data Out log parameter.

TSD bit

The target save disable (TSD) bit (see SPC-6) shall be set to zero for the Format Data Out log parameter, indicating that the logical unit saves the Format Data Out log parameter at vendor specific intervals without any request from an application client.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 356 for the Format Data Out log parameter.

FORMAT DATA OUT field

After a successful format operation, the FORMAT DATA OUT field contains the FORMAT UNIT parameter list (see table 39).

5.2.13.3 Grown Defects During Certification log parameter

The Grown Defects During Certification log parameter for the Format Status log page has the format defined in table 357.

Table 357 Grown Defects During Certification log parameter format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) _____							PARAMETER CODE (0001h)	
1								_____ (LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (08h)								
4	(MSB) _____							GROWN DEFECTS DURING CERTIFICATION	
...									
n								_____ (LSB)	

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 357 for the Grown Defects During Certification log parameter.

TSD bit

The target save disable (TSD) bit (see SPC-6) shall be set to zero for the Grown Defects During Certification log parameter, indicating that the logical unit saves the Grown Defects During Certification log parameter at vendor specific intervals without any request from an application client.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 357 for the Grown Defects During Certification log parameter.

GROWN DEFECTS DURING CERTIFICATION field

After a successful format operation during which certification was performed, the GROWN DEFECTS DURING CERTIFICATION field shall indicate the number of defects detected as a result of performing the certification. The value in the GROWN DEFECTS DURING CERTIFICATION field count reflects only those defects detected and replaced during the successful format operation that were not already part of the PLIST or GLIST.

After a successful format operation during which certification was not performed, the GROWN DEFECTS DURING CERTIFICATION field shall be set to zero.

5.2.13.4 Total Blocks Reassigned During Format log parameter

The Grown Defects During Certification log parameter for the Format Status log page has the format defined in table 358.

Table 358 Total Blocks Reassigned During Format log parameter format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) _____							PARAMETER CODE (0002h)	
1								_____ (LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (08h)								
4	(MSB) _____							TOTAL BLOCKS REASSIGNED DURING FORMAT	
...									
n								_____ (LSB)	

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 358 for the Total Blocks Reassigned During Format log parameter.

TSD bit

The target save disable (TSD) bit (see SPC-6) shall be set to zero for the Total Blocks Reassigned During Format log parameter, indicating that the logical unit saves the Total Blocks Reassigned During Format log parameter at vendor specific intervals without any request from an application client.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 358 for the Total Blocks Reassigned During Format log parameter.

TOTAL BLOCKS REASSIGNED DURING FORMAT field

The TOTAL BLOCKS REASSIGNED DURING FORMAT field contains the count of the total number of logical blocks that were reassigned during the most recent successful format operation.

5.2.13.5 Total New Blocks Reassigned log parameter

The Total New Blocks Reassigned log parameter for the Format Status log page has the format defined in table 359.

Table 359 Total New Blocks Reassigned log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0003h) _____							
1	(LSB)							
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	TOTAL NEW BLOCKS REASSIGNED _____							
n	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 359 for the Total New Blocks Reassigned log parameter.

TSD bit

The target save disable (TSD) bit (see SPC-6) shall be set to zero for the Total New Blocks Reassigned log parameter, indicating that the logical unit saves the Total New Blocks Reassigned log parameter at vendor specific intervals without any request from an application client.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 359 for the Total New Blocks Reassigned log parameter.

TOTAL NEW BLOCKS REASSIGNED field

The TOTAL NEW BLOCKS REASSIGNED field contains a count of the total number of logical blocks that have been reassigned since the completion of the most recent successful format operation.

5.2.13.6 Power On Minutes Since Format log parameter

The Power On Minutes Since Format log parameter for the Format Status log page has the format defined in table 360.

Table 360 Power On Minutes Since Format log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0004h)							
1	_____ (LSB)							
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	POWER ON MINUTES SINCE FORMAT							
n	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 4.2.2.2.2 and shall be set to the value shown in table 360 for the Power On Minutes Since Format log parameter.

TSD bit

The target save disable (TSD) bit (see SPC-6) shall be set to zero for the Power On Minutes Since Format log parameter, indicating that the logical unit saves the Power On Minutes Since Format log parameter at vendor specific intervals without any request from an application client.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 360 for the Power On Minutes Since Format log parameter.

POWER ON MINUTES SINCE FORMAT field

The POWER ON MINUTES SINCE FORMAT field contains the unsigned number of usage minutes (i.e., minutes with power applied regardless of power state) that have elapsed since the most recent successful format operation.

5.2.14 Informational Exceptions log page (2Fh/00h)

The Informational Exceptions log page (see table 361) provides a place for reporting detail about informational exceptions. The page code for the Informational Exceptions log page is 2Fh.

Table 361 defines the parameter codes.

Table 361 Informational exceptions parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Informational exceptions general parameter data	Reset Only	5.2.11	Mandatory
0001h - FFFFh	Vendor specific			

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Informational Exceptions log page has the format shown in table 362.

Table 362 Informational Exceptions log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (2Fh)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
INFORMATIONAL EXCEPTIONS PARAMETERS								
4	FIRST INFORMATIONAL EXCEPTIONS LOG PARAMETER							
...	...							
n	LAST INFORMATIONAL EXCEPTIONS LOG PARAMETER							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

The informational exceptions general parameter data page has the format shown in table 363.

Table 363 Informational exceptions general parameter data

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (0000h)						(LSB)
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)							
3	PARAMETER LENGTH (N-3)							
4	INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE							
5	INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER							
6	MOST RECENT TEMPERATURE READING							
7	VENDOR HDA TEMPERATURE TRIP POINT							
8	MAXIMUM TEMPERATURE							
9								
...	Vendor specific							
11								

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2. The parameter length shall be at least 04h.

INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE field

If the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE field contains zero, no informational exception condition is pending and contents of the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER field are unspecified. If the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE field contains any value other than zero, an informational exception condition exists that has an additional sense code indicated by INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE field and an ADDITIONAL SENSE CODE QUALIFIER indicated by the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER field.

INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER field

The INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER field indicates detailed information related to the condition reported in the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE field. If the condition is reported by the device server, the value returned shall be as defined in 2.4.1.5. If the device server does not have detailed information related to the reported condition, the INFORMATIONAL EXCEPTION ADDITIONAL SENSE CODE QUALIFIER field shall be set to zero.

MOST RECENT TEMPERATURE READING field

The MOST RECENT TEMPERATURE READING field indicates the temperature in degrees Celsius of the SCSI target device at the time the LOG SENSE command is performed. Temperatures equal to or less than zero degrees Celsius shall be indicated by a value of zero. If the device server is unable to detect a valid temperature because of a sensor failure or other condition, the value returned shall be FFh. The temperature should be reported with an accuracy of plus or minus three Celsius degrees while the device is operating at a steady state within the environmental limits specified for the device.

VENDOR HDA TEMPERATURE TRIP POINT field

This field indicates the drive HDA temperature, in degrees Celsius, at which the drive will post a status with Sense Key of RECOVERED ERROR or UNIT ATTENTION and the additional sense code set to WARNING -- SPECIFIED TEMPERATURE EXCEEDED.

MAXIMUM TEMPERATURE

Maximum Temperature field is the maximum temperature in degrees Celsius measured and logged by the device. This parameter value never decreases. The parameter content of this field ranges from 00h to FFh.

5.2.15 Logical Block Provisioning log page (0Ch/00h)

5.2.15.1 Logical Block Provisioning log page overview

Using the format defined in table 182, the Logical Block Provisioning log page reports the logical block provisioning status of the logical unit. The parameter codes for the Logical Block Provisioning log page are listed in table 364.

Table 364 Logical Block Provisioning log page parameters

Parameter code ^[a]	Description	Resettable or Changeable ^[b]	Reference	Support Required
Resources that are associated with thresholds (0000h to 00FFh)				
0000h	Reserved			
0001h	Available LBA Mapping Resource Count	Never	5.2.15.1	Optional ^[c]
0002h	Used LBA Mapping Resource Count	Never	5.2.15.1	
0003h	Available Provisioning Resource Percentage	Never	5.2.15.1	
0004h - 00FFh	Reserved			
Resources that are not associated with thresholds (0000h to 00FFh)				
0100h	De-duplicated LBA Resource Count	Never	5.2.15.1	Optional
0101h	Compressed LBA Resource Count	Never	5.2.15.1	
0102h	Total Efficiency LBA Resource Count	Never	5.2.15.1	
0103h - FFEFh	Reserved			
FFF0h - FFFFh	Vendor Specific			
<p>[a] Parameter codes 0000h to 00FFh are coordinated with the THRESHOLD RESOURCE field in the threshold descriptor of the Logical Block Provisioning mode page (see 5.3.20).</p> <p>[b] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.</p> <p>[c] If this log page is supported, then at least one parameter shall be supported. A logical block provisioning log parameter in the range 0001h to 00FFh should be provided to report resource usage for each threshold resource for which a threshold descriptor in the Logical Block Provisioning mode page (see 5.3.20) is available.</p>				

The Logical Block Provisioning log page has the format defined in table 365.

Table 365 Logical block provisioning log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1b)	SPF (0b)	PAGE CODE (0Ch)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Logical block provisioning log parameter								
4	Logical block provisioning log parameter [first] (if any) (see table 364)							
...								
...								
...	Logical block provisioning log parameter [last] (if any) (see table 364)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The DS bit, the SPF bit, the PAGE CODE field, and the SUBPAGE CODE field shall be set to the values shown in table 365 for the Logical Block Provisioning log page.

5.2.15.2 Available LBA Mapping Resource Count log parameter

5.2.15.2.1 Available LBA Mapping Resource Count log parameter overview

The Available LBA Mapping Resource Count log parameter of the Logical Block Provisioning log page has the format defined in table 366

Table 366 Available LBA Mapping Resource Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	PARAMETER CODE (0001h)							(LSB)
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB)							
...	RESOURCE COUNT							
7								(LSB)
8	Reserved					SCOPE		
9								
...	Reserved							
11								

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 366 for the Available LBA Mapping Resource Count log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 366 for the Available LBA Mapping Resource Count log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of Available LBA mapping resources and is defined in 5.2.15.2.2.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

Table 367 SCOPE field

Code	Description
00b	The scope of the resource count is not reported.
01b	The RESOURCE COUNT field indicates a resource that is dedicated to the logical unit. Usage of resources on other logical units does not impact the resource count.
10b	The resource count field indicates resources that may or may not be dedicated to any logical unit including the addressed logical unit. Usage of resources on other logical units may impact the resource count.
11b	Reserved

5.2.15.2.2 RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of LBA resources expressed as a number of threshold sets for the threshold resource indicated by the parameter code value. The nominal number of LBA resources is calculated as follows:

$LBA\ resources = resource\ count \times threshold\ set\ size$

where: resource count is the value in the RESOURCE COUNT field; and

threshold set size is the number of LBAs in each threshold set (i.e., $2^{(threshold\ exponent)}$ LBAs, where the threshold exponent is indicated in the Logical Block Provisioning VPD page).

5.2.15.3 Used LBA Mapping Resource Count log parameter

The Used LBA Mapping Resource Count log parameter of the Logical Block Provisioning log page has the format defined in table 368

Table 368 Used LBA Mapping Resource Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0002h) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	RESOURCE COUNT							
7	_____ (LSB)							
8	Reserved						SCOPE	
9	_____							
...	Reserved							
11	_____							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 368 for the Used LBA Mapping Resource Count log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 368 for the Used LBA Mapping Resource Count log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of Used LBA Mapping Resource and is defined in 5.2.15.2.2.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

5.2.15.4 Available Provisioning Resource Percentage log parameter

5.2.15.4.1 Available Provisioning Resource Percentage log parameter overview

The Available Provisioning Resource Percentage log parameter of the Logical Block Provisioning log page has the format defined in table 369

Table 369 Available Provisioning Resource Percentage log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0003h)							(LSB)
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
5	RESOURCE COUNT							(LSB)
6	Reserved							
7	Reserved							
8	Reserved					SCOPE		
9	Reserved							
...	Reserved							
11	Reserved							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 369 for the Available Provisioning Resource Percentage log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 369 for the Available Provisioning Resource Percentage log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of Available Provisioning resources and is defined in 5.2.15.4.2.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

5.2.15.4.2 RESOURCE COUNT field

The RESOURCE COUNT field (see table 370) contains an estimate of the percentage of resources available for allocation to LBAs as a percentage of the manufacturer's total resources available for allocation. The units for the reported values are percent and range from 0% to 100%.

Table 370 RESOURCE COUNT field

Code	Description
0 to 100	0% to 100% of the provisioning resources of the logical unit are available
All others	Reserved

5.2.15.5 De-duplicated LBA Resource Count log parameter

The De-duplicated LBA Resource Count log parameter of the Logical Block Provisioning log page (see table 371) contains information about de-duplicated LBA resources.

Table 371 De-duplicated LBA Resource Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	PARAMETER CODE (0100h)						(LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB)							
...	RESOURCE COUNT							
7	(LSB)							
8	Reserved						SCOPE	
9	Reserved							
...	Reserved							
11	Reserved							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 371 for the De-duplicated LBA Resource Count log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 371 for the De-duplicated LBA Resource Count log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of LBA resources made available as a result of de-duplication and is defined in 5.2.15.4.2.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

5.2.15.6 Compressed LBA Resource Count log parameter

The Compressed LBA Resource Count log parameter of the Logical Block Provisioning log page (see table 372) contains information about compressed LBA resources.

Table 372 Compressed LBA Resource Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0101h)						_____ (LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB) _____							
...	RESOURCE COUNT							
7	_____ (LSB)							
8	Reserved					SCOPE		
9	_____							
...	Reserved							
11	_____							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 372 for the Compressed LBA Resource Count log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 372 for the Compressed LBA Resource Count log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of LBA resources made available as a result of compression and is defined in 5.2.15.4.2.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

5.2.15.7 Total Efficiency LBA Resource Count log parameter

The Total Efficiency LBA Resource Count log parameter of the Logical Block Provisioning log page (see table 373) contains information about the combined effects of all LBA resource efficiencies (e.g., the result of the combination of de-duplicated LBA resources and compressed LBA resources).

Table 373 Total Efficiency LBA Resource Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	PARAMETER CODE (0102h)							(LSB)
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (08h)							
4	(MSB)							
...	RESOURCE COUNT							
7								(LSB)
8	Reserved					SCOPE		
9								
...	Reserved							
11								

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be as shown in table 373 for the Total Efficiency LBA Resource Count log parameters.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1 and shall be set as shown in table 373 for the Total Efficiency LBA Resource Count log parameters.

RESOURCE COUNT field

The RESOURCE COUNT field indicates an estimate of the number of LBA resources made available by the combined effects of all LBA resource efficiency methods (e.g., de-duplication and compression) and is defined in 5.2.15.4.2. The algorithm used to calculate this value is not defined by this standard.

SCOPE field

The SCOPE field indicates the scope to which the RESOURCE COUNT field applies and is defined in table 367.

5.2.16 Non-Medium Error log page (06h/00h)

5.2.16.1 Overview

The Non-Medium Error log page (page code 06h) provides for counting the occurrences of recoverable error events other than write, read, or verify failures. No discrimination among the various types of events is provided by parameter code (see table 374). Vendor specific discrimination may be provided through Seagate specific parameter codes.

Table 374 Non-medium error event parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Non-medium error count	Reset Only	5.2.16	Mandatory
8000h - FFFFh	Vendor specific error counts			
All others	Reserved			

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Non-Medium Error log page has the format shown in table 375.

Table 375 Non-Medium Error log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (06h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
NON-MEDIUM ERROR LOG PARAMETERS								
4	FIRST NON-MEDIUM ERROR COUNT LOG PARAMETER (see table 374)							
...	...							
n	LAST NON-MEDIUM ERROR COUNT LOG PARAMETER (see table 373)							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2.

SPF bit, PAGE CODE field, and SUBPAGE CODE field

The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 375 for the Non-Medium Error log page.

NON-MEDIUM ERROR LOG PARAMETERS

The contents of each non-medium error log parameter depends on the value in its PARAMETER CODE field (see table 374).

5.2.16.2 Non-Medium Error Count log parameter

The Non-Medium Error Count log parameter has the format shown in table 376.

Table 376 Non-Medium Error Count log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE _____ (LSB)							
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.2)							
3	PARAMETER LENGTH (n - 3)							
4	(MSB) _____							
...	NON-MEDIUM ERROR COUNT _____							
255	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2, and shall be set as shown in table 376 for the Non-Medium Error Count log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.1.

NON-MEDIUM ERROR COUNT field

The NON-MEDIUM ERROR COUNT field indicates the number of recoverable error events other than read, read reverse, verify, or write failures.

5.2.17 Pending Defects log page (15h/01h)

5.2.17.1 Pending Defects log page overview

Using the format defined in table 198, the Pending Defects log page reports an unsorted list of logical blocks for which the device server has detected an unrecovered medium error. The parameter codes for the Pending Defects log page are listed in table 377.

Table 377 Pending Defects log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Pending Defect count	Never	5.2.17.2	Mandatory
0001h - F000h	Pending Defect	Never	5.2.17.3	Mandatory
All others	Reserved			

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Pending Defects log page has the format shown in table 378.

Table 378 Pending Defects log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (15h)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
PENDING DEFECTS PARAMETERS								
4								
...	PENDING DEFECT PARAMETER [first] (see table 381)							
	...							
...	PENDING DEFECT PARAMETER [last] (see table 381)							
n								

DS bit

The disable save (DS) bit is described in 5.2.2.

SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 and shall be set to the values defined in table 378 for the Pending Defects log page.

Pending Defect Parameter fields

The contents of each pending defect parameter depends on the value in its PARAMETER CODE field (see table 381).

5.2.17.2 Pending Defect Count log parameter

The Pending Defect Count log parameter has the format defined in table 379 and indicates the number of Pending Defect log parameters that are available.

Table 379 Pending Defect Count log parameter format

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB) _____							PARAMETER CODE (0000h)	
1								_____ (LSB)	
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)								
3	PARAMETER LENGTH (04h)								
4	(MSB) _____							PENDING DEFECT COUNT	
...									
n								_____ (LSB)	

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2 and shall be set as defined in table 379 for the Pending Defect Count log parameter.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field is described in 5.2.2.2.1 and shall be set to the value defined in table 379 for the Pending Defect Count log parameter.

PENDING DEFECT COUNT field

The PENDING DEFECT COUNT field indicates the number of Pending Defect log parameters that are available. The PENDING DEFECT COUNT field changes whenever the number of Pending Defect log parameters (see 5.2.17.3) changes.

5.2.17.3 Pending Defect log parameter

A Pending Defect log parameter has the format defined in table 380. If no unrecovered errors have occurred then no Pending Defect log parameters shall be present. A Pending Defect log parameter shall be added for each LBA for which the device server has detected an unrecovered medium error that is not:

- a) a pseudo unrecovered read error (see SBC-6);
- b) a predicted unrecovered read error (see SBC-6); or
- c) a predicted unrecovered write error (see SBC-6).

If all of the supported parameter code values have been used and a new defect is discovered, then the device server shall not add more Pending Defect log parameters and the PENDING ERROR COUNT field shall not be changed.

Pending Defect log parameters may be duplicates of Background Scan parameters in the Background Scan log page (see 5.2.4).

A Pending Defect log parameter shall be removed if the indicated LBA:

- a) is reassigned without error;
- b) is written without error; or
- c) is read without error.

A Pending Defect log parameter may be removed if the indicated LBA is unmapped without error.

A sanitize overwrite operation (see 3.45.3.2) and a format operation (see 3.3.1) shall cause all Pending Defect log parameters to be removed.

Table 380 Pending Defect log parameter format

Bit	7	6	5	4	3	2	1	0	
Byte									
0	(MSB)	PARAMETER CODE (0001h to F000h)						(LSB)	
1									
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)								
	DU	Obsolete	TSD	Obsolete			FORMAT AND LINKING		
3	PARAMETER LENGTH (0Ch)								
4	(MSB)	ACCUMULATED POWER ON HOURS						(LSB)	
...									
7									
8	(MSB)	LOGICAL BLOCK ADDRESS						(LSB)	
...									
15									

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.1 and shall be set as defined in table 380 for a Pending Defect log parameter.

PARAMETER LIST LENGTH field

The PARAMETER LIST LENGTH field is defined in 5.2.2.2.1 and shall be set to the value defined in table 380 for a Pending Defect log parameter.

ACCUMULATED POWER ON HOURS field

The ACCUMULATED POWER ON HOURS field indicates the number of hours that the device server has been powered on since manufacturing at the time the Pending Defect log parameter was created. A value of FFFF_FFFFh indicates that the accumulated power on hours value is unknown.

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field indicates the LBA associated with the unrecovered medium error.

5.2.18 Power Condition Transitions log page (1Ah/00h)

5.2.18.1 Overview

Using the format shown in table 381, the Power Condition Transitions log page (page code 1Ah) provides a count of the occurrences of power condition transition events using the parameter codes listed in table 381.

Table 381 Power Condition Transitions log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support requirements
0001h	Accumulated transitions to active	Never		Mandatory
0002h	Accumulated transitions to idle_a			At least one ^[b]
0003h	Accumulated transitions to idle_b			
0004h	Accumulated transitions to idle_c			
0008h	Accumulated transitions to standby_z			
0009h	Accumulated transitions to standby_y			
all others	Reserved			
<p>[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.</p> <p>[b] If the Power Conditions Transitions log page is supported, at least one of these parameter codes shall be supported.</p>				

5.2.18.2 Power Condition Transitions log page (1Ah)

The Power Condition Transitions log page (see table 382) provides a count of the occurrences of power condition transition events. A device server that implements the Power Condition Transitions log page shall implement one or more of the defined parameters.

Table 382 Power Condition Transitions log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (1Ah)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						
3								(LSB)
POWER CONDITION TRANSITIONS LOG PARAMETERS								
4	FIRST POWER CONDITION TRANSITIONS LOG PARAMETER (see table 383)							
...	...							
n	LAST POWER CONDITION TRANSITIONS LOG PARAMETER (see table 383)							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field and PAGE LENGTH field are described in 5.2.2.

The format for all log parameters in the Power Condition Transitions log page is shown in table 383. All log parameters in the Power Condition Transitions log page contain a four-byte binary value.

Table 383 Power Condition Transitions log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (see table 381)						(LSB)
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)							
3	PARAMETER LENGTH (04h)							
4	(MSB)	PARAMETER VALUE						(LSB)
...								
7								

All Power Condition Transitions log page counters are saturating counters (see table 307). A count is incremented by one for each transition (see table 309). The time in the transition at which the count is incremented is vendor specific.

If a LOG SELECT command attempts to change the value of any log parameter in the Power Condition Transitions log page, the command shall be terminated with CHECK CONDITION status, with sense key set to ILLEGAL REQUEST and additional sense code set to INVALID FIELD IN PARAMETER LIST.

PARAMETER LENGTH field

The PARAMETER LENGTH field shall be set as shown in Table 383 and specifies the length in bytes of the PARAMETER VALUE field that follows. If the application client specifies a parameter length that results in the truncation of the PARAMETER VALUE field, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

PARAMETER VALUE field

The PARAMETER VALUE field contains a saturating counter as described in Table 307 for the corresponding parameter code value in the Power Condition Transitions log parameter PARAMETER CODE field (see table 381).

5.2.19 Protocol-Specific Port log page (18h/00h)

The Protocol-Specific Port log page for SAS defined in Table 384 is used to return information about phy events concerning the SAS target device's phy(s).

A phy is defined as an object in a device that is used to interface to other devices.

Table 384 Protocol-Specific Port log page for SAS

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (18h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
PROTOCOL-SPECIFIC PORT LOG PARAMETER LIST								
4	PROTOCOL-SPECIFIC PORT LOG PARAMETER (first) (see table 385)							
...	...							
...	PROTOCOL-SPECIFIC PORT LOG PARAMETER (last) (see table 385)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

The protocol-specific port log parameter list contains a protocol-specific port log parameter for each SCSI port in the SAS target device.

Table 385 defines the format for the Protocol-Specific Port log parameter for SAS. The SAS log parameter is a list parameter (i.e., not a data counter) and only has cumulative (i.e., not threshold) values (see SPC-6).

Table 385 Protocol-Specific Port log parameter for SAS

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (relative target port identifier) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (y-3)							
4	Reserved				PROTOCOL IDENTIFIER (6h)			
5	Reserved							
6	GENERATION CODE							
7	NUMBER OF PHYS							
SAS PHY LOG DESCRIPTOR LIST								
8	SAS PHY LOG DESCRIPTOR (first) (see table 386)							
...								
8+m								
...	...							
y-m	SAS PHY LOG DESCRIPTOR (last) (see table 386)							
...								
y								

PARAMETER CODE field

The PARAMETER CODE field is defined in Clause 5.2.2.2 and contains the relative target port identifier (see SPC-6) of the SAS target port that the log parameter describes.

PARAMETER LENGTH field

The PARAMETER LENGTH field is defined in Clause 5.2.2.2 and shall be set to the value defined in Table 385.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in Table 385.

GENERATION CODE field

The GENERATION CODE field is defined in the Phy Control and Discover mode page (Clause 5.3.26).

NUMBER OF PHYS field

The NUMBER OF PHYS field contains the number of phys in the SAS target port (not in the entire SAS target device) and indicates the number of SAS phy log descriptors in the SAS phy log descriptor list.

The SAS phy log descriptor list contains SAS phy log descriptors.

Table 386 defines the SAS phy log descriptor.

Table 386 SAS phy log descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
1	PHY IDENTIFIER							
2	Reserved							
3	SAS PHY LOG DESCRIPTOR LENGTH (m - 3)							
4	Reserved	ATTACHED DEVICE TYPE			ATTACHED REASON			
5	REASON				NEGOTIATED LOGICAL LINK RATE			
6	Reserved				ATTACHED SSP INITIATOR PORT	ATTACHED STP INITIATOR PORT	ATTACHED SMP INITIATOR PORT	Reserved
7	Reserved				ATTACHED SSP TARGET PORT	ATTACHED STP TARGET PORT	ATTACHED SMP TARGET PORT	Reserved
8	SAS ADDRESS							
...								
15								
16	ATTACHED SAS ADDRESS							
...								
23								
24	ATTACHED PHY IDENTIFIER							
25	Reserved							
31								
32								
...								
35								
36	(MSB)	RUNNING DISPARITY ERROR COUNT						(LSB)
...								
39								
40	(MSB)	LOSS OF DWORD SYNCHRONIZATION						(LSB)
...								
43								
44	(MSB)	PHY RESET PROBLEM						(LSB)
...								
47								
48	Reserved							
49	PHY EVENT DESCRIPTOR LENGTH							
50								
51	NUMBER OF PHY EVENT DESCRIPTORS							

Table 386 SAS phy log descriptor

Bit Byte	7	6	5	4	3	2	1	0
PHY EVENT DESCRIPTOR LIST								
52								
...								
63	PHY EVENT DESCRIPTOR (first) (see table 390)							
...								
m-11	...							
...	PHY EVENT DESCRIPTOR (last) (see table 390)							
M								

PHY IDENTIFIER field

The PHY IDENTIFIER field specifies the phy identifier of the phy that is to perform or to stop performing a phy test function (i.e., the selected phy). If the PHY IDENTIFIER field specifies a phy that does not exist, then the device server shall terminate the SEND DIAGNOSTIC command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

SAS PHY LOG DESCRIPTOR LENGTH field

The SAS PHY LOG DESCRIPTOR LENGTH field indicates the number of bytes that follow in the SAS phy log descriptor and shall be set to the value defined in Table 386. A SAS PHY LOG DESCRIPTOR LENGTH field set to 00h indicates that there are 44 additional bytes.

NOTE Logical units compliant with SAS and SAS-1.1 only support a 48 byte SAS phy log descriptor.

ATTACHED DEVICE TYPE field

The ATTACHED DEVICE TYPE field indicates the type of device attached to this phy, and is defined in Table 387.

Table 387 Device type field

Code	Description
001b	End device
010b	Expander device
011b	Expander device compliant with a previous version of the SAS standard
All others	Reserved

ATTACHED REASON field

The ATTACHED REASON field indicates the reason received from the attached device for the link reset sequence and is defined in Table 388

REASON field

The REASON field indicates the reason sent by the target device for the last link reset sequence and is defined in Table 388.

Table 388 Reason field definition

Code	Description
0h	Unknown reason
1h	Power on
2h	Hard reset (e.g., the port containing this phy received a HARD_RESET primitive during the hard reset sequence) (see SPL-5), or SMP PHY CONTROL function HARD RESET phy operation (see SPL-5)
3h	SMP PHY CONTROL function LINK RESET phy operation, or TRANSMIT SATA PORT SELECTION SIGNAL phy operation (see SPL-5)
4h	Loss of dword synchronization (see SPL-5)
5h	After the multiplexing sequence completes, MUX (LOGICAL LINK 0) received in logical link 1 or MUX (LOGICAL LINK 1) received in logical link 0 (see SPL-5)
6h	I_T nexus loss timer expired in the STP target port of an STP/SATA bridge when the phy was attached to a SATA device (see SPL-5)
7h	Break Timeout Timer expired (see SPL-5)
8h	Phy test function stopped (see SPL-5)
9h	Expander device reduced functionality (see SPL-5)
Ah to Fh	Reserved

NEGOTIATED LOGICAL LINK RATE field

The NEGOTIATED LOGICAL LINK RATE field is defined in Table 389 and indicates the logical link rate being used by the phy. For physical phys, this is negotiated during the link reset sequence. For virtual phys, this field should be set to the maximum physical link rate supported by the expander device. This field may be different from the negotiated physical link rate when multiplexing is enabled.

Table 389 NEGOTIATED LOGICAL LINK RATE field

NEGOTIATED PHYSICAL LINK RATE field	Multiplexing	NEGOTIATED LOGICAL LINK RATE field
9h (i.e., G2)	Disable	9h (i.e., 3Gb/s)
	Enable	8h (i.e., 1.5Gb/s)
Ah (i.e., G3)	Disable	Ah (i.e., 6Gb/s)
	Enable	9h (i.e., 3Gb/s)
Bh (i.e., G4)	Disable	Bh (i.e., 12Gb/s)
	Enable	Ah (i.e., 6Gb/s)
All others	Any	Same as the NEGOTIATED LOGICAL LINK RATE field

ATTACHED SSP INITIATOR PORT bit

- 1** An ATTACHED SSP INITIATOR PORT bit set to one indicates that an SSP initiator port is present in the attached device.
- 0** An ATTACHED SSP INITIATOR PORT bit set to zero indicates that an SSP initiator port is not present in the attached device.

ATTACHED STP INITIATOR PORT bit

- 1** An ATTACHED STP INITIATOR PORT bit set to one indicates that an STP initiator port is present in the attached device.
- 0** An ATTACHED STP INITIATOR PORT bit set to zero indicates that an STP initiator port is not present in the attached device.

ATTACHED SMP INITIATOR PORT bit

- 1** An ATTACHED SMP INITIATOR PORT bit set to one indicates that an SMP initiator port is present in the attached device.
- 0** An ATTACHED SMP INITIATOR PORT bit set to zero indicates that an SMP initiator port is not present in the attached device.

ATTACHED SSP TARGET PORT bit

- 1** An ATTACHED SSP TARGET PORT bit set to one indicates that an SSP target port is present in the attached device.
- 0** An ATTACHED SSP TARGET PORT bit set to zero indicates that an SSP target port is not present in the attached device.

ATTACHED STP TARGET PORT bit

- 1** An ATTACHED STP TARGET PORT bit set to one indicates that an STP target port is present in the attached device.
- 0** An ATTACHED STP TARGET PORT bit set to zero indicates that an STP target port is not present in the attached device.

ATTACHED SMP TARGET PORT bit

- 1** An ATTACHED SMP TARGET PORT bit set to one indicates that an SMP target port is present in the attached device.
- 0** An ATTACHED SMP TARGET PORT bit set to zero indicates that an SMP target port is not present in the attached device.

SAS ADDRESS field

The SAS ADDRESS field indicates the port identifier (see SPL-5) of the SAS port transmitting the IDENTIFY address frame. For expander ports, the SAS ADDRESS field indicates the device name (see SPL-5) of the expander device transmitting the IDENTIFY address frame.

ATTACHED SAS ADDRESS field

The ATTACHED SAS ADDRESS field contains SAS address of the attached SAS port (see SPL-5).

ATTACHED PHY IDENTIFIER field

The ATTACHED PHY IDENTIFIER field contains the phy identifier of the attached SAS phy in the attached SAS device.

INVALID DWORD COUNT field

The INVALID DWORD COUNT field indicates the number of invalid dwords (see SPL-5) that have been received outside of phy reset sequences (i.e., between when the SP state machine (see SPL-5) sends a Phy Layer Ready (SAS) confirmation or Phy Layer Ready (SATA) confirmation and when it sends a Phy Layer Not Ready confirmation to the link layer). The count shall stop at the maximum value. The INVALID DWORD COUNT field is set to a vendor-specific value after power on.

For the INVALID DWORD COUNT field, RUNNING DISPARITY ERROR COUNT field, LOSS OF DWORD SYNCHRONIZATION COUNT field, and PHY RESET PROBLEM COUNT field, the phy may maintain any size counter but should maintain a 32-bit counter. If it reaches its maximum value, then the counter shall stop and the device server shall set the field to FFFFFFFFh in the SAS phy log descriptor.

RUNNING DISPARITY ERROR COUNT field

The RUNNING DISPARITY ERROR COUNT field indicates the number of dwords containing running disparity errors (see SPL-5) that have been received outside of phy reset sequences. The count shall stop at the maximum value. The RUNNING DISPARITY ERROR COUNT field is set to a vendor-specific value after power on.

LOSS OF DWORD SYNCHRONIZATION COUNT field

The LOSS OF DWORD SYNCHRONIZATION COUNT field indicates the number of times the phy has restarted the link reset sequence because it lost dword synchronization (see SPL-5) (i.e., the SP state machine transitioned from SP15:SAS_PHY_Ready or SP22:SATA_PHY_Ready to SP0:OOB_COMINIT (see SPL-5)). The count shall stop at the maximum value. The LOSS OF DWORD SYNCHRONIZATION COUNT field is set to a vendor-specific value after power on.

PHY RESET PROBLEM COUNT field

The PHY RESET PROBLEM COUNT field indicates the number of times a phy reset problem (see SPL-5) occurred. The count shall stop at the maximum value. The PHY RESET PROBLEM COUNT field is set to a vendor-specific value after power on.

PHY EVENT DESCRIPTOR LENGTH field

The PHY EVENT DESCRIPTOR LENGTH field indicates the number of bytes in the phy event descriptor (see SPL-5).

NUMBER OF PHY EVENT DESCRIPTORS field

The NUMBER OF PHY EVENT DESCRIPTORS field indicates the number of phy event descriptors in the phy event descriptor list.

Each PHY EVENT DESCRIPTOR follows the format defined for the SMP REPORT PHY EVENT function in (see SPL-5).

5.2.19.1 Phy event descriptor

Table 390 defines the phy event descriptor.

Table 390 Phy event descriptor

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
...									
2									
3	PHY EVENT SOURCE								
4	(MSB)	PHY EVENT						(LSB)	
...									
7									
8	(MSB)	PEAK VALUE DETECTOR THRESHOLD						(LSB)	
...									
11									

PHY EVENT SOURCE field

The PHY EVENT SOURCE field, defined in SAS-4.1, indicates the type of phy event being reported in the PHY EVENT field.

PHY EVENT field

The PHY EVENT field indicates the value (i.e., the count or peak value detected) of the phy event indicated by the PHY EVENT SOURCE field.

PEAK VALUE DETECTOR THRESHOLD field

If the phy event source is a peak value detector, then the PEAK VALUE DETECTOR THRESHOLD field indicates the value of the peak value detector that causes the expander device to originate a Broadcast (Expander) (see SAS-4.1). If the phy event source is not a peak value detector, then the PEAK VALUE DETECTOR THRESHOLD field is reserved.

5.2.20 Self-Test Results log page (10h/00h)

The Self-Test Results log page (see table 391) provides the results from the 20 most recent self-tests (see 3.50). Results from the most recent self-test or the self-test currently in progress shall be reported in the first self-test log parameter; results from the second most recent self-test shall be reported in the second self-test log parameter; etc. If fewer than 20 self-tests have occurred, the unused self-test log parameter entries shall be zero filled.

Table 391 Self-Test Results log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (10h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (190h)						(LSB)
3								
SELF-TEST RESULTS LOG PARAMETERS								
4	FIRST SELF-TEST RESULTS LOG PARAMETER (most recent)							
...								
23								
...	...							
384	TWENTIETH SELF-TEST RESULTS LOG PARAMETER (least recent)							
...								
403								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field and PAGE LENGTH field are described in 5.2.2.

Table 392 shows the format of one self-test log parameter.

Table 392 Self-test results log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (0001h TO 0014h)						(LSB)
1								
...	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (10h)							
4	SELF-TEST CODE			Reserved		SELF-TEST RESULTS		
5	SELF-TEST NUMBER							
6	(MSB)	ACCUMULATED POWER ON HOURS						(LSB)
7								
8	(MSB)	ADDRESS OF FIRST FAILURE						(LSB)
...								
15								
16	Reserved				SENSE KEY			
17	ADDITIONAL SENSE CODE							
18	ADDITIONAL SENSE CODE QUALIFIER							
19	Vendor specific							

PARAMETER CODE field

The PARAMETER CODE field identifies the log parameter being transferred. The PARAMETER CODE field for the results of the most recent self-test shall contain 0001h; the PARAMETER CODE field for the results of the second most recent test shall contain 0002h; etc.

PARAMETER LENGTH field

The PARAMETER LENGTH field shall contain 10h.

SELF-TEST CODE field

The SELF-TEST CODE field contains the value in the SELF-TEST CODE field of the SEND DIAGNOSTIC command that initiated this self-test.

Table 393 defines the content of the SELF-TEST RESULTS field.

Table 393 SELF-TEST RESULTS field

Code	Description
0h	The self-test completed without error.
1h	The background self-test was aborted by the application client using a SEND DIAGNOSTIC command (see 3.50) with the SELF-TEST CODE field set to 100b (i.e., abort background self-test).
2h	The self-test routine was aborted by an application client using a method other than a SEND DIAGNOSTIC command with the SELF-TEST CODE field set to 100b (e.g., by a task management function, or by issuing an exception command as defined in SPC-6).
3h	An unknown error occurred while the device server was processing the self-test and the device server was unable to complete the self-test.
4h	The self-test completed with a failure in a test segment, and the test segment that failed is not known.
5h	The first segment of the self-test failed.
6h	The second segment of the self-test failed.
7h	Another segment of the self-test failed and which test is indicated by the contents of the SELF-TEST NUMBER field.
8h	The self-test is aborted by other actuator. (applies to Seagate Dual Actuator (multi LUN config) products only)
9h-Eh	Reserved
Fh	The self-test is in progress.

SELF-TEST NUMBER field

The SELF-TEST NUMBER field identifies the self-test that failed and consists of either:

- a) The number of the segment that failed during the self-test; or
- b) The number of the test that failed and the number of the segment in which the test was run, using a vendor specific method for placing the two values in the one field.

When the segment in which the failure occurred is not able to be identified or need not be identified, the SELF-TEST NUMBER field shall contain 00h.

ACCUMULATED POWER ON HOURS field

The ACCUMULATED POWER ON HOURS field contains the total hours for the device server has been powered on since manufacturing at the time the self-test is completed. If the test is still in progress, the content of the ACCUMULATED POWER ON HOURS field shall be zero. If the power-on hours for the device server at the time the self-test was completed is greater than FFFFh then the content of the ACCUMULATED POWER ON HOURS field shall be FFFFh.

ADDRESS OF FIRST FAILURE field

The ADDRESS OF FIRST FAILURE field contains information that locates the failure on the media. If the logical unit implements logical blocks, the content of the ADDRESS OF FIRST FAILURE field is the first logical block address where a self-test error occurred. This implies nothing about the quality of any other logical block on the logical unit, since the testing during which the error occurred may not have been performed in a sequential manner. This value shall not change (e.g., as the result of block reassignment). The content of the ADDRESS OF FIRST FAILURE field shall be FFFF FFFF FFFF FFFFh if no errors occurred during the self-test or if the error that occurred is not related to an identifiable media address.

SENSE KEY, ADDITIONAL SENSE CODE, and ADDITIONAL SENSE CODE QUALIFIER fields

The SENSE KEY field, ADDITIONAL SENSE CODE field, and ADDITIONAL SENSE CODE QUALIFIER field may contain a hierarchy of additional information relating to error or exception conditions that occurred during the self-test represented in the same format used by the sense data (see 3.40).

5.2.21 Solid State Media log page (11h/00h)

5.2.21.1 Overview

Using the format shown in Table 395, the Solid State media log page (PAGE CODE 11h) reports parameters that are specific to SCSI target devices that contain solid state media. The parameter codes for the Solid State Media log page are listed in Table 394.

Table 394 Solid State Media log parameters

Parameter code	Description	Resettable or Changeable ^[a]	Support requirements
0001h	Percentage Used Endurance Indicator	Never	Mandatory
all others	Reserved		

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Solid State Media log page has the format shown in Table 395.

Table 395 Solid State Media log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (11h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
SOLID STATE MEDIA LOG PARAMETERS (see table 394)								
4	SOLID STATE MEDIA PARAMETER (first							
...	...							
n	SOLID STATE MEDIA PARAMETER (last)							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

5.2.21.2 Percentage Used Endurance Indicator log parameter

The Percentage Used Endurance Indicator log parameter has the format shown in Table 396.

Table 396 Percentage Used Endurance Indicator log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0001h) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
3	PARAMETER LENGTH (04h)							
4								
...	RESERVED							
6								
7	PERCENTAGE USED ENDURANCE INDICATOR							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2 and shall be set to the value shown in table 169 for the Percentage Used Endurance Indicator log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 169 for the Percentage Used Endurance Indicator log parameter.

PERCENTAGE USED ENDURANCE INDICATOR field

The PERCENTAGE USED ENDURANCE INDICATOR field indicates an estimate of the percentage of device life that has been used. The value in the field shall be set to zero at the time of manufacture. A value of 100 indicates that the estimated endurance of the device has been consumed, but may not indicate a device failure (e.g., minimum power-off data retention capability reached for devices using flash technology). The value is allowed to exceed 100. Values greater than 254 shall be reported as 255. The device server shall update the value at least once per power-on hour.

5.2.22 Start-Stop Cycle Counter log page (0Eh/00h)

5.2.22.1 Overview

Using the format shown in table 398, the Start-Stop Cycle Counter log page (page code 0Eh) provides information about manufacturing dates and cycle counts since date of manufacture using the parameter codes listed in table 397.

Table 397 Solid State Media log parameters

Parameter code	Description	Resettable or Changeable ^[a]
0001h	Date of Manufacture	Never
0002h	Accounting Date	Always
0003h	Specified Cycle Count Over Device Lifetime	Never
0004h	Accumulated Start-Stop Cycles	Never
0005h	Specified Load-Unload Count Over Device Lifetime	Never
0006h	Accumulated Load-Unload Cycles	Never
all others	Reserved	

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Start-Stop Cycle Counter log page has the format shown in table 398.

Table 398 Start-Stop Cycle Counter log page (Sheet 1 of 2)

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0b)	PAGE CODE (0Eh)					
1	SUBPAGE CODE(00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
4	(MSB)	PARAMETER CODE 0001h						(LSB)
5	DATE OF MANUFACTURE						(LSB)	
6	PARAMETER CONTROL BYTE – ASCII format list log parameter (see 5.2.2.2.4)							
7	PARAMETER LENGTH (06h)							
8	(MSB)	YEAR OF MANUFACTURE (4 ASCII CHARACTERS)						(LSB)
...								
11	WEEK OF MANUFACTURE (2 ASCII CHARACTERS)						(LSB)	
12	(MSB)	PARAMETER CODE 0002h						(LSB)
13	ACCOUNTING DATE						(LSB)	
14	(MSB)	PARAMETER CODE 0002h						(LSB)
15	ACCOUNTING DATE						(LSB)	
16	PARAMETER CONTROL BYTE – ASCII format list log parameter (see 5.2.2.2.4)							
17	PARAMETER LENGTH (06h)							
18	(MSB)	ACCOUNTING DATE YEAR (4 ASCII CHARACTERS)						(LSB)
...								
21	ACCOUNTING DATE WEEK (2 ASCII CHARACTERS)						(LSB)	
22	(MSB)	PARAMETER CODE 0003h						(LSB)
23	SPECIFIED CYCLE COUNT OVER DEVICE LIFETIME						(LSB)	
24	(MSB)	PARAMETER CODE 0003h						(LSB)
25	SPECIFIED CYCLE COUNT OVER DEVICE LIFETIME						(LSB)	

Table 398 Start-Stop Cycle Counter log page (Sheet 2 of 2)

Bit Byte	7	6	5	4	3	2	1	0	
26	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)								
27	PARAMETER LENGTH (04h)								
28	(MSB)	SPECIFIED CYCLE COUNT OVER DEVICE LIFETIME							
...		(4-BYTE BINARY NUMBER)							
31								(LSB)	
32	(MSB)	PARAMETER CODE 0004h							
33		ACCUMULATED START-STOP CYCLES							(LSB)
34	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)								
35	PARAMETER LENGTH (04h)								
36	(MSB)	ACCUMULATED START-STOP CYCLES							
...		(4-BYTE BINARY NUMBER)							
39								(LSB)	
40	(MSB)	PARAMETER CODE 0005h							
41		SPECIFIED LOAD-UNLOAD COUNT OVER DEVICE LIFETIME							(LSB)
42	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)								
43	PARAMETER LENGTH (04h)								
44	(MSB)	SPECIFIED LOAD-UNLOAD COUNT OVER DEVICE LIFETIME							
...		(4-BYTE BINARY NUMBER)							
47								(LSB)	
48	(MSB)	PARAMETER CODE 0006h							
49		ACCUMULATED LOAD-UNLOAD CYCLES							(LSB)
50	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.2.5)								
51	PARAMETER LENGTH (04h)								
52	(MSB)	ACCUMULATED LOAD-UNLOAD CYCLES							
...		(4-BYTE BINARY NUMBER)							
55								(LSB)	

The year and week in the year that the SCSI target device was manufactured shall be contained in the parameter value of the log parameter in which the parameter code is 0001h. The date of manufacture shall not be saveable by the application client using the LOG SELECT command (i.e., the log parameter DS bit shall be set to one). The date is expressed in numeric ASCII characters (30h – 39h) in the form YYYYWW, as shown in table 398.

The accounting date specified by parameter code 0002h may be saved using a LOG SELECT command to indicate when the device was placed in service. If the parameter is not yet set or is not settable, the default value placed in the parameter field shall be 6 ASCII space characters (20h). The field shall not be checked for validity by the device server.

The parameter value in the specified cycle count over device lifetime log parameter (parameter code 0003h) shall contain a four-byte binary value that indicates how many stop-start cycles may typically be performed over the lifetime of the SCSI target device without degrading the SCSI target device's operation or reliability outside the limits specified by the manufacturer of the SCSI target device. The specified cycle count over device lifetime parameter shall not be saveable by the application client using the LOG SELECT command (i.e., the log parameter DS bit shall be set to one).

The parameter value in the accumulated start-stop cycles log parameter (parameter code 0004h) shall contain a four-byte binary value that indicates how many stop-start cycles the SCSI target device has detected since its date of manufacture. The accumulated start-stop cycles parameter shall not be saveable by the application client using the LOG SELECT command (i.e., the log parameter DS bit shall be set to one). The time at which the count is incremented during a start-stop cycle is vendor specific. For rotating magnetic storage devices, a single start-stop cycle is defined as an operational cycle that begins with the disk spindle at rest, continues while the disk accelerates to its normal operational rotational rate, continues during the entire period the disk is rotating, continues as the disk decelerates toward a resting state, and ends when the disk is no longer rotating. For devices without a spindle or with multiple spindles, the definition of a single start-stop cycle is vendor specific. The count is incremented by one for each complete start-stop cycle. No comparison with the value of parameter 0003h shall be performed by the device server.

The parameter value in the specified load-unload count over device lifetime log parameter (parameter code 0005h) shall contain a four-byte binary value that indicates how many load-unload cycles may be performed over the lifetime of the SCSI target device without degrading the SCSI target device's operation or reliability outside the limits specified by the manufacturer of the SCSI target device. The specified load-unload count parameter shall not be saveable by the application client using the LOG SELECT command (i.e., the log parameter DS bit shall be set to one). The time at which the count is incremented during a specified load-unload count is vendor specific. For rotating magnetic storage devices, a single load-unload cycle is defined as an operational cycle that begins with the disk spindle at rest, continues while the disk accelerates to its normal operational rotational rate, continues during the entire period the disk is rotating, continues as the disk decelerates toward a resting state, and ends when the disk is no longer rotating. For devices without a spindle or with multiple spindles, the definition of a single load-unload cycle is vendor specific. The count is incremented by one for each complete load-unload cycle. No comparison with the value of parameter 0005h shall be performed by the device server.

The parameter value in the accumulated load-unload count over device lifetime log parameter (parameter code 0006h) shall contain a four-byte binary value that indicates the SCSI target device has detected since its date of manufacture. This saturating counter is incremented by one for each complete cycle. The time in the cycle at which the counter is incremented is vendor specific.

For rotating magnetic storage devices (see SBC-5), a single load-unload cycle is defined as an operational cycle that:

- a) begins with the heads unloaded from the medium;
- b) continues while the heads are loaded onto the spinning medium; and
- c) ends when the heads are unloaded from the medium.

The Accumulated Load-Unload Cycles log parameter is not applicable to rotating magnetic storage devices without unloadable heads.

The device server shall not compare the contents of the ACCUMULATED LOAD-UNLOAD CYCLES field to contents of the SPECIFIED LOAD-UNLOAD COUNT OVER DEVICE LIFETIME field.

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE and PAGE LENGTH field are described in 5.2.2.

5.2.23 Supported Log Pages log page (00h/00h)

For the LOG SENSE command, the Supported Log Pages log page (see table 399) returns the list of log pages supported by the logical unit. Logical units that implement the LOG SENSE command shall implement this log page. This log page is not defined for the LOG SELECT command.

Table 399 Supported log pages

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF(1b)	PAGE CODE (00h)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (N-3)						(LSB)
3								
Supported pages list								
4	Supported page descriptor (see table 400) [first]							
...	...							
n	Supported page descriptor (see table 400) [last]							

DS bit, SPF bit, PAGE CODE field and SUBPAGE CODE field

The DS bit, SPF bit, PAGE CODE field and SUBPAGE CODE field are described in 5.2.2.

PAGE LENGTH field

The PAGE LENGTH field indicates the length in bytes of the following supported log page list.

SUPPORTED PAGE DESCRIPTORS field

The supported page descriptors shall contain a list of all log page codes (see table 400) with a subpage code of zero supported by the logical unit in ascending order beginning with page code 00h. The supported page descriptors may or may not include all the log pages that are able to be returned by the device server.

Table 400 Supported page descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved		PAGE CODE					

5.2.24 Supported Log Pages and Subpages log page (00h/FFh)

For the LOG SENSE command, the Supported Log Pages and Subpages log page (see table 401) returns the list of log pages and subpages supported by the logical unit. If log subpages are supported, this page shall be supported. This log page is not defined for the LOG SELECT command.

Table 401 Supported Log Pages and Subpages log page (00h/ FFh)

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (00h)					
1	SUBPAGE CODE (FFh)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
SUPPORTED PAGE/SUBPAGE DESCRIPTORS								
4	FIRST SUPPORTED PAGE/SUBPAGE DESCRIPTOR (see table 402)							
5								
...	...							
n - 1	LAST SUPPORTED PAGE/SUBPAGE DESCRIPTOR (see table 402)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The DS bit, SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 401 for the Supported Log Pages and Subpages log page. The supported page/subpage descriptors (see table 402) shall be in ascending order sorted by page code then subpage code. The supported page/subpage descriptors may or may not include all the log pages and subpages that are able to be returned by the device server.

Table 402 Supported page/subpage descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved		PAGE CODE					
1	SUBPAGE CODE							

PAGE CODE field

The PAGE CODE field indicates the number of a supported log page.

SUBPAGE CODE field

The SUBPAGE CODE field indicates the subpage number of a supported log page.

5.2.25 Supported Subpages log page

For the LOG SENSE command, the Supported Subpages log page (see table 403) returns the list of all subpage codes (i.e., 00h to FFh) that are supported by the logical unit for a specified page code. If log subpages are supported, this page shall be supported. This log page is not defined for the LOG SELECT command.

Table 403 Supported Subpages log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE					
1	SUBPAGE CODE (FFh)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
SUPPORTED SUBPAGE DESCRIPTORS								
4	FIRST SUPPORTED SUBPAGE DESCRIPTOR (see table 404)							
5								
...	...							
n - 1	LAST SUPPORTED SUBPAGE DESCRIPTOR (see table 404)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The DS bit, SPF bit, and SUBPAGE CODE field shall be set as shown in table 403 for the Supported Subpages log page.

PAGE CODE field

The PAGE CODE field (see 5.2.2) indicates the log page for which log page and subpage codes are being returned.

SUPPORTED SUBPAGE descriptors

The supported subpage descriptors (see table 404) shall be in ascending order sorted by page code then subpage code, and shall include a descriptor with subpage code 00h for any implemented log page in which the SPF bit is set to zero. The supported subpage descriptors may or may not include all the subpages that are able to be returned by the device server for a specified page code.

Table 404 Supported subpage descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved		PAGE CODE					
1	SUBPAGE CODE							

PAGE CODE field

The PAGE CODE field indicates the number of a supported log page.

The page code is the same in the page header (see table 403) and in each supported subpage descriptor (see table 404)

SUBPAGE CODE field

The SUBPAGE CODE field indicates the subpage number of a supported log page.

5.2.26 Temperature log page (0Dh/00h)

5.2.26.1 Overview

The Temperature log page provides information about the current operating temperature of the SCSI Target Device using the parameter codes listed in table 405.

Table 405 Temperature log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Support Required
0000h	Temperature	Never	Mandatory
0001h	Reference Temperature	Never	Optional
All others	Reserved		

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Temperature log page has the format shown in table 406.

Table 406 Temperature log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (0)	PAGE CODE (0Dh)					
1	SUBPAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (0Ch)						(LSB)
3								
4	(MSB)	PARAMETER CODE 0000h)						(LSB)
5								
6	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
7	PARAMETER LENGTH (02h)							
8	Reserved							
9	TEMPERATURE							
10	(MSB)	PARAMETER CODE 0001h)						(LSB)
11								
12	PARAMETER CONTROL BYTE – binary format list log parameter (see 5.2.2.2.5)							
13	PARAMETER LENGTH (02h)							
14	Reserved							
15	REFERENCE TEMPERATURE							

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2. The SPF bit, PAGE CODE field, and SUBPAGE CODE field shall be set as shown in table 406 for the Temperature log page.

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2, and shall be set as shown in table 406 for the Temperature log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.2, and shall be set as shown in table 406 for the Temperature log parameter.

TEMPERATURE field

The TEMPERATURE field indicates the temperature of the SCSI target device in degrees Celsius at the time the LOG SENSE command is performed. Temperatures equal to or less than zero degrees Celsius shall cause the TEMPERATURE field to be set to zero. If the device server is unable to detect a valid temperature because of a sensor failure or other condition, then the TEMPERATURE field shall be set to FFh. The temperature should be reported with an accuracy of plus or minus three Celsius degrees while the SCSI target device is operating at a steady state within its environmental limits.

No comparison is performed between the contents of the TEMPERATURE field and the contents of the optional REFERENCE TEMPERATURE field.

REFERENCE TEMPERATURE field

The REFERENCE TEMPERATURE field indicates the maximum reported sensor temperature in degrees Celsius at which the SCSI target device is capable of operating continuously without degrading the SCSI target device's operation or reliability beyond manufacturer accepted limits. If the device server is unable to return a reference temperature and the optional Reference Temperature log parameter is included in the Temperature log page being returned, then REFERENCE TEMPERATURE field is set to FFh.

The reference temperature may change for vendor specific reasons.

5.2.27 Utilization log page (0Eh/01h)

5.2.27.1 Utilization log page overview

Using the format shown in table 427, the Utilization log page reports estimates of the rate at which device wear factors (e.g., damage to the recording medium) are being used. The parameter codes for the Utilization log page are defined in table 407.

Table 407 Utilization log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support Required
0000h	Workload Utilization	Never	5.2.27.2	Mandatory
0001h	Utilization Usage Rate Based on Date and Time	Never	5.2.27.3	Optional
All others	Reserved			

[a] The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.

The Utilization log page has the format defined in table 408.

Table 408 Utilization log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS (1b)	SPF (1b)	PAGE CODE (0Eh)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
UTILIZATION LOG PARAMETERS								
4	Utilization log parameter [first] (see table 407)							
...	...							
...	Utilization log parameter [last] (see table 407)							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 and shall be set to the values shown in table 408 for the Utilization log page.

5.2.27.2 Workload Utilization log parameter

The Workload Utilization log parameter for the Utilization log page has the format defined in table 409.

Table 409 Workload Utilization log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	PARAMETER CODE (0000h)						(LSB)
1	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.2.2)							
2	PARAMETER LENGTH (02h)							
3	(MSB)	WORKLOAD UTILIZATION						(LSB)
4								
5								

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2 and shall be set to the value shown in table 409 for the Workload Utilization log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.2 and shall be set to the value shown in table 409 for the Workload Utilization log parameter.

WORKLOAD UTILIZATION field

The WORKLOAD UTILIZATION field (see table 410) contains an estimate of the utilization associated with the logical unit as a percentage of the manufacturer's designs for various wear factors (e.g., wear of the medium, head load events), if any. The the units for the reported values are percent times 100 and range from 0.00% to 655.35%.

Table 410 WORKLOAD UTILIZATION field

Code	Description
0 to 9999	Less than (i.e., 0.00% to 99.99% of) the designed workload has been utilized.
10000	Exactly the designed workload for the device has been utilized.
10001 to 65534	Greater than (i.e., 100.01% to 655.34% of) the designed workload has been utilized.
65535	Greater than 655.34% of the designed workload has been utilized.

5.2.27.3 Utilization Usage Rate Based on Date and Time

The Utilization Rate Based on Date and Time log parameter for the Utilization log page has the format defined in table 411. If the current date and time has not been initialized by a SET TIMESTAMP command (see SPC-6), then the Utilization Rate Based on Date and Time log parameter shall not be returned in the Utilization log page (see table 409).

Table 411 Utilization Rate Based on Date and Time log parameter format

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____ PARAMETER CODE (0001h) _____ (LSB)							
1								
2	PARAMETER CONTROL BYTE – bounded data counter log parameter (see 5.2.2.2.2.2)							
3	PARAMETER LENGTH (02h)							
4	DATE AND TIME BASED UTILIZATION RATE							
5	Reserved							

PARAMETER CODE field

The PARAMETER CODE field is described in 5.2.2.2.2 and shall be set to the value shown in table 411 for the Utilization Rate Based on Date and Time log parameter.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in 5.2.2.2.2 and shall be set to the value shown in table 411 for the Utilization Rate Based on Date and Time log parameter.

DATE AND TIME BASED UTILIZATION RATE field

The DATE AND TIME BASED UTILIZATION RATE field (see table 412) contains an estimate of the rate at which device wear factors (e.g., damage to the recording medium) associated with the logical unit have been used during the interval that begins at the date and time of manufacture and ends at the timestamp that is reported by a REPORT TIMESTAMP command (i.e., the current value of a device clock) (see SPC-6).

Table 412 DATE AND TIME BASED UTILIZATION RATE field

Code	Description
0 to 99	The Workload Utilization usage rate has been less than (i.e., 0% to 99% of) the designed usage rate during the interval that begins at the date and time of manufacture and ends at the timestamp.
100	The Workload Utilization usage rate has been the exact designed usage rate during the interval that begins at the date and time of manufacture and ends at the timestamp.
101 to 254	The Workload Utilization usage rate has been greater than (i.e., 101% to 254% of) the designed usage rate during the interval that begins at the date and time of manufacture and ends at the timestamp.
255	The Workload Utilization usage rate has been greater than 254% of designed usage rate during the interval that begins at the date and time of manufacture and ends at the timestamp.

5.2.28 Zoned Block Device Statistics log page

Using the format shown in table 414, the Zoned Block Device Statistics log page reports the zoned block device statistics that are listed in table 413.

Table 413 Zoned Block Device Statistics log page parameter codes

Parameter code	Description	Resettable or Changeable ^[a]	Reference	Support
0000h	Maximum Open Zones	Reset Only	5.2.28.1	Mandatory
0001h	Maximum Explicitly Open Zones		5.2.28.2	
0002h	Maximum Implicitly Open Zones		5.2.28.3	
0003h	Minimum Empty Zones		5.2.28.4	
0004h	Maximum Non-sequential Zones ^[b]		5.2.28.5	Optional
0005h	Zones Emptied		5.2.28.6	
0006h	Suboptimal Write Commands ^[b]		5.2.28.7	
0007h	Commands Exceeding Optimal Limit ^[b]		5.2.28.8	
0008h	Failed Explicit Opens		5.2.28.9	
0009h	Read Rule Violations		5.2.28.10	
000Ah	Write Rule Violations		5.2.28.11	
000Bh	Maximum Implicitly Open Sequential Or Before Required Zones ^[c]		5.2.28.12	
All others	Reserved			

a) The keywords in this column – Always, Reset Only, and Never – are defined in 5.2.2.3.
b) Applicable only to sequential write preferred zones (see ZBC-2).
c) Applicable only to sequential or before required zones (see ZBC-2).

The Zoned Block Device Statistics log page has the format shown in table 414.

Table 414 Zoned Block Device Statistics log page

Bit Byte	7	6	5	4	3	2	1	0
0	DS	SPF (1b)	PAGE CODE (14h)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Zoned Block Device Statistics log parameters								
4								
...	Zoned Block Device Statistic log parameter [first]							
15								
...								
n-12								
...	Zoned Block Device Statistic log parameter [last]							
n								

DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The DS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.2.2 and shall be set to the values shown in table 414 for the Zoned Block Device Statistics log page.

5.2.28.1 Maximum Open Zones

The Maximum Open Zones log parameter has the format shown in table 415.

Table 415 Maximum Open Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0000h)							(LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	MAXIMUM OPEN ZONES							
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 415 for the Maximum Open Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Maximum Open Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 415 for the Maximum Open Zones log parameter.

MAXIMUM OPEN ZONES field

The MAXIMUM OPEN ZONES field indicates the maximum number of zones that have been concurrently open with a Zone Condition of EXPLICITLY OPEN or IMPLICITLY OPEN since this log parameter was last reset.

The MAXIMUM OPEN ZONES field shall be set to zero as a result of processing a power on. The MAXIMUM OPEN ZONES field shall be set to the current number of open zones as a result of processing a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.2 Maximum Explicitly Open Zones

The Maximum Explicitly Open Zones log parameter has the format shown in table 416.

Table 416 Maximum Explicitly Open Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0001h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	MAXIMUM EXPLICITLY OPEN ZONES							_____
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 416 for the Maximum Explicitly Open Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Maximum Explicitly Open Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 416 for the Maximum Explicitly Open Zones log parameter.

MAXIMUM EXPLICITLY OPEN ZONES field

The MAXIMUM EXPLICITLY OPEN ZONES field indicates the maximum number of zones that have been concurrently open with a Zone Condition of EXPLICITLY OPEN since this log parameter was last reset.

The MAXIMUM EXPLICITLY OPEN ZONES field shall be set to zero as a result of processing a power on. The MAXIMUM EXPLICITLY OPEN ZONES field shall be set to the current number of zones with a Zone Condition of EXPLICITLY OPEN as a result of processing a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.3 Maximum Implicitly Open Zones

The Maximum Implicitly Open Zones log parameter has the format shown in table 417.

Table 417 Maximum Implicitly Open Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0002h) _____ (LSB)							
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h) _____							
4	_____							
...	Reserved _____							
7	_____							
8	(MSB) _____							
...	MAXIMUM IMPLICITLY OPEN ZONES _____							
11	(LSB) _____							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 417 for the Maximum Implicitly Open Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Maximum Implicitly Open Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 417 for the Maximum Implicitly Open Zones log parameter.

MAXIMUM IMPLICITLY OPEN ZONES field

The MAXIMUM IMPLICITLY OPEN ZONES field indicates the maximum number of zones that have been concurrently open with a Zone Condition of IMPLICITLY OPEN since this log parameter was last reset.

The MAXIMUM IMPLICITLY OPEN ZONES field shall be set to zero as a result of processing a power on. The MAXIMUM IMPLICITLY OPEN ZONES field shall be set to the current number of zones with a Zone Condition of IMPLICITLY OPEN as a result of processing a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.4 Minimum Empty Zones

The Minimum Empty Zones log parameter has the format shown in table 418.

Table 418 Maximum Empty Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0003h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	MAXIMUM EMPTY ZONES							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 418 for the Minimum Empty Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Minimum Empty Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 418 for the Minimum Empty Zones log parameter.

MAXIMUM EMPTY ZONES field

The MINIMUM EMPTY ZONES field indicates the minimum number of zones that have been concurrently had a Zone Condition of EMPTY since this log parameter was last reset.

The MINIMUM EMPTY ZONES field shall be set to the current number of zones with a Zone Condition of EMPTY as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.5 Maximum Non-sequential Zones

For zoned block devices that support the sequential write preferred zone model (see ZBC-2), the Maximum Non-sequential Zones log parameter has the format shown in table 419.

Table 419 Maximum Non-Sequential Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0004h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	MAXIMUM NONSEQ ZONES							_____
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 419 for the Maximum Non-sequential Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Maximum Non-sequential Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 419 for the Maximum Non-sequential Zones log parameter.

MAXIMUM NONSEQ ZONES field

The MAXIMUM NONSEQ ZONES field indicates the maximum number of sequential write preferred zones that have concurrently had the Non-Sequential Write Resources Active attribute set to true (i.e., the NON_SEQ bit set to one) since this log parameter was last reset.

The MAXIMUM NONSEQ ZONES field shall be set to the current number of sequential write preferred zones that have concurrently had the Non-Sequential Write Resources Active attribute set to true (i.e., the NON_SEQ bit set to one) as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.6 Zones Emptied

The Zones Emptied log parameter has the format shown in table 420.

Table 420 Zones Emptied log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0005h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	ZONES EMPTIED							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 420 for the Zones Emptied log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Zones Emptied log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 420 for the Zones Emptied log parameter.

ZONES EMPTIED field

The ZONES EMPTIED field indicates the number of times that the Zone Condition for any zone changed to EMPTY as a result of processing a RESET WRITE POINTER command (see 4.8) with the ALL bit set to zero since this log parameter was last reset.

The ZONES EMPTIED field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.7 Suboptimal Write Commands

For zoned block devices that support the sequential write preferred zone model (see ZBC-2), the Suboptimal Write Commands log parameter has the format shown in table 421.

Table 421 Suboptimal Write Commands log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
1	PARAMETER CODE (0006h)							(LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	Reserved							
...								
7								
8	(MSB)							
...	SUBOPTIMAL WRITE COMMANDS							(LSB)
11								

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 421 for the Suboptimal Write Commands log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Suboptimal Write Commands log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 421 for the Suboptimal Write Commands log parameter.

SUBOPTIMAL WRITE COMMANDS field

The SUBOPTIMAL WRITE COMMANDS field indicates the number of write commands completed without error that specified a starting LBA in a write pointer zone and:

- a) a starting LBA not at the write pointer;
- b) a transfer length is large enough to access another write pointer zone that has a write pointer not equal to the lowest LBA of that write pointer zone; or
- c) accesses a zone with a Zone Condition of FULL, since this log parameter was last reset.

The SUBOPTIMAL WRITE COMMANDS field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.8 Commands Exceeding Optimal Limit

For zoned block devices that support the sequential write preferred zone model (see 4.5.3.3), the Commands Exceeding Optimal Limit log parameter has the format shown in table 422.

Table 422 Commands Exceeding Optimal Limit log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0007h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	COMMANDS EXCEEDING OPTIMAL LIMIT							_____
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 422 for the Commands Exceeding Optimal Limit log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Commands Exceeding Optimal Limit log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 422 for the Commands Exceeding Optimal Limit log parameter.

COMMANDS EXCEEDING OPTIMAL LIMIT field

The COMMANDS EXCEEDING OPTIMAL LIMIT field indicates the number of write commands that resulted in a sequential write preferred zone changing its Zone Condition to IMPLICITLY OPEN and resulted in the number of open zones being greater than the optimal value (i.e., the value of the OPTIMAL NUMBER OF OPEN SEQUENTIAL WRITE PREFERRED ZONES field (see 6.5.2)) since this log parameter was last reset.

The COMMANDS EXCEEDING OPTIMAL LIMIT field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.9 Failed Explicit Opens

The Failed Explicit Opens log parameter has the format shown in table 423.

Table 423 Failed Explicit Opens log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0008h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	FAILED EXPLICIT OPENS							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 423 for the Failed Explicit Opens log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Failed Explicit Opens log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 423 for the Failed Explicit Opens log parameter.

FAILED EXPLICIT OPENS field

The FAILED EXPLICIT OPENS field indicates the number of OPEN ZONE commands that returned CHECK CONDITION status with the additional sense code set to INSUFFICIENT ZONE RESOURCES since this log parameter was last reset.

The FAILED EXPLICIT OPENS field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.10 Read Rule Violations

The Read Rule Violations log parameter has the format shown in table 424.

Table 424 Read Rule Violations log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (0009h)							_____ (LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	READ RULE VIOLATIONS							
11	_____ (LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 424 for the Read Rule Violations log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Read Rule Violations log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 424 for the Read Rule Violations log parameter.

READ RULE VIOLATIONS field

The READ RULE VIOLATIONS field indicates the number of read commands that returned CHECK CONDITION status with the additional sense code set to:

- a) ATTEMPT TO READ INVALID DATA;
- b) READ BOUNDARY VIOLATION;
- c) ZONE IS OFFLINE;
- d) ZONE IS INACTIVE; or
- e) ATTEMPT TO ACCESS GAP ZONE,

since this log parameter was last reset.

The READ RULE VIOLATIONS field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.11 Write Rule Violations

The Write Rule Violations log parameter has the format shown in table 425.

Table 425 Write Rule Violations log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (000Ah)							(LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	WRITE RULE VIOLATIONS							
11	(LSB)							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 425 for the Write Rule Violations log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Write Rule Violations log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 425 for the Write Rule Violations log parameter.

WRITE RULE VIOLATIONS field

The WRITE RULE VIOLATIONS field indicates the number of read commands that returned CHECK CONDITION status with the additional sense code set to:

- a) INSUFFICIENT ZONE RESOURCES;
- b) WRITE BOUNDARY VIOLATION;
- c) UNALIGNED WRITE COMMAND;
- d) ZONE IS OFFLINE;
- e) ZONE IS READ ONLY;
- f) ZONE IS INACTIVE;
- g) ATTEMPT TO ACCESS GAP ZONE; or
- h) INVALID FIELD IN CDB that results from an attempt to write to a sequential write required zone with a Zone Condition of FULL, since this log parameter was last reset.

The WRITE RULE VIOLATIONS field shall be set to zero as a result of processing:

- a) a power on; or
- b) a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.2.28.12 Maximum Implicitly Open Sequential Or Before Required Zones

The Maximum Implicitly Open Sequential Or Before Required Zones log parameter has the format shown in table 426.

Table 426 Maximum Implicitly Open Sequential Or Before Required Zones log parameter

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	PARAMETER CODE (000Bh)							(LSB)
2	DU	Reserved	TSD	Reserved			FORMAT AND LINKING	
3	PARAMETER LENGTH (08h)							
4	_____							
...	Reserved							
7	_____							
8	(MSB) _____							
...	MAXIMUM IMPLICITLY OPEN SEQUENTIAL OR BEFORE REQUIRED ZONES							(LSB)
11	_____							

PARAMETER CODE field

The PARAMETER CODE field is described in SPC-6 and shall be set to the value shown in table 426 for the Maximum Implicitly Open Sequential Or Before Required Zones log parameter.

DU bit, the TSD bit, and the FORMAT AND LINKING field

The DU bit, the TSD bit, and the FORMAT AND LINKING field for the Maximum Implicitly Open Sequential Or Before Required Zones log parameter shall be set for a binary format list log parameter as described in SPC-6.

PARAMETER LENGTH field

The PARAMETER LENGTH field is described in SPC-6 and shall be set to the value shown in table 426 for the Maximum Implicitly Open Sequential Or Before Required Zones log parameter.

MAXIMUM IMPLICITLY OPEN SEQUENTIAL OR BEFORE REQUIRED ZONES field

The MAXIMUM IMPLICITLY OPEN SEQUENTIAL OR BEFORE REQUIRED ZONES field indicates the maximum number of sequential or before required zones (see ZBC-2) that have been concurrently open with a Zone Condition of IMPLICITLY OPEN since this log parameter was last reset.

The MAXIMUM IMPLICITLY OPEN SEQUENTIAL OR BEFORE REQUIRED ZONES field shall be set to zero as a result of:

- a) performing a power on; or
- b) processing a LOG SELECT command with the PCR bit set to one (see SPC-6) that results in resetting parameters in this log page.

5.3 Mode parameters

5.3.1 Mode parameters overview

This subclause describes the mode parameter headers, block descriptors, and mode pages used with MODE SELECT command (see 3.11 and 3.12) and MODE SENSE command (see 3.13 and 3.14) that are applicable to all SCSI devices. Subpages are identical to mode pages except that they include a SUBPAGE CODE field that further differentiates the mode page contents. Mode pages specific to each device type are described in the command standard that applies to that device type.

NOTE Many of the mode parameters in the following pages are changeable. A MODE SENSE command with the PC bit set to one will return a mask indicating the mode parameters that may be changed by a SCSI initiator port. Seagate disk drive product manuals indicate which pages a drive supports, what the default mode values are, and what mode parameters may be changed.

Table 427 defines the mode pages that are applicable to all device types that implement the MODE SELECT and MODE SENSE commands.

Table 427 Mode page codes and subpage codes

Page code	Subpage code	Mode Page Name	Reference
0Ah	02h	Application Tag	5.3.6
1Ch	01h	Background Control	5.3.7
0Ah	06h	Background Operation Control	5.3.8
08h	00h	Caching	5.3.9
0Ah	03h	Command Duration Limit A	5.3.10
0Ah	04h	Command Duration Limit B	5.3.11
0Ah	07h	Command Duration Limit T2A	5.3.12
0Ah	08h	Command Duration Limit T2B	5.3.13
0Ah	00h	Control	5.3.14
0Ah	01h	Control Extension	5.3.15
02h	00h	Disconnect-Reconnect for SAS	5.3.16
03h	00h	Format Device mode page (Obsolete)	5.3.17
0Ah	05h	IO Advice Hints Grouping	5.3.18
1Ch	00h	Informational Exceptions Control	5.3.19
1Ch	02h	Logical Block Provisioning	5.3.20
1Ah	00h	Power Condition	5.3.21
1Ah	01h	Power Consumption	5.3.22
01h	00h	Read-Write Recovery	5.3.23
18h	00h	Logical Unit Control (SAS)	5.3.24
19h	00h	Protocol Specific Port (SAS)	5.3.25
19h	01h	Phy Control and Discover	5.3.26
19h	02h	Share Port Control	5.3.27
19h	03h	Enhanced Phy Control	5.3.28

[a] Valid only for the MODE SENSE command

Table 427 Mode page codes and subpage codes

Page code	Subpage code	Mode Page Name	Reference
19h	E5h	Transceiver Control (Out) - SAS	5.3.29
19h	E6h	Transceiver Control (In) - SAS	5.3.30
04h	00h	Rigid Drive Geometry Parameters page (Obsolete)	5.3.31
00h	not applicable	Seagate specific Unit Attention parameters for HDD	5.3.32
00h	not applicable	Seagate specific Unit Attention parameters for SSD	5.3.33
07h	00h	Verify Error Recovery	5.3.34
0Ah	0Fh	Zoned Block Device Control	5.3.35
09h	00h	Obsolete	
0Ch	00h	Obsolete	
00h - 3Eh	FFh	Return all subpages for the specified page code [a]	
3Fh	00h	Return all pages not including subpages [a]	
3Fh	FFh	Return all pages and subpages [a]	
[a] Valid only for the MODE SENSE command			

5.3.2 Mode parameter list format

The mode parameter list shown in table 428 contains a header, followed by zero or more block descriptors, followed by zero or more variable-length mode pages. Parameter lists are defined for each device type.

Table 428 Mode parameter list

Bit Byte	7	6	5	4	3	2	1	0
	MODE PARAMETER HEADER							
	BLOCK DESCRIPTOR(S)							
	MODE PAGE(S) OR VENDOR SPECIFIC (E.G., PAGE CODE SET TO ZERO)							

5.3.3 Mode parameter header formats

The mode parameter header that is used by the MODE SELECT(6) command (see 3.11) and the MODE SENSE(6) command (see 3.13) is defined in table 429.

Table 429 Mode parameter header(6)

Bit Byte	7	6	5	4	3	2	1	0
0	MODE DATA LENGTH							
1	MEDIUM TYPE							
2	DEVICE-SPECIFIC PARAMETER							
3	BLOCK DESCRIPTOR LENGTH							

The mode parameter header that is used by the MODE SELECT(10) command (see 3.12) and the MODE SENSE(10) command (see 3.14) is defined in table 430.

When using the MODE SENSE command, the MODE DATA LENGTH field indicates the number of bytes that follow in the mode parameter list. When using the MODE SELECT command, the MODE DATA LENGTH field is reserved.

The contents of the MEDIUM TYPE field are unique for each device type. Refer to the mode parameters subclause of the specific device type command standard for definition of these values. Some device types reserve this field.

Table 430 Mode parameter header(10)

Bit Byte	7	6	5	4	3	2	1	0	
0	(MSB)	MODE DATA LENGTH							
1								(LSB)	
2	MEDIUM TYPE								
3	DEVICE-SPECIFIC PARAMETER								
4	Reserved								
5	Reserved								
6	(MSB)	BLOCK DESCRIPTOR LENGTH							
7								(LSB)	

MODE DATA LENGTH field

When using the MODE SENSE command, the MODE DATA LENGTH field indicates the length in bytes of the following data that is available to be transferred. The mode data length does not include the number of bytes in the MODE DATA LENGTH field. When using the MODE SELECT command, this field is reserved.

MEDIUM TYPE field

The contents of the MEDIUM TYPE field are unique for each device type. Refer to the mode parameters subclause of the specific device type command standard for definition of these values. Some device types reserve this field.

WP (Write Protect) bit

- 1** A WP bit set to one indicates that the medium is write-protected. The medium may be write protected when the software write protect (SWP) bit in the Control mode page (see 5.3.14) is set to one or if another vendor specific mechanism causes the medium to be write protected.
- 0** A WP bit set to zero indicates that the medium is not write-protected.

DEVICE-SPECIFIC PARAMETER field

The DEVICE-SPECIFIC PARAMETER field is unique for each device type. Refer to the mode parameters subclause of the specific device type command standard for definition of this field.

LONGLBA (Long LBA) bit

- 0** If the Long LBA (LONGLBA) bit is set to zero, the mode parameter block descriptor(s), if any, are each eight bytes long.
- 1** If the LONGLBA bit is set to one, the mode parameter block descriptor(s), if any, are each sixteen bytes long.

BLOCK DESCRIPTOR LENGTH field

The BLOCK DESCRIPTOR LENGTH field contains the length in bytes of all the block descriptors. It is equal to the number of block descriptors times eight if the LONGLBA bit is set to zero or times sixteen if the LONGLBA bit is set to one, and does not include mode pages or vendor specific parameters (e.g., page code set to zero), if any, that may follow the last block descriptor. A block descriptor length of zero indicates that no block descriptors are included in the mode parameter list. This condition shall not be considered an error.

5.3.4 Mode parameter block descriptors

5.3.4.1 Mode block descriptors overview

If the device server returns a mode parameter block descriptor, it shall return a short LBA mode parameter block descriptor (see 5.3.4.2) in the mode parameter data in response to:

- a) a MODE SENSE (6) command; or
- b) a MODE SENSE (10) command with the LLBAA bit set to zero.

If the device server returns a mode parameter block descriptor and the number of logical blocks is greater than FFFFFFFh, it may return a long LBA mode parameter block descriptor (see 5.3.4.3) in the mode parameter data in response to a MODE SENSE (10) command with the LLBAA bit set to one.

If the application client sends a mode parameter block descriptor in the mode parameter list, it shall send a short LBA mode parameter block descriptor (see 5.3.4.2) for a MODE SELECT (6) command.

If the application client sends a mode parameter block descriptor in the mode parameter list, it may send a long LBA mode parameter block descriptor (see 5.3.4.3) for a MODE SELECT (10) command.

Support for the mode parameter block descriptors is optional. The device server shall establish a unit attention condition with the additional sense code of MODE PARAMETERS CHANGED (see SPC-6 and SAM-6) when the block descriptor values are changed.

5.3.4.2 Short LBA mode parameter block descriptor

Table 431 defines the block descriptor for direct-access block devices used:

- a) with the MODE SELECT (6) and MODE SENSE (6) commands, and
- b) with the MODE SELECT (10) and MODE SENSE (10) commands when the LONGLBA bit is set to zero in the mode parameter header (see 5.3.3).

Table 431 Short LBA mode parameter block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	NUMBER OF BLOCKS							
3	(LSB)							
4	Reserved							
5	(MSB)							
...	LOGICAL BLOCK LENGTH							
7	(LSB)							

A device server shall respond to a MODE SENSE command (see 3.14) by reporting the number of logical blocks specified in the NUMBER OF LOGICAL BLOCKS field sent in the last MODE SELECT command that contained a mode parameter block descriptor. If no MODE SELECT command with a mode parameter block descriptor has been received then the current number of logical blocks shall be returned. To determine the number of logical blocks at which the logical unit is currently formatted, the application client shall use the READ CAPACITY command (see 3.22) rather than the MODE SENSE command.

On a MODE SENSE command, the device server may return a value of zero indicating that it does not report the number of logical blocks in the short LBA mode parameter block descriptor.

On a MODE SENSE command, if the number of logical blocks on the medium exceeds the maximum value that is able to be specified in the NUMBER OF LOGICAL BLOCKS field, the device server shall return a value of FFFFFFFh.

If the logical unit does not support changing its capacity by changing the NUMBER OF LOGICAL BLOCKS field using the MODE SELECT command (see 3.11 and 3.12), the value in the NUMBER OF LOGICAL BLOCKS field is ignored.

If the device supports changing its capacity by changing the NUMBER OF LOGICAL BLOCKS field, then the NUMBER OF LOGICAL BLOCKS field is interpreted as follows:

- a) If the NUMBER OF LOGICAL BLOCKS field is set to zero, the logical unit shall retain its current capacity if the logical block length has not changed. If the NUMBER OF LOGICAL BLOCKS field is set to zero and the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length, the logical unit shall be set to its maximum capacity when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command);
- b) If the NUMBER OF LOGICAL BLOCKS field is greater than zero and less than or equal to its maximum capacity, the logical unit shall be set to that number of logical blocks. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length, the logical unit shall not become format corrupt. This capacity setting shall be retained through power cycles, hard resets, logical unit resets, and L_T nexus losses. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length this capacity setting shall take effect on successful completion of the MODE SELECT command. If the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length this capacity setting shall take effect when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command);
- c) If the NUMBER OF LOGICAL BLOCKS field is set to a value greater than the maximum capacity of the device and less than FFFFFFFFh, then the MODE SELECT command shall be terminated with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST. The logical unit shall retain its previous logical block descriptor settings; or
- d) If the NUMBER OF LOGICAL BLOCKS field is set to FFFFFFFFh, the logical unit shall be set to its maximum capacity. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length, the logical unit shall not become format corrupt. This capacity setting shall be retained through power cycles, hard resets, logical unit resets, and L_T nexus losses. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length this capacity setting shall take effect of successful completion of the MODE SELECT command. If the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length this capacity setting shall take effect when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command).

LOGICAL BLOCK LENGTH field

The LOGICAL BLOCK LENGTH field specifies the length in bytes of each logical block. No change shall be made to any logical blocks on the medium until a format operation is initiated by an application client.

A device server shall respond to a MODE SENSE command (see 3.13 and 3.14) by reporting the length of the logical blocks as specified in the LOGICAL BLOCK LENGTH field sent in the last MODE SELECT command that contained a mode parameter block descriptor. If no MODE SELECT command with a block descriptor has been received then the current logical block length shall be returned (e.g., if the logical block length is 512 bytes and a MODE SELECT command occurs with the LOGICAL BLOCK LENGTH field set to 520 bytes, any MODE SENSE commands would return 520 in the LOGICAL BLOCK LENGTH field). To determine the logical block length at which the logical unit is currently formatted, the application client shall use the READ CAPACITY command rather than the MODE SELECT command.

5.3.4.3 Long LBA mode parameter block descriptor

Table 432 defines the block descriptor for direct-access block devices used with the MODE SELECT (10) command and MODE SENSE (10) command when the LONGLBA bit is set to one in the mode parameter header (see 5.3.3).

Table 432 Long LBA mode parameter block descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)							
...	NUMBER OF LOGICAL BLOCKS							
7								
8	Reserved							
...								
11								
12	(MSB)							
...	LOGICAL BLOCK LENGTH							
15								

A device server shall respond to a MODE SENSE command (see 3.13 and 3.14) by reporting the number of logical blocks specified in the NUMBER OF LOGICAL BLOCKS field sent in the last MODE SELECT command that contained a mode parameter block descriptor. If no MODE SELECT command with a mode parameter block descriptor has been received then the current number of logical blocks shall be returned. To determine the number of logical blocks at which the logical unit is currently formatted, the application client shall use the READ CAPACITY command rather than the MODE SENSE command.

On a MODE SENSE command, the device server may return a value of zero indicating that it does not report the number of logical blocks in the long LBA mode parameter block descriptor.

If the logical unit does not support changing its capacity by changing the NUMBER OF LOGICAL BLOCKS field using the MODE SELECT command (see 3.12), the value in the NUMBER OF LOGICAL BLOCKS field is ignored. If the device supports changing its capacity by changing the NUMBER OF LOGICAL BLOCKS field, then the NUMBER OF LOGICAL BLOCKS field is interpreted as follows:

-
- a) If the NUMBER OF LOGICAL BLOCKS field is set to zero, the logical unit shall retain its current capacity if the logical block length has not changed. If the NUMBER OF LOGICAL BLOCKS field is set to zero and the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length, the logical unit shall be set to its maximum capacity when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command).
 - b) If the NUMBER OF LOGICAL BLOCKS field is greater than zero and less than or equal to its maximum capacity, the logical unit shall be set to that number of logical blocks. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length, the logical unit shall not become format corrupt. This capacity setting shall be retained through power cycles, hard resets, logical unit resets, and I_T nexus losses. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length this capacity setting shall take effect on successful completion of the MODE SELECT command. If the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length, this capacity setting shall take effect when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command);
 - c) If the NUMBER OF LOGICAL BLOCKS field is set to a value greater than the maximum capacity of the device and less than FFFFFFFF FFFFFFFFh, then the device server shall terminate the MODE SELECT command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST. The logical unit shall retain its previous block descriptor settings; or
 - d) If the NUMBER OF LOGICAL BLOCKS field is set to FFFFFFFF FFFFFFFFh, the logical unit shall be set to its maximum capacity. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length, the logical unit shall not become format corrupt. This capacity setting shall be retained through power cycles, hard resets, logical unit resets, and I_T nexus losses. If the content of the LOGICAL BLOCK LENGTH field is the same as the current logical block length this capacity setting shall take effect on successful completion of the MODE SELECT command. If the content of the LOGICAL BLOCK LENGTH field (i.e., new logical block length) is different than the current logical block length this capacity setting shall take effect when the new logical block length takes effect (i.e., after a successful FORMAT UNIT command).

The LOGICAL BLOCK LENGTH field specifies the length in bytes of each logical block. No change shall be made to any logical blocks on the medium until a format operation is initiated by an application client.

A device server shall respond to a MODE SENSE command (see 3.13 and 3.14) by reporting the length of the logical blocks as specified in the LOGICAL BLOCK LENGTH field sent in the last MODE SELECT command that contained a mode parameter block descriptor. If no MODE SELECT command with a block descriptor has been received then the current logical block length shall be returned (e.g., if the logical block length is 512 bytes and a MODE SELECT command occurs with the LOGICAL BLOCK LENGTH field set to 520 bytes, any MODE SENSE command would return 520 in the LOGICAL BLOCK LENGTH field). To determine the logical block length at which the logical unit is currently formatted, the application client shall use the READ CAPACITY command rather than the MODE SELECT command.

5.3.5 Mode page and subpage formats and page codes

The page_0 mode page format is defined in table 433.

Table 433 Page_0 mode page format

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE					
1	PAGE LENGTH (N-1)							
2								
...	MODE PARAMETERS							
n								

The SUB_PAGE mode page format is defined in table 434.

Table 434 SUB_PAGE mode page format

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE					
1	SUBPAGE CODE							
2	(MSB)	PAGE LENGTH (N-3)						(LSB)
3								
4								
...	MODE PARAMETERS							
n								

Each mode page contains a PS bit, an SPF bit, a PAGE CODE field, a PAGE LENGTH field, and a set of mode parameters. The page codes are defined in this subclause and in the mode parameter subclauses in the command standard for the specific device type. Each mode page with a SPF bit set to one contains a SUBPAGE CODE field.

PS (parameters saveable) bit

- 1** When using the MODE SENSE command, a parameters saveable (PS) bit set to one indicates that the mode page may be saved by the logical unit in a nonvolatile, vendor specific location.
- 0** A PS bit set to zero indicates that the device server is not able to save the supported parameters. When using the MODE SELECT command, the PS bit is reserved.

DS bit

The DS bit is described in 5.2.2.

SPF (SubPage Format) bit

- 0** A SubPage Format (SPF) bit set to zero indicates that the page_0 mode page format is being used.
- 1** A SPF bit set to one indicates that the SUB_PAGE mode page format is being used.

PAGE CODE and SUBPAGE CODE fields

The PAGE CODE and SUBPAGE CODE fields identify the format and parameters defined for that mode page. Some page codes are defined as applying to all device types and other page codes are defined for the specific device type. The page codes that apply to a specific device type are defined in the command standard for that device type. The applicability of each subpage code matches that of the page code with which it is associated.

When using the MODE SENSE command, if page code 00h (vendor specific mode page) is implemented, the device server shall return that mode page last in response to a request to return all mode pages (page code 3Fh). When using the MODE SELECT command, this mode page should be sent last.

PAGE LENGTH field

The PAGE LENGTH field specifies the length in bytes of the mode parameters that follow. If the application client does not set this value to the value that is returned for the mode page by the MODE SENSE command, the command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST. The logical unit may implement a mode page that is less than the full mode page length defined, provided no field is truncated and the PAGE LENGTH field correctly specifies the actual length implemented.

MODE PARAMETERS

The MODE PARAMETERS for each mode page are defined in the following subclauses, or in the mode parameters subclause in the command standard for the specific device type. MODE PARAMETERS not implemented by the logical unit shall be set to zero.

5.3.6 Application Tag mode page (0Ah/02h)

The Application Tag mode page (see table 435) specifies the Application Tag that a device server configured for protection information (see 5.3.6) shall use for each LBA range if the ATO bit in the Control mode page (see 5.3.14) is set to one. The mode page policy (see 5.4.14) for this page shall be shared.

If a method not defined by this standard changes the parameter data to be returned by the device server in the Application Tag mode page, then the device server shall establish a unit attention condition for the initiator port associated with every I_T nexus with the additional sense code set to MODE PARAMETERS CHANGED.

Table 435 Application Tag mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE(02h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
4	(MSB)	Reserved						(LSB)
...								
15								
Application Tag Descriptors								
16								
...	Application Tag descriptor (first)							
39								
...	...							
n - 24								
...	Application Tag descriptor (last)							
n								

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in SPC-6.

The SPF bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field shall be set to the values shown in Table 435.

5.3.6.1 Application Tag descriptor

The application tag descriptor format is described in Table 436.

Table 436 Application Tag descriptor format

Bit Byte	7	6	5	4	3	2	1	0	
0	LAST	Reserved							
1	Reserved								
...									
5									
6	(MSB)	LOGICAL BLOCK APPLICATION TAG						(LSB)	
7	LOGICAL BLOCK ADDRESS								
8									(MSB)
...									
15	LOGICAL BLOCK COUNT								
16									(MSB)
...									
23									
...									
23									(LSB)

LAST bit

- 1** A LAST bit set to one specifies that this Application Tag descriptor is the last valid Application Tag descriptor in the Application Tag mode page.
- 0** A LAST bit set to zero specifies that the Application Tag descriptor is not the last valid Application Tag descriptor in the Application Tag mode page.

LOGICAL BLOCK APPLICATION TAG field

The LOGICAL BLOCK APPLICATION TAG field specifies the value to be compared with the LOGICAL BLOCK APPLICATION TAG field associated with data read or written to the LBA.

LOGICAL BLOCK ADDRESS field

The LOGICAL BLOCK ADDRESS field contains the starting LBA for this Application Tag descriptor. The LOGICAL BLOCK ADDRESS field in the first Application Tag descriptor shall be set to 0000_0000_0000_0000h. For subsequent Application Tag descriptors, the contents of the LOGICAL BLOCK ADDRESS field shall contain the sum of the values in:

- a) the LOGICAL BLOCK ADDRESS field in the previous Application Tag descriptor; and
- b) the LOGICAL BLOCK COUNT field in the previous Application Tag descriptor.

The sum of the LOGICAL BLOCK ADDRESS field in the Application Tag descriptor with the LAST bit set to one and the LOGICAL BLOCK COUNT field in the Application Tag descriptor with the LAST bit set to one shall equal the RETURNED LOGICAL BLOCK ADDRESS field in the READ CAPACITY (16) parameter data (see 3.25.2).

If an invalid combination of the LAST bit, LOGICAL BLOCK APPLICATION TAG field, and LOGICAL BLOCK ADDRESS field are sent by the application client, then the device server shall terminate the MODE SELECT command (see 3.12) with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST. The LOGICAL BLOCK COUNT field specifies the number of logical blocks to which this Application Tag descriptor applies.

LOGICAL BLOCK COUNT field

A LOGICAL BLOCK COUNT field set to 0000_0000_0000_0000h specifies that this Application Tag descriptor shall be ignored.

5.3.7 Background Control mode page (1Ch/01h)

The Background Control mode page (see table 437) is a subpage of the Informational Exception Control mode page (see 5.3.19) and provides controls over background operations. The mode page policy (see 5.4.14) for this subpage shall be shared.

Table 437 Background Control mode page

Bit Byte	7	6	5	4	3	2	1	0	
0	PS	SPF(1b)	PAGE CODE (1Ch)						
1	SUBPAGE CODE (01h)								
2	(MSB)	PAGE LENGTH (000Ch)						(LSB)	
3	Reserved						S_L_FULL	LOWIR	EN_BMS
4	Reserved								
5	(MSB)	BACKGROUND MEDIUM SCAN INTERVAL TIME						(LSB)	
6	(MSB)	BACKGROUND PRE-SCAN TIME LIMIT						(LSB)	
7	(MSB)	MINIMUM IDLE TIME BEFORE BACKGROUND SCAN						(LSB)	
8	(MSB)	MAXIMUM TIME TO SUSPEND BACKGROUND SCAN						(LSB)	
9	Reserved								
10	Reserved								
11	Reserved								
12	Reserved								
13	Reserved								
14	Reserved								
15	Reserved								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5.

S_L_FULL bit

- 0 A suspend on log full (S_L_FULL) bit set to zero specifies that the device server shall continue running a background scan operation (see SPC-6) even if the Background Scan log page (see 5.2.4) contains the maximum number of Background Scan parameters (see table 314) supported by the logical unit.
- 1 A S_L_FULL bit set to one specifies that the device server shall suspend a background scan operation if the Background Scan log page contains the maximum number of Background scan log parameters supported by the logical unit.

LOWIR bit

- 0 A log only when intervention required (LOWIR) bit set to zero specifies that the device server shall log all suspected recoverable medium errors or unrecoverable medium errors that are identified during background scan operations in the Background Scan log page.
- 1 A LOWIR bit set to one specifies that the device server shall only log medium errors identified during background scan operations in the Background Scan log page that require application client intervention.

EN_BMS (Enable Background Medium Scan) bit

- 0** An enable background medium scan (EN_BMS) bit set to zero specifies that background medium scan is disabled.
- 1** An EN_BMS bit set to one specifies that background medium scan operations are enabled. If the EN_PS bit is also set to one then a background medium scan operation shall not start until after the pre-scan operation is halted or completed.

If a background medium scan operation is in progress when the EN_BMS bit is changed from one to zero, then the logical unit shall suspend the background medium scan operation before the device server completes the MODE SELECT command, and the background medium scan shall remain suspended until the EN_BMS bit is set to one, at which time the background medium scan operation shall resume, beginning with the logical block being tested when the background medium scan was suspended.

EN_PS (enable pre-scan) bit

- 0** An enable pre-scan (EN_PS) bit set to zero specifies that pre-scan is disabled. If a pre-scan operation is in progress when EN_PS is changed from a one to a zero then pre-scan is halted.
- 1** An EN_PS bit set to one specifies that a pre-scan operation is started after the next power on cycle.

Once this pre-scan has completed, another pre-scan shall not occur unless the EN_PS bit is set to zero, then set to one, and another power on cycle occurs.

BACKGROUND MEDIUM SCAN INTERVAL TIME field

The BACKGROUND MEDIUM SCAN INTERVAL TIME field specifies the minimum time, in hours, between the start of one pre-scan or background medium scan operation and the start of the next background medium scan operation. If the current background medium scan operation takes longer than the value specified in the BACKGROUND MEDIUM SCAN INTERVAL TIME field, then the logical unit shall:

- a) continue the current background pre-scan operation or background medium scan operation until that background scan operation is complete; and
- b) the logical unit shall start the next background medium scan operation starts upon completion of the current background pre-scan operation or background medium scan operation.

BACKGROUND PRE-SCAN TIME LIMIT field

The BACKGROUND PRE-SCAN TIME LIMIT field specifies the maximum time, in hours, for a background pre-scan operation to complete. If the background pre-scan operation does not complete within the specified time then the device server shall halt the background pre-scan operation. A value of zero specifies an unlimited timeout value.

MINIMUM IDLETIME BEFORE BACKGROUND SCAN field

The MINIMUM IDLE TIME BEFORE BACKGROUND SCAN field specifies the time, in milliseconds, that the logical unit shall be idle after suspending a background scan operation before resuming a background scan operation (e.g., after the device server has completed all of the commands in the task set).

MAXIMUM TIME TO SUSPEND BACKGROUND SCAN field

The MAXIMUM TIME TO SUSPEND BACKGROUND SCAN field specifies the time, in milliseconds, that the device server should take to start processing a command received while a logical unit is performing a background scan operation.

5.3.8 Background Operation Control mode page (0Ah/06h)

The Background Operation Control mode page (see table 438) provides controls of device server background operation.

Table 438 Background Operation Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE (06h)							
2	PAGE LENGTH (01FDh)							
3	Reserved							
4	BO_MODE		Reserved					
5	Reserved							
...	Reserved							
n	Reserved							

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5.

BO_MODE field

The background operation mode (BO_MODE) field specifies how host initiated advanced background operations shall operate during read operations or write operations as defined in table 439.

Table 439 BO_MODE field

Code	Description
00b	Host initiated advanced background operation shall be suspended during read operations and write operations and resume advanced background operation when read operations and write operations are complete.
01b	Host initiated advanced background operation shall continue during read operations and write operations.
All others	Reserved

5.3.9 Caching Mode page (08h)

The Caching Mode page for MODE SENSE/MODE SELECT defines the parameters that affect the use of the cache (see table 440).

Table 440 Caching Mode page (08h)

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (08h)					
1	PAGE LENGTH (12h)							
2	IC	ABPF	CAP	DISC	SIZE	WCE	MF	RCD
3	DEMAND READ RETENTION PRIORITY				WRITE RETENTION PRIORITY			
4	(MSB)	DISABLE PREFETCH TRANSFER LENGTH						(LSB)
5								
6	(MSB)	MINIMUM PREFETCH						(LSB)
7								
8	(MSB)	MAXIMUM PREFETCH						(LSB)
9								
10	(MSB)	MAXIMUM PREFETCH CEILING						(LSB)
11								
12	FSW	LBCSS	DRA	Vendor specific		SYNC_PROG		NV_DIS
13	NUMBER OF CACHE SEGMENTS							
14	(MSB)	CACHE SEGMENT SIZE						(LSB)
15								
16	Reserved							
17	(MSB)	Obsolete						(LSB)
...								
19								

PS bit

The returned Parameter Savable (PS) bit of 1 indicates that page 08h parameter data is savable.

SPF bit, the PAGE CODE field and the PAGE LENGTH field

The SPF bit, the PAGE CODE field and the PAGE LENGTH field shall be set to the values shown in table 440 for the Caching mode page.

IC enable bit

- 1** When the Initiator Control (IC) enable bit is set to one, adaptive read look-ahead (ARLA) is disabled.
- 0** When IC is set to ZERO, ARLA is enabled. Since Seagate drives covered by this manual do not organize the cache according to size of segment, but rather by number of segments, this bit is used to enable or disable ARLA (in non-Seagate equipment, this might be used to designate cache size).

Note. ARLA cannot be disabled in some Seagate drives using the ASAll code. See individual drive's Product Manual, Volume 1.

ABPF bit

- 1** The ABORT PREFETCH (ABPF) bit, when set to one, with the DRA bit equal to zero, requests that the SCSI device abort the PREFETCH upon selection. The ABPF set to one takes precedence over the Minimum PREFETCH bytes.
- 0** When set to zero, with the DRA bit equal to zero, the termination of any active PREFETCH is dependent upon Caching Page bytes 4 through 11 and is operation and/or vendor-specific.

CAP (Caching Analysis Permitted) bit

- 1** The Caching Analysis Permitted (CAP) bit, when set to one, enables caching analysis.
- 0** A zero indicates caching analysis is disabled. Caching analysis results are placed in the SCSI logging information table. See individual drive's Product Manual, Volume 1, SCSI Bus Conditions and Miscellaneous Features Supported table.

DISC (Discontinuity) bit

- 1** The Discontinuity (DISC) bit, when set to one, requests that the SCSI device continue the PREFETCH across time discontinuities, such as across cylinders or tracks up to the limits of the buffer, or segment, space available for PREFETCH.
- 0** When set to zero, the DISC requests that prefetches be truncated at time discontinuities.

SIZE (Size Enable) bit

- 1** The Size Enable (SIZE) bit, when set to one, indicates that the Cache Segment Size is to be used to control caching segmentation.
- 0** When SIZE equals zero, the Initiator requests that the Number of Cache Segments is to be used to control caching segmentation. For Seagate drives covered by this manual, SIZE is always zero.

WCE (Write Cache Enable) bit

- 0** SCSI WRITE commands may not return status and completion message bytes until all data has been written to the media.
- 1** SCSI WRITE commands may return status and completion message bytes as soon as all data has been received from the host.

MF (Multiplication Factor) bit

- 0** The Minimum PREFETCH and Maximum PREFETCH fields are interpreted as a number of logical blocks.
- 1** Specifies that the target shall interpret the minimum and maximum PREFETCH fields to be specified in terms of a scalar number which, when multiplied by the number of logical blocks to be transferred for the current command, yields the number of logical blocks for each of the respective types of PREFETCH.

RCD (READ Cache Disable) bit

- 0** SCSI READ commands may access the cache or the media.
- 1** SCSI READ commands must access the media. Data cannot come from the cache.

DEMAND READ RETENTION PRIORITY field

DEMAND READ RETENTION PRIORITY. The cache replacement algorithm does not distinguish between retention in the cache of host-requested data and PREFETCH data. Therefore, this half byte is always 0.

WRITE RETENTION PRIORITY field

WRITE RETENTION PRIORITY. The cache replacement algorithm does distinguish between retention in the cache of host-requested data and PREFETCH data. Therefore, this half byte is always 0.

DISABLE PREFETCH TRANSFER LENGTH field

DISABLE PREFETCH TRANSFER LENGTH. PREFETCH is disabled for any SCSI READ command whose requested transfer length exceeds this value.

MINIMUM PREFETCH field

The MINIMUM PREFETCH specifies the minimum number sectors to prefetch, regardless of the delay it may cause to other commands.

MAXIMUM PREFETCH field

The MAXIMUM PREFETCH specifies the maximum number of logical blocks that may be prefetched. The PREFETCH operation may be aborted before the MAXIMUM PREFETCH value is reached, but only if the MINIMUM PREFETCH value has been satisfied.

MAXIMUM PREFETCH CEILING field

The MAXIMUM PREFETCH Ceiling specifies an upper limit on the number of logical blocks computed as the maximum prefetch. If the MAXIMUM PREFETCH value is greater than the MAXIMUM PREFETCH CEILING, the value is truncated to the MAXIMUM PREFETCH CEILING value.

FSW (FORCE SEQUENTIAL WRITE) bit

- 1** The Force Sequential Write (FSW) bit, when set to one, indicates that multiple block writes are to be transferred over the SCSI bus and written to the media in an ascending, sequential, logical block order.
- 0** When the FSW bit equals zero, the target is allowed to reorder the sequence of writing addressed logical blocks in order to achieve a faster command completion.

LBCSS bit

- 1** A logical block cache segment size (LBCSS) bit set to one specifies that the CACHE SEGMENT SIZE field units shall be interpreted as logical blocks.
- 0** An LBCSS bit set to zero specifies that the CACHE SEGMENT SIZE field units shall be interpreted as bytes. The LBCSS shall not impact the units of other fields.

DRA (Disable READ-Ahead) bit

- 1** The Disable READ-Ahead (DRA) bit, when set to one, requests that the target not read into the buffer any logical blocks beyond the addressed logical block(s).
- 0** When the DRA bit equals zero, the target may continue to read logical blocks into the buffer beyond the addressed logical block(s).

SYNC_PROG field

The synchronize cache progress indication support (SYNC_PROG) field specifies device server progress indication reporting for the SYNCHRONIZE CACHE commands as defined in 3.56.

NV_DIS bit

- 1** An NV_DIS bit set to one specifies that the device server shall disable a non-volatile cache and indicates that a non-volatile cache is supported but disabled.
- 0** An NV_DIS bit set to zero specifies that the device server may use a non-volatile cache and indicates that a non-volatile cache may be present and enabled.

NUMBER OF CACHE SEGMENTS byte

The NUMBER OF CACHE SEGMENTS byte gives the number of segments into which the host requests the drive divide the cache.

CACHE SEGMENT SIZE field

The CACHE SEGMENT SIZE field indicates the requested segment size in bytes. This manual assumes that the Cache Segment Size field is valid only when the Size bit is one.

5.3.10 Command Duration Limit A mode page (0Ah/03h)

The Command Duration Limit A mode page (see table 441) provides controls for command duration limit (see SAM-6) that are applicable to all device types, for commands for which the REPORT SUPPORTED OPERATION CODES command parameter data CDLP field (see 3.37) indicates the Command Duration Limit A mode page. The mode page policy (see 5.4.14) for this mode page should be per I_T nexus. The mode page policy may be shared. If a field in this mode page is changed while there is a command already in the task set, then the new value of the field shall not apply to that command.

Table 441 Command Duration Limit A mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE(03h)							
2	(MSB)	PAGE LENGTH (0020h)						(LSB)
3								
4								
...	Reserved							
7								
Command duration limit descriptor list								
8								
...	Command duration limit descriptor (first)							
11								
12								
...	Command duration limit descriptor (second)							
15								
...	...							
32								
...	Command duration limit descriptor (last)							
35								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set as shown in table 441 for the Command Duration Limit A mode page.

Command duration limit descriptor fields

The command duration limit descriptor (see table 442) describes the command duration limit corresponding to the duration limit descriptor value in the CDB (see appropriate command standard).

EXAMPLE – A duration limit descriptor value of 001b selects the command duration limit contained in the first command duration limit descriptor, a duration limit descriptor value of 010b selects the command duration limit contained in the second command duration limit descriptor, and a duration limit descriptor value of 111b selects the command duration limit contained in the seventh command limit duration descriptor.

Table 442 Command Duration Limit A mode page

Bit Byte	7	6	5	4	3	2	1	0
0	CDLUNIT			Reserved				
1	Reserved							
2	(MSB)	COMMAND DURATION LIMIT						(LSB)
3								

CDLUNIT field

The CDLUNIT field (see table 443) specifies the time units for this command duration limit descriptor.

Table 443 CDLUNIT field

Code	Description
000b	No duration limit is specified
100b	1 microsecond
101b	10 milliseconds
110b	500 milliseconds
All others	Reserved

COMMAND DURATION LIMIT field

A COMMAND DURATION LIMIT field set to a non-zero value specifies the command duration limit in units specified by the CDLUNIT field. A COMMAND DURATION LIMIT field set to zero specifies that no command duration limit is specified by the command duration limit descriptor. If the CDLUNIT field is set to 000b, the COMMAND DURATIONLIMIT field shall be ignored

5.3.11 Command Duration Limit B mode page (0Ah/04h)

The Command Duration Limit B mode page (see table 444) provides controls for command duration limit (see SAM-6) that are applicable to all device types, for commands for which the REPORT SUPPORTED OPERATION CODES command parameter data CDLP field (see 3.37.4) indicates the Command Duration Limit B mode page. The mode page policy (see 5.4.14) for this mode page should be per I_T nexus. The mode page policy may be shared. If a field in this mode page is changed while there is a command already in the task set, then the new value of the field shall not apply to that command.

Table 444 Command Duration Limit B mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE(04h)							
2	(MSB)	PAGE LENGTH (0020h)						(LSB)
3								
4								
...	Reserved							
7								
Command duration limit descriptor list								
8								
...	Command duration limit descriptor (first)							
11								
12								
...	Command duration limit descriptor (second)							
15								
...	...							
32								
...	Command duration limit descriptor (last)							
35								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set as shown in table 444 for the Command Duration Limit B mode page.

Command duration limit descriptor fields

The command duration limit descriptor (see table 442) describes the command duration limit corresponding to the duration limit descriptor value in the CDB if the Command Duration Limit B mode page is indicated (see SPC-6).

5.3.12 Command Duration Limit T2A mode page

The Command Duration Limit T2A mode page (see table 445) provides controls for command duration limit (see SAM-6) that are applicable to all device types, for commands for which the REPORT SUPPORTED OPERATION CODES command parameter data RWCDLP bit and CDLP field (see 3.37) indicate the Command Duration Limit T2A mode page. The mode page policy (see 5.4.14) for this mode page should be per I_T nexus. The mode page policy may be shared. If a field in this mode page is changed while there is a command already in the task set, then the new value of the field shall not apply to that command.

Table 445 Command Duration Limit T2A mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE (07h)							
2	(MSB)	PAGE LENGTH (00E4h)						(LSB)
3								
4	Reserved							
...								
6								
7	Reserved				PERFORMANCE VERSUS LATENCY CONTROLS			
T2 command duration limit descriptor list								
8								
...	T2 command duration limit descriptor (first)							
39								
40								
...	T2 command duration limit descriptor (second)							
71								
...	...							
200								
...	T2 command duration limit descriptor (seventh)							
231								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set as shown in table 445 for the Command Duration Limit T2A mode page.

PERFORMANCE VERSUS LATENCY CONTROLS field

The PERFORMANCE VERSUS LATENCY CONTROLS field (see table 446) specifies how much overall performance (e.g., total reads and writes per second) is allowed to be effected by read write latency controls (i.e., the combination of the REQUESTED LATENCY TARGET fields, PREDICTIVE MISS POLICY fields, LATENCY MISS POLICY fields, NONCONFORMANCE POLICY fields, and CONFORMANCE TARGET fields in every T2 command duration limit descriptor (see 5.3.12.1) in the Command Duration Limit T2A mode page (see 5.3.12) and every T2 command duration limit descriptor in the Command Duration Limit T2B mode page (see 5.3.13).

Table 446 PERFORMANCE VERSUS LATENCY CONTROLS field

Code	Description
0	Read write latency controls have top priority, regardless of their effects on overall performance.
1 to 14	Overall performance may be reduced by up to adjustment percent in order to improve the effectiveness of read write latency controls. Where: adjustment = (3 × code) + 50 and code = the value in the PERFORMANCE VERSUS LATENCY CONTROLS field
15	Overall performance has top priority, regardless of its effect on read write latency controls.

T2 command duration limit descriptor

The T2 command duration limit descriptor (see 5.3.12.1) describes the command duration limit information that corresponds to the duration limit descriptor index in the CDB if the Command Duration Limit T2A mode page is indicated (see 3.37).

5.3.12.1 T2 command duration limit descriptor

The T2 command duration limit descriptor (see table 447) describes the command duration limit information that corresponds to one duration limit descriptor index.

Table 447 T2 command duration limit descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved				T2CDLUNITS			
1	Reserved							
2	(MSB)	MAX INACTIVE TIME						(LSB)
3								
4	(MSB)	MAX ACTIVE TIME						(LSB)
5								
6	MAX INACTIVE TIME POLICY				MAX ACTIVE TIME POLICY			
7	Reserved							
8	(MSB)	RESTRICTED						(LSB)
9								
10	COMMAND DURATION GUIDELINE							
11								
12	RESTRICTED				RESTRICTED			
13	RESTRICTED				RESTRICTED			
14	Reserved				COMMAND DURATION GUIDELINE POLICY			
15	Reserved							BYP_SEQ
16								
...	Reserved							
31								

T2CDLUNITS field

The T2CDLUNITS field (see table 448) specifies the time units for the MAX INACTIVE TIME field, the MAX ACTIVE TIME field, the REQUESTED LATENCY TARGET field, and the ACHIEVABLE LATENCY TARGET field. The default value for the T2CDLUNITS field is the smallest value that the device server allows for time units. If a MODE SELECT command attempts to set a T2CDLUNITS field to a time unit value that is less than the minimum that the device supports, then the command may be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Table 448 T2CDLUNITS field

Code	Description
0h	No value specified
6h	500 nanoseconds
8h	1 milliseconds
Ah	10 milliseconds
Eh	500 milliseconds
all others	Reserved

MAX INACTIVE TIME field

The MAX INACTIVE TIME field specifies an upper limit on the time that elapses before a command becomes an enabled command (i.e., the interval between the time at which the SCSI Command Received transport protocol service indication is invoked (see SAM-6) to the time at which the command becomes an enabled command). A MAX INACTIVE TIME field set to a non-zero value specifies the time upper limit in units indicated by the T2CDLUNITS field. A MAX INACTIVE TIME field set to zero specifies that no time upper limit is specified by this T2 command duration limit descriptor. If the T2CDLUNITS field is set to 0h, the MAX INACTIVE TIME field shall be ignored.

MAX ACTIVE TIME field

The MAX ACTIVE TIME field specifies an upper limit on the time that elapses during the processing of a command (i.e., the interval between the time at which a command first becomes an enabled command to the time the device server returns status for the command). A MAX ACTIVE TIME field set to a non-zero value specifies the time upper limit in units specified by the T2CDLUNITS field. A MAX ACTIVE TIME field set to zero specifies that no time upper limit is specified by this T2 command duration limit descriptor. If the T2CDLUNITS field is set to 0h, the MAX ACTIVE TIME field shall be ignored.

MAX INACTIVE TIME POLICY field

The MAX INACTIVE TIME POLICY field (see table 449) specifies the policy action taken if the max inactive limit is not met (i.e., the time used to cause a command to become an enabled command exceeds the time specified by the MAX INACTIVE TIME field and the T2CDLUNITS field).

Table 449 Max inactive time policy field

Code	Description
0h	The device server shall complete the command at the earliest possible time (i.e, do nothing based on the max time limit not being met).
1h to Ch	Reserved
Dh	The device server shall complete the command with GOOD status, with the sense key set to COMPLETED and the sense code set to DATA CURRENTLY UNAVAILABLE.
Eh	Reserved
Fh	The device server shall terminate the command with CHECK CONDITION status, with the sense key set to ABORTED COMMAND and the additional sense code set to COMMAND TIMEOUT BEFORE PROCESSING.

MAX ACTIVE TIME POLICY field

The MAX ACTIVE TIME POLICY field (see table 450) specifies the policy action taken if the max active time limit is not met (i.e., the time used to process a command exceeds the time specified by the MAX ACTIVE TIME field and the T2CDLUNITS field).

Table 450 Max active time policy field

Code	Description
0h	The device server shall complete the command at the earliest possible time (i.e, do nothing based on the max time limit not being met).
1h to Ch	Reserved
Dh	The device server shall complete the command with GOOD status, with the sense key set to COMPLETED and the sense code set to DATA CURRENTLY UNAVAILABLE.
Eh	The device server shall terminate the command with CHECK CONDITION status, with the sense key set to ABORTED COMMAND and the additional sense code set to COMMAND TIMEOUT DURING PROCESSING or COMMAND TIMEOUT DURING PROCESSING DUE TO ERROR RECOVERY. If the starting LBA contents have been transferred to the application client, then the device server may indicate the largest LBA for which a contiguous range of LBAs have been transferred to the application client starting with the starting LBA of the read command as described in SBC-5.
Fh	The device server shall terminate the command with CHECK CONDITION status, with the sense key set to ABORTED COMMAND and the additional sense code set to COMMAND TIMEOUT BEFORE PROCESSING.

COMMAND DURATION GUIDELINE field

The COMMAND DURATION GUIDELINE field specifies the preferred length of time for the completion of a command. The preferred length of time for the command completion is specified as the non-zero time in units indicated by the T2CDLUNITS field to be added to fastest time for completion of a read command for which the device server is able to return the requested data only by accessing the media. If the T2CDLUNITS field is set to 0h, the COMMAND DURATION GUIDELINE field shall be ignored.

COMMAND DURATION GUIDELINE field

A COMMAND DURATION GUIDELINE field set to zero indicates that no command completion guidance is provided by this T2 command duration limits descriptor.

The combination of COMMAND DURATION GUIDELINE field and the T2CDLUNITS field (i.e., the command duration guideline) shall affect device server processing of a command that selects a T2 command duration limits descriptor as follows:

- a) the length of time with which the device server completes that command is:
 - A) faster for smaller non-zero command duration guideline values; and
 - B) slower for larger non-zero command duration guideline values, in comparison to the non-zero command duration guideline values specified by other T2 command duration limits descriptors; and
- b) larger magnitudes of the difference between the non-zero command duration guideline values in two different T2 command duration limits descriptors result in larger probabilities of differences between the length of time of command completions for the commands that select those descriptors.

EXAMPLE – A host may specify a set of command duration guidelines that is independent of a device server's performance characteristics by specifying 10 milliseconds as the command duration guideline in one or more T2 command duration limits descriptors as a method of associating them with the most rapid preferred command completion. For all other T2 command duration limits descriptors, the command duration guideline is specified as the preferred number of 10 millisecond intervals for command completion minus the average number of milliseconds in which a seek finishes for a hypothetical, average hard disk drive, if for any other T2 command duration limits descriptor, the computed command duration limits guideline value is less than 10 milliseconds, then 10 milliseconds is used as the command duration guideline for that T2 command duration limits descriptor. The magnitude relationships computed in this way provide useful guidance to the device server.

PERFORMANCE VERSUS COMMAND DURATION GUIDELINES field

The contents of the PERFORMANCE VERSUS COMMAND DURATION GUIDELINES field (see 5.3.12) may affect the timing relationships between the processing commands based on the specified command duration guideline and the contents of the COMMAND DURATION GUIDELINE POLICY field.

The command duration guideline interacts with the processing of the COMMAND DURATION GUIDELINE POLICY field.

COMMAND DURATION GUIDELINE POLICY field

The COMMAND DURATION GUIDELINE POLICY field (see Table 451) specifies the policy action taken if a non-zero COMMAND DURATION GUIDELINE field specifies a command duration guideline that the device is unable to achieve for a command.

Table 451 COMMAND DURATION GUIDELINE POLICY field

Code	Description
0h	The device server shall complete the command at the earliest possible time consistent with the specified command duration guideline.
1h^a	The device server shall add one to the duration limit descriptor index in the CDB and process the command using the T2 command duration limit descriptor, if any, indicated by the modified duration limit descriptor index. If the modified duration limit descriptor index is greater than seven or the T2 command duration limit descriptor indicated by the modified duration limit descriptor index does not define a nonzero requested latency target time, then the device server shall process the command using a duration limit descriptor index of 2h.
2h	The device server shall continue processing that command as with no command duration limits descriptor being used.
3h to Ch	Reserved
Dh	The device server shall complete the command with GOOD status, with the sense key set to COMPLETED and the sense code set to DATA CURRENTLY UNAVAILABLE.
Eh	Reserved
Fh	The device server shall terminate the command with CHECK CONDITION status, with the sense key set to ABORTED COMMAND and the additional sense code set to COMMAND TIMEOUT BEFORE PROCESSING.
a	If the COMMAND DURATION GUIDELINE POLICY field is set to this value in the seventh T2 command duration limits descriptor, when the device server shall terminate the MODE SELECT command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

BYP_SEQ bit

A bypass sequestration (BYP_SEQ) bit set to zero specifies that the device server processes a command associated with this T2 command duration limit descriptor as a non-sequestered command or a sequestered command as described in SPC-6. A BYP_SEQ bit set to one specifies that the device server processes a command associated with this T2 command duration limit descriptor as a non-sequestered command (see SPC-6).

5.3.13 Command Duration Limit T2B mode page

The Command Duration Limit T2B mode page (see table 452) provides controls for command duration limit (see SAM-6) that are applicable to all device types, for commands for which the REPORT SUPPORTED OPERATION CODES command parameter data RWCDLP bit and CDLP field (see 3.37) indicate the Command Duration Limit T2B mode page. The mode page policy (see 5.4.14) for this mode page should be per I_T nexus. The mode page policy may be shared. If a field in this mode page is changed while there is a command already in the task set, then the new value of the field shall not apply to that command.

If the Command Duration Limit T2B mode page is supported, the Command Duration Limit T2A mode page (see 5.3.12) shall be supported.

Table 452 Command Duration Limit T2B mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE (08h)							
2	(MSB)	PAGE LENGTH (00E4h)						(LSB)
3								
4								
...	Reserved							
6								
7	Reserved				PERFORMANCE VERSUS LATENCY CONTROLS			
T2 command duration limit descriptor list								
8								
...	T2 command duration limit descriptor (first)							
39								
40								
...	T2 command duration limit descriptor (second)							
71								
...	...							
200								
...	T2 command duration limit descriptor (seventh)							
231								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set as shown in table 452 for the Command Duration Limit T2A mode page.

T2 command duration limit descriptor

The T2 command duration limit descriptor (see 5.3.12.1) describes the command duration limit information that corresponds to the duration limit descriptor index in the CDB if the Command Duration Limit T2B mode page is indicated (see SPC-6)

5.3.14 Control mode page (0Ah)

The Control mode page (see table 453) provides controls over SCSI features that are applicable to all device types (e.g., task set management and error logging). If a field in this mode page is changed while there is a task already in the task set, it is vendor specific whether the old or new value of the field applies to that task. The mode page policy (see 5.4.14) for this mode page shall be shared, or per I_T nexus.

Table 453 Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (0Ah)					
1	PAGE LENGTH (0Ah)							
2	TST			TMF_ONLY	DPICZ	D_SENSE	GLTSD	RLEC
3	QUEUE ALGORITHM MODIFIER				NUAR	QERR		DQUE Obsolete
4	VS	RAC	UA_INTLCK_CTRL		SWP	RAERP Obsolete	UAAERP Obsolete	EAERP Obsolete
5	ATO	TAS	ATMPE	RWWP	Reserved	AUTOLOAD MODE		
6	(MSB)	Obsolete formerly						
7	READY AER HOLDOFF PERIOD							(LSB)
8	(MSB)	BUSY TIMEOUT PERIOD						
9								(LSB)
10	(MSB)	EXTENDED SELF-TEST COMPLETION TIME						
11								(LSB)

PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field

The PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field are described in 5.3.5.

TST (task set type) field

A task set type (TST) field specifies the type of task set in the logical unit (see table 454).

Table 454 Task set type (TST) field

Code	Description
000b	The logical unit maintains one task set for all I_T nexuses
001b	The logical unit maintains separate task sets for each I_T nexus
010b - 111b	Reserved

Regardless of the mode page policy (see 5.4.14) for the Control mode page, the shared mode page policy shall be applied to the TST field. If the most recent MODE SELECT changes the setting of this field, then the device server shall establish a unit attention condition (see SAM-6) for the initiator port associated with every I_T nexus except the I_T nexus on which the MODE SELECT command was received, with the additional sense code set to MODE PARAMETERS CHANGED.

TMF_ONLY (Allow Task Management Functions Only) bit

- 0** The allow task management functions only (TMF_ONLY) bit set to zero specifies that the device server shall process tasks with the ACA task attribute received on the faulted I_T nexus when an ACA condition has been established (see SAM-6).
- 1** A TMF_ONLY bit set to one specifies that the device server shall terminate all tasks received on the faulted I_T nexus with an ACA ACTIVE status when an ACA condition has been established.

DPICZ bit

- 0** A disable protection information check if protect field is zero (DPICZ) bit set to zero indicates that checking of protection information bytes is enabled.
- 1** A DPICZ bit set to one indicates that checking of protection information is disabled on commands with:
 - a) the RDPROTECT field (see SBC-5) set to zero;
 - b) the VRPROTECT field (see SBC-5) set to zero; or
 - c) the ORPROTECT field (see SBC-5) set to zero.

D_SENSE (DESCRIPTOR FORMAT SENSE DATA) bit

- 0** A descriptor format sense data (D_SENSE) bit set to zero specifies that the device server shall return the fixed format sense data when returning sense data in the same I_T_L_Q nexus transaction as a CHECK CONDITION status.
- 1** A D_SENSE bit set to one specifies that the device server shall return descriptor format sense data when returning sense data in the same I_T_L_Q nexus transaction as a CHECK CONDITION status, except as defined in 2.4.1.

GLTSD (Global Logging Target Save Disable) bit

- 0** A global logging target save disable (GLTSD) bit set to zero specifies that the logical unit implicitly saves, at vendor specific intervals, each log parameter in which the TSD bit (see 5.2) is set to zero.
- 1** A GLTSD bit set to one specifies that the logical unit shall not implicitly save any log parameters.

RLEC (Report Log Exception Condition) bit

- 1** A report log exception condition (RLEC) bit set to one specifies that the device server shall report log exception conditions as described in 5.2.2.
- 0** A RLEC bit set to zero specifies that the device server shall not report log exception conditions.

QUEUE ALGORITHM MODIFIER field

The QUEUE ALGORITHM MODIFIER field (see table 455) specifies restrictions on the algorithm used for reordering tasks having the SIMPLE task attribute (see SAM-6).

Table 455 QUEUE ALGORITHM MODIFIER field

Code	Description
0h	Restricted reordering
1h	Unrestricted reordering allowed
2h - 7h	Reserved
8h - Fh	Vendor specific

A value of zero in the QUEUE ALGORITHM MODIFIER field specifies that the device server shall order the processing sequence of tasks having the SIMPLE task attribute such that data integrity is maintained for that I_T nexus (i.e., if the transmission of new SCSI transport protocol requests is halted at any time, the final value of all data observable on the medium shall have exactly the same value as it would have if all the tasks had been given the ORDERED task attribute).

A value of one in the QUEUE ALGORITHM MODIFIER field specifies that the device server may reorder the processing sequence of tasks having the SIMPLE task attribute in any manner. Any data integrity exposures related to task sequence order shall be explicitly handled by the application client through the selection of appropriate commands and task attributes.

NUAR bit

- 1** A no unit attention on release (NUAR) bit set to one specifies that the device server shall not establish a unit attention condition as described in 5.13.11.2.2.
- 0** A NUAR bit set to zero specifies that the device server shall establish a unit attention condition as described in SPC-6.

QERR (queue error management) field

The queue error management (QERR) field (see table 456) specifies how the device server shall handle other tasks when one task is terminated with CHECK CONDITION status (see SAM-6). The task set type (see the TST field definition in this subclause) defines which other tasks are affected. If the TST field equals 000b, then all tasks from all I_T nexuses are affected. If the TST field equals 001b, then only tasks from the same I_T nexus as the task that is terminated with CHECK CONDITION status are affected.

Table 456 Queue error management (QERR) field

Code	Definition
00b	If an ACA condition is established, the affected tasks in the task set shall resume after the ACA condition is cleared (see SAM-6). Otherwise, all tasks other than the task that received the CHECK CONDITION status shall be processed as if no error occurred.
01b	All the affected tasks in the task set shall be aborted when the CHECK CONDITION status is sent. If the TAS bit is set to zero, a unit attention condition (see SAM-6) shall be established for the initiator port associated with every I_T nexus that had tasks aborted except for the I_T nexus on which the CHECK CONDITION status was returned, with the additional sense code set to COMMANDS CLEARED BY ANOTHER INITIATOR. If the TAS bit is set to one, all affected tasks in the task set for I_T nexuses other than the I_T nexus for which the CHECK CONDITION status was sent shall be completed with a TASK ABORTED status and no unit attention shall be established. For the I_T nexus to which the CHECK CONDITION status is sent, no status shall be sent for the tasks that are aborted.
10b	Reserved
11b	Affected tasks in the task set belonging to the I_T nexus on which a CHECK CONDITION status is returned shall be aborted when the status is sent.

DQUE (Disable Queuing) bit

NOTE The DQUE bit has been declared obsolete by the T10 committee and is not supported.

VS bit

- 0** The VENDOR SPECIFIC (VS) bit is not supported in Seagate products.

RAC (report a check) bit

- 1** The report a check (RAC) bit provides control of reporting long busy conditions or CHECK CONDITION status. A RAC bit set to one specifies that the device server should return CHECK CONDITION status rather than returning BUSY status if the reason for returning the BUSY status may persist for a longer time than that specified by the AUTOLOAD MODE field.
- 0** A RAC bit set to zero specifies that the device server may return BUSY status regardless of the length of time the reason for returning BUSY status may persist.

UA_INTLCK_CTRL (unit attention interlocks control) field

The unit attention interlocks control (UA_INTLCK_CTRL) field (see table 457) controls the clearing of unit attention conditions reported in the same I_T_L_Q nexus transaction as a CHECK CONDITION status and whether returning a status of BUSY, TASK SET FULL or RESERVATION CONFLICT results in the establishment of a unit attention condition (see SAM-6).

Table 457 Unit attention interlocks control (UA_INTLCK_CTRL) field

Code	Definition
00b	The logical unit shall clear any unit attention condition reported in the same I_T_L_Q nexus transaction as a CHECK CONDITION status and shall not establish a unit attention condition when a task is terminated with BUSY, TASK SET FULL, or RESERVATION CONFLICT status.
01b	Reserved ^[a]
10b [a]	The logical unit shall not clear any unit attention condition reported in the same I_T_L_Q nexus transaction as a CHECK CONDITION status and shall not establish a unit attention condition when a task is terminated with BUSY, TASK SET FULL, or RESERVATION CONFLICT status.
11b [a]	The logical unit shall not clear any unit attention condition reported in the same I_T_L_Q nexus transaction as a CHECK CONDITION status and shall establish a unit attention condition for the initiator port associated with the I_T nexus on which the BUSY, TASK SET FULL, or RESERVATION CONFLICT status is being returned. Depending on the status, the additional sense code shall be set to PREVIOUS BUSY STATUS, PREVIOUS TASK SET FULL STATUS, or PREVIOUS RESERVATION CONFLICT STATUS. Until it is cleared by a REQUEST SENSE command, a unit attention condition shall be established only once for a BUSY, TASK SET FULL, or RESERVATION CONFLICT status regardless to the number of commands terminated with one of those status values.
[a] A REQUEST SENSE command still clears any unit attention condition that it reports.	

SWP (Software Write Protect) bit

- 1** A software write protect (SWP) bit set to one specifies that the logical unit shall inhibit writing to the medium after writing all cached or buffered write data, if any. When SWP is one, all commands requiring writes to the medium shall be terminated with CHECK CONDITION status, with the sense key set to DATA PROTECT, and the additional sense code set to WRITE PROTECTED. When SWP is one and the device type's command standard defines a write protect (WP) bit in the DEVICE-SPECIFIC PARAMETER field in the mode parameter header, the WP bit shall be set to one for subsequent MODE SENSE commands.
- 0** A SWP bit set to zero specifies that the logical unit may allow writing to the medium, depending on other write inhibit mechanisms implemented by the logical unit. When the SWP bit is set to zero, the value of the WP bit, if defined, is device type specific. For a list of commands affected by the SWP bit and details of the WP bit see the command standard for the specific device type.

RAERP, UAAERP, and EAERP bits

NOTE These three bits have been declared obsolete by the T10 committee and are not supported.

RAERP (Ready AER Permission) bit (obsolete)

- 1** A Ready AER Permission (RAERP) bit of one specifies that the target may issue an asynchronous event report upon completing its initialization sequence instead of generating a unit attention condition.
- 0** A RAERP bit of zero specifies that the target shall not issue an asynchronous event report upon completing its initialization sequence.

UAAERP (UNIT ATTENTION AER Permission) bit (obsolete)

- 1** A UNIT ATTENTION AER Permission (UAAERP) bit of one specifies that the target may issue an asynchronous event report instead of creating a unit attention condition upon detecting an unit attention condition event (other than upon completing an initialization sequence).
- 0** A UAAERP bit of zero specifies that the target shall not issue an asynchronous event reporting instead of creating a unit attention condition.

EAERP (Error AER Permission) bit (obsolete)

- 1** An Error AER Permission (EAERP) bit of one specifies that the target may issue an asynchronous event report upon detecting a deferred error condition instead of waiting to report the deferred error on the next command.
- 0** An EAERP bit of zero specifies that the target shall not report deferred error conditions via an asynchronous event reporting.

ATO (application tag owner) bit

- 1** An application tag owner (ATO) bit set to one specifies that the contents of the LOGICAL BLOCK APPLICATION TAG field in the protection information, if any, shall not be modified by the device server.
- 0** An ATO bit set to zero specifies that the contents of the LOGICAL BLOCK APPLICATION TAG field in the protection information, if any, may be modified by the device server. If the ATO bit is set to zero, the device server shall ignore the contents of the LOGICAL BLOCK APPLICATION TAG field in the protection information when received from the application client.

TAS (Task Aborted Status) bit

- 0** A task aborted status (TAS) bit set to zero specifies that aborted tasks shall be terminated by the device server without any response to the application client.
- 1** A TAS bit set to one specifies that tasks aborted by the actions of an I_T nexus other than the I_T nexus on which the command was received shall be terminated with a TASK ABORTED status (see SAM-6).

ATMPE bit

- 0** An application tag mode page enabled (ATMPE) bit set to zero specifies that the Application Tag mode page (see 5.3.6) is disabled and the contents of logical block application tags are not defined by this standard.
- 1** An ATMPE bit set to one specifies that the Application Tag mode page is enabled.

If:

- a) the ATMPE is set to one;
- b) the ATO bit is set to one;
- c) the value in the DPICZ bit allows protection information checking for the specified command; and
- d) the APP_CHK bit is set to one in the Extended INQUIRY VPD page (see 5.4.10);

then:

knowledge of the value of the Application Tag shall come from the values in the Application Tag mode page as specified by the DPICZ bit.

RWWP bit

- 0** A reject write without protection (RWWP) bit set to zero specifies that the device server shall process write commands that are specified to include user data without protection information (e.g., a WRITE(10) command with the WRPROTECT field set to 000b (see 3.64)).
- 1** A RWWP bit set to one specifies that the device server in a logical unit that has been formatted with protection information shall terminate with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN CDB any write command that is specified to include user data without protection information.

AUTOLOAD MODE field

The AUTOLOAD MODE field specifies the action to be taken by a removable medium device server when a medium is inserted. For devices other than removable medium devices, this field is reserved. Table 458 shows the usage of the AUTOLOAD MODE field.

Table 458 AUTOLOAD MODE field

Code	Definition
000b	Medium shall be loaded for full access.
001b	Medium shall be loaded for medium auxiliary memory access only.
010b	Medium shall not be loaded.
011b - 111b	Reserved

READY AER HOLDOFF PERIOD field

NOTE This field has been declared obsolete by the T10 committee and are not supported.

BUSY TIMEOUT PERIOD field

The BUSY TIMEOUT PERIOD field specifies the maximum time, in 100 milliseconds increments, that the application client allows for the device server to return BUSY status for unanticipated conditions that are not a routine part of commands from the application client. This value may be rounded down as defined in Clause 2.3. A 0000h value in this field is undefined by this manual. An FFFFh value in this field is defined as an unlimited period.

EXTENDED SELF-TEST COMPLETION TIME field

The EXTENDED SELF-TEST COMPLETION TIME field contains advisory data that is the time in seconds that the device server requires to complete an extended self-test when the device server is not interrupted by subsequent commands and no errors occur during processing of the self-test. The application client should expect this time to increase significantly if other commands are sent to the logical unit while a self-test is in progress or if errors occur during the processing of the self-test. Device servers supporting SELF-TEST CODE field values other than 000b for the SEND DIAGNOSTIC command (see 3.50) shall support the EXTENDED SELF-TEST COMPLETION TIME field. The EXTENDED SELF-TEST COMPLETION TIME field is not changeable.

5.3.15 Control Extension mode page (0Ah/01h)

The Control Extension mode page (see table 459) is a subpage of the Control mode page (see 5.3.14) and provides controls over SCSI features that are applicable to all device types. The mode page policy (see 5.4.14) for this mode page shall be shared. If a field in this mode page is changed while there is a task already in the task set, it is vendor specific whether the old or new value of the field applies to that task.

Table 459 Control Extension mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (1Ch)						(LSB)
3								
4	Reserved				DLC	TCMOS	SCSIP	IALUAE
5	Reserved				INITIAL COMMAND PRIORITY			
6	MAXIMUM SENSE DATA LENGTH							
7	NON-SEQUESTERED COMMANDS COUNT							
8	SEQUESTERED COMMANDS COUNT							
9	PWROMACT	HRDRMACT	SSUMACT	FMTMACT	Reserved			
10								
...	Reserved							
31								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field are described in 5.3.5 and shall be set as shown in table 459 for the Control Extension mode page.

DLC bit

A device life control (DLC) bit set to one specifies that the SCSI target device shall not degrade performance of the logical unit in order to extend device life (e.g., manage endurance). A DLC bit set to zero specifies that the SCSI target device may degrade performance of the logical unit in order to extend device life.

TCMOS (Timestamp Changeable By Methods Outside this manual) bit

- 1** A timestamp changeable by methods outside this manual (TCMOS) bit set to one specifies that the timestamp may be initialized by methods outside the scope of this manual.
- 0** A TCMOS bit set to zero specifies that the timestamp shall not be changed by any method except those defined by this manual.

SCSIP (SCSI precedence) bit

- 1** A SCSI precedence (SCSIP) bit set to one specifies that the timestamp changed using a SET TIMESTAMP command shall take precedence over methods outside the scope of this manual.
- 0** A SCSIP bit set to zero specifies that methods outside this manual may change the timestamp and that the SET TIMESTAMP command is illegal.

IALUAE (Implicit Asymmetric Logical Unit Access Enabled) bit

- 1** An Implicit Asymmetric Logical Unit Access Enabled (IALUAE) bit set to one specifies that implicit asymmetric logical unit access state changes are allowed.
- 0** An IALUAE bit set to zero specifies that implicit asymmetric logical unit access state changes be disallowed and indicates that implicit asymmetric logical unit access state changes are disallowed or not supported.

INITIAL COMMAND PRIORITY field

The INITIAL COMMAND PRIORITY field specifies the priority that may be used as the task priority (see SAM-6) for tasks received by the logical unit on any I_T nexus (i.e., on any I_T_L nexus) where a priority has not been modified by a SET PRIORITY command. If a MODE SELECT command specifies an INITIAL COMMAND PRIORITY value that is different than the current INITIAL PRIORITY, then the device server shall set any priorities that have not been set with a SET PRIORITY command to a value different than the new initial priority value to the new priority. The device server shall establish a unit attention condition for the initiator port associated with every I_T_L nexus that receives a new priority, with the additional sense code set to PRIORITY CHANGED.

MAXIMUM SENSE DATA LENGTH field

The MAXIMUM SENSE DATA LENGTH field specifies the maximum number of bytes of sense data the device server shall return in the same I_T_L_Q nexus transaction as the status. A MAXIMUM SENSE DATA LENGTH field set to zero specifies that there is no limit. The device server shall not return more sense data bytes in the same I_T_L_Q nexus transaction as the status than the smaller of the length indicated by the:

- a) MAXIMUM SENSE DATA LENGTH field; and
- b) MAXIMUM SUPPORTED SENSE DATA LENGTH field in the Extended INQUIRY VPD page (see 5.4.10).

NON-SEQUESTERED COMMANDS COUNT field

A non-zero value in the NON-SEQUESTERED COMMANDS COUNT field specifies one of the conditions under which a sequestered command is able to become a non-sequestered command as described in SPC-6. If the NON-SEQUESTERED COMMANDS COUNT field is set to zero, the device server processes all commands as non-sequestered commands.

If the number of non-sequestered commands that the device server is already processing is equal to or greater than the non-zero value in the NON-SEQUESTERED COMMANDS COUNT field at the initial time a read command or a write command enters the Enabled state (see SAM-6), then the device server processes that command as a sequestered command (see SPC-6).

If the number of non-sequestered commands being processed by the device server becomes less than the value in the NON-SEQUESTERED COMMANDS COUNT field, then the device server transitions one sequestered command, if any, to a non-sequestered command as described in (see SPC-6).

If the NON-SEQUESTERED COMMANDS COUNT field is modified by a MODE SELECT command, the results may be affected by parameter rounding (see 2.3).

SEQUESTERED COMMANDS ORDERING field

The SEQUESTERED COMMANDS ORDERING field (see table 459) specifies how the device server selects a sequestered command, if any, to become a non-sequestered command (see SPC-6). If the SEQUESTERED COMMANDS ORDERING field is modified by a MODE SELECT command, the results may be affected by parameter rounding. If a MODE SELECT command modifies the SEQUESTERED COMMANDS ORDERING field and the device server has no sequestered commands, then the modification shall affect all subsequent commands.

Table 460 SEQUESTERED COMMANDS ORDERING field

Code	Description
00h	The sequestered command that has been known to the device server for the longest time shall be selected to become a non-sequestered command.
01h	The selection of a sequestered command to become a non-sequestered command shall be based on optimizing the I/O operations per second completed by the device server.
02h	The selection of a sequestered command to become a non-sequestered command shall be based on maximizing the I/O operations per second completed by the device server in a way that is consistent with applicable information from other sources (e.g., Command Duration Limit T2A mode page (see 5.3.15) fields including, the INACTIVE TIME LIMIT field, the COMMAND DURATION GUIDELINE field, and the PERF VERSUS COMMAND DURATION GUIDELINES field).
All others	Reserved

PWROMACT bit

For a WRITE BUFFER command with the MODE field set to 0Eh (see 3.74.11), a power on deferred microcode activates (PWROMACT) bit set to zero indicates that deferred microcode (see SPC-6) is activated as a result of a power on. A PWROMACT bit set to one indicates that deferred microcode is not activated as a result of a power on.

HRDRMACT bit

For a WRITE BUFFER command with the MODE field set to 0Eh, a hard reset deferred microcode activates (HRDRMACT) bit set to zero indicates that deferred microcode is activated as a result of a hard reset. A HRDRMACT bit set to one indicates that deferred microcode is not activated as a result of a hard reset.

SSUMACT bit

For a WRITE BUFFER command with the MODE field set to 0Eh, a START STOP UNIT command deferred microcode activates (SSUMACT) bit set to zero indicates that deferred microcode is activated as a result of processing a START STOP UNIT command (see SBC-5). An SSUMACT bit set to one indicates that deferred microcode is not activated as a result of processing a START STOP UNIT command.

FMTMACT bit

For a WRITE BUFFER command with the MODE field set to 0Eh, a FORMAT UNIT command deferred microcode activates (FMTMACT) bit set to zero indicates that deferred microcode is activated as a result of processing a FORMAT UNIT command (see SBC-5). An FMTMACT bit set to one indicates that deferred microcode is not activated as a result of processing a FORMAT UNIT command.

5.3.16 Disconnect-Reconnect mode page (02h) for SAS

The Disconnect-Reconnect mode page for SAS provides the application client the means to tune the performance of the service delivery subsystem. Table 461 defines the parameters which are applicable to SSP. If any field in the Disconnect-Reconnect mode page is not implemented, the value assumed for the functionality of the field shall be zero (i.e., as if the field in the mode page is implemented and the field is set to zero).

The application client sends the values in the fields to be used by the device server to control the SSP connections by means of a MODE SELECT command. The device server shall then communicate the field values to the SSP target port. The field values are communicated from the device server to the SSP target port in a vendor-specific manner.

SAS devices shall only use the parameter fields defined below in Table 461. If any other fields within the Disconnect-Reconnect mode page of the MODE SELECT command contain a non-zero value, the device server shall terminate the MODE SELECT command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

Table 461 Disconnect-Reconnect mode page for SAS

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (02h)					
1	PAGE LENGTH (0Eh)							
2	Reserved							
3	Reserved							
4	(MSB)	BUS INACTIVITY TIME LIMIT						(LSB)
5	Reserved							
6	Reserved							
7	Reserved							
8	(MSB)	MAXIMUM CONNECT TIME LIMIT						(LSB)
9	Reserved							
10	(MSB)	MAXIMUM BURST SIZE						(LSB)
11	Reserved							
12	Restricted							
13	Reserved							
14	(MSB)	FIRST BURST SIZE						(LSB)
15	Reserved							

The PARAMETERS SAVEABLE (PS) bit is defined in 5.3.5.

The PAGE CODE (PS) field shall be set to 02h.

The PAGE LENGTH field shall be set to 0Eh.

BUS INACTIVITY TIME LIMIT field

The value in the BUS INACTIVITY TIME LIMIT field contains the maximum period that an SSP target port is permitted to maintain a connection without transferring a frame to the SSP initiator port. This value shall be the number of 100 ms increments between frames that the SSP target port transmits during a connection. When this number is exceeded, the SSP target port shall prepare to close the connection (i.e., by requesting to have the link layer transmit DONE). This value may be rounded as defined in 2.3. A value of zero in this field shall specify that there is no bus inactivity time limit.

MAXIMUM CONNECT TIME LIMIT field

The value in the MAXIMUM CONNECT TIME LIMIT field contains the maximum duration of a connection. This value shall be the number of 100 ms increments that an SSP target port transmits during a connection after which the SSP target port shall prepare to close the connection (e.g., a value of one in this field means that the time is less than or equal to 100 ms and a value of two in this field means that the time is less than or equal to 200 ms). If an SSP target port is transferring a frame when the maximum connection time limit is exceeded, the SSP target port shall complete transfer of the frame before preparing to close the connection. A value of zero in this field shall specify that there is no maximum connection time limit. The maximum connection time limit is enforced by the port layer. This value may be rounded as defined in 2.3.

MAXIMUM BURST SIZE field

For read data, the value in the MAXIMUM BURST SIZE field contains the maximum amount of data that is transferred during a connection by an SSP target port per I_T_L_Q nexus without transferring at least one frame for a different I_T_L_Q nexus. If the SSP target port:

- a) has read data to transfer for only one I_T_L_Q nexus, and
- b) has no requests to transfer write data for any I_T_L_Q nexus;

then the SSP target port shall prepare to close the connection after the amount of data specified by the MAXIMUM BURST SIZE field is transferred to the SSP initiator port.

For write data, the value shall specify the maximum amount of data that an SSP target port requests via a single XFER_RDY frame.

This value shall be specified in 512-byte increments (e.g., a value of one in this field means that the number of bytes transferred to the SSP initiator port for the nexus is less than or equal to 512 and a value of two in this field means that the number of bytes transferred to the SSP initiator port for the nexus is less than or equal to 1 024). The device server may round this value down as defined in 2.3. A value of zero in this field shall specify that there is no maximum burst size.

In terms of the SCSI transport protocol services, the device server shall limit the Request Byte Count argument to the Receive Data-Out () protocol service and the Send Data-In () protocol service to the amount specified in this field.

FIRST BURST SIZE field

If the ENABLE FIRST BURST field in the COMMAND frame is set to zero, the FIRST BURST SIZE field is ignored.

If the ENABLE FIRST BURST field in the COMMAND frame is set to one, the value in the FIRST BURST SIZE field contains the maximum amount of write data in 512-byte increments that may be sent by the SSP initiator port to the SSP target port without having to receive an XFER_RDY frame from the SSP target port (e.g., a value of one in this field means that the number of bytes transferred by the SSP initiator port is less than or equal to 512 and a value of two in this field means that the number of bytes transferred by the SSP initiator port is less than or equal to 1 024).

Specifying a non-zero value in the FIRST BURST SIZE field is equivalent to an implicit XFER_RDY frame for each command requiring write data where the WRITE DATA LENGTH field of the XFER_RDY frame is set to 512 times the value of the FIRST BURST SIZE field

The rules for data transferred using the value in the FIRST BURST SIZE field are the same as those used for data transferred for an XFER_RDY frame (i.e., the number of bytes transferred using the value in the FIRST BURST SIZE field is as if that number of bytes was requested by an XFER_RDY frame).

If the amount of data to be transferred for the command is less than the amount of data specified by the FIRST BURST SIZE field, the SSP target port shall not transmit an XFER_RDY frame for the command. If the amount of data to be transferred for the command is greater than the amount of data specified by the FIRST BURST SIZE field, the SSP target port shall transmit an XFER_RDY frame after it has received all of the data specified by the FIRST BURST SIZE field from the SSP initiator port. All data for the command is not required to be transferred during the same connection in which the command is transferred.

A value of zero in this field shall specify that there is no first burst size (i.e., an SSP initiator port shall transmit no write DATA frames to the SSP target port before receiving an XFER_RDY frame).

5.3.17 Format Parameters page (03h)

This mode page has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products.

The Format Parameters page implementation is defined in Table 462. This table summarizes the function and defines the default or changeability status for each bit. The actual implementation of reserving spare areas for defect management takes place during the FORMAT UNIT command.

Table 462 Format Parameters page (03h)

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (03h)					
1	PAGE LENGTH (16h)							
2,3	TRACKS PER ZONE							
4,5	ALTERNATE SECTORS PER ZONE							
6,7	ALTERNATE TRACKS PER ZONE							
8,9	ALTERNATE TRACKS PER VOLUME							
10,11	SECTORS PER TRACK							
12,13	DATA BYTES PER PHYSICAL SECTOR							
14,15	INTERLEAVE							
16,17	TRACK SKEW FACTOR							
18,19	CYLINDER SKEW FACTOR							
20	SSEC	HSEC	RMB	SURF	DRIVE TYPE			
21,22,23	Reserved							

PS (Page Savable) bit

The only time this page of parameters may be sent is immediately before sending a FORMAT UNIT command to the drive. The Current parameters for this page are updated immediately but any changes between these Current parameters and the existing media format are not in effect until after the FORMAT UNIT command is completed. A PS bit of 1 indicates this page is savable. The PS bit is not used with the MODE SELECT command.

The PAGE CODE (PS) field shall be set to 03h.

The PAGE LENGTH field shall be set to 16h.

TRACKS PER ZONE field

The TRACKS PER ZONE field indicates the number of tracks the drive allocates to each defect management zone. A zone can be one or more tracks or one or more cylinders. See individual drive's Product Manual, Volume 1, for number of tracks allocated to each defect management zone for that drive model.

ALTERNATE SECTORS PER ZONE field

The ALTERNATE SECTORS PER ZONE field indicates the number of spare sectors to be reserved for the defined defect management zone. A value of zero indicates that no sectors are to be reserved in each zone for defect management. This is to accommodate hosts that want to manage the defects themselves.

ALTERNATE TRACKS PER ZONE field

The ALTERNATE TRACKS PER ZONE field indicates the number of spare tracks to be reserved at the end of each defect management zone. A value of zero indicates that no spare tracks are to be reserved in each zone for defect management by the drive.

ALTERNATE TRACKS PER VOLUME field

The ALTERNATE TRACKS PER VOLUME field indicates the number of spare tracks to be reserved at the end of the drive volume. The drive uses these locations for replacing defective sectors. A value of zero indicates that no spare tracks are to be reserved at the end of the unit for defect management. The initiator may change this value for a number between 0 and 255 that is a multiple of the total number of Data Read/Write heads installed. However, it is not changeable on some products.

SECTORS PER TRACK field

The SECTORS PER TRACK field indicates the average number of physical sectors the drive has per disk track. This value depends on the selected sector size and ZBR zones. The number of user accessible sectors per track may be fewer than the reported value, since sectors per Track includes sectors set aside for defect management. This value cannot be used to calculate drive user accessible capacity.

DATA BYTES PER PHYSICAL SECTOR field

The DATA BYTES PER PHYSICAL SECTOR field indicates the number of data bytes the drive shall allocate per physical sector. This value equals the block length reported in the MODE SENSE block descriptor. The bytes per physical sector is not directly changeable by the initiator and is not verified on a MODE SELECT command.

INTERLEAVE field

The INTERLEAVE field is not supported on Seagate products.

TRACK SKEW FACTOR field

The TRACK SKEW FACTOR field indicates the average number of physical sectors between the last logical block on one track and the first logical block on the next sequential track of the same cylinder. A value of zero indicates no skew.

NOTE This value is not changeable by a SCSI initiator port.

CYLINDER SKEW FACTOR field

The CYLINDER SKEW FACTOR field indicates the average number of physical sectors between the last logical block of one cylinder and the first logical block of the next cylinder. A value of zero indicates no skew. Cylinder skew will be utilized by a drive but is not changeable by a SCSI initiator port.

SSEC bit set and HSEC bits

A HSEC bit set to one indicates that the target shall use hard sector formatting. The HSEC bit and the SSEC bit are mutually exclusive in MODE SELECT commands.

Possible combinations of MODE SENSE Report Default Values:

SSEC	HSEC	
0	0	Target shall not return this combination
1	0	Target supports Soft sector formatting only
0	1	Target supports Hard sector formatting only
1	1	Target supports both Soft and Hard sector formatting

Possible combinations of MODE SENSE Report Changeable Values

SSEC	HSEC	
0	0	Sector formatting Not changeable
1	0	Target shall not return this combination
0	1	Target shall not return this combination
1	1	Target supports both Soft and Hard sector formatting

RMB (Removable Medium) bit

- 0** A removable medium (RMB) bit set to zero indicates that the medium is not removable.
- 1** A RMB bit set to one indicates that the medium is removable.

SURF (Surface) bit

The SURF (Surface) bit indicates how the target shall map the logical block addressing into physical block addressing.

- 0** A SURF bit set to zero indicates that the target shall allocate progressive addresses to all sectors within a cylinder prior to allocating sector addresses to the next cylinder.
- 1** A SURF bit set to one indicates that the target shall allocate progressive addresses to all sectors on a surface prior to allocating sector addresses to the next surface.

DRIVE TYPE field

The DRIVE TYPE field bits are defined as follows:

- a) The Hard Sectoring (HSEC) bit (bit 6) set to one indicates the drive shall use hard sector formatting.
- b) Bits 0-5, and 7 are not implemented by the drive and are always zero. All bits (0-7) are not changeable.
- c) See individual drive's Product Manual, Volume 1, MODE SENSE Data clause for changeable values.

5.3.18 IO Advice Hints Grouping mode page (0Ah/05h)

The IO Advice Hints Grouping mode page (see table 463) provides the application client with the means to obtain or modify the IO advice hints of the logical unit and the group number associated with those IO advice hints.

The mode page policy (see 5.4.14) for this page shall be shared.

Table 463 IO Advice Hints Grouping mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE(05h)							
2	(MSB)	PAGE LENGTH (40Ch)						(LSB)
3								
4								
...	Reserved							
15								
IO advice hints for group descriptor list								
16								
...	IO advice hints for group descriptor (group 0)							
31								
...	...							
1024								
...	IO advice hints for group descriptor (group 63)							
1039								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set to the values shown in table 463 for the IO Advice Hints Grouping mode page.

The format of each IO advice hints group descriptor is shown in table 464. There is one IO advice hints group descriptor for each group number. The logical block markup descriptor (see SBC-5) in each IO advice hints group descriptor affects the processing of commands as described in 2.2.8.

Table 464 IO advice hints group descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	IO ADVICE HINTS MODE		Reserved				CS_ENABLE	IC_ENABLE
1								
...	Reserved							
3								
4	(MSB)	LOGICAL BLOCK MARKUP DESCRIPTOR (see SBC-5)						(LSB)
...								
p-1								
p								
...	PAD (if any)							
15								

IO ADVICE HINTS MODE field

The IO ADVICE HINTS MODE field specifies the mode of the logical block markup descriptor and is described in table 465.

Table 465 IO ADVICE HINTS MODE field

Code	Description
00b	The logical block markup descriptor is valid (see 2.2.8).
01b	The logical block markup descriptor is invalid (see 2.2.8).
All others	Reserved

CS_ENABLE bit

The cache segment enable (CS_ENABLE) bit specifies whether cache segments (see SBC-5) are associated with the cache ID that is the group number associated with this IO advice hints descriptor. If the CS_ENABLE bit is set to zero, then no independent cache segments are associated with the cache ID for the group number associated with this IO advice hints descriptor. If the CS_ENABLE bit is set to one, then independent cache segments are associated with the cache ID for the group number associated with this IO advice hints descriptor.

IC_ENABLE bit

The information collection enable (IC_ENABLE) bit specifies whether the group's information collection function (see 2.2.8) is enabled. If the IC_ENABLE bit is set to zero, then the information collection function is not enabled. If the IC_ENABLE bit is set to one, then the information collection function is enabled.

If the Group Statistics and Performance (n) log pages are not supported, then in the IO advice hints group descriptors for group 0 to group 31, the IC_ENABLE bit shall be set to zero and shall not be changeable.

In the IO advice hints group descriptors for group 32 to group 63, the IC_ENABLE bit shall be set to zero, and shall not be changeable.

LOGICAL BLOCK MARKUP DESCRIPTOR field

The logical block markup descriptor is described in SBC-5.

5.3.19 Informational Exceptions Control mode page (1Ch)

The Informational Exceptions Control mode page (see table 466) defines the methods used by the device server to control the reporting and the operations of specific informational exception conditions. This page shall only apply to informational exceptions that report an additional sense code of FAILURE PREDICTION THRESHOLD EXCEEDED or an additional sense code of WARNING to the application client. The mode page policy (see 5.4.14) for this mode page shall be shared, or per I_T nexus.

Informational exception conditions occur as the result of vendor specific events within a logical unit. An informational exception condition may occur asynchronous to any commands issued by an application client.

Table 466 Informational Exceptions Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (1Ch)					
1	PAGE LENGTH (0Ah)							
2	PERF	Reserved	EBF	EWASC	DEXCPT	TEST	EBACKERR	LOGERR
3	Reserved				MRE			
4	(MSB)							
...	INTERVAL TIMER							
7	(LSB)							
8	(MSB)							
...	REPORT COUNT							
11	(LSB)							

PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field

The PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field are described in 5.3.5.

PERF (Performance) bit

- 0** If the performance (PERF) bit is set to zero, informational exception operations that are the cause of delays are acceptable.
- 1** If the PERF bit is set to one, the device server shall not cause delays while doing informational exception operations. A PERF bit set to one may cause the device server to disable some or all of the informational exceptions operations, thereby limiting the reporting of informational exception conditions.

EBF (Enable Background Function) bit

- 1** If background functions are supported and the Enable Background Function (EBF) bit is set to one, then the device server shall enable background functions.
- 0** If the EBF bit is set to zero, the device server shall disable the functions. Background functions with separate enable control bits (e.g., background medium scan defined in 4.3.7) are not controlled by this bit.

For the purposes of the EBF bit, background functions are defined as idle time functions that may impact performance that are performed by a device server operating without errors but do not impact the reliability of the logical unit (e.g., read scan).

EWASC (Enable Warning) bit

- 0** If the enable warning (EWASC) bit is set to zero, the device server shall disable reporting of the warning. The MRIE field is ignored when DEXCPT is set to one and EWASC is set to zero.
- 1** If the EWASC bit is set to one, warning reporting shall be enabled. The method for reporting the warning when the EWASC bit is set to one is determined from the MRIE field.

DEXCPT (Disable Exception Control) bit

- 0** A disable exception control (DEXCPT) bit set to zero indicates the failure prediction threshold exceeded reporting shall be enabled. The method for reporting the failure prediction threshold exceeded when the DEXCPT bit is set to zero is determined from the MRIE field.
- 1** A DEXCPT bit set to one indicates the device server shall disable reporting of the failure prediction threshold exceeded. The MRIE field is ignored when DEXCPT is set to one and EWASC is set to zero.

TEST bit

- 1** If DEXCPT bit is set to zero and the TEST bit set to one, then the device server shall create a test device failure as specified by the MRIE field, INTERVAL TIMER field, and REPORT COUNT field (see table 466). The test device failure shall be reported with the additional sense code set to FAILURE PREDICTION THRESHOLD EXCEEDED (FALSE). If both the TEST bit and the DEXCPT bit are set to one, then the MODE SELECT command shall be terminated with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.
- 0** A TEST bit set to zero shall instruct the device server not to generate any test device failure notifications.

EBACKERR (enable background error) bit

- 0** An enable background error (EBACKERR) bit set to zero indicates the target shall disable reporting of background self-test errors (SPC-6) and background scan errors (see SBC-5).
- 1** An EBACKERR bit set to one indicates reporting of background self-test errors and background scan errors shall be enabled. The method for reporting background self-test errors and background scan errors is determined by contents of the mrie field. Background self-test errors and background scan errors shall be reported as soon as the method specified in the mrie field occurs (i.e., the interval timer field and report count field do not apply for background self-test errors and background scan errors).

LOGERR (Log Error) bit

- 0** If the log errors (LOGERR) bit is set to zero, the logging of informational exception conditions by a device server is vendor specific.
- 1** If the LOGERR bit is set to one, the device server shall log informational exception conditions.

MRIE (Method Of Reporting Informational Exceptions) field

The value in the method of reporting informational exceptions (MRIE) field (see table 466) defines the method that shall be used by the device server to report informational exception conditions. The priority of reporting multiple information exceptions is vendor specific.

Table 467 Method of reporting informational exceptions (MRIE) field

MRIE	Description
0h	No reporting of informational exception condition: The device server shall not report information exception conditions.
1h	Asynchronous event reporting: Obsolete
2h	Generate unit attention: The device server shall report informational exception conditions by establishing a unit attention condition (see SAM-6) for the initiator port associated with every I_T nexus, with the additional sense code set to indicate the cause of the informational exception condition. As defined in SAM-6, the command that has the CHECK CONDITION status with the sense key set to UNIT ATTENTION is not processed before the informational exception condition is reported.
3h	Conditionally generate recovered error: The device server shall report informational exception conditions, if the reporting of recovered errors is allowed, ^[a] by returning a CHECK CONDITION status. If the TEST bit is set to zero, the status may be returned after the informational exception condition occurs on any command for which GOOD status or INTERMEDIATE status would have been returned. If the TEST bit is set to one, the status shall be returned on the next command received on any I_T nexus that is normally capable of returning an informational exception condition when the test bit is set to zero. The sense key shall be set to RECOVERED ERROR and the additional sense code shall indicate the cause of the informational exception condition. The command that returns the CHECK CONDITION for the informational exception shall complete without error before any informational exception condition may be reported.
4h	Unconditionally generate recovered error: The device server shall report informational exception conditions, regardless of whether the reporting of recovered errors is allowed, ^[a] by returning a CHECK CONDITION status. If the TEST bit is set to zero, the status may be returned after the informational exception condition occurs on any command for which GOOD status or INTERMEDIATE status would have been returned. If the TEST bit is set to one, the status shall be returned on the next command received on any I_T nexus that is normally capable of returning an informational exception condition when the TEST bit is set to zero. The sense key shall be set to RECOVERED ERROR and the additional sense code shall indicate the cause of the informational exception condition. The command that returns the CHECK CONDITION for the informational exception shall complete without error before any informational exception condition may be reported.
5h	Generate no sense: The device server shall report informational exception conditions by returning a CHECK CONDITION status. If the TEST bit is set to zero, the status may be returned after the informational exception condition occurs on any command for which GOOD status or INTERMEDIATE status would have been returned. If the TEST bit is set to one, the status shall be returned on the next command received on any I_T nexus that is normally capable of returning an informational exception condition when the TEST bit is set to zero. The sense key shall be set to NO SENSE and the additional sense code shall indicate the cause of the informational exception condition. The command that returns the CHECK CONDITION for the informational exception shall complete without error before any informational exception condition may be reported.
6h	Only report informational exception condition on request: The device server shall preserve the informational exception(s) information. To find out about information exception conditions the application client polls the device server by issuing a REQUEST SENSE command. In the REQUEST SENSE parameter data that contains the sense data, the sense key shall be set to NO SENSE and the additional sense code shall indicate the cause of the informational exception condition.
7h - Bh	Reserved
Ch - Fh	Vendor specific

[a] Error reporting is controlled by the post error (PER) bit in the Read-Write Error Recovery mode page (see 5.3.23).

INTERVAL TIMER field

The INTERVAL TIMER field specifies the period in 100 millisecond increments that the device server shall use for reporting that an informational exception condition has occurred (see table 468). After an informational exception condition has been reported, the interval timer shall be started. An INTERVAL TIMER field set to zero or FFFF_FFFFh specifies that the period for reporting an informational exception condition is vendor specific.

REPORT COUNT field

The REPORT COUNT field specifies the maximum number of times the device server may report an informational exception condition to the application client. A REPORT COUNT field set to zero specifies that there is no limit on the number of times the device server may report an informational exception condition.

The device server shall use the values in the INTERVAL TIMER field and the REPORT COUNT field based on the value in the MRIE field as shown in table 468.

Table 468 Use of the INTERVAL TIMER field and the REPORT COUNT field based on the MRIE field

MRIE ^[a]	Description
2h to 6h	If reporting of an informational exception condition is enabled (see table 467), then the device server shall: <ol style="list-style-type: none"> 1) report an informational exception condition when the condition is first detected; and 2) if the value in the REPORT COUNT field is not equal to one, then: <ol style="list-style-type: none"> 1. if the INTERVAL TIMER field is not set to zero or FFFF_FFFFh, then wait the time specified in the INTERVAL TIMER field, and, if that informational exception condition still exists, report the informational exception again; and 2. while the informational exception condition exists, continue to report the informational exception condition after waiting the time specified in the INTERVAL TIMER field until the condition has been reported the number of times specified by the REPORT COUNT field.
Ch to Fh	The device server may use or may ignore the values in the INTERVAL TIMER field and the REPORT COUNT field to report the informational exception condition based on the device specific implementation.
[a] For values in the MRIE field (see table 466) not shown in this table, the INTERVAL TIMER field and the REPORT COUNT field shall be ignored.	

Maintaining the interval timer and the report counter across power cycles, hard resets, logical unit resets, and I_T nexus losses by the device server is vendor specific.

5.3.20 Logical Block Provisioning mode page (1Ch/02h)

5.3.20.1 Introduction

The Logical Block Provisioning mode page (see table 469) specifies the parameters that a device server that supports logical block provisioning threshold values (see SBC-5) shall use to report logical block provisioning threshold notifications (see SBC-5). The mode page policy (see 5.4.14) for this page shall be shared.

If a method not defined by this standard changes the parameter data to be returned by a device server in the Logical Block Provisioning mode page, then the device server shall establish a unit attention condition for the SCSI initiator port associated with every I_T nexus with the additional sense code set to MODE PARAMETERS CHANGED.

Table 469 Logical Block Provisioning mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (1Ch)					
1	SUBPAGE CODE (02h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3	Reserved							
4	Reserved							SITUA
5	Reserved							
...	Reserved							
15	Reserved							
Threshold descriptors								
16	Threshold descriptor [first] (see 5.3.20.2)							
...	...							
23	Threshold descriptor [last] (see 5.3.20.2)							
...	...							
1024	Threshold descriptor [last] (see 5.3.20.2)							
...	...							
n	Threshold descriptor [last] (see 5.3.20.2)							

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5 and shall be set to the values shown in table 469 for the Logical Block Provisioning mode page.

SITUA bit

- 1** specifies that the logical block provisioning threshold notification unit attention condition is established on a single I_T nexus as described in SBC-5.
- 0** specifies that the logical block provisioning threshold notification unit attention condition is established on multiple I_T nexuses as described in SBC-5.

Threshold descriptors fields

The threshold descriptors are defined in 5.3.20.2.

5.3.20.2 Threshold descriptor format

The threshold descriptor format is defined in table 470.

Table 470 Threshold descriptor format

Bit Byte	7	6	5	4	3	2	1	0	
0	ENABLED	Reserved	THRESHOLD TYPE			THRESHOLD ARMING			
1	THRESHOLD RESOURCE								
2	Reserved								
3									
4	(MSB)	THRESHOLD COUNT							
...									
n	(LSB)								

ENABLED bit

- 1** an ENABLED bit set to one specifies that the threshold is enabled.
- 0** an ENABLED bit set to zero specifies that the threshold is disabled.

THRESHOLD TYPE field

The THRESHOLD TYPE field (see table 471) specifies the type of this threshold.

Table 471 THRESHOLD TYPE field

Code	Description
000b	If the THRESHOLD COUNT field specifies a soft threshold, the threshold is enabled, and that threshold is reached, then the device server shall establish a unit attention condition as described in SBC-5.
001b	If the THRESHOLD COUNT field specifies a percentage threshold, the threshold is enabled, and that threshold is reached, then the device server shall establish a unit attention condition as described in SBC-5.
All others	Reserved

THRESHOLD ARMING field

The THRESHOLD ARMING field (see table 472) specifies the arming method used for operation of this threshold.

Table 472 THRESHOLD ARMING field

Code	Description	Reference
000b	The threshold operates as an armed decreasing threshold.	SBC-5
001b	The threshold operates as an armed increasing threshold.	SBC-5
All others	Reserved	

THRESHOLD RESOURCE field

The THRESHOLD RESOURCE field specifies the resource of this threshold. The contents of this field are as defined for parameters codes 0000h to 00FFh in the Logical Block Provisioning log page (see 5.2.15).

The valid combinations of the THRESHOLD TYPE field, the THRESHOLD ARMING field, and the THRESHOLD RESOURCE field are shown in SBC-5.

THRESHOLD COUNT field

The THRESHOLD COUNT field specifies the center of the threshold range for this threshold expressed as:

- a) a number of threshold sets (i.e., the number of LBA mapping resources expressed as a number of threshold sets), if the value in the THRESHOLD TYPE field is set to 000b; or
- b) a percentage value, if the value in the THRESHOLD TYPE field is set to 001b.

5.3.21 Power Condition mode page (1Ah)

The Power Condition mode page provides an application client with methods to control the power condition of a logical unit (see SPC-6). These methods include:

- a) Specifying that the logical unit transition to a power condition without delay; and
- b) Activating and setting of idle condition and standby condition timers to specify that the logical unit wait for a period of inactivity before transitioning to a specified power condition.

The mode page policy (see 5.4.14) for this mode page shall be shared.

When a device server receives a command while in a power condition based on a setting in the Power Condition mode page, the logical unit shall transition to the power condition that allows the command to be processed. If either the idle condition timer or the standby condition timer has been set, then they shall be reset on receipt of the command. On completion of the command, the timer(s) shall be started.

Logical units that contain cache memory shall write all cached data to the medium for the logical unit (e.g., as a logical unit does in response to a SYNCHRONIZE CACHE command as described in 3.55 and 3.56) prior to entering into any power condition that prevents accessing the media (e.g., before a hard drive stops its spindle motor during transition to the standby power condition).

The logical unit shall use the values in the Power Condition mode page to control its power condition after a power on or a hard reset until a START STOP UNIT command setting a power condition is received.

Table 473 defines the Power Condition mode page.

Table 473 Power Condition mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (1Ah)					
1	PAGE LENGTH (26h)							
2	PM_BG_PRECEDENCE		Reserved					STANDBY_Y
3	Reserved				IDLE_C	IDLE_B	IDLE_A	STANDBY_Z
4	(MSB)							
...	IDLE_A CONDITION TIMER							
7	(LSB)							
8	(MSB)							
...	STANDBY_Z CONDITION TIMER							
11	(LSB)							
12	(MSB)							
...	IDLE_B CONDITION TIMER							
15	(LSB)							
16	(MSB)							
...	IDLE_C CONDITION TIMER							
19	(LSB)							
20	(MSB)							
...	STANDBY_Y CONDITION TIMER							
23	(LSB)							
24	Reserved							
...	Reserved							
38	Reserved							
39	CCF_IDLE		CCF_STANDBY		CCF_STOPPED		Reserved	

PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field

The PS bit, SPF bit, PAGE CODE field, and PAGE LENGTH field are described in 5.3.5.

PM_BG_PRECEDENCE field

The PM_BG_PRECEDENCE field (see table 474) specifies the interactions between background functions (see SPC-6) and power management.

The behavior of the idle and standby condition timers controlled by this mode page is defined in the power condition overview and the power condition state machine (see SPC-6).

Table 474 PM_BG_PRECEDENCE field

Code	Description
00b	Vendor specific
01b	<p>Performing background functions take precedence over maintaining low power conditions as follows:</p> <ul style="list-style-type: none"> a) if the logical unit is in a low power condition as the result of a power condition timer associated with that condition expiring, then: <ul style="list-style-type: none"> 1) the logical unit shall change from that power condition, if necessary, to the power condition required to perform the background function, when: <ul style="list-style-type: none"> a) a timer associated with a background scan operation expires, and that function is enabled (see SBC-5); or b) an event occurs to initiate a device specific background function, and that function is enabled (see SPC-6); 2) the logical unit shall perform the background function(s) based on the definitions in this standard and other command standards (e.g., if the device server receives a command while performing a background function, then the logical unit shall suspend the function to process the command); 3) if more than one condition is met to initiate a background function, then: <ul style="list-style-type: none"> a) all initiated background functions shall be performed; and b) the order of performing the functions is vendor specific; and 4) when all initiated background functions have been completed, the device server shall check to see if any power condition timers have expired. If any power condition timer has expired, then the logical unit shall change to the power condition associated with the highest priority timer that has expired; <p>or</p> <ul style="list-style-type: none"> b) if the logical unit is performing a background function, and a power condition timer expires, then the logical unit shall perform all initiated background functions before the logical unit changes to a power condition associated with a timer has expired.
10b	<p>Maintaining low power conditions take precedence over performing background functions as follows:</p> <ul style="list-style-type: none"> a) if the logical unit is in a low power condition, then the logical unit shall not change from that power condition to perform a background function; b) the device server may perform any initiated and enabled background function based on the definitions in this standard or other command standards, if all of the following are true: <ul style="list-style-type: none"> A) a condition is met to initiate a background function; B) that background function is enabled; C) the logical unit changes to a power condition in which the background function may be performed (e.g., the device server processes a medium access command causing the logical unit to change its power condition to continue processing that command); and D) all outstanding application client requests have been completed; <p>or</p> <ul style="list-style-type: none"> c) if the logical unit is performing a background function, and a power condition timer expires that causes a change to a power condition in which the logical unit is unable to continue performing the background function, then the logical unit shall: <ul style="list-style-type: none"> A) suspend the background function; and B) change to the power condition associated with the timer that expired.
11b	Reserved

STANDBY_Y bit

- 1** If the STANDBY_Y bit is set to one, then the standby_y condition timer is enabled.
- 0** If the STANDBY_Y bit is set to zero, then the device server shall ignore the standby_y condition timer.

IDLE_C bit

- 1** If the IDLE_C bit is set to one, then the idle_c condition timer is enabled.
- 0** If the IDLE_C bit is set to zero, then the device server shall ignore the idle_c condition timer.

IDLE_B bit

- 1** If the IDLE_B bit is set to one, then the idle_b condition timer is enabled.
- 0** If the IDLE_B bit is set to zero, then the device server shall ignore the idle_b condition timer.

IDLE_A bit

- 1** If the IDLE_A bit is set to one, then the idle_a condition timer is enabled.
- 0** If the IDLE_A bit is set to zero, then the device server shall ignore the idle_a condition timer.

STANDBY_Z bit

- 1** If the STANDBY_Z bit is set to one, then the standby_z condition timer is enabled.
- 0** If the STANDBY_Z bit is set to zero, then the device server shall ignore the standby_z condition timer.

If any of the power condition enable bits (e.g., the IDLE_C bit or the STANDBY_Y bit) are set to zero and are not changeable (see 3.13.1.2), then the device server does not implement the power condition timer associated with that enable bit (see SPC-6).

IDLE_A CONDITION TIMER field

The IDLE_A CONDITION TIMER field specifies the initial value, in 100 millisecond increments, for the idle_a power condition timer (see SPC-6). This value may be rounded up or down to the nearest implemented time as described in 2.3.

STANDBY_Z CONDITION TIMER field

The STANDBY_Z CONDITION TIMER field specifies the initial value, in 100 millisecond increments, for the standby_z power condition timer (see SPC-6). This value may be rounded up or down to the nearest implemented time as described in 2.3.

IDLE_B CONDITION TIMER field

The IDLE_B CONDITION TIMER field specifies the initial value, in 100 millisecond increments, for the idle_b power condition timer (see SPC-6). This value may be rounded up or down to the nearest implemented time as described in 2.3.

IDLE_C CONDITION TIMER field

The IDLE_C CONDITION TIMER field specifies the initial value, in 100 millisecond increments, for the idle_c power condition timer (see SPC-6). This value may be rounded up or down to the nearest implemented time as described in 2.3.

STANDBY_Y CONDITION TIMER field

The STANDBY_Y CONDITION TIMER field specifies the initial value, in 100 millisecond increments, for the standby_y power condition timer (see SPC-6). This value may be rounded up or down to the nearest implemented time as described in 2.3.

CCF_IDLE field

The Check Condition From idle_c processing control (CCF_IDLE) field is defined in Table 475.

Table 475 CCF_IDLE field

Code	
00b	Restricted ^[a]
01b	If the transition was from an idle_c power condition, returning CHECK CONDITION status is disabled. ^[b]
10b	If the transition was from an idle_c power condition, returning CHECK CONDITION status is enabled. ^[b]
11b	Reserved

[a] See SAS-4.1 for command processing in the Active_Wait state and Idle_Wait state.

[b] For direct-access block devices see the Active_Wait state in SBC-5 for the definition of command processing in that state. For devices that are not direct-access block devices, see the state in (SPC-6) for the definition of command processing in that state.

CCF_STANDBY field

The CHECK CONDITION From Standby (CCF_STANDBY) field is defined in Table 476.

Table 476 CCF_STANDBY field

Code	
00b	Restricted ^[a]
01b	If transition was from a standby power condition, returning CHECK CONDITION status is disabled. ^[b]
10b	If transition was from a standby power condition, returning CHECK CONDITION status is enabled. ^[b]
11b	Reserved

[a] See SAS-4.1 for command processing in the Active_Wait state and Idle_Wait state.

[b] For direct-access block devices see the Active_Wait state in SBC-5 for the definition of command processing in that state. For devices that are not direct-access block devices, see the state in (SPC-6) for the definition of command processing in that state.

CCF_STOPPED field

The CHECK CONDITION if from stopped (CCF_STOPPED) field is defined in Table 477.

Table 477 CCF_STOPPED field

Code	
00b	Restricted ^[a]
01b	If the transition was from a standby power condition, returning CHECK CONDITION is disabled. ^[b]
10b	If the transition was from a standby power condition, returning CHECK CONDITION is enabled. ^[b]
11b	Reserved

[a] See SAS-4.1 for command processing in the Active_Wait state and Idle_Wait state.

[b] For direct-access block devices see the Active_Wait state in SBC-5 for the definition of command processing in that state. For devices that are not direct-access block devices, see the state in (SPC-6) for the definition of command processing in that state.

5.3.22 Power Consumption Mode page (1Ah/01h)

The Power Consumption mode page (see table 478) provides a method to set the power consumption level while in the active power condition (see SPC-6) to:

- a) a relative power consumption level (see SPC-6); or
- b) a maximum power consumption level (see SPC-6) that is based on the contents of the power consumption descriptors in the Power Consumption VPD page (see 5.4.16).

The mode page policy (see 5.4.14) for this mode page shall be shared.

Table 478 Power Consumption mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (1Ah)					
1	SUBPAGE CODE (01h)							
2	(MSB)	PAGE LENGTH (000Ch)						(LSB)
3								
4	Reserved							
5								
6	Reserved						ACTIVE LEVEL	
7	POWER CONSUMPTION IDENTIFIER							
8								
...	Reserved							
15								

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field and PAGE LENGTH field

The PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field and PAGE LENGTH field are described in 5.2.2 and shall be set as shown in table 478 for the Power Consumption mode page.

ACTIVE LEVEL field

The ACTIVE LEVEL field (see table 479) specifies the relative active power consumption level, in any.

Table 479 ACTIVE LEVEL field

Code	Description
00b	The active power consumption level is specified by the POWER CONSUMPTION IDENTIFIER field.
01b	Highest relative active power consumption level
10b	Intermediate relative active power consumption level
11b	Lowest relative active power consumption level

If the application client specifies an unsupported value for the ACTIVE LEVEL field, the device server shall terminate the MODE SELECT command with CHECK CONDITION status, with the sense key set to ILLEGALREQUEST, and the additional sense code set to INVALID FIELD IN PARAMETER LIST.

- n** If the ACTIVE LEVEL field is set to a non-zero value, the POWER CONSUMPTION IDENTIFIER field is ignored.
- 0** If the ACTIVE LEVEL field is set to zero, the POWER CONSUMPTION IDENTIFIER field specifies the power consumption identifier from one of the power consumption descriptors in the Power Consumption VPD page (see 5.4.16) that the device server is to use as described in SPC-6.

If the application client specifies an ACTIVE LEVEL field set to zero and a value for the POWER CONSUMPTIONIDENTIFIER field that is not contained in a power consumption descriptor in the Power Consumption VPD page, then the device server shall terminate the MODE SELECT command with CHECK CONDITION status, with the sense key set to ILLEGAL REQUEST, and the additional sense code set to INVALID FIELD INPARAMETER LIST.

5.3.23 Read-Write Error Recovery mode page (01h)

The Read-Write Error Recovery mode page (see table 480) specifies the error recovery parameters the device server shall use during any command that performs a read or write operation to the medium (e.g., READ commands, WRITE commands, and WRITE AND VERIFY commands).

Table 480 Read-Write Error Recovery mode page

Bit Byte	7	6	5	4	3	2	1	0	
0	PS	SPF (0b)	PAGE CODE (01h)						
1	PAGE LENGTH (0Ah)								
2	AWRE	ARRE	TB	RC	ERROR RECOVERY BITS				
					EER	PER	DTE	DCR	
3	READ RETRY COUNT								
4	Obsolete								
5	Obsolete								
6	Obsolete								
7	Reserved						Restricted for MMC-6		
8	WRITE RETRY COUNT								
9	Reserved								
10	(MSB)	RECOVERY TIME LIMIT							
11							(LSB)		

PS (Parameters Savable) bit

The parameters savable (PS) bit is only used with the MODE SENSE command. This bit is reserved with the MODE SELECT command. A PS bit set to one indicates that the device server is capable of saving the mode page in a non-volatile vendor-specific location.

PAGE CODE field and PAGE LENGTH field

The PAGE CODE field and PAGE LENGTH field are described in 5.3.5.

AWRE (Automatic Write Reallocation Enabled) bit

- 0** An automatic write reallocation enabled (AWRE) bit set to zero specifies that the device server shall not perform automatic reallocation of defective logical blocks during write operations.
- 1** An AWRE bit set to one specifies that the device server shall enable automatic reallocation of defective logical blocks during write operations. The automatic reallocation shall be performed only if the device server has the valid data (e.g., original data in a buffer or recovered from the medium). The valid data shall be placed in the reallocated logical block. The device server shall report any failures that occur during the reallocation operation. Error reporting as specified by the error recovery bits (i.e., the EER bit, the PER bit, the DTE bit, and the DCR bit) shall be performed only after completion of the reallocation. See the REASSIGN BLOCKS command (see 3.30) for error procedures.

ARRE (Automatic Read Reallocation Enabled) bit

- 0** An automatic read reallocation enabled (ARRE) bit set to zero specifies that the device server shall not perform automatic reallocation of defective logical blocks during read operations.
- 1** An ARRE bit set to one specifies that the device server shall enable automatic reallocation of defective logical blocks during read operations. All error recovery actions required by the error recovery bits (i.e., the EER bit, the PER bit, the DTE bit, and the DCR bit) shall be processed. The automatic reallocation shall then be performed only if the device server successfully recovers the data. The recovered data shall be placed in the reallocated logical block. The device server shall report any failures that occur during the reallocation operation. Error reporting as specified by the error recovery bits (i.e., the EER bit, the PER bit, the DTE bit, and the DCR bit) shall be performed only after completion of the reallocation operation. See the REASSIGN BLOCKS command (see 3.30) for error procedures.

TB (Transfer Block) bit

- 0** A transfer block (TB) bit set to zero specifies that the device server shall not transfer a logical block to the data-in buffer if the logical block is not recovered within the recovery limits specified.
- 1** A TB bit set to one specifies that the device server shall transfer a logical block to the data-in buffer before returning CHECK CONDITION status if the logical block is not recovered within the recovery limits specified. The data returned in this case is vendor-specific. The TB bit does not affect the action taken for recovered data.

RC (Read Continuous) bit

- 0** A read continuous (RC) bit set to zero specifies that error recovery operations that cause delays are acceptable during the data transfer. Data shall not be fabricated.
- 1** An RC bit set to one specifies the device server shall transfer the entire requested length of data without adding delays to perform error recovery procedures. This implies that the device server may send data that is erroneous or fabricated in order to maintain a continuous flow of data. The device server shall assign priority to the RC bit over conflicting bits within this byte.

NOTE Fabricated data may be data already in a buffer or any other vendor-specific data. The RC bit may be used in image processing, audio, or video applications.

EER (Enable Early Recovery) bit

- 1** An enable early recovery (EER) bit set to one specifies that the device server shall use the most expedient form of error recovery first.
- 0** An EER bit set to zero specifies that the device server shall use an error recovery procedure that minimizes the risk of error mis-detection or mis-correction. This bit only applies to data error recovery and it does not affect positioning retries.

PER (Post Error) bit

- 1** A post error (PER) bit set to one specifies that if a recovered read error occurs during a command performing a read or write operation, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to RECOVERED ERROR. If the DTE bit is set to one, then the PER bit shall be set to one
- 0** A PER bit set to zero specifies that if a recovered read error occurs during a command performing a read or write operation, then the device server shall perform error recovery procedures within the limits established by the error recovery parameters and only terminate the command with CHECK CONDITION status if the error becomes uncorrectable based on the established limits.

DTE (Data Terminate On Error) bit

- 1** A data terminate on error (DTE) bit set to one specifies that the device server shall terminate the data-in or data-out buffer transfer upon detection of a recovered error.
- 0** A DTE bit set to zero specifies that the device server shall not terminate the data-in or data-out buffer transfer upon detection of a recovered error.

DCR (Disable Correction) bit

- 1** A disable correction (DCR) bit set to one specifies that ECC shall not be used for data error recovery.
- 0** A DCR bit set to zero allows the use of ECC for data error recovery. If the EER bit is set to one, the DCR bit shall be set to zero.

The combinations of the error recovery bits (i.e., the EER bit, the PER bit, the DTE bit, and the DCR bit) are explained in table 481.

Table 481 Combined error recovery bit descriptions (Sheet 1 of 3)

EER	PER	DTE	DCR	Description
0	0	0	0	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations and shall perform error correction in an attempt to recover the data.</p> <p>The device server shall not report recovered errors. The device server shall terminate a command with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecoverable data error occurs during a read operation, the data in the block with the unrecoverable error may or may not be transferred to the data-in buffer depending on the setting of the transfer block (TB) bit.</p>
0	0	0	1	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations but shall not perform error correction in an attempt to recover the data.</p> <p>The device server shall not report recovered errors. The device server shall terminate a command with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecoverable data error occurs during a read operation, the data in the block with the unrecoverable error may or may not be transferred to the data-in buffer depending on the setting of the transfer block (TB) bit.</p>
0	0	1	0	Invalid mode. The PER bit shall be set to one if the DTE bit is set to one. ^[a]
0	0	1	1	Invalid mode. The PER bit shall be set to one if the DTE bit is set to one. ^[a]
0	1	0	0	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations and shall perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate a command with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecovered read error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p> <p>If a recovered error occurs while the device server is performing a read or write operation, then, after the operation is complete, the device server shall terminate the command with CHECK CONDITION status with the sense key set to RECOVERED ERROR. The INFORMATION field in the sense data shall contain the LBA of the last recovered error that occurred during the command.</p>
0	1	0	1	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations but shall not perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate a command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecovered read error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p> <p>If a recovered error occurs while the device server is performing a read or write operation, then, after the operation is complete, the device server shall terminate the command with CHECK CONDITION status with the sense key set to RECOVERED ERROR. The INFORMATION field in the sense data shall contain the LBA of the last recovered error that occurred during the command.</p>

Table 481 Combined error recovery bit descriptions (Sheet 2 of 3)

EER	PER	DTE	DCR	Description
0	1	1	0	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations and shall perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate a command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted if any error, either recoverable or unrecoverable, is detected. The INFORMATION field in the sense data shall contain the LBA of the block in error.</p> <p>If an unrecoverable data error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p>
0	1	1	1	<p>The device server shall perform the full number of retries as specified in the READ RETRY COUNT field for read operations, the WRITE RETRY COUNT field for write operations, and the VERIFY RETRY COUNT field (see 5.3.34) for verify operations but shall not perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate a command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted if any error, either recoverable or unrecoverable, is detected. The INFORMATION field in the sense data shall contain the LBA of the block in error.</p> <p>If an unrecoverable data error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p>
1	0	0	0	<p>The device server shall perform the fewest possible number of retries and perform error correction in an attempt to recover the data.</p> <p>The device server shall not report recovered errors. The device server shall terminate a command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecoverable data error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p>
1	0	0	1	Invalid mode. The DCR bit shall be set to zero if the EER bit is set to one. ^[a]

Table 481 Combined error recovery bit descriptions (Sheet 3 of 3)

EER	PER	DTE	DCR	Description
1	1	0	0	<p>The device server shall perform the fewest possible number of retries and perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate a command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted only if an unrecoverable error is detected.</p> <p>If an unrecoverable data error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer</p> <p>If a recovered error occurs while the device server is performing a read or write operation, then, after the operation is complete, the device server shall terminate the command with CHECK CONDITION status with the sense key set to RECOVERED ERROR. The INFORMATION field in the sense data shall contain the LBA of the last recovered error that occurred during the command.</p>
1	1	0	1	Invalid mode. The DCR bit shall be set to zero if the EER bit is set to one. ^[a]
1	1	1	0	<p>The device server shall perform the fewest possible number of retries and perform error correction in an attempt to recover the data.</p> <p>The device server shall terminate the command performing a read or write operation with CHECK CONDITION status before the transfer count is exhausted if any error, either recoverable or unrecoverable, is detected. The INFORMATION field in the sense data shall contain the LBA of the block in error.</p> <p>If an unrecoverable data error occurs during a read operation, the transfer block (TB) bit determines whether the data for the logical block with the unrecovered read error is transferred to the data-in buffer.</p>
1	1	1	1	Invalid mode. The DCR bit shall be set to zero if the EER bit is set to one. ^[a]
<p>[a] If an invalid combination of the error recovery bits is sent by the application client the device server shall terminate the MODE SELECT command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST.</p>				

READ RETRY COUNT field

The READ RETRY COUNT field specifies the number of times that the device server shall attempt its recovery algorithm during read operations per logical block.

WRITE RETRY COUNT field

The WRITE RETRY COUNT field specifies the number of times that the device server shall attempt its recovery algorithm during write operations per logical block.

RECOVERY TIME LIMIT field

The RECOVERY TIME LIMIT field specifies in milliseconds the maximum time duration that the device server shall use for data error recovery procedures. The device server may round this value as described in 2.3. The limit in this field specifies the maximum error recovery time allowed for any individual command. A RECOVERY TIME LIMIT field set to zero specifies that the device server shall use its default value.

When both a retry count and a recovery time limit are specified, the field that specifies the recovery action of least duration shall have priority.

To disable all types of correction and retries the application client should set the EER bit to zero, the PER bit to one, the DTE bit to one, the DCR bit to one, the READ RETRY COUNT field to 00h, the WRITE RETRY COUNT field to 00h, and the RECOVERY TIME LIMIT field to 0000h.

5.3.24 Logical Unit mode page (18h) for SAS

The SAS Protocol-Specific Logical Unit mode page (see SPL-5) contains parameters that affect SSP target port operation on behalf of the logical unit.

The mode page policy (see 5.4.14) for the Protocol-Specific Logical Unit mode page short format subpage shall be either shared or per target port. If a SAS target device has multiple SSP target ports, the mode page policy should be per target port. Parameters in this page shall affect all phys in the SSP target port if the mode page policy is per target port, and shall affect all SSP target ports in the SAS target device if the mode page policy is shared.

Table 482 defines the format of the page for SAS.

Table 482 Protocol-Specific Logical Unit mode page for SAS

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (18h)					
1	PAGE LENGTH (06h)							
2	Reserved			TRANSPORT LAYER RETRIES	PROTOCOL IDENTIFIER (6h)			
3	Reserved							
4	Reserved							
...								
7								

PS bit

The PARAMETERS SAVEABLE (PS) bit is defined in 5.3.5.

SPF bit

The SPF bit shall be set to zero for access to the short format mode page.

PAGE CODE field

The PAGE CODE field shall be set to 18h.

PAGE LENGTH field

The PAGE LENGTH field shall be set to 06h.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field shall be set to 6h indicating this is a SAS specific mode page.

TRANSPORT LAYER RETRIES bit

- 1** A TRANSPORT LAYER RETRIES bit set to one specifies that the target port shall support transport layer retries for XFER_RDY and DATA frames for the logical unit as described in SAS-4.1 Transport Layer.
- 0** A TRANSPORT LAYER RETRIES bit set to zero specifies that transport layer retries shall not be used.

5.3.25 Protocol-Specific Port mode page (19h) for SAS

This clause describes the Protocol-Specific Port mode page implemented by products that are SAS-4.1 compliant. The Protocol-Specific Port mode page contains parameters that affect SSP target port operation. If the mode page is implemented by one logical unit in a SCSI target device, then it shall be implemented by all logical units in the SCSI target device that support the MODE SELECT or MODE SENSE commands.

The mode page policy (see 5.4.14) for this mode page shall be either shared or per target port. If a SAS target device has multiple SSP target ports, then the mode page policy should be per target port.

Parameters in this mode page:

- a) shall affect all phys in the SSP target port if the mode page policy is per target port; or
- b) shall affect all SSP target ports in the SAS target device if the mode page policy is shared.

Table 483 defines the format of the page for SAS.

Table 483 Protocol-Specific Port mode page for SAS

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (19h)					
1	PAGE LENGTH (0Eh)							
2	Reserved	CONTINUE AWT	BROADCAST ASYNCHRONOUS EVENT	READY LED MEANING	PROTOCOL IDENTIFIER (6h)			
3	Reserved							
4	(MSB)	I_T NEXUS LOSS TIME						(LSB)
5								
6	(MSB)	INITIATOR RESPONSE TIMEOUT						(LSB)
7								
8	(MSB)	REJECT TO OPEN LIMIT						(LSB)
9								
10	MAXIMUM ALLOWED XFER_RDY							
11								
...	Reserved							
15								

The PARAMETERS SAVEABLE (PS) bit is defined in 5.3.5.

The SPF bit shall be set to zero for access to the short format mode page.

The PAGE CODE field shall be set to 19h.

The PAGE LENGTH field shall be set to 0Eh.

CONTINUE AWT BIT

- 0** A CONTINUE AWT bit set to zero specifies that the SAS port shall stop the Arbitration Wait Time timer and set the Arbitration Wait Time timer to zero when it receives an OPEN_REJECT (RETRY).
- 1** A CONTINUE AWT bit set to one specifies that the SAS port shall not stop the Arbitration Wait Time timer and shall not set the Arbitration Wait Time timer to zero when the SAS port receives an OPEN_REJECT (RETRY).

BROADCAST ASYNCHRONOUS EVENT bit

- 0** A BROADCAST ASYNCHRONOUS EVENT bit set to zero specifies that the device server shall disable origination of BROADCAST (ASYNCHRONOUS EVENT).
- 1** A BROADCAST ASYNCHRONOUS EVENT bit set to one specifies that the device server shall enable origination of BROADCAST (ASYNCHRONOUS EVENT).

READY LED MEANING bit

The READY LED MEANING bit specifies the READY LED signal behavior. Regardless of the mode page policy (see 5.4.14) for this mode page, the shared mode page policy shall be applied to the READY LED MEANING bit.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in table 483 indicating that this is a SAS specific mode page.

I_T NEXUS LOSS TIME field

The I_T NEXUS LOSS TIME field contains the time that the SSP target port shall retry connection requests to an SSP initiator port that are rejected with responses indicating the SSP initiator port may no longer be present before recognizing an I_T nexus loss. table 417 defines the values of the I_T NEXUS LOSS TIME field. If this mode page is not implemented, the I_T nexus loss time is vendor specific. This value is enforced by the port layer.

Table 484 I_T NEXUS LOSS TIME values

Code	Description
0000h	Vendor-specific amount of time.
0001h to FFFEh	Time in milliseconds.
FFFFh	The SSP target port shall never recognize an I_T nexus loss (i.e., it shall retry the connection requests forever).

INITIATOR RESPONSE TIMEOUT field

The INITIATOR RESPONSE TIMEOUT field contains the time in milliseconds that the SSP target port shall wait for the receipt of a frame (e.g., a write DATA frame) before aborting the command associated with that frame. An INITIATOR RESPONSE TIMEOUT field value of zero indicates that the SSP target port shall disable the initiator response timeout timer. If this mode page is not implemented, the logical unit shall not implement an initiator response timeout timer. This value is enforced by the transport layer.

REJECT TO OPEN LIMIT field

The REJECT TO OPEN LIMIT field contains the minimum time in 10 μ s increments that the target port shall wait to establish a connection request with an initiator port on an I_T nexus after receiving an OPEN_REJECT (RETRY), OPEN_REJECT (RESERVED CONTINUE 0), or OPEN_REJECT (RESERVED CONTINUE 1). This value may be rounded as defined in 2.3. A REJECT TO OPEN LIMIT field set to 0000h indicates that the minimum time is vendor specific. This minimum time is enforced by the port layer.

MAXIMUM ALLOWED XFER_RDY field

The MAXIMUM ALLOWED XFER_RDY field specifies the maximum number of times a device server may call the Receive Data-Out transport protocol service as described in 9.2.1.8. A MAXIMUM ALLOWED XFER_RDY field set to zero specifies that there is no limit to the number of times a device server may call the Receive Data-Out transport protocol service.

5.3.26 Phy Control And Discover subpage (19h/01h)

The Phy Control And Discover subpage contains SAS phy-specific parameters. The mode page policy (see 5.4.14) for this subpage shall be shared. Parameters in this subpage shall affect only the referenced phy.

Table defines the format of the subpage for SAS.

Table 485 SAS - Phy Control And Discover subpage

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (19h)					
1	SUBPAGE CODE (01h)							
2	PAGE LENGTH (N - 3)							
3								
4	Reserved							
5	Reserved				PROTOCOL IDENTIFIER (6h)			
6	GENERATION CODE							
7	NUMBER OF PHYS							
SAS phy mode descriptor list								
8	FIRST SAS PHY MODE DESCRIPTOR (see table 486)							
...	...							
...	...							
...	LAST SAS PHY MODE DESCRIPTOR (see table 486)							
n								

The PARAMETERS SAVEABLE (PS) bit is defined in 5.3.5.

The SPF bit (see 5.3.5) shall be set to one to access the long format mode pages.

The PAGE CODE field (see 5.3.5) shall be set to 19h.

The SUBPAGE CODE field (see 5.3.5) shall be set to 01h.

The PAGE LENGTH field (see 5.3.5) shall be set to $(4 + (\text{the value of the NUMBER OF PHYS field}) \times (\text{the length in bytes of the SAS phy mode descriptor}))$.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field shall be set to 6h indicating this is a SAS specific mode page.

GENERATION CODE field

The GENERATION CODE field is a one-byte counter that shall be incremented by one by the device server every time the values in this mode page or the Enhanced Phy Control mode page (see 5.3.28) are changed. A GENERATION CODE field set to 00h indicates the generation code is unknown. The device server shall wrap this field to 01h as the next increment after reaching its maximum value (i.e., FFh). The GENERATION CODE field is also contained in the Enhanced Phy Control mode page (see 5.3.28) and the Protocol-Specific Port log page and may be used to correlate phy settings across mode page and log page accesses.

NUMBER OF PHYS field

The NUMBER OF PHYS field contains the number of phys in the SAS target device and indicates the number of SAS phy mode descriptors that follow. This field shall not be changeable with MODE SELECT.

SAS PHY MODE DESCRIPTOR fields

A SAS phy mode descriptor shall be included for each phy in the SAS target device (not just the SAS target port), starting with the lowest numbered phy and ending with the highest numbered phy.

Table 486 defines the SAS phy mode descriptor.

Table 486 SAS phy mode descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved							
1	PHY IDENTIFIER							
2	Reserved							
3	Reserved							
4	Reserved	ATTACHED DEVICE TYPE			Reserved			
5	REASON				NEGOTIATED PHYSICAL LINK RATE			
6	Reserved				ATTACHED SSP INITIATOR PORT	ATTACHED STP INITIATOR PORT	ATTACHED SMP INITIATOR PORT	Reserved
7	Reserved				ATTACHED SSP TARGET PORT	ATTACHED STP TARGET PORT	ATTACHED SMP TARGET PORT	Reserved
8	SAS ADDRESS							
...								
15	SAS ADDRESS							
16	ATTACHED SAS ADDRESS							
...								
23	ATTACHED SAS ADDRESS							
24	ATTACHED PHY IDENTIFIER							
25	Reserved							
...								
31	Reserved							
32	PROGRAMMED MINIMUM PHYSICAL LINK RATE				HARDWARE MINIMUM PHYSICAL LINK RATE			
33	PROGRAMMED MAXIMUM PHYSICAL LINK RATE				HARDWARE MAXIMUM PHYSICAL LINK RATE			
34	Reserved							
...								
41	Reserved							
42	Vendor specific							
43	Vendor specific							
44	Reserved							
...								
47	Reserved							

PHY IDENTIFIER field

The PHY IDENTIFIER field indicates the phy identifier (see SPL-5) of the phy for which information is being returned.

ATTACHED DEVICE TYPE field

The ATTACHED DEVICE TYPE field indicates the device type attached to this phy and is defined in Table 387.

NEGOTIATED PHYSICAL LINK RATE field

If the NEGOTIATED PHYSICAL LINK RATE field (see table 389) is not set to a physical link rate, then the management device server may set the ATTACHED DEVICE TYPE field to 000b.

ATTACHED SSP INITIATOR PORT bit

An ATTACHED SSP INITIATOR PORT bit set to:

- 0** zero indicates that an SSP initiator port is not present in the attached device.
- 1** one indicates that an SSP initiator port is present in the attached device.

ATTACHED STP INITIATOR PORT bit

An ATTACHED STP INITIATOR PORT bit set to one indicates that an STP initiator port is present in the attached device.

ATTACHED SMP INITIATOR PORT bit

An ATTACHED SMP INITIATOR PORT bit set to one indicates that an SMP initiator port is present in the attached device.

ATTACHED SSP TARGET PORT bit

An ATTACHED SSP TARGET PORT bit set to one indicates that an SSP target port is present in the attached device.

ATTACHED STP TARGET PORT bit

An ATTACHED STP TARGET PORT bit set to one indicates that an STP target port is present in the attached device.

ATTACHED SMP TARGET PORT bit

An ATTACHED SMP TARGET PORT bit set to one indicates that an SMP target port is present in the attached device.

SAS ADDRESS field

The SAS ADDRESS field indicates the port identifier (see SPL-5) of the SAS port transmitting the IDENTIFY address frame. For expander ports, the SAS ADDRESS field indicates the device name (see SPL-5) of the expander device transmitting the IDENTIFY address frame.

ATTACHED SAS ADDRESS field

The ATTACHED SAS ADDRESS field contains SAS address of the attached SAS port (see SPL-5).

ATTACHED PHY IDENTIFIER

The ATTACHED PHY IDENTIFIER field contains the phy identifier of the attached SAS phy in the attached SAS device.

HARDWARE MINIMUM PHYSICAL LINK RATE field

The HARDWARE MINIMUM PHYSICAL LINK RATE field indicates the minimum physical link rate supported by the phy. The values are defined in table 347.

HARDWARE MAXIMUM PHYSICAL LINK RATE field

The HARDWARE MAXIMUM PHYSICAL LINK RATE field indicates the maximum physical link rate supported by the phy. The values are defined in table 347. If the phy is a virtual phy, this field should be set to the maximum physical link rate supported by the expander device.

Table 487 The HARDWARE MINIMUM & MAXIMUM PHYSICAL LINK RATE field values

Code	Description
0h to 7h	Reserved
8h	1.5 Gbps
9h	3.0 Gbps
Ah	6.0 Gbps
Bh	12.0 Gbps
Ch to Fh	Reserved for future physical link rates

MAXIMUM PHYSICAL LINK RATE field

MAXIMUM PHYSICAL LINK RATE field are defined in the SMP DISCOVER function (see SAS-4.1). These fields shall not be changeable with MODE SELECT.

PROGRAMMED MINIMUM PHYSICAL LINK RATE field and PROGRAMMED MAXIMUM PHYSICAL LINK RATE field

The PROGRAMMED MINIMUM PHYSICAL LINK RATE field and PROGRAMMED MAXIMUM PHYSICAL LINK RATE field are defined in the SMP PHY CONTROL function (see SPL-5) for accesses with MODE SELECT commands and in the SMP DISCOVER function (see SPL-5) for accesses with MODE SENSE commands.

Table 488 lists the PROGRAMMED MINIMUM and MAXIMUM PHYSICAL LINK RATE field values.

Table 488 The PROGRAMMED MINIMUM and MAXIMUM PHYSICAL LINK RATE field values

Code	Description
0h	Do not change current value
1h to 7h	Reserved
8h	1.5 Gbps
9h	3.0 Gbps
Ah	6.0 Gbps
Bh	12.0 Gbps
Ch to Fh	Reserved for future physical link rates

5.3.27 Shared Port Control mode page (19h/02h)

The Port Control Mode Page contains parameters that affect SAS target port operation. If the mode page is implemented by one logical unit in a SCSI target device, then it shall be implemented by all logical units in the SCSI target device that support the MODE SELECT or MODE SENSE commands.

The mode page policy (see 5.4.14) for this mode page shall be shared.

Table 489 defines the format of this mode page.

Table 489 Shared Port Control Mode Page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (19h)					
1	SUBPAGE CODE (02h)							
2	(MSB)	PAGE LENGTH (000Ch)						(LSB)
3								
4	Reserved							
5	Reserved				PROTOCOL IDENTIFIER (6h)			
6	(MSB)	POWER LOSS TIMEOUT						(LSB)
7								
8	Reserved							
9	POWER GRANT TIMEOUT							
10								
...	Reserved							
15								

The Parameters Saveable (PS) bit is defined in 5.3.5.

The SubPage Format (SPF) bit is defined in 5.3.5 and shall be set to the value defined in table 489.

The PAGE CODE field is defined in 5.3.5 and shall be set to the value defined in table 489.

The SUBPAGE CODE field is defined in 5.3.5 and shall be set to the value defined in table 489.

The PAGE LENGTH field is defined in 5.3.5 and shall be set to the value defined in table 489.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in table 489 indicating that this is a SAS SSP specific mode page.

POWER LOSS TIMEOUT field

The POWER LOSS TIMEOUT field contains the maximum time, in one millisecond increments, that a target port shall respond to connection requests with OPEN_REJECT (RETRY) after receiving NOTIFY (POWER LOSS EXPECTED) (see SAS-4.1). A POWER LOSS TIMEOUT field set to 0000h specifies that the maximum time is vendor-specific. The power loss timeout shall be restarted on each NOTIFY (POWER LOSS EXPECTED) that is received.

POWER GRANT TIMEOUT field

The POWER GRANT TIMEOUT field contains the minimum time, in one second increments, that a SAS target device shall wait to receive a PWR_GRANT from a power source device. A POWER GRANT TIMEOUT field set to 00h specifies that the time limit is vendor specific.

5.3.28 Enhanced Phy Control mode page (19h/03h)

The Enhanced Phy Control mode page contains parameters that affect SAS target phy operation. If the mode page is implemented by one logical unit in a SCSI target device, then it shall be implemented by all logical units in the SCSI target device that support the MODE SELECT or MODE SENSE commands.

The mode page policy (see 5.4.14) for this mode page shall be shared.

Table 490 defines the format of this mode page.

Table 490 Enhanced Phy Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF(1b)	PAGE CODE (19h)					
1	SUBPAGE CODE (03h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
4	Reserved							
5	Reserved				PROTOCOL IDENTIFIER (6h)			
6	GENERATION CODE							
7	NUMBER OF PHYS							
Enhanced phy control mode descriptor list								
8								
...	Enhanced phy control mode descriptor (first) (see table 491)							
27								
...	...							
n - 19								
...	Enhanced phy control mode descriptor (last) (see table 491)							
n								

The Parameters Saveable (PS) bit is defined in 5.3.5.

The SubPage Format (SPF) bit is defined in 5.3.5 and shall be set to the value defined in table 490.

The PAGE CODE field is defined in 5.3.5 and shall be set to the value defined in table 490.

The SUBPAGE CODE field is defined in 5.3.5 and shall be set to the value defined in table 490.

The PAGE LENGTH field is defined in 5.3.5 and shall be set to the value defined in table 490 (i.e., 4 + (the value of the NUMBER OF PHYS field) * (the length in bytes of the SAS phy mode descriptor)).

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in table 490 indicating that this is a SAS specific mode page.

GENERATION CODE field

The GENERATION CODE field is defined in the Phy Control and Discover mode page (see 5.3.26).

NUMBER OF PHYS field

The NUMBER OF PHYS field contains the number of phys in the SAS target device and indicates the number of enhanced phy control mode descriptors in the enhanced phy control mode descriptor list. This field shall not be changeable with the MODE SELECT command.

ENHANCED PHY CONTROL MODE DESCRIPTOR

The enhanced phy control mode descriptor list contains an enhanced phy control mode descriptor for each phy in the SAS target device, not just the SAS target port, starting with the lowest numbered phy and ending with the highest numbered phy.

Table 491 defines the enhanced phy control mode descriptor.

Table 491 Enhanced phy control mode descriptor

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1	PHY IDENTIFIER								
2	(MSB)	DESCRIPTOR LENGTH (0010h)						(LSB)	
3									
4	PROGRAMMED PHY CAPABILITIES								
...									
7									
8	CURRENT PHY CAPABILITIES								
...									
11									
12	ATTACHED PHY CAPABILITIES								
...									
15									
16	Reserved								
17									
18	Reserved			NEGOTIATED SSC	NEGOTIATED PHYSICAL LINK RATE				
19	Reserved							HARDWARE MUXING SUPPORTED	

PHY IDENTIFIER field

The PHY IDENTIFIER field indicates the phy identifier (see SPL-5) of the phy for which information is being returned.

DESCRIPTOR LENGTH field

The DESCRIPTOR LENGTH field contains the length in bytes that follow in the descriptor and shall be set to the value defined in table 491.

The fields in the enhanced phy control mode descriptor not defined in this subclause are defined in the SMP DISCOVER response (see SPL-5). These fields shall not be changeable with the MODE SELECT command.

PROGRAMMED PHY CAPABILITIES field

The PROGRAMMED PHY CAPABILITIES field indicates the SNW-3 phy capabilities bits that are going to be transmitted in the next link reset sequence containing SNW-3 as defined in SPL-5.

CURRENT PHY CAPABILITIES field

The CURRENT PHY CAPABILITIES field indicates the outgoing SNW-3 phy capabilities bits transmitted in the last link reset sequence as defined in SPL-5. If the last link reset sequence did not include SNW-3 or was a SATA link reset sequence, then the CURRENT PHY CAPABILITIES field shall be set to 00000000h.

ATTACHED PHY CAPABILITIES field

The ATTACHED PHY CAPABILITIES field indicates the incoming SNW-3 phy capabilities bits received in the last SNW-3 as defined in SPL-5. If the last link reset sequence did not include SNW-3 or was a SATA link reset sequence, then the ATTACHED PHY CAPABILITIES field shall be set to 00000000h.

NEGOTIATED SSC bit

A NEGOTIATED SSC bit set to:

- 0** indicates that SSC is disabled
- 1** indicates that SSC is enabled

The NEGOTIATED SSC bit is only valid if the NEGOTIATED PHYSICAL LINK RATE field is greater than or equal to 8h.

NEGOTIATED PHYSICAL LINK RATE field

The NEGOTIATED PHYSICAL LINK RATE field is defined in table 389. If the phy is a physical phy, this field indicates the physical link rate negotiated during the link reset sequence. If the phy is a virtual phy, this field should be set to the maximum physical link rate supported by the expander device. The negotiated physical link rate may be less than the programmed minimum physical link rate or greater than the programmed maximum physical link rate if the programmed physical link rates have been changed since the last link reset sequence.

HARDWARE MUXING SUPPORTED bit

A HARDWARE MUXING SUPPORTED bit set to:

- 0** indicates that the phy does not support multiplexing
- 1** indicates that the phy supports multiplexing

This value is not adjusted based on the negotiated physical link rate.

5.3.29 SAS – Transceiver Control (Out) subpage (19h/E5h)

5.3.29.1 Introduction

The Transceiver Control (Out) subpage (see table 492) of the SAS Protocol-Specific Port mode page is used to adjust the transceiver parameter values of a phy. This subpage, when implemented, must comply with the following additional itemized requirements:

- 1) The transceiver parameter settings may only be adjusted temporarily using the contents of this mode page, and cannot be saved.
- 2) New phy settings are not to take effect until after status is returned for the MODE SELECT command that is issued to adjust the phy settings.
- 3) The Transceiver Control subpage shall not be returned for a MODE SENSE command to return all pages. It shall only be returned to a MODE SENSE command, specifically, for the Transceiver Control subpage (19h/E5h).
- 4) Transceiver Control Subpage E5h must include all mode descriptor for each link rate of each phy. For non-supported link rate, fill the mode descriptor bytes with 00.

Table 492 SAS Transceiver Control (Out) subpage

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF(1b)	PAGE CODE (19h)					
1	SUBPAGE CODE (E5h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
4	Reserved							
5	Reserved				PROTOCOL IDENTIFIER (6h)			
6	Reserved							
7	NUMBER OF PHYS (02h for a dual ported disk drive)							
8								
...	Reserved							
14								
15	TRANSCEIVER CONTROLS MODE DESCRIPTORS LENGTH							
16	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 08h							
...	...							
32	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 09h							
...	...							
48	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 0Ah							
...	...							
64	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 0Bh							
...	...							
80	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 08h							
...	...							
96	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 09h							
...	...							
112	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 0Ah							

Table 492 SAS Transceiver Control (Out) subpage

Bit Byte	7	6	5	4	3	2	1	0
...	...							
128	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 0Bh							
...	...							
144	00							

The PARAMETERS SAVEABLE (PS) bit is defined in SPC-6.

The SUBPAGE FORMAT (SPF) bit is defined in SPC-6 and shall be set to the value defined in table 492.

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 492.

The SUBPAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 492.

PAGE LENGTH field

The PAGE LENGTH field is defined in SPC-6 and shall be set to the value defined in table 492 (i.e., 4 + (the value of the NUMBER OF PHYS field) × (the length in bytes of the SAS phy mode descriptor)).

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in table 492 indicating that this is a SAS specific mode page.

NUMBER OF PHYS field

The NUMBER OF PHYS field contains the number of phys in the SAS target device and indicates the number of enhanced phy control mode descriptors in the enhanced phy control mode descriptor list. If a target device has 2 operational target ports (2 phys), then this field shall be set to 2h. Target devices with only one port shall set this field to 1h. This field shall not be changeable with the MODE SELECT command.

TRANSCIEVER CONTROLS MODE DESCRIPTORS LENGTH fields

This Transceiver Controls Mode Descriptors Length fields shall contain the total length in bytes of each phy's transceiver controls mode descriptor. Since the descriptors are the same length, this value is not provided in each descriptor, but rather, once in this subpage prior to the descriptor(s). The field is unchangeable.

5.3.29.2 Transceiver Controls Mode descriptors

Detail for the mode descriptor(s) for transceiver controls can be found in Table 493 and Table 494. Each field is defined below the table. All supported link rates and controls shall be listed in page E5h.

Table 493 Transceiver Controls Mode descriptor (1.5Gb, 3Gb and 6Gb Link Rate)

Bit Byte	7	6	5	4	3	2	1	0
0	PHY IDENTIFIER							
1	CONTROLLABLE LINK RATE							
2	DRIVER STRENGTH CONTROL							
3	DRIVER EMPHASIS CONTROL							
4	DRIVER SLEW RATE CONTROL							
5	MANUFACTURER DEFINE BYTES FOR TRANSMITTER CONTROL							
...								
8								
9	RECEIVER THRESHOLD CONTROL							
10	RECEIVER EQUALIZATION GAIN CONTROL							
11	MANUFACTURER DEFINE BYTES FOR RECEIVER CONTROL							
12								
13	INTERNAL RX EYE MARGIN			RESET	Reserved	Reserved	IREC	
14	INTERNAL RX EYE HEIGHT							
15	INTERNAL RX EYE WIDTH							

Table 494 Transceiver Controls descriptor (12Gb Link Rate)

Bit Byte	7	6	5	4	3	2	1	0
0	PHY IDENTIFIER							
1	CONTROLLABLE LINK RATE							
2	C1 VALUE OF TX							
3	C2 VALUE OF TX							
4	C3 VALUE OF TX							
5	Reserved			RESET	Reserved	IREC COMPLETED	IREC	
6	FFE COEFFICIENT 0 / INTERNAL RX EYE HEIGHT MARGIN							
7	FFE COEFFICIENT 1 / INTERNAL RX EYE WIDTH MARGIN							
8	DFE COEFFICIENT 0							
9	DFE COEFFICIENT 1							
10	DFE COEFFICIENT 2							
11	DFE COEFFICIENT 3							
12	DFE COEFFICIENT 4							
13	HOST C1 RELATIVE VALUE							
14	HOST C2 RELATIVE VALUE							
15	HOST C3 RELATIVE VALUE							

PHY IDENTIFIER field

SAS devices may have more than one target port. If a target device has 2 operational target ports (2 phys - primary and secondary port), then this field shall be set to either 0h for the primary port or 1h for the secondary port. This field is unchangeable.

CONTROLLABLE LINK RATE field

The Controllable Link Rate field shall contain the controllable link rate for the phy. Table 495 lists the supported values Controllable Link Rates. This field is not changeable.

Table 495 Controllable Link Rates

Value	Definition
0x00	Phy exists, but does not support "Transceiver Control" controls
0x01 – 0x07	Reserved
0x08	Phy supports Transceiver Control controls for 1.5 Gbps
0x09	Phy supports Transceiver Control controls for 3.0 Gbps
0x0A	Phy supports Transceiver Control controls for 6.0 Gbps
0x0B	Phy supports Transceiver Control controls for 12.0 Gbps
0x0C – 0xFF	Reserved

DRIVER STRENGTH CONTROL or C1 PRE-CURSOR CONTROL (12Gb only) field

This field shall contain either the user input (MODE SELECT) or current (MODE SENSE) driver strength output or the 12G mode pre-cursor C1 setting of the SAS transmitter. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command. This field shall be supported as described in Table 496. The field is changeable but not savable.

Table 496 DRIVER STRENGTH CONTROL or C1 PRE-CURSOR CONTROL (12G Mode Only) values

Value	Definition
0x66 (write only) (1.5G - 6G)	Write 66h shall reset the driver strength setting back to factory default value.
0x00 – Range Limit (write only)	User input for driver strength control setting or C1 pre-cursor setting. If the new user input is out of range specified in subpage 19h/E5h, the target device shall maintain the current setting.
Read Only	The current setting value shall be displayed.

DRIVER EMPHASIS CONTROL or C2 AMPLITUDE CONTROL (12G Mode Only) field

This field shall contain either the user input (MODE SELECT) or current (MODE SENSE) driver emphasis setting the 12G mode amplitude C2 setting of the SAS transmitter. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command. This field shall be supported as described in Table 497. This field is changeable but not savable.

Table 497 DRIVER EMPHASIS CONTROL or C2 AMPLITUDE CONTROL (12G Mode Only)

Value	Definition
0x66 (write only) (1.5G - 6G)	Write 66h shall reset the driver pre-emphasis setting back to factory default value.
0x00 – Range Limit (write only)	User input for driver pre-emphasis control setting or C2 amplitude setting. If the new user input is out of range specified in subpage 19h/E5h, the target device shall maintain the current setting.
Read Only	The current setting value shall be displayed.

DRIVER SLEW RATE CONTROL or C3 CONTROL (12G Mode Only) field

This field shall contain either the user input (MODE SELECT) or current (MODE SENSE) driver slew rate setting of the target device SAS phy. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command. This field shall be supported as described in Table 498. This field is changeable but not savable.

Table 498 DRIVER SLEW RATE CONTROL or C3 POST CURSOR CONTROL (12G mode only)

Value	Definition
0x66 (write only) (1.5G - 6G)	Write 66h shall reset the driver slew rate setting back to factory default value.
0x00 – Range Limit (write only)	User input for driver slew rate control setting or C3 post cursor setting. If the new user input is out of range specified in subpage 19h/E5h, the target device shall maintain the current setting.
Read Only	The current setting value shall be displayed.

MANUFACTURER DEFINED BYTES FOR TRANSMITTER CONTROL field

The manufacturer Defined Bytes For Transmitter Control field may be used by the manufacturer who needs additional control bytes for the transmitter. All control bytes shall accept 66h as reset code which change the control byte back to factory default setting. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command.

RECEIVER THRESHOLD CONTROL field

The Receiver Threshold Control field contains either the user input (MODE SELECT) or current (MODE SENSE) receiver threshold setting of the target device SAS phy. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command. The Receiver Threshold Control field shall be supported as described in table 499. This field is changeable but not savable.

Table 499 Receiver Threshold Control

Value	Definition
0x66 (write only)	Write 66h shall reset the receiver threshold setting back to factory default value.
0x00 – Range Limit (write only)	User input for receiver threshold control setting. If the new user input is out of range specified in subpage 19h/E5h, the target device shall maintain the current setting.
Read Only	The current setting value shall be displayed.

RECEIVER EQUALIZATION GAIN CONTROL field

The Receiver Equalization Gain Control field contains either the user input (MODE SELECT) or current (MODE SENSE) receiver equalization gain setting of the target device SAS phy. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command. This field shall be supported as described in table 500. This field is changeable but not savable.

Table 500 Receiver Equalization Gain Control field

Value	Definition
0x66 (write only)	Write 66h shall reset the receiver equalization gain setting back to factory default value for the driver voltage.
0x00 – Range Limit (write only)	User input for receiver equalization gain control setting. If the new user input is out of range specified in subpage 19h/E5h, the target device shall maintain the current setting
Read Only	The current setting value shall be displayed.

MANUFACTURER DEFINED BYTES FOR RECEIVER CONTROL field

The Manufacturer Defined Bytes For Receiver Control field may be used by manufacturer who needs additional control bytes for the receiver. All control bytes shall accept 66h as reset code which change the control byte back to factory default setting. If the user input setting is out of range of the transceiver capability, the target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for the MODE SELECT command.

EYE WIDTH MARGIN and EYE HEIGHT MARGIN field - Read Only

These fields shall contain IRE margin after IREC (Internal RX Eye Capture) is performed. The margin calculation are based on the following formula:

$$\text{Eye Width Margin} = (\text{Captured Eye Width} - \text{Spec Min Eye Width}) / \text{Spec Min Eye Width} \times 100\%$$

$$\text{Eye Height Margin} = (\text{Captured Eye Height} - \text{Spec Min Height Width}) / \text{Spec Min Eye Height} \times 100\%$$

In case the Captured Eye is less than Spec Min. Eye, then FFh should be used.

IREC (INTERNAL RX EYE CAPTURE) bit

This bit controls the Internal RX Eye Capture process (see table 500), and provides the internal eye height, eye width and eye margin.

IREC COMPLETED bit - Read Only

This bit indicates the Internal RX Eye Capture process (see table 500) is completed and provides the internal eye height, eye width and eye margin.

RESET bit

This bit controls the TX to C1, C2 and C3, and controls the reset function of IREC bits (see table 500).

Table 501 RESET and IREC bit function

RESET (Mode Select)	IREC (Mode Select)	IREC Completed	Mode Sense data after Mode Select was executed with different RESET bit and IREC bit settings.
0	0	0	<ul style="list-style-type: none"> n No change on current C1, C2, C3 n All FFE and DFE coefficients shall be updated
0	0	1	<ul style="list-style-type: none"> n Set IREC Completed bit to 1 when RX eye capture is completed n IRC Margin shall be displayed n RX eye height and eye width shall be displayed instead of RX FFE coefficients. n All DFE coefficients shall be updated
1	0	Don't Care	<ul style="list-style-type: none"> n Set TX to C1, C2, C3 (no retrain) n All FFE and DFE coefficients shall be updated n After reset operation completed, Reset bit shall be set to 0, IREC Completed bit shall be set to 0. n All FFE and DFE coefficients shall be updated.
1	1	Don't Care	<ul style="list-style-type: none"> n No change on current C1, C2, C3 n Perform internal RX eye capture n After RX eye capture completed, Reset bit shall be set to 0 and IREC Completed bit shall be set to 1. n IRC Margin shall be displayed n RX eye height and eye width shall be displayed instead of RX FFE coefficients. n All DFE coefficients shall be updated

FFE TAP 0, 1 / RX EYE HEIGHT AND RX EYE WIDTH (Read only)

The FFE Tap 0, 1 field shall contain the current (MODE SENSE) FFE Tap 0 and Tap 1 coefficient with the RESET bit is set to 0 and IREC Completed bit set to 0. The RX Eye Height And RX Eye Width fields shall contain the current (MODE SENSE) RX eye height and RX eye width with IREC completed bit set to 1.

DFE COEFFICIENT 0 - 4 (Read only)

This field shall contain the current (MODE SENSE) DFE coefficient of the receiver. If the number of DFE coefficients is more than 5, then only the first 5 coefficients shall be displayed.

HOST TRANSMITTER C1, C2 AND C3 RELATIVE SETTING (Read Only)

This field shall contain the user input (MODE SELECT) of the C1, C2 and C3 relative setting of host transmitter.

During the speed negotiation, the C1, C2 and C3 of the Host transmitter will be adjusted by Up or Hold or Down.

Keep track of the adjustment by each Up = +1, each Hold = 0 and each Down = -1, i.e. C1 is adjusted by 3 Up tics and 1 Down, the relative Host C1 is $1+1+1-1 = 2$.

5.3.30 SAS – Transceiver Control (In) subpage (19h/E6h)

5.3.30.1 Introduction

The Transceiver Control (In) subpage of the SAS Protocol-Specific Port mode page (see table 502) is used to return the transceiver parameter values of a phy. The Transceiver Control subpage shall not be returned for a MODE SENSE command to return all pages. It shall only be returned to a MODE SENSE command, specifically, for the Transceiver Control subpage (19h/E6h). The target device shall return a CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to INVALID FIELD IN PARAMETER LIST for a MODE SELECT command issued for this subpage.

Table 502 SAS - Transceiver Control (In) subpage

(Sheet 1 of 2)

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	Page Code (19h)					
1	SUBPAGE CODE (E6h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
4	Reserved							
5	Reserved				PROTOCOL IDENTIFIER (6h)			
6	Reserved							
7	NUMBER OF PHYS (02h for a dual ported disk drive)							
8	Reserved							
...								
14								
15	TRANSCEIVER CONTROLS MODE DESCRIPTOR LENGTH = 16							
16	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 08h							
...	...							
32	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 09h							
...	...							
48	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 0Ah							
...	...							
64	Phy Transceiver Controls mode descriptor (first) PHY IDENTIFIER = 0							
	CONTROLLABLE LINK RATE = 0Bh							
...	...							
80	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 08h							
...	...							
96	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1							
	CONTROLLABLE LINK RATE = 09h							
...	...							

(continued) **(Sheet 2 of 2)**

112	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1
	CONTROLLABLE LINK RATE = 0Ah
...	...
128	Phy Transceiver Controls mode descriptor (second) PHY IDENTIFIER = 1
	CONTROLLABLE LINK RATE = 0Bh
...	...
144	00

The PARAMETERS SAVEABLE (PS) bit is defined in SPC-6.

The SUBPAGE FORMAT (SPF) bit is defined in SPC-6 and shall be set to the value defined in table 502.

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 502.

The SUBPAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 502.

PAGE LENGTH field

The PAGE LENGTH field is defined in SPC-6 and shall be set to the value defined in table 502 (i.e., 4 + (the value of the NUMBER OF PHYS field) × (the length in bytes of the SAS phy mode descriptor)).

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set to the value defined in table 502 indicating that this is a SAS specific mode page.

NUMBER OF PHYS field

SAS devices may have more than one target port. If a target device has 2 operational target ports (2 phys), then this field shall be set to 2h. Target devices with only one port shall set this field to 1h. The field is unchangeable.

TRANSCEIVER CONTROLS MODE DESCRIPTOR LENGTH field

The Transceiver Controls Mode Descriptor Length field shall contain the total length in bytes of each phy's transceiver controls mode descriptor. Since the descriptors are the same length, this value is not provided in each descriptor, but rather, once in this subpage prior to the descriptor(s). The field is unchangeable.

5.3.30.2 Transceiver Controls Mode descriptors

Detail for the mode descriptor(s) for transceiver controls can be found in Table 503 and Table 504. Each field is defined below the table. All supported link rates and controls shall be listed in page E5h.

Table 503 Transceiver Controls descriptor (1.5Gb - 6Gb Link Rate)

Bit Byte	7	6	5	4	3	2	1	0
0	PHY IDENTIFIER							
1	CONTROLLABLE LINK RATE							
2	DRIVER STRENGTH CONTROL							
3	DRIVER EMPHASIS CONTROL							
4	DRIVER SLEW RATE CONTROL							
5	MANUFACTURER DEFINED BYTES FOR TRANSMITTER CONTROL							
...								
8								
9	RECEIVER THRESHOLD CONTROL							
10	RECEIVER EQUALIZATION GAIN CONTROL							
11	MANUFACTURER DEFINE BYTES FOR RECEIVER CONTROL							
12								
13	INTERNAL RX EYE MARGIN			RESET	Reserved	Reserved	IREC	
14	INTERNAL RX EYE HEIGHT							
15	INTERNAL RX EYE WIDTH							

Table 504 Transceiver Controls descriptor (1.5G, 3G, 6G and 12G)

Bit Byte	7	6	5	4	3	2	1	0
0	PHY IDENTIFIER							
1	CONTROLLABLE LINK RATE							
2	MAX DRIVER STRENGTH CONTROL [12G: MAX C1 WHEN C2 AND C3 ARE SET TO MIN]							
3	MAX DRIVER EMPHASIS CONTROL [12G: MAX C1 WHEN C1 AND C3 ARE SET TO 0]							
4	MAX DRIVER SLEW RATE CONTROL [12G: MAX C1 WHEN C1 AND C2 ARE SET TO MIN]							
5	DRIVER STRENGTH CONTROL CHANGE PER STEP [12G: C1 CHANGE PER STEP]							
6	DRIVER EMPHASIS CONTROL CHANGE PER STEP [12G: C2 CHANGE PER STEP]							
7	DRIVER SLEW RATE CONTROL CHANGE PER STEP [12G: C2 CHANGE PER STEP]							
8	Reserved (00h)							
9	MAX RECEIVER THRESHOLD CONTROL							
10	MAX RECEIVER EQUALIZATION GAIN CONTROL							
11	RECEIVER THRESHOLD CONTROL CHANGE PER STEP							
12	RECEIVER EQUALIZATION GAIN CONTROL CHANGE PER STEP							
13-15	Reserved							

PHY IDENTIFIER field

SAS devices may have more than one target port. If a target device has 2 operational target ports (2 phys - primary and secondary port), then this field shall be set to either 0h for the primary port or 1h for the secondary port. The field is unchangeable.

CONTROLLABLE LINK RATE field

This field shall contain the controllable link rate for the phy. Table 505 lists the supported values for the field. This field is not changeable.

Table 505 Controllable Link Rates field

Value	Definition
0x00	Phy exists, but does not support Transceiver Control controls
0x01 – 0x07	Reserved
0x08	Phy supports Transceiver Control controls for 1.5 Gbps
0x09	Phy supports Transceiver Control controls for 3.0 Gbps
0x0A	Phy supports Transceiver Control controls for 6.0 Gbps
0x0B	Phy supports Transceiver Control controls for 12.0 Gbps
0x0C – 0xFF	Reserved

MAX DRIVER STRENGTH CONTROL or C1 MAX SETTING when C2 and C3 set to MIN (12G Mode Only) field

This field shall contain the max allowable driver strength output setting of the target device SAS phy. The field is changeable but not savable.

MAX DRIVER EMPHASIS CONTROL or C2 MAX SETTING when C1 and C3 set to 0 (12G Mode Only) field

This field shall contain the max allowable driver emphasis setting of the target device SAS phy. This field is changeable but not savable.

MAX DRIVER SLEW RATE CONTROL or C3 CONTROL (12G Mode Only) field

This field shall contain the max allowable driver slew rate setting of the target device SAS phy. This field is changeable but not savable.

DRIVER STRENGTH CONTROL CHANGE PER STEP or C1 CONTROL (12G Mode Only) field

This field shall contain the approximate voltage change (in mV unit) for each increment or decrement of driver strength control setting. The field is unchangeable.

DRIVER EMPHASIS CONTROL CHANGE PER STEP or C2 CONTROL (12G Mode Only) field

This field shall contain the approximate percentage of amplitude change (in % unit) for each increment or decrement of driver emphasis control setting. This field shall be used to establish the transceiver driver pre-emphasis or de-emphasis. The field value should be treated as a 2's-complement signed value that can range from 1 to +100 for pre-emphasis, or -1 to -100 for de-emphasis. The field is unchangeable.

DRIVER SLEW RATE CONTROL CHANGE PER STEP or C3 CONTROL (12G Mode Only) field

This field shall contain the approximate slew rate change (in mV/nsec unit) for each increment or decrement of driver slew rate control setting. The field is unchangeable.

MAX RECEIVER THRESHOLD CONTROL field

This field contains max allowable threshold setting of the target device SAS phy. The field is unchangeable.

MANUFACTURER DEFINED BYTES INFO FOR TRANSMITTER CONTROL field

This field can be used by manufacturer who needs additional control bytes for the transmitter.

MAX RECEIVER EQUALIZATION GAIN CONTROL field

This field contains the max allowable receiver equalization gain setting of the target device SAS phy. The field is unchangeable.

RECEIVER THRESHOLD CONTROL CHANGE PER STEP field

This field shall contain the approximate voltage change (in mV unit) for each increment or decrement of receiver threshold control setting. The field is unchangeable.

RECEIVER EQUALIZATION GAIN CONTROL CHANGE PER STEP field

This field shall contain the approximate gain change for each increment or decrement of receiver equalization gain control setting. The field is unchangeable.

MANUFACTURER DEFINED BYTES INFO FOR RECEIVER CONTROL field

This field can be used by manufacturer who needs additional control bytes for the receiver.

5.3.31 Rigid Drive Geometry Parameters page (04h)

This mode page has been declared obsolete by the T10 committee. However, it is included because it may be implemented on some products. The Rigid Drive Geometry Parameters page implementation is defined in Table 506. This table summarizes the function and defines the default value.

Table 506 Rigid Drive Geometry Parameters page (04h)

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (04h)					
1	PAGE LENGTH (16h)							
2	NUMBER OF CYLINDERS (MSB)							
3	NUMBER OF CYLINDERS							
4	NUMBER OF CYLINDERS (LSB)							
5	NUMBER OF HEADS							
6,7,8	STARTING CYLINDER—WRITE PRECOMP							
9,10,11	STARTING CYLINDER—REDUCED WRITE CURRENT							
12,13	DRIVE STEP RATE							
14,15,16	LANDING ZONE CYLINDER							
17	0	0	0	0	0	0	RPL	
18	ROTATIONAL OFFSET XXh							
19	Reserved							
20	(MSB)							
21	MEDIUM ROTATION RATE							
	(LSB)							
22	Reserved							
23	Reserved							

PS (Parameter Savable) bit

The Parameter Savable (PS) bit of 1 indicates that page 04 parameter data is savable and is saved when a Format Function is performed. In some drives an exception exists that applies to bytes 17 and 18. In the exception drives, bytes 17 and 18 are only saved if the SMP bit in the MODE SELECT command (Table 82) is 1. See individual drive's Product Manual, Volume 1, SCSI bus conditions and miscellaneous features supported. This PS bit is not applicable to the MODE SELECT command.

SPF bit

The SPF bit is described in 5.2.2 and shall be set as shown in table 506.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 506.

PAGE LENGTH field

The PAGE LENGTH field is defined in SPC-6 and shall be set to the value defined in table 506.

NUMBER OF CYLINDERS field

The NUMBER OF CYLINDERS field defines the number of physical cylinders used for data storage. This may or may not include spare cylinders set aside for flaw reallocation. See individual drive's Product Manual, Volume 1, which specifies what the drive reports.

The drive uses some additional cylinders for storing drive parameters, defect lists, or for diagnostic purposes. These are not accessible by the user.

NUMBER OF HEADS field

The NUMBER OF HEADS field indicates the maximum number of data (read/write) heads on the drive.

STARTING CYLINDER—WRITE PRECOMP, STARTING CYLINDER—REDUCED WRITE CURRENT, DRIVE STEP RATE, and LANDING ZONE CYLINDER fields

Not applicable.

RPL (rotational position locking) field

Not supported.

ROTATIONAL OFFSET field

Not supported.

MEDIUM ROTATION RATE field

On MODE SENSE command, these bytes return drive nominal rotation rate in revolutions per minute for synchronous spindle operation. The bytes have no meaning for MODE SELECT.

See individual drive's Product Manual, MODE SENSE Data clause, for changeable values.

5.3.32 Seagate Specific Unit Attention parameters page (00h) for HDD

The Seagate Specific Unit Attention parameters page is the last page to be reported by the drive.

Table 507 Seagate Specific Unit Attention parameters page (00h) for HDD

Bit Byte	7	6	5	4	3	2	1	0	
0	PS	SPF (0b)	PAGE CODE (00h)						
1	PAGE LENGTH (0Ah)								
2	PM	Reserved	INQUIRY LENGTH	UNIT ATTENTION	Reserved	ROUND	STRICT	SCSI-2	
3	DAR	SELF SEEK	Reserved				SDTE	Reserved	
4	VJIT Disabled	Reserved			JIT3	JIT2	JIT1	JIT0	
5	Reserved								
6	Reserved								
7	Reserved								
8	Reserved								
9	Reserved								
10	(MSB)	COMMAND AGING LIMIT							
11							(LSB)		

PS (Parameter Savable) bit

A Parameter Savable (PS) bit of one indicates that the drive is capable of saving the page in a nonvolatile vendor-specific location (used only with MODE SENSE command).

SPF bit

The SPF bit is described in 5.2.2 and shall be set as shown in table 507.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 507.

PAGE LENGTH field

The PAGE LENGTH field specifies the length in bytes of the mode parameters that follow. If the initiator does not set this value to the value that is returned for the page by the MODE SENSE command, the drive shall terminate the command with CHECK CONDITION status. The sense key shall be set to ILLEGAL REQUEST with the additional sense code set to Invalid Field In Parameter List. See STRICT bit set to 0 description for exceptions.

PM (Performance Mode) bit

The PM (Performance Mode) bit is used to control the drive's cache management algorithm to allow best performance in different types of systems. It is the initiator's responsibility to determine which setting is best for that system.

- 1** A PM value of 1 indicates that the number of cache segments is fixed to the value set in mode page 08h.
- 0** A PM value of 0 indicates that the drive will optimize the number of segments depending on the command activity observed by the drive. The number of segments value (in mode page 08h) is ignored with the PM value is 0.

IL (INQUIRY Length) bit

- 1** When the INQUIRY Length (IL) bit is set to one, the standard INQUIRY data available to a host is limited to the 36 bytes required by the SCSI-2 specification.
- 0** When the IL bit is set to zero, 148 bytes of standard INQUIRY data are available. The Additional Length field in byte 4 of the INQUIRY data is updated to reflect the actual number of additional bytes available.

UNIT ATTENTION bit

- 1** When the UNIT ATTENTION bit is set to one, then UNIT ATTENTION is logged in sense only; no CHECK CONDITION status is presented following any reset.
- 0** When this bit is set to zero, then Check Condition is presented for all affected initiators following a reset until REQUEST SENSE is issued by each initiator (as per current operation).

ROUND bit

- 1** When the ROUND bit is set to one, the drive treats and reports rounded parameters as described in 2.3.
- 0** When ROUND is set to zero, the drive shall round the parameter and handle command completion reporting as if the parameter had not been rounded.

STRICT bit

- 1** When the STRICT bit is set to one, the drive checks for initiator attempts to change unchangeable parameters. If the drive detects an attempt, it rejects the command in the standard way, i.e., CHECK CONDITION status from drive, REQUEST SENSE from the initiator, and Illegal Request Sense key (5h) back from the drive.
- 0** When the STRICT bit is set to zero, the drive ignores the values of the unchangeable parameters in a MODE SELECT command. The drive does not reject the command trying to change unchangeable parameters or trying to send a mode page that is shorter than the supported length.

Caution: Utilization of this forgiving option by a SCSI initiator port that does not analyze the impact of the truncation could adversely affect COMMAND AGING LIMIT field.

SCSI-2 bit

- 1** When set to one, the SCSI-2 bit changes the following SCSI-3 features from their SCSI-3 definition to the SCSI-2 definition:
 - a) Control Mode Page (0Ah) Length from 0Ah to 06h; and
 - b) Caching Page (08h) Length from 12h to 0Ah.
- 0** When S2 is set to zero, all features remain as specified in other portions of this specification.

DAR (Deferred Auto Reallocation) bit

- 1** Deferred reallocation is enabled. When an unrecoverable read error occurs, the drive remembers the LBA of the error; when a subsequent write command occurs for that LBA and the AWRE bit in mode page 1 is enabled, then the LBA is reallocated before the write command is completed.
- 0** Deferred reallocation is disabled.

Self Seek bit

- 1** If the Self Seek bit is set to one, the drive will enter self seek mode for testing purposes. Such testing could include, but is not limited to, power dissipation and acoustics. While in this mode, the drive will accept SCSI commands and will process them in between the self seek operations, including a MODE SELECT to turn this bit back off. As such, this bit should be off for normal drive operations.
- 0** If this bit is set to zero, the drive will not self seek; normal operating mode.

SDTE (SMART Depopulation Trigger Enable) bit

- 1** When this bit is set to 1, the drive will Enable SMART based depopulation triggers.
- 0** When this bit is set to 0, the drive will Disable SMART based depopulation triggers.

VJIT Disabled bit

- 1** When this bit is set to 1, the drive will always use the fastest seek type (i.e., JIT 0). JIT bits 0:3 of byte 4 are ignored.
- 0** When this bit is set to 0, the drive will operate according to the settings of JIT bits 0:3.

JIT (Just in Time) bits

The four JIT (Just In Time) bits allow you to enable and disable certain seek speeds. JIT0 represents the fastest seek type used by the drive, JIT1 represents the second fastest, JIT2 represents the third fastest, and JIT3 represents the slowest seek type. You can use these bits to reduce acoustics by disabling the fastest seeks. This can also reduce power consumption (from seek activity). These JIT settings only affect user read and write operations. Background drive operations and user seek commands will always use the fastest seek type. When the bit is set to 1, the drive is allowed to use this seek type and any slower seek types in its seek speed algorithm. When the bit is set to 0, the drive is not allowed to use this seek type in its seek speed algorithm unless a faster seek type is selected. If all JIT bits are set to zero or if all bits are set to one, the drive can use any of the seek speeds.

COMMAND AGING LIMIT field

The COMMAND AGING LIMIT field specifies the maximum time, in milliseconds, that a command is allowed to languish in the command queue before it is marked as the next command to be processed.

5.3.33 Seagate Specific Unit Attention parameters page (00h) for SSD

The Seagate Specific Unit Attention parameters page is the last page to be reported by the drive.

Table 508 Seagate Specific Unit Attention parameters page (00h) for SSD

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (00h)					
1	PAGE LENGTH (0Ah)							
2	Reserved	Reserved	INQUIRY LENGTH	UNIT ATTENTION	Reserved	ROUND	STRICT	SCSI-2
3	Reserved							
4	Reserved							
5	Reserved							
6	Reserved							TTE
7	Reserved							
8	Reserved							
9	Reserved							
10	Reserved							
11	Reserved							

PS (Parameter Savable) bit

A Parameter Savable (PS) bit of one indicates that the drive is capable of saving the page in a nonvolatile vendor-specific location (used only with MODE SENSE command).

SPF bit

The SPF bit is described in 5.2.2 and shall be set as shown in table 508.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 508.

PAGE LENGTH field

The PAGE LENGTH field specifies the length in bytes of the mode parameters that follow. If the initiator does not set this value to the value that is returned for the page by the MODE SENSE command, the drive shall terminate the command with CHECK CONDITION status. The sense key shall be set to ILLEGAL REQUEST with the additional sense code set to Invalid Field In Parameter List. See STRICT bit set to 0 description for exceptions.

IL (INQUIRY Length) bit

- 1** When the INQUIRY Length (IL) bit is set to one, the standard INQUIRY data available to a host is limited to the 36 bytes required by the SCSI-2 specification.
- 0** When the IL bit is set to zero, 148 bytes of standard INQUIRY data are available. The Additional Length field in byte 4 of the INQUIRY data is updated to reflect the actual number of additional bytes available.

UNIT ATTENTION bit

- 1** When the UNIT ATTENTION bit is set to one, then UNIT ATTENTION is logged in sense only; no CHECK CONDITION status is presented following any reset.
- 0** When this bit is set to zero, then Check Condition is presented for all affected initiators following a reset until REQUEST SENSE is issued by each initiator (as per current operation).

ROUND bit

- 1** When the ROUND bit is set to one, the drive treats and reports rounded parameters as described in 2.3.
- 0** When ROUND is set to zero, the drive shall round the parameter and handle command completion reporting as if the parameter had not been rounded.

STRICT bit

- 1** When the STRICT bit is set to one, the drive checks for initiator attempts to change unchangeable parameters. If the drive detects an attempt, it rejects the command in the standard way, i.e., CHECK CONDITION status from drive, REQUEST SENSE from the initiator, and Illegal Request Sense key (5h) back from the drive.
- 0** When the STRICT bit is set to zero, the drive ignores the values of the unchangeable parameters in a MODE SELECT command. The drive does not reject the command trying to change unchangeable parameters or trying to send a mode page that is shorter than the supported length.

Caution: Utilization of this forgiving option by a SCSI initiator port that does not analyze the impact of the truncation could adversely affect data integrity.

SCSI-2 bit

- 1** When set to one, the SCSI-2 bit changes the following SCSI-3 features from their SCSI-3 definition to the SCSI-2 definition:
 - a) Control Mode Page (0Ah) Length from 0Ah to 06h; and
 - b) Caching Page (08h) Length from 12h to 0Ah.
- 0** When S2 is set to zero, all features remain as specified in other portions of this specification.

TTE (Thermal Throttle Enable) bit

- 1** If set to 1, drive activity is limited based on temperature.
- 0** If set to 0, drive activity is not limited-based on temperature.

5.3.34 Verify Error Recovery mode page (07h)

The Verify Error Recovery mode page (see table 509) specifies the error recovery parameters the device server shall use during verify medium operations (e.g., from VERIFY commands and the verify medium operations of the WRITE AND VERIFY commands). Verify medium operations do not trigger automatic read reassignment.

Table 509 Verify Error Recovery mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (0b)	PAGE CODE (07h)					
1	PAGE LENGTH (0Ah)							
2	Reserved			Obsolete		ERROR RECOVERY BITS		Obsolete
					PER	DTE		
3	VERIFY RETRY COUNT							
4	Obsolete							
5	Reserved formerly							
...	HEAD OFFSET COUNT (Byte 5), DATA STROBE OFFSET COUNT (Byte 6) and WRITE							
9	RETRY COUNT (Byte 8) Bytes 7 and 9 were Reserved							
10	(MSB)	VERIFY RECOVERY TIME LIMIT						
11								(LSB)

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5. The SPF bit, the PAGE CODE field, and the PAGE LENGTH field shall be set to the values shown in table 256 for the Verify Error Recovery mode page.

PER bit and DTE bit

The PER bit and the DTE bit (i.e., the error recovery bits) are defined in 5.3.23. The combinations of these bits are defined in table 481.

VERIFY RETRY COUNT field

The VERIFY RETRY COUNT field specifies the number of times that the device server shall attempt its recovery algorithm during a verify operation.

VERIFY RECOVERY TIME LIMIT field

The VERIFY RECOVERY TIME LIMIT field specifies in milliseconds the maximum time duration that the device server shall use error recovery procedures to recover data for an individual logical block during a verify operation. The device server may round this value as described in 2.3.

If both a verify retry count and a verify recovery time limit are specified, then the one that requires the least time for data error recovery actions shall have priority.

To disable all types of correction and retries, the application client should set:

- a) the PER bit to one;
- b) the DTE bit to one;
- c) the VERIFY RETRY COUNT field to 00h; and
- d) the VERIFY RECOVERY TIME LIMIT field to 0000h.

5.3.35 Zoned Block Device Control mode page

The Zoned Block Device Control mode page (see table 510) defines parameters that affect the operation of the zoned block device.

Table 510 Zoned Block Device Control mode page

Bit Byte	7	6	5	4	3	2	1	0
0	PS	SPF (1b)	PAGE CODE (0Ah)					
1	SUBPAGE CODE (0Fh)							
2	(MSB)	PAGE LENGTH (001Ch)						
3								(LSB)
4				Reserved				URSWRZ_M
5				Reserved				U-UA_CTL
6				Reserved				
...				Reserved				
31				Reserved				

PS bit, SPF bit, PAGE CODE field, SUBPAGE CODE field, and PAGE LENGTH field

The parameters saveable (PS) bit, the subpage format (SPF) bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field are defined in 5.3.5.

SPF bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field

The SPF bit, the PAGE CODE field, the SUBPAGE CODE field, and the PAGE LENGTH field shall be set to the values shown in (see table 510) for the Zoned Block Device Control mode page.

URSWRZ_M bit

An unrestricted read in sequential write required zone management (URSWRZ_M) bit set to zero specifies that the device server is not configured to support reading unwritten logical blocks or reads across zone boundaries in sequential write required zones. A URSWRZ_M bit set to one specifies that the device server is configured to support reading unwritten logical blocks and reads across zone boundaries in sequential write required zones. The processing of reads in sequential write required zones is described in ZBC-2.

U-UA_CTL bit

The unrestricted read in sequential write required zone unit attention control (U-UA_CTL) bit specifies the additional sense code to be used for any unit attention condition caused by a change in the URSWRZ bit (see 5.4.23). If the processing of a MODE SELECT command causes a change in the value of the URSWRZ_M bit, then the device server shall establish a unit attention condition for the SCSI initiator port (see SAM-6) associated with each I_T nexus, except the I_T nexus on which the MODE SELECT command was received with the additional sense code set to:

- a) MODE PARAMETERS CHANGED, if the U-UA_CTL bit is set to zero; or
- b) INQUIRY DATA HAS CHANGED, if the U-UA_CTL bit is set to one.

5.4 Vital product data parameters

5.4.1 Vital product data parameters overview and page codes

This subclause describes the vital product data (VPD) page structure and the VPD pages (see table 511) that are applicable to all SCSI devices. These VPD pages are returned by an INQUIRY command with the EVPD bit set to one (see 3.8) and contain vendor specific product information about a logical unit and SCSI target device. The vital product data may include vendor identification, product identification, unit serial numbers, device operating definitions, manufacturing data, field replaceable unit information, and other vendor specific information.

Table 511 Vital product data page codes

Page code	VPD Page Name	Reference
00h	Supported VPD Pages	5.4.21
01h - 7Fh	ASCII Information	5.4.2
80h	Unit Serial Number	5.4.22
83h	Device Identification	5.4.9
84h	Software Interface Identification	n/s
85h	Management Network Addresses	n/s
86h	Extended INQUIRY Data	5.4.10
87h	Mode Page Policy	5.4.14
88h	SCSI Ports	5.4.20
8Ah	Power Condition	5.4.15
8Bh	Device Constituents	n/s
8Ch	CFA Profile Information	n/s
8Dh	Power Consumption	5.4.16
90h	Protocol Specific Logical Unit Information	5.4.17
91h	Protocol Specific Port Information	5.4.18
92h	SCSI Feature Sets	5.4.19
B0h	Block Limits	5.4.5
B1h	Block Device Characteristics	5.4.3
B2h	Logical Block Provisioning	5.4.13
B3h	Referrals	n/s
B4h	Supported Block Lengths and Protection Types	n/s
B5h	Block Device Characteristics Extension	5.4.4
B6h	Zoned Block Device Characteristics	5.4.23
B7h	Block Limits Extension	5.4.6
B8h	Format Presets	n/s
C0h	Firmware Numbers page	5.4.11
C1h	Date Code page	5.4.7
C2h	Jumper Settings page	5.4.12
C3h	Device Behavior page	5.4.8

n/s = not supported

5.4.2 ASCII Information VPD page (01h - 7Fh)

The ASCII Information VPD page (see table 512) contains information for the field replaceable unit code returned in the sense data (see 2.4).

Table 512 ASCII Information VPD page

Bit Byte	7	6	5	4	3	2	1	0	
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE					
1	PAGE CODE (01h - 7Fh)								
2	Reserved								
3	PAGE LENGTH (N-3)								
4	ASCII LENGTH (M-4)								
5	(MSB)	ASCII INFORMATION						(LSB)	
...									
m									
m+1	Vendor specific information								
...									
n									

PERIPHERAL QUALIFIER and the PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field contains the same value as in the PAGE OR OPERATION CODE field of the INQUIRY CDB (see 3.8) and is associated with the FIELD REPLACEABLE UNIT CODE field returned in the sense data.

NOTE The FIELD REPLACEABLE UNIT CODE field in the sense data provides for 255 possible codes, while the PAGE CODE field provides for only 127 possible codes. For that reason it is not possible to return ASCII Information VPD pages for the upper code values.

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the following VPD page data. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

ASCII LENGTH field

The ASCII LENGTH field specifies the length in bytes of the ASCII INFORMATION field that follows. A value of zero in this field indicates that no ASCII information is available for the specified page code. The relationship between the ASCII LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

ASCII INFORMATION field

The ASCII INFORMATION field contains ASCII information concerning the field replaceable unit identified by the page code. The data in this field shall be formatted in one or more character string lines. Each line shall contain only graphic codes (i.e., code values 20h through 7Eh) and shall be terminated with a NULL (00h) character.

VENDOR SPECIFIC INFORMATION field

The contents of the vendor specific information field is not defined in this manual.

5.4.3 Block Device Characteristics VPD page (B1h)

The Block Device Characteristics VPD page (see table 513) contains parameters indicating characteristics of the logical unit.

Table 513 Block Device Characteristics VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B1h)							
2	(MSB)	PAGE LENGTH (003Ch)						(LSB)
3								
4	(MSB)	MEDIUM ROTATION RATE						(LSB)
5								
6	PRODUCT TYPE							
7	WABEREQ		WACEREQ		NOMINAL FORM FACTOR			
8	Reserved	MACT	ZONED		RBWZ	BOCS	FUAB	VBULS
9								
...	Reserved							
11								
12	(MSB)	DEPOPULATION TIME						(LSB)
...								
15								
16								
...	Reserved							
63								

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in SPC-6.

PAGE CODE and PAGE LENGTH fields

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6 and shall be set to the values shown in Table 513.

MEDIUM ROTATION RATE field

The MEDIUM ROTATION RATE field is defined in Table 514.

Table 514 Medium Rotation Rate field

Code	Definition
0000h	Medium rotation rate is not reported
0001h	Non-rotating medium (e.g., solid state)
0002h to 0400h	Reserved
0401h to FFFEh	Nominal medium rotation rate in revolutions per minute (e.g., 7 200 rpm = 1C20h, 10 000 rpm = 2710h, and 15 000 rpm = 3A98h)
FFFFh	Reserved

PRODUCT TYPE field

The PRODUCT TYPE field (see table 515) defines the product type of the storage device.

Table 515 Product Type field

Code	Definition
00h	Not indicated
01h	CFast™ (see CFast)
02h	CompactFlash® (see CF)
03h	Memory Stick™ (see MS)
04h	MultiMediaCard (see e-MMC)
05h	Secure Digital Card (see SD Card)
06h	XQD™ (see XQD)
07h	Universal Flash Storage (see UFS)
08h to EFh	Reserved
F0h to FFh	Vendor specific

WABEREQ field

If a write medium operation has not been performed on a logical block referenced by a mapped LBA since a sanitize block erase operation was performed, and no other error occurs during the processing of a read command specifying that LBA, then the write after block erase required (WABEREQ) field indicates the device server behavior (see table 516).

Table 516 WABEREQ field

Code	Definition
00b	Not specified
01b	The device server completes the read command specifying that LBA with GOOD status and any data transferred to the Data-In Buffer is indeterminate.
10b	The device server terminates the read command specifying that LBA with CHECK CONDITION status with sense key set to MEDIUM ERROR and the additional sense code set to an appropriate value other than WRITE AFTER SANITIZE REQUIRED (e.g., ID CRC OR ECC ERROR).
11b	The device server terminates the read command specifying that LBA with CHECK CONDITION status with sense key set to MEDIUM ERROR and the additional sense code set to WRITE AFTER SANITIZE REQUIRED.

WACEREQ field

If a write medium operation has not been performed on a logical block referenced by a mapped LBA since a sanitize cryptographic erase operation was performed, and no other error occurs during the processing of a read command specifying that LBA, then the write after cryptographic erase required (WACEREQ) field indicates the device server behavior (see table 517).

Table 517 WACEREQ field

Code	Definition
00b	Not specified
01b	The device server completes the read command specifying that LBA with GOOD status and any data transferred to the Data-In Buffer is indeterminate.
10b	The device server terminates the read command specifying that LBA with CHECK CONDITION status with sense key set to MEDIUM ERROR and the additional sense code set to an appropriate value other than WRITE AFTER SANITIZE REQUIRED (e.g., ID CRC OR ECC ERROR).
11b	The device server terminates the read command specifying that LBA with CHECK CONDITION status with sense key set to MEDIUM ERROR and the additional sense code set to WRITE AFTER SANITIZE REQUIRED.

NOMINAL FORM FACTOR field

The NOMINAL FORM FACTOR field indicates the nominal form factor of the device containing the logical unit and is defined in Table 518.

Table 518 Nominal Form Factor Field

Code	Definition
0h	Nominal form factor is not reported
1h	5.25 inch
2h	3.5 inch
3h	2.5 inch
4h	1.8 inch
5h	Less than 1.8 inch
All others	Reserved

MACT bit

A multiple actuator (MACT) bit set to:

- 1** Indicates that the device server is contained in a SCSI target device with multiple actuators.
- 0** Indicates that the device server does not report whether it is contained in a SCSI target device with multiple actuators.

ZONED field

The ZONED field indicates the type of zoned block capabilities implemented by the device server as defined in table 519.

Table 519 ZONED field

Code	Definition
00b	Not reported
01b	Device server implements the host aware zoned block device capabilities defined in ZBC-2
10b	Device server implements device managed zoned block device capabilities
11b	Reserved

RBWZ bit

A reassign blocks write zero (RBWZ) bit set to one indicates that during the processing of a REASSIGN BLOCKS command that does not recover logical block data, the device server writes zeros as described in 3.30.1. A RBWZ bit set to zero indicates that during the processing of a REASSIGN BLOCKS command that does not recover the logical block data, the device server writes vendor specific data as described in 3.30.1.

BOCS bit

- 1** A BOCS bit set to one indicates that Background Operation Control is supported as described in 5.3.8
- 0** A BOCS bit set to zero indicates that Background Operation Control is not supported.

FUAB bit

- 1** A FUAB bit set to one indicates that the device server interprets the SYNCHRONIZE CACHE command and the FUA bit in read commands and write commands in compliance with this standard.
- 0** A FUAB bit set to zero indicates that the device server interprets the SYNCHRONIZE CACHE command and the FUA bit in read commands and write commands in compliance with SBC-5.

VBULS bit

- 1** A VBULS bit set to one indicates that the device server supports unmapped LBAs while processing VERIFY commands (see 3.59, 3.60, 3.61, and 3.62) and WRITE AND VERIFY commands (see 3.68, 3.69, 3.70, and 3.71) with the BYTCHK field set to 01b.
- 0** A VBULS bit set to zero indicates that the device server does not support unmapped LBAs while processing VERIFY commands and WRITE AND VERIFY commands with the BYTCHK field set to 01b.

DEPOPULATION TIME field

The DEPOPULATION TIME field indicates the maximum time in seconds for the device server to perform the operations associated with a REMOVE ELEMENT AND TRUNCATE command.

5.4.4 Block Device Characteristics Extension VPD page (B5h)

The Block Device Characteristics Extension VPD page (see table 520) contains parameters indicating characteristics of the logical unit.

Table 520 Block Device Characteristics Extension VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B5h)							
2	(MSB)	PAGE LENGTH (007Ch)						(LSB)
3	Reserved							
4	UTILIZATION TYPE							
5	UTILIZATION UNITS							
6	UTILIZATION INTERVAL							
8	(MSB)	UTILIZATION B						(LSB)
...								
11								
12	(MSB)	UTILIZATION A						(LSB)
...								
15								
16	Reserved							
...								
127								

PERIPHERAL QUALIFIER field

The PERIPHERAL QUALIFIER field is defined in SPC-6.

PAGE CODE field, PERIPHERAL DEVICE TYPE field, and PAGE LENGTH field

The PAGE CODE field, PERIPHERAL DEVICE TYPE field, and PAGE LENGTH field are defined in SPC-6 and shall be set to the values shown in table 520 for the Block Device Characteristics Extension VPD page.

UTILIZATION TYPE field

The UTILIZATION TYPE field (see table 521) indicates the designed utilization characteristics for the direct access block device based on the contents of the UTILIZATION A field and the UTILIZATION B field evaluated using the units indicated by the UTILIZATION UNITS field over the time interval indicated by the UTILIZATION INTERVAL field.

Table 521 UTILIZATION TYPE field

Code	Definition
01h	Combined writes and reads: the UTILIZATION A field contains designed number of host requested bytes transferred by write operations and host requested bytes transferred by read operations. The UTILIZATION B field is reserved.
02h	Writes only: the UTILIZATION A field contains designed number of host requested bytes transferred by write operations. The UTILIZATION B field is reserved.
03h	Separate writes and reads: the UTILIZATION A field contains designed number of host requested bytes transferred by write operations. The UTILIZATION B field contains designed number of host requested bytes transferred by read operations.
All others	Reserved

UTILIZATION UNITS field

The UTILIZATION UNITS field (see table 522) indicates the units of measure for the values, if any, in the UTILIZATION A field and the UTILIZATION B field.

Table 522 UTILIZATION UNITS Field

Code	Definition
02h	megabytes
03h	gigabytes
04h	terabytes
05h	petabytes
06h	exabytes
All others	Reserved

UTILIZATION INTERVAL field

The UTILIZATION INTERVAL field (see table 523) indicates a nominal calendar time reference interval over which the values, if any, in the UTILIZATION A field and the UTILIZATION B field may be applied.

Table 523 UTILIZATION INTERVAL Field

Code	Definition
0Ah	per day
0Eh	per year
All others	Reserved

UTILIZATION A field and the UTILIZATION B field

The UTILIZATION A field and the UTILIZATION B field indicate the designed utilization characteristics for the direct access block device as:

- a) defined by the utilization type field;
- b) expressed in the units defined by the utilization units field; and
- c) over the time interval defined by the utilization interval field.

5.4.5 Block Limits VPD page (B0h)

The Block Limits VPD page (see table 524) provides the application client with the means to obtain certain operating parameters of the logical unit.

Table 524 Block Limits VPD page (Sheet 1 of 2)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B0h)							
2	(MSB)	PAGE LENGTH (003Ch)						(LSB)
3	Reserved							WSNZ
5	MAXIMUM COMPARE AND WRITE LENGTH							
6	(MSB)	OPTIMAL TRANSFER LENGTH GRANULARITY						(LSB)
8	(MSB)	MAXIMUM TRANSFER LENGTH						(LSB)
11	OPTIMAL TRANSFER LENGTH							(LSB)
12	(MSB)	MAXIMUM TRANSFER LENGTH						(LSB)
15	OPTIMAL TRANSFER LENGTH							(LSB)
16	(MSB)	MAXIMUM PREFETCH LENGTH						(LSB)
19	MAXIMUM PREFETCH LENGTH							(LSB)
20	(MSB)	MAXIMUM UNMAP LBA COUNT						(LSB)
23	MAXIMUM UNMAP LBA COUNT							(LSB)
24	(MSB)	MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT						(LSB)
27	MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT							(LSB)
28	(MSB)	OPTIMAL UNMAP GRANULARITY						(LSB)
31	OPTIMAL UNMAP GRANULARITY							(LSB)
32	UGAVALID	(MSB)	UNMAP GRANULARITY ALIGNMENT					(LSB)
35	UNMAP GRANULARITY ALIGNMENT							(LSB)
36	(MSB)	MAXIMUM WRITE SAME LENGTH						(LSB)
43	MAXIMUM WRITE SAME LENGTH							(LSB)
44	(MSB)	MAXIMUM ATOMIC TRANSFER LENGTH						(LSB)
47	MAXIMUM ATOMIC TRANSFER LENGTH							(LSB)
48	(MSB)	ATOMIC ALIGNMENT						(LSB)
51	ATOMIC ALIGNMENT							(LSB)
52	(MSB)	ATOMIC TRANSFER LENGTH GRANULARITY						(LSB)
55	ATOMIC TRANSFER LENGTH GRANULARITY							(LSB)

Table 524 Block Limits VPD page (Sheet 2 of 2)

Bit Byte	7	6	5	4	3	2	1	0	
56	(MSB)								
...	MAXIMUM ATOMIC TRANSFER LENGTH WITH ATOMIC BOUNDARY								
59								(LSB)	
60	(MSB)								
...	MAXIMUM ATOMIC BOUNDARY SIZE								
63								(LSB)	

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in SPC-6.

PAGE CODE field and PAGE LENGTH field

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6 and shall be set to the values shown in table 524 for the Block Limits VPD page.

WSNZ bit

- 1** A write same non-zero (WSNZ) bit set to one indicates that the device server does not support a value of zero in the NUMBER OF LOGICAL BLOCKS field in the WRITE SAME command CDBs (see 3.77, 3.78, and 3.79).
- 0** A WSNZ bit set to zero indicates that the device server may or may not support a value of zero in the NUMBER OF LOGICAL BLOCKS field of the WRITE SAME commands.

MAXIMUM COMPARE AND WRITE LENGTH field

A MAXIMUM COMPARE AND WRITE LENGTH field set to a non-zero value indicates the maximum value that the device server accepts in the NUMBER OF LOGICAL BLOCKS field in the COMPARE AND WRITE command (see SBC-5). A MAXIMUM COMPARE AND WRITE LENGTH field set to zero indicates that the device server does not support the COMPARE AND WRITE command. The device server shall set the MAXIMUM COMPARE AND WRITE LENGTH field to a value less than or equal to the value in the MAXIMUM TRANSFER LENGTH field.

OPTIMAL TRANSFER LENGTH GRANULARITY field

The OPTIMAL TRANSFER LENGTH GRANULARITY field set to a non-zero value indicates the optimal transfer length granularity size in logical blocks for a single command shown in the command column of table 525. If a device server receives one of these commands with a transfer size that is not equal to a multiple of this value, then the device server may incur significant delays in processing the command. An OPTIMAL TRANSFER LENGTH GRANULARITY field set to 0000_0000h indicates that the device server does not report optimal transfer length granularity.

Table 525 Transfer limits for commands

Command	Field that specifies the transfer size	Block Limits VPD page field(s) that indicate maximum limits	Additional sense code if the value in the specified field exceeds the maximum limit
COMPARE AND WRITE	CDB NUMBER OF LOGICAL BLOCKS field	MAXIMUM COMPARE AND WRITE LENGTH field	INVALID IN FIELD IN CDB
ORWRITE (16) / (32)	CDB TRANSFER LENGTH field	MAXIMUM TRANSFER LENGTH field	
PREFETCH (10) / (16)	CDB PREFETCH LENGTH field	MAXIMUM PREFETCH LENGTH field	
READ (10) / (12) / (16) / (32)	CDB TRANSFER LENGTH field	MAXIMUM TRANSFER LENGTH field	
VERIFY (10) / (12) / (16) / (32)	CDB VERIFICATION LENGTH field		
WRITE (10) / (12) / (16) / (32)	CDB TRANSFER LENGTH field		
READ (10) / (12) / (16) / (32)			
XDWRITEREAD (10) / (32)			
XPWRITE (10) / (32)			
Any individual block device range descriptor in a POPULATE TOKEN command (see SBC-5)	Block device range descriptor NUMBER OF LOGICAL BLOCKS field	MAXIMUM TRANSFER LENGTH field	
Any individual block device range descriptor in a WRITE USING TOKEN command (see SBC-5)			

MAXIMUM TRANSFER LENGTH field

The MAXIMUM TRANSFER LENGTH field set to a non-zero value indicates the maximum transfer length in logical blocks that the device server accepts for a single command shown in table 524. If a device server receives one of these commands with a transfer size greater than this value, then the device server shall terminate the command with CHECK CONDITION status with the sense key set to ILLEGAL REQUEST and the additional sense code set to the value shown in table 525. A MAXIMUM TRANSFER LENGTH field set to 0000_0000h indicates that the device server does not report a limit on the transfer length.

OPTIMAL TRANSFER LENGTH field

The OPTIMAL TRANSFER LENGTH field set to a non-zero value indicates the optimal transfer size in logical blocks for a single command shown in table 524. If a device server receives one of these commands with a transfer size greater than this value, then the device server may incur significant delays in processing the command. An OPTIMAL TRANSFER LENGTH field set to 0000_0000h indicates that the device server does not report an optimal transfer size.

MAXIMUM PREFETCH LENGTH field

The MAXIMUM PREFETCH LENGTH field indicates the maximum prefetch length in logical blocks that the device server accepts for a single PRE-FETCH command. The device server should set the MAXIMUM PREFETCH LENGTH field to less than or equal to the MAXIMUM TRANSFER LENGTH field.

MAXIMUM UNMAP LBA COUNT field

The MAXIMUM UNMAP LBA COUNT field set to a non-zero value indicates the maximum number of LBAs that may be unmapped by an UNMAP command (see 3.58). If the number of LBAs that may be unmapped by an UNMAP command is constrained only by the amount of data that may be contained in the UNMAP parameter list (see 3.58.2), then the device server shall set the MAXIMUM UNMAP LBA COUNT field to FFFF_FFFFh. If the device server implements the UNMAP command, then the value in this field shall be greater than or equal to one. A MAXIMUM UNMAP LBA COUNT field set to 0000_0000h indicates that the device server does not implement the UNMAP command.

MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field

The MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field set to a non-zero value indicates the maximum number of UNMAP block descriptors (see 3.58.2) that shall be contained in the parameter data transferred to the device server for an UNMAP command (see 3.58). If there is no limit on the number of UNMAP block descriptors contained in the parameter data, then the device server shall set the MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field to FFFF_FFFFh. If the device server implements the UNMAP command, then the value in the MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field shall be greater than or equal to one. A MAXIMUM UNMAP BLOCK DESCRIPTOR COUNT field set to 0000_0000h indicates that the device server does not implement the UNMAP command.

OPTIMAL UNMAP GRANULARITY field

The OPTIMAL UNMAP GRANULARITY field set to a non-zero value indicates the optimal granularity in logical blocks for unmap requests (e.g., an UNMAP command or a WRITE SAME (16) command with the UNMAP bit set to one). An unmap request with a number of logical blocks that is not a multiple of this value may result in unmap operations on fewer LBAs than requested. An OPTIMAL UNMAP GRANULARITY field set to 0000_0000h indicates that the device server does not report an optimal unmap granularity.

UGVALID bit

- 1** An UGVALID (unmap granularity alignment valid) bit set to one indicates that the UNMAP GRANULARITY ALIGNMENT field is valid.
- 0** A UGINVALID bit set to zero indicates that the UNMAP GRANULARITY ALIGNMENT field is not valid.

UNMAP GRANULARITY ALIGNMENT field

The UNMAP GRANULARITY ALIGNMENT field indicates the LBA of the first logical block to which the OPTIMAL UNMAP GRANULARITY field applies. The unmap granularity alignment is used to calculate an optimal unmap request starting LBA as follows:

$$\text{optimal unmap request starting LBA} = (n \times \text{optimal unmap granularity}) + \text{unmap granularity alignment}$$

where:

- n is zero or any positive integer value;
- optimal unmap granularity is the value in the OPTIMAL UNMAP GRANULARITY field; and
- unmap granularity alignment is the value in the UNMAP GRANULARITY ALIGNMENT field.

An unmap request with a starting LBA that is not optimal may result in unmap operations on fewer LBAs than requested.

MAXIMUM WRITE SAME LENGTH field

A MAXIMUM WRITE SAME LENGTH field set to a non-zero value indicates the maximum value that the device server accepts in the NUMBER OF LOGICAL BLOCKS field for a WRITE SAME command. A MAXIMUM WRITE SAME LENGTH field set to zero indicates that the device server does not report a limit on the number of logical blocks that may be requested for a single WRITE SAME command.

MAXIMUM ATOMIC TRANSFER LENGTH field

If the ATOMIC BOUNDARY field in the CDB (see 3.72 and 3.73) is set to zero, then a MAXIMUM ATOMIC TRANSFER LENGTH field set to a non-zero value indicates the maximum atomic transfer length in logical blocks that the device server supports for a single atomic write command (see 3.72 and 3.73). A MAXIMUM ATOMIC TRANSFER LENGTH field set to 0000_0000h indicates that the device server does not indicate a maximum atomic transfer length. The maximum atomic transfer length indicated by the MAXIMUM ATOMIC TRANSFER LENGTH field shall be less than or equal to the maximum transfer length indicated by the MAXIMUM TRANSFER LENGTH field. The maximum atomic transfer length indicated by the MAXIMUM ATOMIC TRANSFER LENGTH field shall be a multiple of the value in the ATOMIC TRANSFER LENGTH GRANULARITY field. If the ATOMIC BOUNDARY field in the CDB is set to a non-zero value, then the MAXIMUM ATOMIC TRANSFER LENGTH field is ignored.

ATOMIC ALIGNMENT field

The ATOMIC ALIGNMENT field indicates the required alignment of the starting LBA in an atomic write command. If the ATOMIC ALIGNMENT field is set to 0000_0000h, then there is no alignment requirement for atomic write commands.

If the ATOMIC ALIGNMENT field is non-zero, then the starting LBA of an atomic write request shall meet the following:

$$\text{atomic request starting LBA} = n \times \text{atomic alignment}$$

where:

n is zero or any positive integer value; and
atomic alignment is the value in the ATOMIC ALIGNMENT field,

ATOMIC TRANSFER LENGTH GRANULARITY field

The ATOMIC TRANSFER LENGTH GRANULARITY field indicates the minimum transfer length for a WRITE ATOMIC command. Atomic write operations are required to have a transfer length that is a multiple of the atomic transfer length granularity. An ATOMIC TRANSFER LENGTH GRANULARITY field set to 0000_0000h indicates that there is no atomic transfer length granularity requirement.

ATOMIC BOUNDARY field

If the ATOMIC BOUNDARY field in the CDB (see 3.72 and 3.73) is set to a non-zero value, then a MAXIMUM ATOMIC TRANSFER LENGTH WITH ATOMIC BOUNDARY field set to a non-zero value indicates the maximum transfer length in logical blocks that the device server supports for a single atomic write command (see SBC-5). A MAXIMUM ATOMIC TRANSFER LENGTH WITH ATOMIC BOUNDARY field set to 0000_0000h indicates that the device server does not indicate a maximum atomic transfer length with atomic boundary. The maximum atomic transfer length with atomic boundary indicated by the MAXIMUM ATOMIC TRANSFER LENGTH WITH ATOMIC BOUNDARY field shall be less than or equal to the maximum transfer length indicated by the MAXIMUM TRANSFER LENGTH field. The maximum atomic transfer length with atomic boundary indicated by the MAXIMUM ATOMIC TRANSFER LENGTH WITH BOUNDARY field shall be a multiple of the value in the ATOMIC TRANSFER LENGTH GRANULARITY field. If the ATOMIC BOUNDARY field in the CDB is set to zero, then the MAXIMUM ATOMIC TRANSFER LENGTH WITH ATOMIC BOUNDARY field is ignored.

MAXIMUM ATOMIC BOUNDARY SIZE field

A MAXIMUM ATOMIC BOUNDARY SIZE field set to a non-zero value indicates that the device server supports atomic write commands performing more than one atomic operation. The maximum atomic boundary size indicates the maximum number of logical blocks on which the device server is able to perform atomic operations (see SBC-5). A MAXIMUM ATOMIC BOUNDARY SIZE field set to 0000h indicates that the device server does not support atomic write commands performing more than one atomic operation. The MAXIMUM ATOMIC BOUNDARY SIZE field shall be a multiple of the value in the ATOMIC TRANSFER LENGTH GRANULARITY field.

5.4.6 Block Limits Extension VPD page (B7h)

The Block Limits Extension VPD page (see table 526) provides the application client with the means to obtain certain operating parameters of the logical unit.

Table 526 Block Limits Extension VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B7h)							
2	(MSB)	PAGE LENGTH (n-4)						(LSB)
3	Reserved							
4	Reserved							
5	Reserved							
6	(MSB)	MAXIMUM NUMBER OF STREAMS						(LSB)
7	Reserved							
8	(MSB)	OPTIMAL STREAM WRITE SIZE						(LSB)
9	Reserved							
10	(MSB)	STREAM GRANULARITY SIZE						(LSB)
...	Reserved							
13	Reserved							
14	Reserved							
...	Reserved							
n	Reserved							

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE field are defined in SPC-6.

PAGE CODE field and PAGE LENGTH field

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6 and shall be set to the values shown in table 526 for the Block Limits Extension VPD page.

MAXIMUM NUMBER OF STREAMS field

The MAXIMUM NUMBER OF STREAMS field indicates the maximum number of streams that the device server supports and the maximum value for the stream identifier plus one. A maximum number of streams field set to 0000h indicates that the device server does not support Stream Control.

OPTIMAL STREAM WRITE SIZE field

The OPTIMAL STREAM WRITE SIZE field indicates the alignment and size of the optimal stream write as a number of logical blocks. The optimal stream write size is the same for all streams in the device server.

STREAM GRANULARITY SIZE field

The STREAM GRANULARITY SIZE field indicates the stream granularity size in number of optimal stream write size blocks as described in 3.54.

5.4.7 Date Code page (C1h)

Table 527 ETF Log Date Code page (C1h)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER		PERIPHERAL DEVICE TYPE					
1	PAGE CODE (C1h)							
2	00h							
3	PAGE LENGTH (10h)							
4	(MSB)							
...	ETF LOG DATE IN ASCII							
11	(LSB)							
12	(MSB)							
...	COMPILE DATE CODE							
19	(LSB)							
20	LAST SPINDOWN POWER CYCLE COUNT							
21								
22	(MSB)							
...	LAST SPINDOWN TIMESTAMP							
27	(LSB)							

PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table 527.

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the following VPD page data. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

ETF Log field

The ETF Log date code field contains ASCII data. The data is stored in the format MMDDYYYY. Leading ASCII zero characters are added to single-digit months or days.

COMPILE DATE CODE field

The COMPILE DATE CODE field contains 8 ASCII bytes of data for a date of the form MMDDYYYY.

LAST SPINDOWN POWER CYCLE COUNT field

The LAST SPINDOWN POWER CYCLE COUNT field contains the power cycle count saved at the last spin down.

LAST SPINDOWN TIMESTAMP field

The LAST SPINDOWN TIMESTAMP field contains the timestamp saved at the last spin down.

5.4.8 Device Behavior page (C3h)

The Device Behavior page (see table) will be used by the regression tests to determine what behavior should be expected from a particular firmware package.

Table 528 Device Behavior page (C3h)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (C3h)							
2	Reserved							
3	PAGE LENGTH							
4	VERSION NUMBER							
5	BEHAVIOR CODE							
6	BEHAVIOR CODE VERSION NUMBER							
7 ... 22	ASCII FAMILY NUMBER (16 bytes)							
23	NUMBER OF INTERLEAVES							
24	DEFAULT NUMBER OF CACHE SEGMENTS							
25+	Feature Flags and Additional Byte Fields will go here but are undefined at this time.							

PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table 528.

PAGE LENGTH field

PAGE LENGTH defines the length of the Device Behavior information in bytes. If the ALLOCATION LENGTH is too small to transfer all of the page, the page length shall not be adjusted to reflect the truncation.

VERSION NUMBER field

The VERSION NUMBER is a one-byte short form notation for the 24-byte assignment in the Firmware Numbers page. Version Numbers are registered by Engineering services.

BEHAVIOR CODE and BEHAVIOR CODE VERSION NUMBER fields

The BEHAVIOR CODE and BEHAVIOR CODE VERSION NUMBER are jointly assigned by the Firmware Engineering Managers of all SCSI design locations.

ASCII FAMILY NUMBER field

The ASCII FAMILY NUMBER field contains the drive model number. The data is left-aligned within this field.

NUMBER OF INTERLEAVES field

The NUMBER OF INTERLEAVES field indicates the number of data interleaves used by the ECC correction algorithm.

DEFAULT NUMBER OF CACHE SEGMENTS field

The DEFAULT NUMBER OF CACHE SEGMENTS field gives the number of segments into which the host requests the drive divide the cache.

5.4.9 Device Identification VPD page (83h)

The Device Identification VPD page (see table) provides the means to retrieve zero or more identification descriptors applying to the logical unit. Logical units may have more than one identification descriptor (e.g., if several types or associations of identifier are supported). Device identifiers consist of one or more of the following:

- Logical unit names;
- SCSI target port identifiers;
- SCSI target port names;
- SCSI target device names;
- Relative target port identifiers;
- SCSI target port group number; or
- Logical unit group number.

Identification descriptors shall be assigned to the peripheral device (e.g., a disk drive) and not to the currently mounted media, in the case of removable media devices. Operating systems are expected to use the identification descriptors during system configuration activities to determine whether alternate paths exist for the same peripheral device.

Table 529 Device Identification VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (83h)							
2	MSB	PAGE LENGTH (n-3)						LSB
3								
Identification descriptor list								
4	Identification Descriptor (first) (see table 530)							
...								
...	Identification Descriptor (last) (see table 530)							
n								

PERIPHERAL QUALIFIER and the PERIPHERAL DEVICE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table .

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the following VPD page data. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

Identification Descriptor field

Each IDENTIFICATION DESCRIPTOR (see table 530) contains information identifying the logical unit, physical device, or access path used by the command and returned parameter data.

Table 530 Identification Descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	PROTOCOL IDENTIFIER				CODE SET			
1	PIV	Reserved	ASSOCIATION		IDENTIFIER TYPE			
2	Reserved							
3	IDENTIFIER LENGTH (n – 3)							
4	IDENTIFIER							
...								
n								

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field may indicate the SCSI transport protocol to which identification descriptor applies. If the ASSOCIATION field contains a value other than 1h or 2h or the PIV bit is set to zero, then the PROTOCOL IDENTIFIER field should be ignored. If the ASSOCIATION field contains a value of 1h or 2h and the PIV bit is set to one, then the PROTOCOL IDENTIFIER field shall contain one of the values shown in table 531 to indicate the SCSI transport protocol to which identification descriptor applies.

CODE SET field

The CODE SET field specifies the code set used for the identifier field, as described in Table . This field is intended to be an aid to software that displays the identifier field.

Value	Description
0h	Reserved
1h	The IDENTIFIER field shall contain binary values
2h	The IDENTIFIER field shall contain ASCII graphic codes (i.e., code values 20h through 7Eh)
3h - Fh	Reserved

PIV (Protocol Identifier Valid) bit

- 0** A protocol identifier valid (PIV) bit of zero indicates the PROTOCOL IDENTIFIER field should be ignored. If the ASSOCIATION field contains a value of 1h or 2h then a PIV bit set to one indicates the PROTOCOL IDENTIFIER field contains a valid protocol identifier selected from the values shown in table 531. If the ASSOCIATION field contains a value other than 1h or 2h then the PIV bit should be ignored.

Table 531 PROTOCOL IDENTIFIER values

Protocol Identifier	Description	Protocol Standard
0h	Fibre Channel	FCP-5
1h	Obsolete	
2h	SSA	SSA-S3P
3h	IEEE 1394	SBP-2
4h	Remote Direct Memory Access (RDMA)	SRP
5h	Internet SCSI	iSCSI
6h	SAS Serial SCSI Protocol	SAS
7h - Fh	Reserved	

ASSOCIATION field

The ASSOCIATION field indicates the entity that the Identification descriptor describes. If a physical or logical device returns an Identification descriptor with the ASSOCIATION field set to 0h, it shall return the same descriptor when it is accessed through any other path.

The ASSOCIATION field specifies the entity with which the Identifier field is associated, as described in Table 532.

Table 532 ASSOCIATION field

Value	Description
0h	The IDENTIFIER field is associated with the addressed physical or logical device
1h	The IDENTIFIER field is associated with the port that received the request
2h	The IDENTIFIER field is associated with the SCSI target device that contains the addressed logical unit.
3h	Reserved

IDENTIFIER TYPE field

The IDENTIFIER TYPE field specifies the format and assignment authority for the identifier, as described in tables 533 and 534.

Table 533 IDENTIFIER Type field

Value	Description
0h	No assignment authority was used and consequently there is no guarantee that the identifier is globally unique (i.e., the identifier is vendor specific).
1h	The first 8 bytes of the IDENTIFIER field are a Vendor ID. The organization associated with the Vendor ID is responsible for ensuring that the remainder of the identifier field is unique. One recommended method of constructing the remainder of the identifier field is to concatenate the product identification field from the standard INQUIRY data field and the product serial number field from the unit serial number page.
2h	The IDENTIFIER field contains a Canonical form IEEE Extended Unique Identifier, 64-bit (EUI-64). In this case, the identifier length field shall be set to 8. Note that the IEEE guide-lines for EUI-64 specify a method for unambiguously encapsulating an IEEE 48-bit identifier within an EUI-64.
3h	The IDENTIFIER field contains an FC-PH, FC-PH3 or FC-FS Name_Identifier. Any FC-PH, FC-PH3 or FC-FS identifier may be used, including one of the four based on a Canonical form IEEE company_id.
4h	If the ASSOCIATION field contains 1h, the Identifier value contains a four-byte binary number identifying the port relative to other ports in the device using the values shown Table 532. The CODE SET field shall be set to 1h and the IDENTIFIER LENGTH field shall be set to 4h. If the ASSOCIATION field does not contain 1h, use of this identifier type is reserved.
5h	If the Association value is 1h, the Identifier value contains a four-byte binary number identifying the port relative to other ports in the device using the values shown Table 532. The CODE SET field shall be set to 1h and the IDENTIFIER LENGTH field shall be set to 4h. If the ASSOCIATION field does not contain 1h, use of this identifier type is reserved.
6h	If the ASSOCIATION value is 0h, the IDENTIFIER value contains a four-byte binary number identifying the port relative to other ports in the device using the values shown Table 532. The CODE SET field shall be set to 1h and the IDENTIFIER LENGTH field shall be set to 4h. If the ASSOCIATION field does not contain 0h, use of this identifier type is reserved.
7h	The MD5 logical unit identifier shall not be used if a logical unit provides unique identification using identifier types 2h or 3h. A bridge device may return a MD5 logical unit identifier type for that logical unit that does not support the Device Identification VPD page.
8h - Fh	Reserved.

IDENTIFIER LENGTH field

The IDENTIFIER LENGTH field specifies the length in bytes of the IDENTIFIER field. If the ALLOCATION LENGTH field of the command descriptor block is too small to transfer all of the identifier, the identifier length shall not be adjusted to reflect the truncation.

IDENTIFIER field

The IDENTIFIER field contains the identifier as described by the Association, Identifier Type, CODE SET, and IDENTIFIER LENGTH fields. The example described in this clause and shown in Table 534 is not a normative part of this manual. This example of a complete device identification VPD page assumes that the product is a direct-access device with an T10 Vendor ID of "XYZ_Corp," a product identification of "Super Turbo Disk," and a product serial number of "2034589345." Furthermore, it is assumed that the manufacturer has been assigned a 24-bit IEEE company_id of 01ABCDh by the IEEE Registration Authority Committee and that the manufacture has assigned a 24-bit extension_identifier of 234567h to this logical unit. The combined 48-bit identifier is reported in the 64-bit format as defined by the IEEE 64-bit Global Identifier (EUI-64) standard. The data returned in the device identification VPD page for this logical unit is shown in Table 534.

Table 534 Device Identification page example

Bytes	Hexadecimal values	ASCII values
00–15	00 83 00 32 02 01 00 22 58 59 5A 5F 43 6F 72 70	...2...XYZ_Corp [5]
16–31	53 75 70 65 72 20 54 75 72 62 6F 20 44 69 73 6B	Super Turbo Disk
32–47	32 30 33 34 35 38 39 33 34 35 01 02 00 08 01 AB	2034589345.....
48–53	CD FF FF 23 45 67
Notes.		
<ul style="list-style-type: none"> a) Non-printing ASCII characters are shown as "...". b) Byte 00 is the beginning of the VPD page (see table 511). c) Byte 04 is the beginning of the Identification descriptor for the Vendor ID based identifier (Identifier type 1 see Table 533). d) Byte 42 is the beginning of the Identification Descriptor for the EUI-64 identifier (Identifier type 2, see Table 533). e) For Seagate devices, this will say "Seagate." 		

5.4.10 Extended INQUIRY Data VPD page (86h)

The Extended INQUIRY Data VPD page (see table 535) provides the application client with a means to obtain information about the logical unit.

Table 535 Extended INQUIRY Data VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (86h)							
2	(MSB)	PAGE LENGTH (3Ch)						(LSB)
3								
4	ACTIVATE MICROCODE	SPT			GRD_CHK	APP_CHK	REF_CHK	
5	Reserved	UASK_SUP	GROUP_SUP	PRIOR_SUP	HEADSUP	ORDSUP	SIMPSUP	
6	Reserved			WU_SUP	Obsolete	NV_SUP	V_SUP	
7	Reserved	NO_PI_CHK	P_I_I_SUP	Reserved			LUICLR = 1	
8	LU COLLECTION TYPE		R_SUP	RTD_SUP	Reserved	HSSRELEF	Obsolete	
9	Reserved			MULTI I_T NEXUS MICROCODE DOWNLOAD				
10	(MSB)	EXTENDED SELF-TEST COMPLETION MINUTES						(LSB)
11								
12	POA_SUP	HRA_SUP	VSA_SUP	DMS_VALID	Reserved			
13	MAXIMUM SUPPORTED SENSE DATA LENGTH							
14	Bind support byte							
	IBS	IAS	Reserved			SAC	NRD1	NRD0
15	(MSB)	MAXIMUM INQUIRY CHANGE LOGS						(LSB)
16								
17	(MSB)	MAXIMUM MODE PAGE CHANGE LOGS						(LSB)
18								
19	Download microcode support byte							
	DM_MD_4 ^a	DM_MD_5 ^b	DM_MD_6 ^c	DM_MD_7 ^d	DM_MD_D ^e	DM_MD_E ^f	DM_MD_F ^g	Reserved
20								
...	Reserved							
63								

- a** The DM_MD_4 bit indicates support for the download microcode and activate (i.e., 04h) mode.
b The DM_MD_5 bit indicates support for the download microcode, save, and activate (i.e., 05h) mode.
c The DM_MD_6 bit indicates support for the download microcode with offsets and activate (i.e., 06h) mode.
d The DM_MD_7 bit indicates support for the download microcode with offsets, save, and activate (i.e., 07h) mode.
e The DM_MD_D bit indicates support for the download microcode with offsets, select activation events, save, and defer activate (i.e., 0Dh) mode.
f The DM_MD_E bit indicates support for the download microcode with offsets, save, and defer activate (i.e., 0Eh) mode.
g The DM_MD_F bit indicates support for the activate deferred microcode (i.e., 0Fh) mode.

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE and PAGE LENGTH field

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6, and shall be set to the value shown in table 557 for the Extended INQUIRY Data VPD page.

ACTIVATE MICROCODE field

The ACTIVATE MICROCODE field (see table 536) indicates how a device server activates microcode and establishes a unit attention condition during the processing of a WRITE BUFFER command (see 3.74) with the download microcode mode set to 05h or 07h (see SPC-6).

Table 536 ACTIVATE MICROCODE field

Value	Meaning
00b	The actions of the device server are not indicated.
01b	The device server: 1) activates the microcode before completion of the final command in the WRITE BUFFER sequence; and 2) establishes zero or more unit attention conditions as described in SPC-6.
10b	The device server: 1) activates the microcode after: A) a vendor specific event; B) a power on event; or C) a hard reset event; and 2) establishes a unit attention condition for the SCSI initiator port associated with every I_T nexus with the additional sense code set to MICROCODE HAS BEEN CHANGED.
11b	Reserved.

SPT (Supported Protection Type) field

The supported protection type (SPT) field indicates the type of protection the logical unit supports based on the contents of the PERIPHERAL DEVICE TYPE field. If the PROTECT bit (see 3.8.1) is set to zero, the SPT field is reserved. If the device server supports the Supported Block Lengths and Protection Types VPD page (see SBC-5) and the SBLP bit is set to one in the Control mode page (see 5.3.14), then the SPT field shall be set to 110b (i.e., specified in the Supported Block Lengths and Protection Types VPD page).

If the PERIPHERAL DEVICE TYPE field is set to 00h (i.e., direct access block device) and the PROTECT bit is set to one, then (see table 537) defines the contents of the SPT field.

Table 537 SPT field for device type value 00h

Code	Protection type supported		
	Type 1	Type 1	Type 1
000b	yes	no	no
001b	yes	yes	no
010b	no	yes	no
011b	yes	no	yes
100b	no	no	yes
101b	no	yes	yes
110b	See the Supported Block Lengths and Protection Types VPD page in SBC-5		
111b	yes	yes	yes

If the PERIPHERAL DEVICE TYPE field is set to 01h (i.e., direct access block device) and the PROTECT bit is set to one, then (see table 538) defines the contents of the SPT field.

Table 538 SPT field for device type value 00h

Code	Protection type supported
001b	Logical block protection
All others	Reserved

If the PROTECT bit is set to one and the PERIPHERAL DEVICE TYPE field is set to a value other than 00h or 01h, the SPT field is reserved.

If the SPT field is set to 110b, the bit shall be set to zero.

For the GRD_CHK, APP_CHK and REF_CHK bits, if the SPT field is **not** set to 110b:

GRD_CHK (Guard Check) bit

- 0** A guard check (GRD_CHK) bit set to zero indicates that the device server does not check the LOGICAL BLOCK GUARD field in the protection information (see SBC-5), if any.
- 1** A GRD_CHK bit set to one indicates that the device server checks the LOGICAL BLOCK GUARD field in the protection information, if any.

APP_CHK (Application Tag Check) bit

- 0** An application tag check (APP_CHK) bit set to zero indicates that the device server does not check the LOGICAL BLOCK APPLICATION TAG field in the protection information (see SBC-5), if any.
- 1** An APP_CHK bit set to one indicates that the device server checks the LOGICAL BLOCK APPLICATION TAG field in the protection information, if any.

REF_CHK (Reference Tag Check) bit

- 0** A reference tag check (REF_CHK) bit set to zero indicates that the device server does not check the LOGICAL BLOCK REFERENCE TAG field in the protection information (see SBC-5), if any.
- 1** A REF_CHK bit set to one indicates that the device server checks the LOGICAL BLOCK REFERENCE TAG field in the protection information, if any.

UASK_SUP (Unit Attention Sense Key Supported) bit

- 1** A unit attention condition sense key specific data supported (UASK_SUP) bit set to one indicates that the device server returns sense-key specific data for the UNIT ATTENTION sense key (see 2.4.1.1.4.6).
- 0** A UASK_SUP bit set to zero indicates that the device server does not return sense-key specific data for the UNIT ATTENTION sense key.

GROUP_SUP (Grouping Function Supported) bit

- 1** A grouping function supported (GROUP_SUP) bit set to one indicates that the grouping function (see SBC-5) is supported by the device server.
- 0** A GROUP_SUP bit set to zero indicates that the grouping function is not supported.

PRIOR_SUP (Priority Supported) bit

- 1** A priority supported (PRIOR_SUP) bit set to one indicates that task priority (see SAM-6) is supported by the logical unit.
- 0** A PRIOR_SUP bit set to zero indicates that task priority is not supported.

HEADSUP (Head of Queue Supported) bit

- 1** A head of queue supported (HEADSUP) bit set to one indicates that the HEAD OF QUEUE task attribute (see SAM-6) is supported by the logical unit.
- 0** A HEADSUP bit set to zero indicates that the HEAD OF QUEUE task attribute is not supported. If the HEADSUP bit is set to zero, application clients should not specify the HEAD OF QUEUE task attribute as an Execute Command procedure call argument.

ORDSUP (Ordered Supported) bit

- 1** An ordered supported (ORDSUP) bit set to one indicates that the ORDERED task attribute (see SAM-6) is supported by the logical unit.
- 0** An ORDSUP bit set to zero indicates that the ORDERED task attribute is not supported. If the ORDSUP bit is set to zero, application clients should not specify the ORDERED task attribute as an Execute Command procedure call argument.

SIMPSUP (Simple Supported) bit

- 1** A simple supported (SIMPSUP) bit set to one indicates that the SIMPLE task attribute (see SAM-6) is supported by the logical unit. Logical units that support the full task management model (see SAM-6) shall set the SIMPSUP bit to one.
- 0** A SIMPSUP bit set to zero indicates that the SIMPLE task attribute is not supported. If the SIMPSUP bit is set to zero, application clients should not specify the SIMPLE task attribute as an Execute Command procedure call argument.

WU_SUP bit

- 0** A write uncorrectable supported (WU_SUP) bit set to zero indicates that the device server does not support application clients setting the WR_UNCOR bit to one in the WRITE LONG command (see 3.76).
- 1** A WU_SUP bit set to one indicates that the device server supports application clients setting the WR_UNCOR bit to one in the WRITE LONG command.

NV_SUP bit

- 1** An NV_SUP bit set to one indicates that the device server supports a non-volatile cache and that the applicable command standard defines features using this cache.
- 0** An NV_SUP bit set to zero indicates that the device server may or may not support a non-volatile cache.

V_SUP bit

- 1** A V_SUP bit set to one indicates that the device server supports a volatile cache and that the applicable command standard defines features using this cache (e.g., the FUA bit in SBC-5).
- 0** A V_SUP bit set to zero indicates that the device server may or may not support a volatile cache.

NO_PI_CHK bit

- 1** a NO PROTECTION INFORMATION CHECKING (NO_PI_CHK) bit set to one indicates that the device server disables checking of all protection information for the associated protection information interval when performing a write operation if:
 - a) the LOGICAL BLOCK APPLICATION TAG field is set to FFFFh and type 1 protection (see SBC-5) is enabled;
 - b) the LOGICAL BLOCK APPLICATION TAG field is set to FFFFh and type 2 protection (see SBC-5) is enabled; or
 - c) the LOGICAL BLOCK APPLICATION TAG field is set to FFFFh, the LOGICAL BLOCK REFERENCE TAG field is set to FFFF FFFFh, and type 3 protection (see SBC-5) is enabled.
- 0** A NO_PI_CHK bit set to zero indicates that the device server checks protection information as specified by the WRPROTECT field (see SBC-5) when performing a write operation.

P_I_I_SUP bit

- 1** A protection information interval supported (P_I_I_SUP) bit set to one indicates that the logical unit supports protection information intervals (see SBC-5).
- 0** A P_I_I_SUP bit set to zero indicates that the logical unit does not support protection information intervals.

LUICLR bit

- 1** A logical unit I_T nexus clear (LUICLR) bit set to one indicates the SCSI target device clears any unit attention condition with an additional sense code of REPORTED LUNS DATA HAS CHANGED in each logical unit accessible to an I_T nexus after reporting the unit attention condition for any logical unit over that I_T nexus (see SAM-6).
- 0** An LUICLR bit set to zero indicates the SCSI target device clears unit attention conditions as defined in SPC-6.

The LUICLR bit shall be set to one.

LU COLLECTION TYPE field

The logical unit collection type (LU COLLECTION TYPE) field (see table 561) indicates the type of logical unit collection (see SPC-6) used by a logical unit conglomerate to report primary target port asymmetric access state.

Table 539 LU COLLECTION TYPE field

Code	Description
000b	Collection type not reported
001b	Conglomerate collection type
010b	Logical unit group collection type
All others	Reserved

R_SUP bit

- 0** A referrals supported (R_SUP) bit set to zero indicates that the device server does not support referrals (see SBC-5).
- 1** An R_SUP bit set to one indicates that the device server supports referrals.

RTD_SUP bit

- 0** An RTD_SUP bit set to zero indicates that the RTD bit in MODE SELECT commands is not supported.
- 1** An RTD bit set to one indicates that the RTD bit in MODE SELECT commands is supported.

HSSRELEF bit

- 1** A HSSRELEF bit set to one indicates the device server implements alternate reset handling for history snapshots.
- 0** A history snapshots release effects (HSSRELEF) bit set to zero indicates the device server implements normal reset handling for history snapshots.

MULTI_I_T NEXUS MICROCODE DOWNLOAD field

The MULTI_I_T NEXUS MICROCODE DOWNLOAD field (see SPC-6) indicates how the device server handles concurrent attempts to download microcode using the WRITE BUFFER command (see SPC-6) from multiple I_T nexuses.

EXTENDED SELF-TEST COMPLETION MINUTES field

The EXTENDED SELF-TEST COMPLETION MINUTES field contains advisory data that is the time in minutes that the device server requires to complete an extended self-test provided the device server is not interrupted by subsequent commands and no errors occur during processing of the self-test. The application client should expect the self-test completion time to exceed the value in this field if other commands are sent to the logical unit while a self-test is in progress or if errors occur during the processing of the self-test. If a device server supports SELF-TEST CODE field values other than 000b for the SEND DIAGNOSTIC command (see 3.50) and the self-test completion time is greater than 18 hours, then the device server shall support the EXTENDED SELF-TEST COMPLETION MINUTES field. A value of 0000h indicates that the EXTENDED SELF-TEST COMPLETION MINUTES field is not supported. A value of FFFFh indicates that the extended self-test takes 65 535 minutes or longer.

POA_SUP bit

- 1** A power on activation supported (POA_SUP) bit set to one indicates that the device server supports a WRITE BUFFER command with the MODE field set to 0Dh (see 3.74.10) and the PO_ACT bit set to one.
- 0** A POA_SUP bit set to zero indicates that the device server does not support a WRITE BUFFER command with the MODE field set to 0Dh and the PO_ACT bit set to one.

HRA_SUP bit

- 1** A hard reset activation supported (HRA_SUP) bit set to one indicates that the device server supports a WRITE BUFFER command with the MODE field set to 0Dh (see 3.74.11) and the HR_ACT bit set to one.
- 0** A HRA_SUP bit set to zero indicates that the device server does not support a WRITE BUFFER command with the MODE field set to 0Dh and the HR_ACT bit set to one.

VSA_SUP bit

- 1** A vendor specific activation supported (VSA_SUP) bit set to one indicates that the device server supports a WRITE BUFFER command with the MODE field set to 0Dh (see 3.74.10) and the VSE_ACT bit set to one.
- 0** A VSA_SUP bit set to zero indicates that the device server does not support a WRITE BUFFER command with the MODE field set to 0Dh and the VSE_ACT bit set to one.

MAXIMUM SUPPORTED SENSE DATA LENGTH field

The MAXIMUM SUPPORTED SENSE DATA LENGTH field indicates the maximum length in bytes of sense data (see 2.4) that the device server is capable of returning in the same I_T_L_Q nexus transaction as the status. A MAXIMUM SUPPORTED SENSE DATA LENGTH field set to zero indicates that the device server does not report a maximum length. This value shall be less than or equal to 252.

BIND SUPPORT BYTE

The bind support byte indicates support for logical unit binding and unbinding (see SPC-6). A bind support byte set to zero indicates that logical unit binding and unbinding are not supported. In a logical unit conglomerate, the bind support byte value for a subsidiary logical unit shall be the same as the bind support byte value for the administrative logical unit associated with that subsidiary logical unit.

IBS bit set

- 1** indicates that implicit bind operations (see SPC-6) are supported by the device server.
- 0** indicates that implicit bind operations are not supported by the device server.

IAS bit

- 1** indicates that the implicit management of affiliations (see SPC-6) is supported by the device server.
- 0** indicates that the implicit management of affiliations is not supported by the device server.

SAC bit

- 1** indicates that the SET AFFILIATION command (see SPC-6) is supported by the device server.
- 0** A SAC bit set to zero indicates that the SET AFFILIATION command is not supported by the device server.

NRD1 bit

- 1** indicates that BIND commands (see SPC-6) with the NRD bit set to one are supported by the device server.
- 0** indicates that BIND commands with the NRD bit set to one are not supported by the device server.

NRD0 bit

- 1** indicates that BIND commands with the NRD bit set to zero are supported by the device server.
- 0** indicates that BIND commands with the NRD bit set to zero are not supported by the device server.

MAXIMUM INQUIRY CHANGE LOGS field

The MAXIMUM INQUIRY CHANGE LOGS field indicates the maximum number of log parameters supported in the Last *n* Inquiry Data Changed log page (see SPC-6). A value of 0000h indicates that the Last *n* Inquiry Data Changed log page is not supported. For example, a value of 0005h indicates that the Last *n* Inquiry Data Changed log supports four Inquiry Data Changed Indicator log parameters.

MAXIMUM MODE PAGE CHANGE LOGS field

The MAXIMUM MODE PAGE CHANGE LOGS field indicates the maximum number of log parameters supported in the Last *n* Mode Page Data Changed log page (see SPC-6). A value of 0000h indicates that the Last *n* Mode Page Data Changed log page is not supported. For example, a value of 0005h indicates that the Last *n* Mode Page Data Changed log supports four Mode Page Data Changed Indicator log parameters.

DOWNLOAD MICROCODE SUPPORT BYTE

The download microcode support byte (see table 535) indicates the WRITE BUFFER microcode download modes (see SPC-6) that the device server supports. If the DMS_VALID bit is set to one, then each of the DM_MD_4 bit, the DM_MD_5 bit, the DM_MD_6 bit, the DM_MD_7 bit, the DM_MD_D bit, the DM_MD_E bit, and the DM_MD_F bit being set to:

- a) one indicates that the corresponding microcode download mode is supported; and
- b) zero indicates that the corresponding microcode download mode is not supported.

5.4.11 Firmware Numbers page (C0h)

Table 540 Firmware Numbers page (C0h)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER		PERIPHERAL DEVICE TYPE					
1	PAGE CODE (C0h)							
2	00h							
3	PAGE LENGTH							
4 ... 11	SCSI FIRMWARE RELEASE NUMBER							
12 ... 19	SERVO FIRMWARE RELEASE NUMBER							
20 ... 27	SAP BLOCK POINT NUMBERS (MAJOR/MINOR)							
28 ... 31	SERVO FIRMWARE RELEASE DATE							
32 ... 35	SERVO ROM RELEASE DATE							
36 ... 43	SAP FIRMWARE RELEASE NUMBER							
44 ... 47	SAP FIRMWARE RELEASE DATE							
48 ... 51	SAP FIRMWARE RELEASE YEAR							
52 ... 55	SAP MANUFACTURING KEY							
56 ... 59	SERVO FIRMWARE PRODUCT FAMILY AND PRODUCT FAMILY MEMBER IDs							

PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table 540.

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the following VPD page data. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

SCSI FIRMWARE RELEASE NUMBER field

The SCSI FIRMWARE RELEASE NUMBER fields contain ASCII data. The least significant ASCII character of the Drive firmware number shall appear as the last byte of the field.

SERVO FIRMWARE RELEASE NUMBER field

The SERVO FIRMWARE RELEASE NUMBER fields contain ASCII data. The least significant ASCII character of the Drive firmware number shall appear as the last byte of the field.

SAP BLOCK POINT NUMBERS (MAJOR/MINOR)

This field contains the Servo Adaptive Parameter Block Point Number.

SERVO FIRMWARE RELEASE DATE field

Servo Firmware Release Date indicates the date of the firmware release.

SERVO ROM RELEASE DATE field

Servo ROM Release Date indicates the date of the ROM release.

SAP FIRMWARE RELEASE NUMBER field, SAP FIRMWARE RELEASE DATE field, and SAP FIRMWARE RELEASE YEAR field

These fields are created independently from the servo firmware. These fields contain ASCII data.

SAP MANUFACTURING KEY field

The SAP MANUFACTURING KEY field contains a binary code used by manufacturing to identify the SAP.

SERVO FIRMWARE PRODUCT FAMILY and PRODUCT FAMILY MEMBER IDs field

The high order word of the SERVO FIRMWARE PRODUCT FAMILY and PRODUCT FAMILY MEMBER IDs field contains a binary code which corresponds to the Servo Firmware Family ID. The low order word of this field contains a binary code which corresponds to the Product Family Member ID.

5.4.12 Jumper Settings page (C2h)

The Jumper Settings VPD page is obsolete and not supported on newer products.

Table 541 Jumper Settings page (C2h)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (C2h)							
2	00h							
3	PAGE LENGTH (02h)							
4	DS	MS	WP	PE	DRIVE ID			
5	Reserved							TE

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table .

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the following VPD page data. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

DS (Delayed Motor Start) bit

The Delayed Motor Start (DS) bit when set to 1 indicates that this jumper is on.

MS (Motor Start) bit

The Motor Start (MS) bit when set to 1 indicates that the jumper is on.

WP (Write Protect) bit

The Write Protect (WP) bit when set to 1 indicates that the write protect jumper is on.

PE (Parity Enable) and PD (Parity Disable) bits

NOTE These bits are obsolete and are not supported.

Drive ID field

The Drive ID is shown below in Table 542. Bit 3 is the most significant bit and bit 0 is the least significant bit.

Table 542 Drive ID bit

Bit 3	Bit 2	Bit 1	Bit 0	Drive ID
0	0	0	0	0
0	0	0	1	1
0	0	1	0	2
0	0	1	1	3
0	1	0	0	4
0	1	0	1	5
0	1	1	0	6
0	1	1	1	7
1	0	0	0	8
1	0	0	1	9
1	0	1	0	10
1	0	1	1	11
1	1	0	0	12
1	1	0	1	13
1	1	1	0	14
1	1	1	1	15

TE (Terminator Enable) bit

NOTE This bit is obsolete and is not supported.

5.4.13 Logical Block Provisioning VPD page (82h)

The Logical Block Provisioning VPD page (see table 543) provides the application client with logical block provisioning related operating parameters of the logical unit.

Table 543 Logical Block Provisioning VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B2h)							
2	(MSB)	PAGE LENGTH (n - 3)						(LSB)
3								
4	THRESHOLD EXPONENT							
5	LBPB	LBPWS	LBPWS10	LBPRZ			ANC_SUP	DP
6	MINIMUM PERCENTAGE				PROVISIONING TYPE			
7	THRESHOLD PERCENTAGE							
8								
...	PROVISIONING GROUP DESCRIPTOR (if any)							
63								

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in SPC-6.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value shown in table 543 for the Logical Block Provisioning VPD page.

PAGE LENGTH field

The PAGE LENGTH field is defined in SPC-6. If the DP bit is set to zero, then the PAGE LENGTH field shall be set to 0004h. If the DP bit is set to one, then the PAGE LENGTH field shall be set to the value defined in table 543.

THRESHOLD EXPONENT field

The THRESHOLD EXPONENT field set to a non-zero value indicates the threshold set size in LBAs as a power of 2 (i.e., the threshold set size is equal to $2^{(\text{threshold exponent})}$). A THRESHOLD EXPONENT field set to zero indicates that the logical unit does not support logical block provisioning thresholds.

If logical block provisioning thresholds are supported, then the threshold exponent shall be a non-zero value selected such that:

$$(\text{capacity} \div 2^{(\text{threshold exponent})}) < 2^{(32)}$$

where:

capacity is 1 + the LBA of the last logical block as returned in the READ CAPACITY (16) parameter data (see 3.25.2) (i.e., the number of logical blocks on the direct access block device);

and

$2^{(32)}$ is the constant value 1_0000_0000h (i.e., 4 294 967 296).

LBPU bit

- 1** A logical block provisioning unmap (LBPU) bit set to one indicates that the device server supports the UNMAP command (see 3.58).
- 0** An LBPU bit set to zero indicates that the device server does not support the UNMAP command.

LBPWS bit

- 1** A logical block provisioning write same (LBPWS) bit set to one indicates that the device server supports the use of the WRITE SAME (16) command (see 3.78) to unmap LBAs.
- 0** An LBPWS bit set to zero indicates that the device server does not support the use of the WRITE SAME (16) command to unmap LBAs.

LBPWS10 bit

- 1** A logical block provisioning write same 10 (LBPWS10) bit set to one indicates that the device server supports the use of the WRITE SAME (10) command (see 3.77) to unmap LBAs.
- 0** An LBPWS10 bit set to zero indicates that the device server does not support the use of the WRITE SAME (10) command to unmap LBAs.

LBPRZ field

The logical block provisioning read zeros (LBPRZ) field is described in table 544.

Table 544 LBPRZ field

Code	Description
000b	The logical block data represented by unmapped LBAs is vendor specific
xx1b	The logical block data represented by unmapped LBAs is set to zeros
010b	The logical block data represented by unmapped LBAs is set to the provisioning initialization pattern
All others	Reserved

ANC_SUP bit

- 1** An anchor supported (ANC_SUP) bit set to one indicates that the device server supports anchored LBAs (see SBC-5).
- 0** An ANC_SUP bit set to zero indicates that the device server does not support anchored LBAs.

DP bit

- 1** A descriptor present (DP) bit set to one indicates a PROVISIONING GROUP DESCRIPTOR field is present.
- 0** A DP bit set to zero indicates a PROVISIONING GROUP DESCRIPTOR field is not present.

MINIMUM PERCENTAGE field

A MINIMUM PERCENTAGE field set to zero indicates that the logical unit does not report a minimum percentage of resources required by the device. A MINIMUM PERCENTAGE field set to a non-zero indicates the minimum percentage of resources required by the device server as described in table 545. This value indicates the point where a device server may begin device initiated advanced background operations.

Table 545 MINIMUM PERCENTAGE field

Code	Description
0	The logical unit does not report a minimum percentage of resources required
1 to 30 (i.e., 01h to 1Eh)	1% to 30% of the total allocation resources
All others	Reserved

PROVISIONING TYPE field

The PROVISIONING TYPE field is defined in table 546.

Table 546 Provisioning Type field

Code	Description
000b	The device server does not report a provisioning type.
001b	The logical unit is resource provisioned (see SBC-5).
010b	The logical unit is thin provisioned (see SBC-5).
All others	Reserved

THRESHOLD PERCENTAGE field

A THRESHOLD PERCENTAGE field set to zero indicates that the logical unit does not support logical block provisioning percentages. If logical block provisioning percentages are supported, then the threshold percentage shall be set to a non-zero value selected from the values in table 547. The units for the threshold percentage is tenths of a percent. This percentage represents the range over which logical block provisioning threshold percentages operates as described in SBC-5.

Table 547 MINIMUM PERCENTAGE field

Code	Description
0	The logical unit does not support logical block provisioning percentages
1 to 255 (i.e., 01h to FFh)	0.1% to 25.5% of the total allocation resources

PROVISIONING GROUP DESCRIPTOR field

The PROVISIONING GROUP DESCRIPTOR field, if any, contains a designation descriptor (see SPC-6) for the LBA mapping resources used by this logical unit.

If a PROVISIONING GROUP DESCRIPTOR field is present:

- a) the ASSOCIATION field shall be set to 00b (i.e. logical unit); and
- b) the DESIGNATOR TYPE field shall be set to:
 - A) 1h (i.e., T10 vendor ID based); or
 - B) 3h (i.e., NAA).

5.4.14 Mode Page Policy VPD page (87h)

The Mode Page Policy VPD page (see table 548) indicates which mode page policy (see table 550) is in effect for each mode page supported by the logical unit.

Table 548 Mode Page Policy VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (87h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Mode page policy descriptor list								
4	Mode page policy descriptor [first] (see table 549)							
...								
7	...							
...								
n-3	Mode page policy descriptor [last] (see table 549)							
...								
n								

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 548.

PAGE LENGTH field

The PAGE LENGTH field indicates the length of the mode page policy descriptor list. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

Each mode page policy descriptor (see table 549) contains information describing the mode page policy for one or more mode pages or subpages (see 5.3.5). The information in the mode page policy descriptors in this VPD page shall describe the mode page policy for every mode page and subpage supported by the logical unit.

Table 549 Mode page policy descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	Reserved		POLICY PAGE CODE					
1	POLICY SUBPAGE CODE							
2	MLUS	Reserved					MODE PAGE POLICY	
3	Reserved							

POLICY PAGE CODE field and POLICY SUBPAGE CODE field

The POLICY PAGE CODE field and POLICY SUBPAGE CODE field indicate the mode page and subpage to which the descriptor applies.

If the first mode page policy descriptor in the list contains a POLICY PAGE CODE field set to 3Fh and a POLICY SUBPAGE CODE field set to FFh, then the descriptor applies to all mode pages and subpages not described by other mode page policy descriptors. The POLICY PAGE CODE field shall be set to 3Fh and the POLICY SUBPAGE CODE field shall be set to FFh only in the first mode page policy descriptor in the list.

If the POLICY PAGE CODE field contains a value other than 3Fh and a POLICY SUBPAGE CODE field contains a value other than FFh, then the POLICY PAGE CODE field and the POLICY SUBPAGE CODE field indicate a single mode page and subpage to which the descriptor applies.

If the POLICY PAGE CODE field contains a value other than 3Fh, then POLICY SUBPAGE CODE field shall contain a value other than FFh. If the POLICY SUBPAGE CODE field contains a value other than FFh, then POLICY PAGE CODE field shall contain a value other than 3Fh.

MLUS bit

If the SCSI target device has more than one logical unit:

- 1** A multiple logical units share (MLUS) bit set to one indicates the mode page and subpage identified by the POLICY PAGE CODE field and POLICY SUBPAGE CODE field is shared by more than one logical unit.
- 0** A MLUS bit set to zero indicates the logical unit maintains its own copy.

The MLUS bit is set to one in the mode page policy descriptors or descriptor that indicates the mode page policy for the:

- a) Disconnect-Reconnect mode page (see SPC-6) for FC, and (see 5.3.16) for SAS and;
- b) Protocol Specific Port mode page (see 5.3.25).

MODE PAGE POLICY field

The MODE PAGE POLICY field (see table 550) indicates the mode page policy for the mode page and subpage identified by the POLICY PAGE CODE field and POLICY SUBPAGE CODE field.

Table 550 MODE PAGE POLICY field

Code	Description
00b	Shared
01b	Per target port
10b	Obsolete
11b	Per I_T nexus

5.4.15 Power Conditions Vital Product Data page (8Ah)

The Power Condition VPD page (see table 551) indicates which power conditions (see SPC-6) are supported by the logical unit and provides information about how those power conditions operate.

Table 551 Power Condition VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (8Ah)							
2	(MSB)	PAGE LENGTH (000Eh)						(LSB)
3								
4	Reserved					STANDBY_Y	STANDBY_Z	
5	Reserved				IDLE_C	IDLE_B	IDLE_A	
6	(MSB)	STOPPED CONDITION RECOVERY TIME						(LSB)
7								
8	(MSB)	STANDBY_Z CONDITION RECOVERY TIME						(LSB)
9								
10	(MSB)	STANDBY_Y CONDITION RECOVERY TIME						(LSB)
11								
12	(MSB)	IDLE_A CONDITION RECOVERY TIME						(LSB)
13								
14	(MSB)	IDLE_B CONDITION RECOVERY TIME						(LSB)
15								
16	(MSB)	IDLE_C CONDITION RECOVERY TIME						(LSB)
17								

PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field and PAGE LENGTH field

These fields are defined in SPC-6, and shall be set to the value shown in table 551 for the Power Condition VPD page.

If set to one, a power condition support bit (i.e., the STANDBY_Y bit, the STANDBY_Z bit, the IDLE_C bit, the IDLE_B bit, and the IDLE_A bit) indicates that:

- the associated power condition may be entered with the START STOP UNIT command (see SBC-5) if that command is implemented; and
- the associated power condition may be entered with a power condition timer if the associated timer is supported and enabled (see 5.3.21).

STANDBY_Y power conditions support bit

- 1** This bit set to one indicates that the logical unit supports the standby_y power condition as described in this subclause.
- 0** This bit set to zero indicates that the logical unit does not support the standby_y power condition.

STANDBY_Z power conditions support bit

- 1** This bit set to one indicates that the logical unit supports the standby_z power condition as described in this subclause.
- 0** This bit set to zero indicates that the logical unit does not support the standby_z power condition.

IDLE_C power conditions support bit

- 1** This bit set to one indicates that the logical unit supports the idle_c power condition as described in this subclause.
- 0** A IDLE_C bit set to zero indicates that the logical unit does not support the idle_c power condition.

IDLE_B power conditions support bit

- 1** This bit set to one indicates that the logical unit supports the idle_b power condition as described in this subclause.
- 0** A IDLE_B bit set to zero indicates that the logical unit does not support the idle_b power condition.

IDLE_A power conditions support bit

- 1** This bit set to one indicates that the logical unit supports the idle_a power condition as described in this subclause.
- 0** A IDLE_A bit set to zero indicates that the logical unit does not support the idle_a power condition.

STOPPED CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the stopped power condition to the active power condition. This field is only applicable to SCSI target devices that implement the START STOP UNIT command (see SBC-5). This time does not include the processing time for the command that caused this transition to occur or any SCSI transport protocol specific waiting time (e.g., the NOTIFY (ENABLE SPINUP) requirement described in SPL-5). A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

STANDBY_Z CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the standby_z power condition to the active power condition. This time does not include the processing time for the command that caused this transition to occur or any SCSI transport protocol specific waiting time (e.g., the NOTIFY (ENABLE SPINUP) requirement described in SPL). A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

STANDBY_Y CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the standby_y power condition to the active power condition. This time does not include the processing time for the command that caused this transition to occur or any SCSI transport protocol specific waiting time (e.g., the NOTIFY (ENABLE SPINUP) requirement described in SPL). A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

IDLE_A CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the idle_a power condition to the active power condition. This time does not include the processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

IDLE_B CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the idle_b power condition to the active power condition. This time does not include the processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

IDLE_C CONDITION RECOVERY TIME field

This field indicates the time, in one millisecond increments, that the logical unit takes to transition from the idle_c power condition to the active power condition. This time does not include the processing time for the command that caused this transition to occur. A value of zero indicates that the recovery time is not specified. A value of FFFFh indicates that the recovery time is more than 65.534 seconds.

5.4.16 Power Consumption Vital Product Data page (8Dh)

The Power Consumption VPD page (see table 552) provides an application client with a list of the available settings to limit the maximum power consumption of the logical unit while in the active power condition (see SPC-6).

Table 552 Power Consumption VPD page

Bit Byte	7	6	5	4	3	2	1	0	
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE					
1	PAGE CODE (8Dh)								
2	(MSB)	PAGE LENGTH (n-3)							
3								(LSB)	
Power consumption descriptor list									
4	Power consumption descriptor [first]								
...									
7	...								
...									
n-3	Power consumption descriptor [last]								
...									
n									

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE and PAGE LENGTH fields

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6, and shall be set to the value shown in table 552 for the Power Consumption VPD page.

Each power consumption descriptor (see table 553) describes one maximum power consumption level that the application client may establish for use by the active power condition (see SPC-6) using the Power Consumption mode page (see 5.3.21) as described in SPC-6.

Table 553 Power consumption descriptor format

Bit Byte	7	6	5	4	3	2	1	0
0	POWER CONSUMPTION IDENTIFIER							
1	Reserved				POWER CONSUMPTION UNITS			
2	(MSB)	POWER CONSUMPTION VALUE						(LSB)
3								

POWER CONSUMPTION IDENTIFIER field

The POWER CONSUMPTION IDENTIFIER field provides a reference handle to specify which descriptor is selected by the Power Consumption mode page as described in SPC-6.

POWER CONSUMPTION UNITS field

The POWER CONSUMPTION UNITS field (see table 554) indicates the units used for the POWER CONSUMPTION VALUE field.

Table 554 POWER CONSUMPTION UNITS field

Code	Description
000b	Gigawatts
001b	Megawatts
010b	Kilowatts
011b	Watts
100b	Milliwatts
101b	Microwatts
all others	Reserved

POWER CONSUMPTION VALUE field

The POWER CONSUMPTION VALUE field indicates the maximum power consumption associated with the identifier in the POWER CONSUMPTION IDENTIFIER field using the units specified by the POWER CONSUMPTION UNITS field.

5.4.17 Protocol Specific Logical Unit Information VPD page (90h)

The Protocol Specific Logical Unit Information VPD page (see SPC-6) contains parameters for the logical unit that are protocol specific based on the I_T nexus being used to access the logical unit.

The Protocol Specific Logical Unit Information VPD page shall only return information relating to SAS target ports.

Table 555 defines the Protocol Specific Logical Unit Information VPD page for logical units with SSP ports.

Table 555 Protocol Specific Logical Unit Information VPD page for SAS SSP

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (90h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
Logical unit information descriptor list								
4	Logical unit information descriptor (first) (see table 556)							
...								
...	...							
...	Logical unit information descriptor (last) (see table 556)							
n								

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in 3.8.2.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set as shown in table 555 for the Protocol Specific Logical Unit Information VPD page for SAS SSP.

PAGE LENGTH field

The PAGE LENGTH field is defined in 2.2.6.

Logical unit information descriptor list

The logical unit information descriptor list is defined in SPC-6 and shall contain a logical unit information descriptor for each SAS target port known to the SCSI device server.

Table 556 defines the logical unit information descriptor for logical units with SSP target ports.

Table 556 Logical unit information descriptor for SAS SSP

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB) _____							
1	RELATIVE PORT IDENTIFIER							(LSB)
2	Reserved				PROTOCOL IDENTIFIER (6h)			
3	Reserved							
...								
5								
6	(MSB) _____							
7	DESCRIPTOR LENGTH (0004h)							(LSB)
Per logical unit SCSI transport specific data								
8	Reserved							TLR CONTROL SUPPORTED
9	Reserved							
...								
11								

RELATIVE PORT IDENTIFIER field

The RELATIVE PORT IDENTIFIER field is defined in SPC-6.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set as shown in table 556 for the logical unit information descriptor for SAS SSP indicating that this is a SAS SSP specific descriptor.

DESCRIPTOR LENGTH field

The DESCRIPTOR LENGTH field is defined in SPC-6 and shall be set as shown in table 556 for the logical unit information descriptor for SAS SSP.

TLR CONTROL SUPPORTED bit

- 1** indicates that the combination of the SSP target port and logical unit support the TLR CONTROL field in the SSP frame header (see SPL-5).
- 0** indicates that the combination of the SSP target port and logical unit do not support the TLR CONTROL field in the SSP frame header.

5.4.18 Protocol Specific Port Information VPD page (91h)

The Protocol Specific Port Information VPD page (see SPC-6) contains parameters for the SAS target ports that are protocol specific and are the same for all logical units in the SAS target device.

Table 557 Protocol Specific Port Information VPD page for SAS SSP

Bit Byte	7	6	5	4	3	2	1	0	
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE					
1	PAGE CODE (91h)								
2	(MSB)	PAGE LENGTH (n-3)							
3								(LSB)	
Port information descriptor list									
4	Port information descriptor (first) (see table 556)								
...									
...	...								
...	Port information descriptor (last) (see table 556)								
n									

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in 3.8.2.

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set as shown in table 541 for the Protocol Specific Logical Unit Information VPD page for SAS SSP.

PAGE LENGTH field

The PAGE LENGTH field is defined in 2.2.6.

Port information descriptor list

The port information descriptor list is defined in SPC-4 and shall contain a port information descriptor for each SAS target port known to the SCSI device server.

Table 558 defines the port information descriptor for the SSP target ports.

Table 558 Logical unit information descriptor for SAS SSP

Bit Byte	7	6	5	4	3	2	1	0
0	(MSB)	RELATIVE PORT IDENTIFIER						(LSB)
1								
2		Reserved			PROTOCOL IDENTIFIER (6h)			
3		Reserved						PWR_D_S
4								
5		Reserved						
6	(MSB)	DESCRIPTOR LENGTH (n-7)						(LSB)
7								
SAS phy information descriptor list								
9								
...		SAS phy information descriptor (first) (see table 545)						
11								
...		...						
9								
...		SAS phy information descriptor (last) (see table 545)						
11								

RELATIVE PORT IDENTIFIER field

The RELATIVE PORT IDENTIFIER field is defined in SPC-6.

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field is defined in SPC-6 and shall be set as shown in table 558 for the port information descriptor for SAS SSP indicating that this is a port information descriptor for SAS SSP.

PWR_D_S bit

A power disable supported (PWR_D_S) bit set to one indicates that the POWER DISABLE signal (see SAS-5) is supported. A PWR_D_S bit set to zero indicates that the POWER DISABLE signal is not supported.

DESCRIPTOR LENGTH field

The DESCRIPTOR LENGTH field is defined in SPC-6.

SAS phy information descriptor list

The SAS phy information descriptor list contains a SAS phy information descriptor for each SAS phy in the SAS target port.

Table 559 defines the SAS phy information descriptor.

Table 559 SAS phy information descriptor for SAS SSP

Bit Byte	7	6	5	4	3	2	1	0	
0	Reserved								
1	PHY IDENTIFIER								
2	Reserved							SSP PERSISTENT CAPABLE	
3	Reserved								

PHY IDENTIFIER field

The PHY IDENTIFIER field is defined in the SMP DISCOVER response (see SPL-5).

SSP PERSISTENT CAPABLE bit

- 1** indicates that the phy supports a persistent connection (see SPL-5).
- 0** indicates that the phy does not support persistent connections.

5.4.19 SCSI Feature Sets VPD page (92h)

The SCSI Feature Sets VPD page (see table 562) indicates the SCSI feature sets supported by the device server.

Table 560 SCSI Feature Sets VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (92h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
4								
...	Reserved							
7								
Feature set code list								
8	(MSB)	FEATURE SET CODE (see table 563) [first]						(LSB)
9								
...								
n-1	(MSB)	FEATURE SET CODE (see table 563) [last]						(LSB)
n								

PERIPHERAL QUALIFIER, PERIPHERAL DEVICE TYPE and PAGE LENGTH fields

The PERIPHERAL QUALIFIER field, PERIPHERAL DEVICE TYPE and PAGE LENGTH field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field is defined in 3.8.2 and shall be set as shown in table 560 for the SCSI Feature Sets VPD page.

FEATURE SET CODE fields

The feature set code list shall contain a list of feature set codes that indicate the SCSI feature sets implemented by the device server in ascending order. Each FEATURE SET CODE field (see table 563) indicates one SCSI feature set implemented by the device server.

Table 561 Feature set codes

Code	Description	Reference aaa ^[a]
0000h	Reserved	SPC-6
0001h	SPC Discovery 2016 feature set	SPC-6
0002h to 00FFh	Reserved	SPC-6
0000h	Reserved	
0101h	SBC Base 2016 feature set	SBC-5
0102h	SBC Base 2010 feature set	SBC-5
0103h	SBC Basic Provisioning 2016 feature set	SBC-5
0104h	SBC Drive Maintenance 2016 feature set	SBC-5
0105h to 01FFh	Reserved	
0200h to 02FFh	SSC feature sets	SSC-5
0300h to 03FFh	ZBC feature sets	ZBC-2
all others	Reserved	

a A referenced standard may not define all the feature set codes assigned to it in this table. Unless otherwise specified, an undefined feature set code is reserved.

5.4.20 SCSI Ports VPD page (88h)

The SCSI Ports VPD page (see table 562) contains designation descriptors for all the SCSI ports in a SCSI target device.

The SCSI Ports VPD page only reports information on SCSI ports known to the device server processing the INQUIRY command. The REPORT LUNS well-known logical unit (see 3.36) may be used to return information on all SCSI ports in the SCSI device (i.e., all target ports and all initiator ports).

If the device server detects that a SCSI port is added or removed from the SCSI device and the SCSI port designation descriptor list changes, then the device server shall establish a unit attention condition (see SAM-6) for the initiator port associated with every I_T nexus, with the additional sense code set to INQUIRY DATA HAS CHANGED.

Table 562 SCSI Ports VPD page

Bit Byte	7	6	5	4	3	2	1	0	
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE					
1	PAGE CODE (88h)								
2	(MSB)	PAGE LENGTH (n-3)							
3								(LSB)	
Designation descriptor list									
4		SCSI port designation descriptor [first] (see table 563)							
...									
		...							
...		SCSI port designation descriptor [last] (see table 563)							
n									

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and PAGE LENGTH field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE and PAGE LENGTH fields

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6, and shall be set to the value shown in table 562 for the SCSI Ports VPD page. Each SCSI port designation descriptor (see table 563) identifies a SCSI port. The SCSI port designation descriptors may be returned in any order.

Table 563 SCSI port designation descriptor

Bit Byte	7	6	5	4	3	2	1	0
0 1	Reserved							
2 3	(MSB)	RELATIVE PORT IDENTIFIER (see table 564)						(LSB)
4 5	Reserved							
6 7	(MSB)	INITIATOR PORT TRANSPORTID LENGTH (k-7)						(LSB)
8 ... k	INITIATOR PORT TRANSPORTID (if any)							
k+1 k+2	Reserved							
k+3 k+4	(MSB)	TARGET PORT DESCRIPTORS LENGTH (n-(k+4))						(LSB)
Target port descriptor list								
k+5	Target port descriptor [first] (see table 562)							
...								
... n	Target port descriptor [last] (see table 562)							

RELATIVE PORT IDENTIFIER field

The RELATIVE PORT IDENTIFIER field (see table 564) contains the relative port identifier of the SCSI port to which the SCSI port designation descriptor applies.

Table 564 Relative Port Identifier field

Code	Description
0h	Reserved
1h	Relative port 1, historically known as port A
2h	Relative port 1, historically known as port B
3h to FFFFh	Relative port 3 through 65 535

INITIATOR PORT TRANSPORTID LENGTH field

The INITIATOR PORT TRANSPORTID LENGTH field indicates the length of the INITIATOR PORT TRANSPORTID field.

zero value indicates no INITIATOR PORT TRANSPORTID field is present (i.e., the SCSI port is not an initiator port).

non-zero value indicates a TransportID identifying the initiator port as defined in SPC-6.

TARGET PORT DESCRIPTORS LENGTH field

The TARGET PORT DESCRIPTORS LENGTH field indicates the length of the target port descriptors, if any. A TARGET PORT DESCRIPTORS LENGTH field set to zero indicates no target port descriptors are present (i.e., the SCSI port is not a target port).

Each target port descriptor (see table 565) contains an identifier for the target port. The target port descriptors may be returned in any order.

Table 565 Target port Descriptor

Bit Byte	7	6	5	4	3	2	1	0
0	PROTOCOL IDENTIFIER				CODE SET			
1	PIV (1b)	Reserved	ASSOCIATION (01b)		DESIGNATOR TYPE			
2	Reserved							
3	DESIGNATOR LENGTH (n – 3)							
4	DESIGNATOR							
...								
n								

PROTOCOL IDENTIFIER field

The PROTOCOL IDENTIFIER field indicates the SCSI transport protocol to which the designation descriptor applies as described in table 565.

CODE SET field, PIV field, ASSOCIATION field, DESIGNATOR TYPE field, DESIGNATOR LENGTH field, and DESIGNATOR field

The CODE SET field, PIV field, ASSOCIATION field, DESIGNATOR TYPE field, DESIGNATOR LENGTH field, and DESIGNATOR field are as defined in the Device Identification VPD page designation descriptor (see SPC-6), with the following additional requirements:

- the PIV bit shall be set to one (i.e., the PROTOCOL IDENTIFIER field always contains a SCSI transport protocol identifier); and
- the ASSOCIATION field shall be set to 01b (i.e., the descriptor always identifies a target port).

5.4.21 Supported Vital Product Data pages (00h)

The Supported VPD Pages VPD page (see table 566) contains a list of the VPD page codes that the device server reports as supported. The Supported VPD Pages VPD page list may or may not include all the VPD pages that are able to be returned by the device server.

Table 566 Supported Vital Product Data pages

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (00h)							
2	(MSB)	PAGE LENGTH (n-3)						(LSB)
3								
4								
...	SUPPORTED VPD PAGE LIST							
n								

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field is defined in SPC-6 and shall be set to the value defined in table 566.

PAGE LENGTH field

The PAGE LENGTH field indicates the length of the mode page policy descriptor list. The relationship between the PAGE LENGTH field and the CDB ALLOCATION LENGTH field is defined in 2.2.6.

SUPPORTED VPD PAGE LIST field

The SUPPORTED VPD PAGE LIST field shall contain a list of all vital product data page codes (see 5.4.1) implemented for the target or logical unit in ascending order beginning with page code 00h.

5.4.22 Unit Serial Number VPD page (80h)

The Unit Serial Number VPD page provides a product serial number for the target or logical unit. See Table 567 following.

Table 567 Unit Serial Number page (80h)

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (80h)							
2	(MSB)	PAGE LENGTH (14h)						(LSB)
3								
4	(MSB)	PRODUCT SERIAL NUMBER						(LSB)
...								
11								
12	(MSB)	PRINTED CIRCUIT BOARD SERIAL NUMBER						(LSB)
...								
23								

PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field

The PERIPHERAL QUALIFIER field and the PERIPHERAL DEVICE TYPE field are defined in Standard INQUIRY data (see 3.8.2).

PAGE CODE field

The PAGE CODE field shall be set to the value defined in table 567.

PAGE LENGTH field

The PAGE LENGTH field specifies the length of the product serial number plus the printed circuit board serial number.

PRODUCT SERIAL NUMBER field

The PRODUCT SERIAL NUMBER field contains right-aligned ASCII data that is vendor-assigned serial number. If the product serial number is not available, the target shall return ASCII spaces (20h) in this field.

PRINTED CIRCUIT BOARD SERIAL NUMBER field

The PRINTED CIRCUIT BOARD SERIAL NUMBER field contains right-aligned ASCII data that is vendor-assigned serial number. If the printed circuit board serial number is not available, the target shall return ASCII spaces (20h) in this field.

5.4.23 Zoned Block Device Characteristics VPD page (B6h)

The Zoned Block Device Characteristics VPD page (see table 568) provides a list of parameters that are specific to zoned block devices.

Table 568 Zoned Block Device Characteristics VPD page

Bit Byte	7	6	5	4	3	2	1	0
0	PERIPHERAL QUALIFIER			PERIPHERAL DEVICE TYPE				
1	PAGE CODE (B6h)							
2	(MSB) PAGE LENGTH (003Ch)							
3	(LSB)							
4	ZONED BLOCK DEVICE EXTENSION			Reserved		AAORB	URSWRZ	
5	Reserved							
...								
7								
8	(MSB) OPTIMAL NUMBER OF OPEN SEQUENTIAL WRITE PREFERRED ZONES							
...								
11								
12	(MSB) OPTIMAL NUMBER OF NON-SEQUENTIALLY WRITTEN SEQUENTIAL WRITE PREFERRED ZONES							
...								
15								
16	(MSB) MAXIMUM NUMBER OF OPEN SEQUENTIAL WRITE REQUIRED ZONES							
...								
19								
20	Reserved							
...								
63								

PERIPHERAL QUALIFIER and PERIPHERAL DEVICE TYPE fields

The PERIPHERAL QUALIFIER field and PERIPHERAL DEVICE TYPE field are defined in standard INQUIRY data (see 3.8.2).

PAGE CODE and PAGE LENGTH fields

The PAGE CODE field and PAGE LENGTH field are defined in SPC-6 and shall be set to the values shown in table 568 for the Zoned Block Device Characteristics VPD page.

ZONED BLOCK DEVICE EXTENSION field

If the PERIPHERAL DEVICE TYPE field is set to 00h, then the ZONED BLOCK DEVICE EXTENSION field (see table 569) indicates how the device server for a zoned block device extends the direct access block device type. If the PERIPHERAL DEVICE TYPE field is not set to 00h, then the ZONED BLOCK DEVICE EXTENSION field shall be set to 0h.

Table 569 ZONED BLOCK DEVICE EXTENSION field

Code	Description	Reference
0h	Zone block device extension not reported	
1h	Host aware zone block device model	ZBC-2
2h	Domains and realms zone block device model	ZBC-2
all others	Reserved	

AAORB bit

An activations aligned on realm boundaries (AAORB) bit set to zero indicates that the device server does not restrict the alignment of the zone range specified in a ZONE ACTIVATE command (see 4.10) or a ZONE QUERY command (see 4.11). An AAORB bit set to one indicates that the device server requires the zone range specified in a ZONE ACTIVATE command or a ZONE QUERY command to align with realm starting and ending LBAs (see 4.5).

URSWRZ bit

- 0** An unrestricted read in sequential write required zone (URSWRZ) bit set to zero indicates that the device server does not support reading unwritten logical blocks or reads across zone boundaries in sequential write required zones.
- 1** A URSWRZ bit set to one indicates that the device server supports reading unwritten logical blocks and reads across zone boundaries in sequential write required zones.

OPTIMAL NUMBER OF OPEN SEQUENTIAL WRITE PREFERRED ZONES field

The OPTIMAL NUMBER OF OPEN SEQUENTIAL WRITE PREFERRED ZONES field indicates the recommended upper limit for the number of sequential write preferred zones that are open zones. A value of FFFF_FFFFh indicates that the optimal number of sequential write preferred zones that are open zones is not reported.

OPTIMAL NUMBER OF NON-SEQUENTIALLY WRITTEN SEQUENTIAL WRITE PREFERRED ZONES field

The OPTIMAL NUMBER OF NON-SEQUENTIALLY WRITTEN SEQUENTIAL WRITE PREFERRED ZONES field indicates the recommended upper limit for the number of sequential write preferred zones in which at least one non-sequential write operation has occurred (see ZBC-2). A value of FFFF_FFFFh indicates that the optimal number of non-sequentially written sequential write preferred zones is not reported.

MAXIMUM NUMBER OF OPEN SEQUENTIAL WRITE REQUIRED ZONES field

The MAXIMUM NUMBER OF OPEN SEQUENTIAL WRITE REQUIRED ZONES field indicates the maximum number of sequential write required zones that are allowed to be open zones (see ZBC-2). A value of FFFF_FFFFh indicates that there is no limit for the number of sequential write required zones having a Zone Condition of IMPLICIT OPEN and EXPLICIT OPEN.

A

Abbreviations 33
 ABPF. See Abort Prefetch
 ADDITIONAL CDB LENGTH 40
 ADDITIONAL CDB LENGTH field 40
 ADDITIONAL LENGTH 104, 126
 ADDITIONAL LENGTH field 107
 Diagnostic Data Bytes 181
 Standard Inquiry Data 104
 Additional Length
 Diagnostic Data Bytes 181
 Additional sense 25
 additional sense
 qualifier code 60
 Additional Sense code 25
 additional sense code 60
 Address Field Logical Block Address Format 327
 Address Field Physical Sector Address Format 328
 ALLOCATION LENGTH
 CDB 10-byte 38
 CDB 12-byte 39
 CDB 6-byte 38
 CDB for long LBA 16-byte 39
 CDB for long LBA 32-byte 41
 Definition 43
 Receive Diagnostic Results command 181
 Allocation Length
 Inquiry command 103
 Log Sense command 116
 Mode Sense command 121
 Persistent Reserve In command 125
 Read Buffer command 154
 Read Capacity command 89, 95, 100, 164, 167
 Read Defect Data command 170
 Report Device Identifier command 187
 Report LUNS command 190, 201
 Request Sense command 207
 Allocation length 43
 ALLOCATION LENGTH field
 Receive Diagnostic Results command 181
 Application Client log page 342
 ARRE bit 490
 ASCII Information 528
 ASCII Information VPD page (01h - 7Fh) 528
 AWRE bit 490

B

Background Control mode
 Page description 446
 Background medium scan features 345
 Background Scan log page 344
 BLOCK DESCRIPTOR 436
 Block Device Characteristics 529
 Block Device Characteristics Extension 532
 Block Device Characteristics VDP page (B1h) 529

BLOCK LENGTH IN BYTES 166
 BLOCK LENGTH IN BYTES field 166
 Block Limits 534
 Block Limits Extension 539
 BUFFER CAPACITY
 BUFFER CAPACITY field 155
 Read Buffer Header 155
 BUFFER ID
 Read Buffer Command 154
 Write Buffer Command 277
 BUFFER OFFSET
 Read Buffer Command 154

C

Cache Statistics 351
 Cache statistics page 351
 CHANGE DEFINITION command 72
 Change Definition command 72
 check condition status 45
 Command
 alphabetical listing 65, 68
 for all devices 65
 for direct access devices 65
 Command Descriptor Block (CDB) 37
 Command type
 All devices 65, 68
 Direct access devices 65, 68
 Compile Date Code
 ETF Log Date Code page 540
 Control mode page (0Ah) 461
 Conventions 36

D

Date Code 540
 Date Code page 540
 Definitions 25
 Device Behavior 541
 Device Identification 542
 Device type field 401, 402, 419, 420
 Diagnostic Data Bytes
 Receive Diagnostic Results command 181
 Diagnostic data list 181
 Diagnostic operation 181
 Diagnostic page format 324
 Diagnostic Parameters
 Background Scan log page 344
 Cache Statistics page 351
 Log page codes 334
 PAGE CODE field identifies 324
 Supported Diagnostic Pages 326
 Supported Log Pages log page 413
 Temperature log page 416
 Diagnostic parameters 324
 Direct access block commands 65
 Disable Page Out bit 149

Disable Prefetch Transfer Length
 Caching Parameters page 450
 Disabled Physical Element

Translate Address page 331, 332
 Disabled Physical Element Mask

Translate Address page 331, 332

DPO
 See Disable Page Out bit 146, 149

E

EN_BMS
 Enable Background Medium Scan 447
 Enable Vital Product Data bit 103
 Error Code
 Diagnostic Data Bytes 181
 Error code
 definition 180
 ETF Log Date Code page 540
 ETF Log field 540
 EVPD. See Enable Vital Product Data bit
 Extended bytes from index address descriptor 85
 Extended INQUIRY Data 547
 Extended INQUIRY Data VPD page (86h) 547
 Extended physical sector address descriptor 86
 extended sense
 codes 60

F

Factory Log page 374
 Factory log page 374
 field
 maximum-value 45
 minimum-value 45
 Field Replaceable Unit
 Diagnostic Data Bytes 181
 Field replaceable unit 180
 Firmware Numbers 553
 Fixed length CDBs 38
 CDB for 10-byte commands 38
 CDB for 12-byte commands 39
 CDB for 6-byte commands 38
 CDB for long LBA 16-byte commands 39
 Format parameters
 page 472
 FORMAT UNIT command 74
 FORMAT UNIT parameter list 78
 FRU. see Field Replaceable Unit
 FUA
 See Force unit access bit 146

G

GROUP NUMBER field 149
 Grouping function 44

I

Identification Descriptor 543
 illegal request sense key 45
 Information
 Response codes 70h and 71h sense data format 57
 Informational Exceptions Control mode page (1Ch) 477
 INQUIRY command 103

J

Jumper Settings 555
 Jumper settings page 555

K

Keywords 35

L

Log parameters 334
 LOG SELECT command 111
 LOG SENSE command 116
 Logical block address 43
 LOGICAL BLOCK ADDRESS field 149
 LOGICAL BLOCK LENGTH
 Mode Parameter Block Descriptor 440
 Logical Block Provisioning 557
 LUN LIST LENGTH field 192

M

maximum-value field 45
 Medium Scan Parameter 347
 minimum-value field 45
 Mode Page Policy 560
 Mode page policy 118
 Mode parameter block descriptor formats 438
 Mode parameter header 436
 Mode parameters 434
 Caching Parameters page 449
 Control Extension mode page 467
 Control mode page 461
 Disconnect-Reconnect mode page for SAS 470
 General block descriptor format 438
 MODE DATA LENGTH field 437
 Mode parameter header 436
 Mode parameter header formats 436
 Mode parameter list format 436
 Page_0 Mode page format 442
 Power Condition mode page 484
 Sub_page mode page format 442
 Verify Error Recovery mode page 525
 Mode Select command 45
 MODE SELECT(10) command 120
 MODE SELECT(6) command 118
 MODE SENSE(10) command 124
 MODE SENSE(6) command 121
 PAGE CODE and SUBPAGE CODE fields 122

N

NEGOTIATED LOGICAL LINK RATE field 402
 Non-Medium Error log page (06h) 390
 NUMBER OF CYLINDERS 518
 NUMBER OF CYLINDERS field 519

O

OPERATION CODE

CDB 10-byte 38
 CDB 12-byte 39
 CDB 16-byte Long LBA 39
 CDB 32-byte Long LBA 41
 CDB 6-byte 38
 Defined 29
 Description 42
 Values sorted by Command Name 65, 68
 Variable length CDB 40

OVERWRITE 215

OVERWRITE service action 215

P

PAGE CODE 180

Page Code

ASCII Implemented Operating Definition page 541
 Caching Parameters page 449
 Rigid Drive Geometry Parameters page 518
 Translate Address page 330, 331, 332

PAGE CODE and SUBPAGE CODE fields. See Mode Sense (6) command

Page Length

ETF Log Date Code page 540
 Translate Address page 330, 331, 332

Parameter List Length 43

PARAMETER LIST LENGTH field 113

parameter value

rounding 45

PC. See Page Control field 111, 112

PCR

See Parameter Code Reset 111

Percentage Used Endurance Indicator log parameter 409

PERIPHERAL DEVICE TYPE 104

Peripheral Device Type

ETF Log Date Code page 540

PERIPHERAL QUALIFIER 104

Peripheral Qualifier Description 105

Peripheral Qualifier

ETF Log Date Code page 540

Persistent reservations type 129

PERSISTENT RESERVE IN command 125

Persistent Reserve In command 126

PERSISTENT RESERVE OUT command 136

PERSISTENT RESERVE OUT parameter list 138

PERSISTENT RESERVE OUT service actions 137

Phy event descriptor 404

Physical Element Length

Translate Address page 331, 332

Power Condition 562

Power Condition mode page (1Ah) 484

Power Condition Transitions log page 396, 398, 418

Power Conditions Vital Product Data page (8Ah) 562

Power Consumption 564

Power Consumption Mode page (1Ah/ 01h) 488

Power Consumption Vital Product Data page 564

Power on time parameter 374

PPC. See Parameter Pointer Control bit 116

PRESISTANT RESERVE IN command

PRGENERATION (Persistent Reservations Generation) field
 126

Protocol-specific Port log parameter for SAS 399

R

RDPROTECT field 146

READ BUFFER command 154

READ CAPACITY command

READ CAPACITY (10) command 165

READ CAPACITY (16) command 167

READ Command

READ (10) command 146

READ (12) command 150

READ (16) command 151

READ (32)command 152

READ (6) command 144

READ DEFECT DATA command

READ DEFECT DATA (10) command 170

READ DEFECT DATA (12) command 172

READ FULL STATUS 133

READ LONG command

READ LONG (10) command 174

READ LONG (16) command 176

READ RESERVATION 127

READ RETRY COUNT

Read-Write Error Recovery Mode page 490

READ RETRY COUNT field 494

Read-Write Error Recovery mode page 490

REASSIGN BLOCKS command 177

Rebuild Assist Input diagnostic page 331

Rebuild Assist Output diagnostic page 332

RECEIVE DIAGNOSTIC RESULTS command 180, 324

recovered error sense key 45

RELEASE command

RELEASE(10) command 184

RELEASE(6) command 183

REPORT CAPABILITIES 130

REPORT LUNS command 190

REQUEST SENSE command 207

RESERVE(10) command 209

RESERVE(6) command 208

Retry algorithm 372

Rezero Unit command 212

Rigid drive geometry parameters
page 518

Rigid Drive Geometry Parameters page 518

rounded parameter 45

rounding of parameter values 45

S

S.M.A.R.T. see Self-Monitoring Analysis and Reporting Technology

SANITIZE command 213

SANITIZE service actions 214

SAS Protocol-Specific Logical Unit mode page 495

Save Parameters bit 111

SCSI Enclosure Services pages 330

SCSI Ports 572

SCSI Ports VPD page 571, 572

Seek command 228

Seek Extended command 229

Self-monitoring analysis and reporting technology
measurement 374

SELF-TEST CODE field 406

Self-Test Results log page (10h) 405

SEND DIAGNOSTIC command 230, 324

Send Diagnostic command 180

Sense data 46

SERVICE ACTION field 40, 42

Solid State Media log page 408, 444, 452, 453, 454, 455, 460,
475, 481

Solid State Media log parameters 408, 410

Stable error correction code syndrome 372

Standard INQUIRY data 104

Standard INQUIRY data format 104

Start-Stop Cycle Counter log page (0Eh) 410

Supported 575

Supported page/subpage descriptor 414, 415

Supported Vital Product Data pages 575

Symbols 33

T

Target port Descriptor 574

Target Port Group Support field 108

Temperature log page 416

Temperature log page (0Dh) 416

Temperature log page parameter codes 416, 421

TPGS. See Target Port Group Support field 108

Transfer length 43

TRANSFER LENGTH field 149

Translate Address page 327

U

Unit Serial Number 576

Unit Serial Number page 576

Unrecoverable error 372

V

Variable length CDB formats 40

Typical variable length CDB 40

Typical variable length CDB for long LBA 32-byte commands
41

VENDOR IDENTIFICATION field 109

Vendor Unique Fault Information

Diagnostic Data Bytes 181

VERIFY command

VERIFY (10) command 247

VERIFY (12) command 257

VERIFY (16) command 258

VERIFY (32) command 259

Verify Error Recovery mode page 525

VERSION DESCRIPTOR fields 109

VERSION field 107

Vital Product Data 110

Vital Product Data page

ASCII Information VDP page 528

Device Behavior page 541

Device Identification VPD page 542

ETF Log Date Code page 540

Supported Vital Product Data pages 575

Unit Serial Number page 576

W

WRITE AND VERIFY command

275

WRITE AND VERIFY (10) command 270

WRITE AND VERIFY (12) command 271

WRITE AND VERIFY (16) command 272

WRITE AND VERIFY (32) command 273

WRITE ATOMIC (32) command 276

WRITE BUFFER command 277

WRITE command

WRITE (10) command 262

WRITE (12) command 266

WRITE (16) command 267

WRITE (32) command 268

WRITE (6) command 261

WRITE LONG command

WRITE LONG (10) command 286

WRITE LONG (16) command 287

WRITE RETRY COUNT

Read-Write Error Recovery Mode page 490

WRITE RETRY COUNT field 494

WRITE STREAM (16) command 293



Seagate Technology LLC

AMERICAS Seagate Technology LLC 47488 Kato Road, Fremont, California 94538, United States, 510-661-1000