Usher in a new era of domination.





FIRECUDA

SEAGATE

Seagate FireCuda 530R SSD

Usher in a new era of domination.

FireCuda 530R SSD, the latest evolution of our bestselling PCIe Gen4 SSD, unleashes ultra-fast speeds, extreme durability, and unrivalled performance. With leading-edge components in a slim M.2 2280 form factor, it's ideal for pro-level gamers and creators. FireCuda 530R SSD supports Microsoft[™] DirectStorage for seamless gaming, and is available in 1TB, 2TB, or 4TB capacities.



Key Features

Peak Performance

Level up with ultra-fast PCIe Gen4 SSD speeds for accelerated gaming and content creation

Easy Gaming

530R

PCIe Gen4 SSD

(000)

Supports Microsoft's DirectStorage technology for faster load times.

Tough Stuff

Extremely durable, with endurance of up to 5,050TBW

Usher in a new era of domination.



SEAGATE FIRECUDA 530R SSD

Inside & Out

Built with leading edge components including the Seagate validated E18 controller, all in a slim M.2 2280 form factor

High Capacity

Choose from 1TB, 2TB, or 4TB capacity options for all your gaming needs

No Worries

Backed by 5-year warranty, 3-years Rescue Services¹, and SeaTools 5 support 1 Rescue Data Recovery Services not available in all countries.



RETAIL PACKAGING	BOX DIMEN	SIONS MASTER CARTON D	DIMENSIONS PALLET DIMENSIONS
Length (in/mm)	6.102in/15	5mm 11.496in/292	2mm 47.992in/1219mm
Width (in/mm)	4.291in/10	9mm 6.024in/153n	9mm 20in/508mm
Depth (in/mm)	0.945in/24	4mm 5.512in/140n	0mm 27.795in/706mm
Weight (lb/kg)	0.154lb/0.0	07kg 2.138lb/0.97	7kg 105.822lb/48kg
QUANTITIES			
Boxes per Master Carton	10	The second s	
Master Cartons per Pallet	48		
Pallet Layers	4		
SYSTEM REQUIREMENTS		WHAT'S INCLUDED	

M.2 (M key) slot, PCIe[®] G4 ×4 interface (backwards compatible with PCIe G3 interface) Windows[®] 11, Windows 10

Seagate[®] FireCuda[®] 530R SSD

Linux

REGION	MODEL NUMBER	CAPACITY	LIMITED WARRANTY (YEARS)	UPC CODE	EAN CODE	MULTI-PACK UPC
ww	ZP1000GM3A063	1000GB	5	763649183083	8719706437691	10763649183080
WW	ZP2000GM3A063	2000GB	5	763649183090	8719706437707	10763649183097
WW	ZP4000GM3A063	4000GB	5	763649183106	8719706437714	10763649183103

Usher in a new era of domination.

SEAGATE FIRECUDA 530R SSD

		And the state of the second second second	
SPECIFICATIONS		FIRECUDA 530R SSD	
Capacity	4TB	2ТВ	1TB
Standard Model	ZP4000GM30063	ZP2000GM30063	ZP1000GM30063
Interface	PCIe Gen4 ×4 NVMe 1.4	PCIe Gen4 ×4 NVMe 1.4	PCIe Gen4 ×4 NVMe 1.4
NAND Flash Memory	3D TLC	3D TLC	3D TLC
Form Factor	M.2 2280-D2	M.2 2280-D2	M.2 2280-D2
PERFORMANCE			
Sequential Read (Max, MB/s), 128KB ¹	7400	7400	7400
Sequential Write (Max, MB/s), 128KB ¹	6800	6900	7000
Random Read (Max, IOPS), 4KB QD32 T16 ¹	1,300,000	1,300,000	1,300,000
Random Write (Max, IOPS), 4KB QD32 T16 ¹	1,300,000	1,300,000	1,300,000
ENDURANCE/RELIABILITY			
Total Bytes Written (TB)	5050	2400	1100
Mean Time Between Failures (MTBF, hours)	1,800,000	1,800,000	1,800,000
Rescue Data Recovery Services (years) ²	3	3	3
Warranty, Limited (years)	5	5	5
POWER MANAGEMENT			
Active Power, Average (W)	8.9	8.6	8.3
Idle Power PS3, Average (mW)	29	28	22
Low Power L1.2 mode (mW)	<5	<5	<5
ENVIRONMENTAL			
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70
Temperature, Nonoperating (°C)	-40 to 85	-40 to 85	-40 to 85
Shock, Nonoperating: 0.5ms (Gs)	1500	1500	1500
SPECIAL FEATURES			
TRIM	Yes	Yes	Yes
S.M.A.R.T.	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes
PHYSICAL			
_ength (mm/in, max)	80.85mm/3.183in	80.85mm/3.183in	80.85mm/3.183in
Width (mm/in, max)	22.15mm/0.872in	22.15mm/0.872in	22.15mm/0.872in
Height (mm/in, max)	3.58mm/0.140in	3.58mm/0.140in	2.23mm/0.087in
Neight (g/lb)	9.2g/0.020lb	8.8g/0.019lb	7.3g/0.016lb

1 Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.7.0.0 ×64 on Windows 10 host with PCIe Gen4 motherboard.

2 Rescue Data Recovery Services not available in all countries.

SEAGATE.COM

© 2024 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda[®] is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The NVMe word mark and/or NVMExpress design mark are trademarks of NVMExpress, Inc. The PCIe word mark and/or PCIExpress design mark are registered trademarks and/or service marks of PCI-SIG. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and drive capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS7.1-2403US