



M.2 SSD DATA SHEET

## NyTRO 4350

Consistent high performance for the modern data centre.



The Seagate NyTRO<sup>®</sup> 4350 NVMe<sup>™</sup> SSD brings consistent application performance and TCO savings to data centres with its small form factor, low latency and power consumption and high QoS.



### Best-Fit Applications

- Server Boot
- Cloud Computing
- Caching

## Key Advantages

**Best-in-class performance** PCIe Gen4 NVMe<sup>™</sup> SSD provides 10x the bandwidth of SATA SSDs

**Wide range of capacities** up to 1.92 TB supporting PCIe Gen4 NVMe interface and M.2 2280 form factor

**Enhanced durability and reliability** with 1 DWPD at 2M hours MTBF

Boost the read/write performance of QoS and data centre applications

**Less energy** with low power consumption for 24x7 operations

**Be protected** and rest easy with included power loss data protection

**Supports TCG Pyrite** offering password security to protect user data



Specifications	1.92 TB	960 GB	480 GB
Standard Model (TCG Pyrite)	XP1920SE30001	XP960SE30001	XP480SE30001
<b>Features</b>			
Interface	PCIe Gen4 x4, NVMe 1.4	PCIe Gen4 x4, NVMe 1.4	PCIe Gen4 x4, NVMe 1.4
NAND Flash Type	3D eTLC	3D eTLC	3D eTLC
Form Factor	M.2 2280	M.2 2280	M.2 2280
<b>Performance</b>			
Sequential Read (MB/s) Sustained, 128 KB <sup>1</sup>	5,500	5,500	5,500
Sequential Write (MB/s) Sustained, 128 KB <sup>1</sup>	2,000	1,400	700
Random Read (IOPS) Sustained, 4 KB <sup>2</sup>	800,000	600,000	400,000
Random Write (IOPS) Sustained, 4KB <sup>2</sup>	58,000	34,000	17,000
Average Read Latency (µs), 4 KB QD1	75	75	75
Average Write Latency (µs), 4 KB QD1	30	30	40
<b>Endurance/Reliability</b>			
Lifetime Endurance (Drive Writes per Day)	1	1	1
Total Bytes Written (TB)	3,800	1,890	936
Non-recoverable Read Errors per Bits Read	1 per 10E17	1 per 10E17	1 per 10E17
Mean Time Between Failures (MTBF, hours)	2,000,000	2,000,000	2,000,000
Warranty, Limited (years)	5	5	5
<b>Power Management</b>			
3.3V Overall Average Active Power (W)	10.7	8.1	6.3
Average Idling Power (W)	3.4	3.2	3.1
<b>Environmental</b>			
Temperature, Operating Internal (°C)	0°C – 70°C	0°C – 70°C	0°C – 70°C
Temperature, Non-operating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Temperature Change Rate/Hr, Max (°C)	30°C per hour	30°C per hour	30°C per hour
Shock, 0.5ms (Gs)	1,500 Gs	1,500 Gs	1,500 Gs
<b>Physical</b>			
Height (mm/in, max)	4.08 mm/0.160 in	4.08 mm/0.160 in	4.08 mm/0.160 in
Height, Component Top (mm/in, max)	1.60 mm/0.062 in	1.60 mm/0.062 in	1.60 mm/0.062 in
Height, Component Bottom (mm/in, max)	1.60 mm/0.062 in	1.60 mm/0.062 in	1.60 mm/0.062 in
Width (mm/in, max)	22.15 mm/0.872 in	22.15 mm/0.872 in	22.15 mm/0.872 in
Length (mm/in, max)	80.15 mm/3.155 in	80.15 mm/3.155 in	80.15 mm/3.155 in
Weight (g/lb, max)	10 g/0.022 lb	10 g/0.022 lb	10 g/0.022 lb
Carton Unit Quantity	20	20	20

<sup>1</sup> Sequential performance measured at queue depth of 32 at beginning of life. System application performance may vary based on host and prior system workload.

<sup>2</sup> Random performance measured at queue depth of 256 at beginning of life. System application performance may vary based on host and prior system workload.

seagate.com



© 2023 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Nytro, the Nytro logo, Seagate Secure, and the Seagate Secure logo are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. The NVMe word mark and/or NVMeExpress design mark are trademarks of NVMeExpress, Inc. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. The export or re-export of Seagate hardware or software is regulated by the U.S. Department of Commerce, Bureau of Industry and Security (for more information, visit [www.bis.doc.gov](http://www.bis.doc.gov)), and may be controlled for export, import and use in other countries. Seagate reserves the right to change, without notice, product offerings or specifications. SC29.1-2306US