

DATA SHEET

Fast. Dependable. Versatile.

## BarraCuda 120 SSD



The 2.5-inch SATA SSD, Seagate® BarraCuda™ 120 SSD, features a next-gen controller combined with the latest 3D TLC NAND technology to provide your PC with increased dependability and speed. It is specifically designed for improved performance, reliability and efficiency. PC upgrades love our legendary BarraCuda internal drives.



### Best-Fit Applications

- Desktops and all-in-one PCs
- Laptops
- Home servers
- Gaming PCs

### Key Advantages

---

Unlock maximum SATA 6 Gb/s SSD speeds with 3D TLC NAND that delivers up to 560/540 MB/s sequential read/write and up to 90K IOPS random read/write.

---

Easily upgrade from hard drives with a plug-and-play 2.5-inch, 7 mm form factor and SATA interface

---

Trust in Seagate's robust 5-year limited warranty and BarraCuda's established dependability.

---

Achieve endurance and reliability with up to 1,170 TB Total Bytes Written and 1,800,000 hours Mean Time Between Failures.

---

Seagate has been the industry leader in compute storage for over 40 years, because we're committed to data storage excellence.

---

Choose from multiple capacities (up to 2 TB) for all your applications, media, files and more.

---

Download our free SeaTools™ SSD software to take advantage of drive performance reporting, S.M.A.R.T. attributes, health monitoring, firmware updates, diagnostics, and managing logs.

---



Specifications	2TB	1TB	500GB	250GB
Model Number	ZA2000CM10003	ZA1000CM10003	ZA500CM10003	ZA250CM10003
Interface	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s	SATA 6 Gb/s
NAND Flash Memory	3D TLC	3D TLC	3D TLC	3D TLC
Form Factor	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm	2.5 in x 7 mm
<b>Performance</b>				
Sequential Read (Max, MB/s), 128KB <sup>1</sup>	560	560	560	560
Sequential Write (Max, MB/s), 128KB <sup>1</sup>	540	540	540	540
Random Read (Max, IOPS), 4 KB QD32 <sup>1</sup>	90,000	90,000	90,000	90,000
Random Write (Max, IOPS), 4 KB QD32 <sup>1</sup>	90,000	90,000	90,000	90,000
<b>Endurance/Reliability</b>				
Total Bytes Written (TB)	1,170	600	300	150
Mean Time Between Failures (MTBF, hours)	1,800,000	1,800,000	1,800,000	1,800,000
Warranty, Limited (years)	5	5	5	5
<b>Power Management</b>				
Active Power, Average (W)	2.8	2.7	2.5	2.5
Idle Power, Average (mW)	128	120	115	116
DevSleep (mW)	5	5	5	5
<b>Environmental</b>				
Temperature, Operating Internal (°C)	0°C – 70°C	0°C – 70°C	0°C – 70°C	0°C – 70°C
Temperature, Non-operating (°C)	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C	-40°C – 85°C
Shock, Non-operating: 0.5 ms (Gs)	1,500	1,500	1,500	1,500
<b>Physical</b>				
Height (mm/in, max)	7.1 mm/0.279 in	7.1 mm/0.279 in	7.1 mm/0.279 in	7.1 mm/0.279 in
Width (mm/in, max)	70.1 mm/2.759 in	70.1 mm/2.759 in	70.1 mm/2.759 in	70.1 mm/2.759 in
Depth (mm/in, max)	100.35 mm/3.951 in	100.35 mm/3.951 in	100.35 mm/3.951 in	100.35 mm/3.951 in
Weight (lb/g)	50 g/0.11 lb	50 g/0.11 lb	50 g/0.11 lb	50 g/0.11 lb
<b>Bulk Pack Specifications</b>				
Carton Unit Quantity	20	20	20	20
Cartons Per Pallet/Layer	84 / 12	84 / 12	84 / 12	84 / 12
<b>Special Features</b>				
TRIM	Yes	Yes	Yes	Yes
S.M.A.R.T.	Yes	Yes	Yes	Yes
Halogen-free	Yes	Yes	Yes	Yes
RoHS compliance	Yes	Yes	Yes	Yes

<sup>1</sup> Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.6.0.0 x64 on Windows 10 host.



Specifications				
Retail Packaging	Product Dimensions	Box Dimensions	Master Carton Dimensions	Pallet Dimensions
Length (in/mm)	—	0.945 in/24 mm	6.024 in/153 mm	47.992 in/1,219 mm
Width (in/mm)	—	4.291 in/109 mm	11.496 in/292 mm	20 in/508 mm
Depth (in/mm)	—	6.102 in/155 mm	5.512 in/140 mm	27.795 in/706 mm
Weight (lb/kg)	—	0.22 lb/0.1 kg	2.646 lb/1.2 kg	130.734 lb/59.3 kg
Quantities				
Boxes per Master Carton	10			
Master Cartons per Pallet	48			
Pallet Layers	4			

System Requirements	What's Included
---------------------	-----------------

- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• SATA 6 Gb/s or SATA 3 Gb/s port</li> <li>• Windows® 10, Windows 8.1 or Windows 7</li> <li>• Linux</li> </ul> | <ul style="list-style-type: none"> <li>• Seagate® BarraCuda™ 120 SSD</li> </ul> |
|---|---|

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
WW	ZA250CM1A003	250GB	5	763649139288	8719706020855	10763649139285
WW	ZA500CM1A003	500GB	5	763649139295	8719706020862	10763649139292
WW	ZA1000CM1A003	1TB	5	763649139301	8719706020879	10763649139308
WW	ZA2000CM1A003	2TB	5	763649139318	8719706020886	10763649139315

seagate.com



© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. BarraCuda, the BarraCuda logo, and SeaTools are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and drive capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2022.2-2104GB April 2021