



DATA SHEET

Scalable. Responsive. Innovative.
Exos 2X14



Seagate manufactures hard drives that specifically address the needs of the hyperscale storage market. As the highest-performing hard drive in the Seagate® X class, the Exos® 2X14 enterprise dual-actuator hard drive utilizes MACH.2™ technology enabling up to 2× the performance of an enterprise single-actuator 3.5-inch hard drive.



Best-Fit Applications

- Hyperscale applications/cloud data centers
- Massive scale-out data centers
- Big data applications
- Content delivery networks
- Mainstream enterprise external storage arrays
- Distributed file systems, including Hadoop and Ceph
- Enterprise backup and restore—D2D, virtual tape
- Centralized surveillance
- High-bandwidth streaming applications

Highest Performance for Highest Rack Space Efficiency

MACH.2 technology enables up to 2× the performance of an enterprise single-actuator 3.5-inch hard drive¹

Highest 14TB hard drive performance, making it the logical choice for cloud data center and massive scale-out data center applications

14TB of capacity available as two independently addressable, 7TB logical units

PowerBalance™ feature optimizes IOPS/Watt

Helium sealed-drive design delivers lower total cost of ownership through lower power and weight

Next-generation helium side-sealed weld technology for added handling robustness and leak protection

Digital environmental sensors to monitor internal drive conditions for optimal operation and performance

Latest hermetic interconnect technology supporting higher data rate heads and higher pin counts for extreme thermal conditions

Proven enterprise-class reliability backed by **5-year limited warranty and 2.5M-hr MTBF rating**

¹ When operating both actuators simultaneously



Specifications	12Gb/s SAS	12Gb/s SAS
Capacity	14TB	14TB
Hyperscale (4Kn)	ST14000NM0001	—
Standard Model FastFormat™ (512e/4Kn) ¹	—	ST14000NM0081
Capacity per Logical Unit	7TB	7TB
Features		
Helium Sealed-Drive Design	Yes	Yes
Protection Information (T10 DIF)	No	No
SuperParity	Yes	Yes
Low Halogen	Yes	Yes
PowerChoice™ Idle Power Technology	Yes	Yes
PowerBalance™ Power/Performance Technology	Yes	Yes
Hot-Plug Support ²	Yes	Yes
Cache, Multisegmented (MB)	256	256
Organic Solderability Preservative	Yes	Yes
RSA 2048 Firmware Verification (SD&D)	Yes	Yes
Reliability/Data Integrity		
Mean Time Between Failures (MTBF, hours)	2,500,000	2,500,000
Reliability Rating @ Full 24x7 Operation (AFR)	0.35%	0.35%
Nonrecoverable Read Errors per Bits Read	1 sector per 10E15	1 sector per 10E15
Power-On Hours per Year (24x7)	8,760	8,760
512e Sector Size (Bytes per Sector)	—	512
4Kn Sector Size (Bytes per Sector)	4096	4096
Limited Warranty (years)	5	5
Performance		
Spindle Speed (RPM)	7200RPM	7200RPM
Interface Access Speed (Gb/s)	12.0, 6.0, 3.0	12.0, 6.0, 3.0
Max. Sustained Transfer Rate OD (MB/s, MiB/s) ³	524, 500	524, 500
Random Read/Write 4K QD16 (IOPS) ³	304/384	304/448
Average Latency (ms)	4.16	4.16
Interface Ports	Single	Single
Rotation Vibration @ 20-1500 Hz (rad/sec ²)	12.5	12.5
POWER CONSUMPTION		
Idle A (W) Average	7.2W	7.2W
Random Read/Write 4K/16Q (W) ³	12.3/8.7	12.3/8.7
Sequential Read/Write 256K/16Q (W) ³	13.5/11.8	13.5/11.8
Power Supply Requirements	+12 V and +5 V	+12 V and +5 V
Environmental		
Temperature, Operating (°C)	5°C – 60°C	5°C – 60°C
Vibration, Nonoperating: 2 to 500Hz (Grms)	2.27	2.27
Shock, Operating 2ms (Read/Write) (Gs)	50	50
Shock, Nonoperating 2ms (GS)	200	200
Physical		
Height (in/mm, max) ⁴	1.028in/26.1mm	1.028in/26.1mm
Width (in/mm, max) ⁴	4.01in/101.85mm	4.01in/101.85mm
Depth (in/mm, max) ⁴	5.787in/147mm	5.787in/147mm
Weight (lb/gm)	1.51lb/685g	1.51lb/685g
Carton Unit Quantity	20	20
Cartons per Pallet/Cartons per Layer	40/8	40/8

¹ FastFormat models ship in 512e format state. When switching from 512e to 4Kn by executing the FastFormat routine, all data on the drive will be deleted. Note that data must be aligned to 4K sectors to see improved performance in 4Kn format.

² Supports Hotplug operation per the SAS-3 and SPL-3 specifications

³ When operating both actuators simultaneously

⁴ These base deck dimensions conform to the Small Form Factor Standard (SFF-8301) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8323.

© 2020 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Exos, the Exos logo, MACH.2, PowerBalance, and PowerChoice are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS2015.3-2007US July 2020