

Video 2.5 HDD

Data Sheet

Reliable. Quiet. Low Power

- Purpose-built 2.5-inch drive tuned for video streaming, 24x7 operation and low power consumption¹
- Small form factor—1/6 the size of 3.5-inch solutions—allows system cost reduction, operational power savings and fanless design while supporting flexibility in a sleeker industrial system design.
- Eco-friendly power consumption enables energy-efficient, always-on systems with up to 55% in power savings in comparison to 3.5-inch solutions.
- Proven Seagate reliability of 0.55% AFR supports longevity in demanding consumer electronic environments.
- Designed for cool, quiet, worry-free operation.
- Media streaming optimised for smooth content delivery of up to 12 HD streams.

Best-fit Applications

- DVR and media centre applications
- Home cinema PCs
- Karaoke and audio jukeboxes
- Cable, satellite and IPTV set-top boxes
- In-camera or surveillance systems

¹ Seagate® Video 2.5 HDD was previously known as the Pipeline HD® Mini hard drive.





Video 2.5 HDD

DATA SHEET



Specifications	500 GB ¹	320 GB ¹
Model Number	ST500VT000	ST320VT000
Interface Options	SATA 6 Gb/s	SATA 6 Gb/s
Performance		
Cache, Multi-segmented (MB)	16	16
Simultaneous HDTV Streams Supported (Assumes 20 MB host buffer per stream)	12	12
Power-on to Ready (typical, sec)	3.0	3.0
Standby to Ready (typical, sec)	2.5	2.5
Sustained Data Transfer Rate (MB/s)	100	100
Voltage		
Voltage Tolerance (including noise)	5V ± 5%	5V ± 5%
Reliability		
Non-recoverable Read Errors per Bits Read	1 sector per 10 ¹⁴	1 sector per 10 ¹⁴
Annualised Failure Rate (AFR)	0.55%	0.55%
Load/Unload Cycles (software/hardware-controlled power cycles)	20,000 600,000	20,000 600,000
Warranty, Limited (years)	3	3
Power Management		
Start-up Current 5V (amps max)	1.0	1.0
Operating Seeks (W)	1.5	1.5
Idling Average (W)	0.66	0.66
Standby/Sleep Mode (typical, W)	0.18	0.18
Environmental		
Temperature (°C)		
Operating (drive case max)	60	60
Non-operating (drive case min)	0	0
Non-operating (ambient)	-40 to 70	-40 to 70
Temperature Gradient, Operating/Non-operating (°C per hour max)	20/35	20/35
Relative Humidity, Operating/Non-operating (non-condensing, %)	5 to 95	5 to 95
Wet bulb Temperature, Operating/Non-operating (°C max)	37.7/40.0	37.7/40.0
Shock		
Operating: 2 ms (max, Gs)	400	400
Non-operating: 1 ms (max, Gs)	1,000	1,000
Vibration, Operating		
5 Hz to 200 Hz (Gs, max displacement applies below 10 Hz)	2.0	2.0
200 Hz to 500 Hz (Gs, 0 to peak)	1.0	1.0
Vibration, Non-operating		
5 Hz to 500 Hz (Gs, max displacement applies below 22 Hz)	5.0	5.0
Acoustics		
PVR Profile (typical/max, bels)	2.2/2.4	2.2/2.4
Physical		
Height (mm/in) ²	7.0/0.276	7.0/0.276
Width (mm/in) ²	70.1/2.76	70.1/2.76
Depth (mm/in) ²	100.55/3.959	100.55/3.959
Weight (g/lb, max)	95/0.209	95/0.209
Carton Unit Quantity	50	50
Cartons per Pallet	60	60
Cartons per Layer	10	10

¹ One gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes when referring to drive capacity.

² These base deck dimensions conform to the Small Form Factor Standard (SFF-8203) found at www.sffcommittee.org. For connector-related dimensions, see SFF-8223.

seagate.com

AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, +1 408 658 1000
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, +65 6485 3888
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18 rue du Dôme, 92100 Boulogne-Billancourt, France, +33 1 4186 10 00

© 2017 All rights reserved. Printed in USA. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. Pipeline and Pipeline HD are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes; and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1722.4-1707, July 2017