



DATA SHEET

# Accelerate. Dominate. Endure. FireCuda 510 SSD



Built specifically for professional-level gamers, the Seagate® FireCuda® 510 SSD brings the intense speeds, lasting endurance, and large capacity needed to accelerate PC storage performance.



## Best-Fit Applications

- Gaming PC desktops
- Gaming PC laptops
- High-performance PCs and workstations
- Creative professional systems



## Key Advantages

**NVMe PCIe Gen3 x4** interface unleashes the speed of NAND and delivers up to 6x faster performance than SATA SSDs

**Blazing-fast sequential read/writes** bring faster load times, faster program installations, and faster processing

**Ultra-high random read/write IOPS** translates to faster program response times and more responsive multiple program multitasking

**Enhanced dynamic SLC cache** provides longer bursts of data

**Multiple capacities up to 2 TB** for the storage of huge files and games without the worry of maxing out your drive or partitioning

**M.2 2280 form factor** for massive speed and capacity in a compact package for installation in tight spaces, leaving room for other components

**Top-tier endurance** gives pro-level gamers peace of mind with a 5-year limited warranty and MTBF of 1.8 M hours

**SeaTools™ SSD enhanced gaming tool** with drive management and health monitoring so gamers can tune the drive to their performance needs

**Three years of Rescue Data Recovery Services<sup>1</sup>**, offering an industry-leading 95% success rate against unexpected data loss.

1 Rescue Data Recovery Services not available in all countries.



Specifications	2 TB	1 TB	500 GB	250 GB
Standard Model (TCG Pyrite)	ZP2000GM30001	ZP1000GM30031	ZP500GM30021	ZP250GM30001
Interface	PCIe Gen3 x4, NVMe 1.3	PCIe Gen3 x4, NVMe 1.3	PCIe Gen3 x4, NVMe 1.3	PCIe Gen3 x4, NVMe 1.3
NAND Flash Memory	3D TLC	3D TLC	3D TLC	3D TLC
Form Factor	M.2 2280-D2	M.2 2280-S2	M.2 2280-S2	M.2 2280-S2
<b>Performance</b>				
Sequential Read (Max, MB/s), 128 KB <sup>1</sup>	3,450	3,450	3,450	3,200
Sequential Write (Max, MB/s), 128 KB <sup>1</sup>	3,200	3,100	2,500	1,300
Random Read (Max, IOPS), 4 KB QD32 T8 <sup>1</sup>	620,000	620,000	420,000	210,000
Random Write (Max, IOPS), 4 KB QD32 T8 <sup>1</sup>	600,000	600,000	600,000	320,000
<b>Endurance/Reliability</b>				
Total Bytes Written (TB)	2,600	1,300	650	300
Mean Time Between Failures (MTBF, hours)	1,800,000	1,800,000	1,800,000	1,800,000
Rescue Data Recovery Services (years) <sup>2</sup>	3	3	3	3
Warranty, Limited (years)	5	5	5	5
<b>Power Management</b>				
Active Power, Average (W)	6.0	5.3	4.6	3.0
Idle Power PS3, Average (mW)	26.4	20	16	16
Low Power L1.2 mode (mW)	2	2	2	2
<b>Environmental</b>				
Temperature, Operating Internal (°C)	0 to 70	0 to 70	0 to 70	0 to 70
Temperature, Non-operating (°C)	-40 to 85	-40 to 85	-40 to 85	-40 to 85
Shock, Non-operating: 0.5 ms (Gs)	1,500	1,500	1,500	1,500
<b>Special Features</b>				
TRIM	Yes	Yes	Yes	Yes
S.M.A.R.T.	Yes	Yes	Yes	Yes
Halogen-free	Yes	Yes	Yes	Yes
RoHS compliance	Yes	Yes	Yes	Yes
<b>Physical</b>				
Length (mm/in, max)	80.15 mm/3.156 in	80.15 mm/3.156 in	80.15 mm/3.156 in	80.15 mm/3.156 in
Width (mm/in, max)	22.15 mm/0.872 in	22.15 mm/0.872 in	22.15 mm/0.872 in	22.15 mm/0.872 in
Height (mm/in, max)	3.58 mm/0.140 in	2.23 mm/0.087 in	2.23 mm/0.087 in	2.23 mm/0.087 in
Weight (lb/g)	8.7 g/0.019 lb	8.7 g/0.019 lb	8.7 g/0.019 lb	8.7 g/0.019 lb

<sup>1</sup> Fresh out of box (FOB) performance obtained on newly formatted drive. Performance may vary based on SSD's firmware version, system hardware, and configuration. Performance based on CrystalDiskMark v.6.0.2 x64 on Windows 10 host.

<sup>2</sup> Rescue Data Recovery Services not available in all countries.



Ordering Information			
Specifications			
Retail Packaging	Box Dimensions	Master Carton Dimensions	Pallet Dimensions
Depth/Length (in/mm)	5.285 in/134.25 mm	5.078 in/129 mm	47.992 in/1,219 mm
Width (in/mm)	4.291 in/109 mm	10.944 in/278 mm	20 in/508 mm
Height (in/mm)	0.944 in/24 mm	6.653 in/169 mm	27.795 in/706 mm
Weight (lb/kg),	0.136 lb/0.062 kg	2.028 lb/0.92 kg	104.80 lb/47.54 kg
Quantities			
Boxes per Master Carton	10		
Master Cartons per Pallet	48		
Pallet Layers	4		

System Requirements	What's Included
---------------------	-----------------

- M.2 (M key) slot, PCIe G3 x4 interface
- Windows® 10, Windows 8.1
- Linux
- Seagate® FireCuda® 510 SSD

Region	Model Number	Capacity	Limited Warranty (years)	UPC Code	EAN Code	Multi-Pack UPC
WW	ZP250GM3A001	250GB	5	763649153376	8719706031813	10763649153373
WW	ZP500GM3A021	500GB	5	763649153383	8719706031820	10763649153380
WW	ZP1000GM3A011	1 TB	5	763649153390	8719706031837	10763649153397
WW	ZP2000GM30021	2 TB	5	763649133996	8719706016605	10763649133993

seagate.com



© 2021 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. FireCuda, the FireCuda logo, and SeaTools are either trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors, such as chosen interface and disk capacity. Seagate reserves the right to change, without notice, product offerings or specifications. DS1999.5-2101GB January 2021